

Va Sheriffs Assoc - '21/'22 Lube Skid #2 / OAE - #021585

	Lube Skid	
	----- Maintainer Body -----	
1	Lube skid assembly, 6.5' long x 42" wide, includes the following items: Forklift sleeves Lifting D-rings (4) Reel rack Dispenser holders with drip containment	
	----- Painting Equipment & Accessories -----	
1	Lube skid assembly (6.5'L x 42"W) painted urethane "Black" color. Not a base coat/clear coat or Metallic	
	----- Product Tanks -----	
4	55 gallon composite tank for lube skid (oils, water, A-F, def). Equipped with the following: Vented fill cap Suction screen Shut-off valve on tank suction line Tank rack Temperature Range: -40°F to 136°F, Not for hydraulic system reservoir use	
1	Tee (plumb) two lube skid product tanks together	
	----- Product Pump Kits -----	
1	Lube Skid Air Kit - Oil, 5:1 ratio Samson piston pump, 1-3 GPM delivery (Varies with oil type) Includes control valve, Hannay 1/2" X 50' spring rewind reel, with rollers (019647/019646) high-flow non-drip non-metered rigid dispenser (019593) NOTE: Not for top of tank mounting, remote-mount only	
1	Lube Skid Air Kit - Anti-Freeze (non-corrosion resistant) Samson Aluminum diaphragm pump Samson pump 022035, 0-10 GPM delivery / (control valve & regulator). Hannay 1/2" X 50' spring rewind reel (non-corrosion resistant), with rollers, high-flow non-drip rigid dispenser	
2	Metered Dispenser, Digital, Samson w/ formable hose extension and non-drip tip (ILOS) Compatible with: Oil, Anti-Freeze 8-GPM	
1	Lube Skid Air Kit - Oil / Anti-freeze Evacuation Diaphragm pump 1" x 30' 0-15 GPM delivery w/ hydraulic, 10wt or 20wt @ 60 degrees F. 0-8 GPM delivery w/ 30wt, 50wt or 90 wt @ 60 degrees F. 1" x 30' spring reel, with rollers (017401), 4-way control & suction screen, control valve & regulator (Not for water / solvent) Does not include: Tank-full sensor, indicator light, buzzer, pump shut-down, or bypass switch 212°F Maximum operating temperature	
	----- Lube Equipment & Accessories -----	
1	HP filter & element for oil products, includes visual indicator 9-Micron for hydraulic oil 23-Micron for Mid-weight and Gear oil	
1	Air manifold (aluminum) for lube skid, to centrally locate multiple pump kit ball valves / controls Includes 3/8" ports 1/2" FRL, and 1/2" remotely plumbed coupler for adding quick connect	
1	Lifting straps (2x 021531) for 6.5'L x 42"W lube skid	
1	NOTE:	
	~Freight not included ~Standard skids are sold as is, no options available under this contract	