Va Sheriffs Assoc. - '21/'22 Lube Skid #4 / OOAE - #021586

	Va Sheriffs Assoc '21/'22	1
	Lube Skid	
	Maintainer Body	
1	Lube skid assembly, 6.5' long x 42" wide, includes the following items:	
	Forklift sleeves	
	Lifting D-rings (4)	
	Reel rack	
	Dispenser holders with drip containment	
	Disposition included with any contamination	
	Painting Equipment & Accessories	
1	Lube skid assembly (6.5'L x 42"W) painted urethane "Black" color. Not a base coat/clear coat or	
ı	Metallic	
	inetallic	
	Product Tanks	
4	55 gallon composite tank for lube skid (oils, water, A-F, def). Equipped with the following:	
7	Vented fill cap	
	Suction screen	
	Shut-off valve on tank suction line	
	Tank rack	
	Temperature Range: -40°F to 136°F, Not for hydraulic system reservoir use	
	Temperature Nange40 1 to 150 1, Not for hydraulic system reservoir use	
	Product Pump Kits	
2	Lube Skid Air Kit - Oil, 5:1 ratio Samson piston pump, 1-3 GPM delivery (Varies with oil type)	
	Includes control valve, Hannay 1/2" X 50' spring rewind reel, with rollers (019647/019646)	
	high-flow non-drip non-metered rigid dispenser (019593)	
	NOTE: Not for top of tank mounting, remote-mount only	
3	Metered Dispenser, Digital, Samson w/ formable hose extension and non-drip tip (ILOS)	
	Compatible with: Oil, Anti-Freeze 8-GPM	
1	Lube Skid Air Kit - Anti-Freeze (non-corrosion resistant) Samson Aluminum diaphragm pump	
•	Samson pump 022035, 0-10 GPM delivery / (control valve & regulator).	
	Hannay 1/2" X 50' spring rewind reel (non-corrosion resistant), with rollers, high-flow non-drip	
	rigid dispenser	
1	Lube Skid Air Kit - Oil / Anti-freeze Evacuation Diaphragm pump 1" x 30'	
1	0-15 GPM delivery w/ hydraulic, 10wt or 20wt @ 60 degrees F.	
	0-15 GPM delivery w/ nydraulic, 10wt or 20wt @ 60 degrees F.	
	1" x 30' spring reel, with rollers (017401), 4-way control & suction screen, control valve &	
	regulator (Not for water / solvent)	
	Does not include: Tank-full sensor, indicator light, buzzer, pump shut-down, or bypass switch	
	212°F Maximum operating temperature	
	Lube Equipment & Accessories	
2	HP filter & element for oil products, includes visual indicator	
_	9-Micron for hydraulic oil	
	23-Micron for Mid-weight and Gear oil	
1	Air manifold (aluminum) for lube skid, to centrally locate multiple pump kit ball valves / controls	
	Includes 3/8" ports 1/2" FRL, and 1/2" remotely plumbed coupler for adding quick connect	
1	Lifting straps (2x 021531) for 6.5'L x 42"W lube skid	
	3	
1	NOTE:	
	~Freight not included	
	~Standard skids are sold as is, no options available under this contract	