Walk-Behind Aerators





Quick Specs

	<u>LA IV EST</u>	<u>LA V EST</u>
Honda®	4 cycle GX120, 7.2 cu	4 cycle GX120, 7.2 cu
	in (118 cc)	in (118 cc)
Clutch	Belt tightener	Belt tightener
Drive: Primary		0
•	4L section V-Belt	4L section V-Belt
Drive: Tine &	a: 1 // 10 : 1 1 1 1 1	
Drum	Single #40 nickel-plated	Single #40 nickel-plated
	chain	chain
Tines, Coring Type	.75 in (19 mm) formed	.75 in (19 mm) formed
	from 0.08 in (2 mm)	from 0.08 in (2 mm)
	hollow hardened alloy	hollow hardened alloy
	steel	steel
Number of Tines	42	42
Coring Depth	Up to 2.75" (70mm)	Up to 2.75" (70mm)
Core Diameter	.75 in (19 mm)	.75 in (19 mm)
Aerating Width	26.5 in (673 mm)	26.5 in (673 mm)
Aerating Pattern	3.75 in x 7 in (95 mm x	3.75 in x 7 in (95 mm x
	178 mm)	178 mm)
Holes per Sq Ft	up to 9/sq ft (59 m ²)	up to 9/sq ft (59 m ²)
Productivity	up to 40,000 sq ft/hr	up to 40,000 sq ft/hr
100000000 0	$(3,176 \text{ m}^2/\text{hr})$ at 3.5 mph	$(3,176 \text{ m}^2/\text{hr})$ at 3.5 mph
	(4.83 kph)	(4.83 kph)
Tires	(2) 8 x 2.25 semi-	(2) 8 x 2.25 semi-
	pneumatic w/ball	pneumatic w/ball
	bearings	bearings
Fuel Capacity	.53 gal (2 L)	.53 gal (2 L)
Weight: Wet w/o		
Weights	220 lb (100 kg)	250 lb (113 kg)
Weight: Wet	20111 (1101	202 11 (122 1)
w/Weights	261 lb (118 kg)	292 lb (132 kg)
Weight: Wet		
w/Weights &	304 lb (138 kg)	357 lb (162 kg)
Water in Drum		
Width	28 in (711 mm)	35.5 in (902 mm)
Length	53.5 in (1,359 mm)	53.5 in (1,359 mm)
Height	48.8 in (1,240 mm)	48.5 in (1,232 mm)
	(2,2 10 1111)	(1,202 1111)

