Power Rakes



Quick Specs

RYAN Mataway Dethatcher

Honda® Engine Model 4-Cycle GX390; recoil start; on/off swithc; low-oil alert

 $\begin{array}{lll} \mbox{Honda} \& \mbox{Displacement} & 23.7 \ \mbox{cu in (389 cc)} \\ \mbox{Fuel Capacity} & 1.6 \ \mbox{gal (6.1 L)} \\ \mbox{Oil Capacity} & 1.16 \ \mbox{qt (1.1 L)} \end{array}$

Clutch Spring-loaded belt tightener

Drive 4L-section V-belt to front wheels by gear box and sealed roller chain; triple 3V-section V-

belts engine to reel

Tires Front: (2) 4.10/3.50 x 4, 2-ply penumatic, knob tread; Rear: (2) 4.10/3.50-4, 2-ply

pneumatic, sawtooth tread

Cutting Depth Adjustable for any desired depth to 1.5 in (38 mm) Flail Blade Type 1/8 in (3 mm) at 1 in (25 mm) spacing

Fixed Blade Type 1/32 in (1 mm) at 1/2 in (13 mm) spacing; 1/32 in (1 mm) at 1 in (25 mm) spacing; 1/16 in

(2 mm) at 1 in (25 mm) spacing; 1/16 in (2 mm) at 1 1/2 in (38 mm) spacing

 Weight: Wet
 376 lb (171 kg) w/o reel

 Width
 35.5 in (902 mm)

 Length
 50 in (1,270 mm)

 Height
 44 in (1,118 mm)

Lubrication Oil splash in gear case, grease fittings elsewhere

Operating Width 19 in (483 mm)

Productivity Single Pass: 80%; 18,700 sq ft/hr; Double Pass: 80%; 9,400 sq ft/hr

