



Division of THC Enterprises, Inc.

Easton, MD * Baltimore, MD * Chesapeake, VA Chester, PA *
Clinton, MD * Cheswick, PA * Salem, VA

Phone 800-338-7274 Fax 410-820-9916

Visit us on the web! www.mawaste.com



PROPOSAL

Remittance Address for Deposits:

10641 Cordova Road
Easton, MD 21601

SOLD TO

SHIP TO

Quote #: RSSQ35959

Account:

Terms:

Date: 07/14/21

Sales Rep Fred Seitz

| QTY | DESCRIPTION | UNIT PRICE | EXT PRICE |
|-----|-------------|------------|-----------|
|-----|-------------|------------|-----------|

All Pricing on Requested Options Quoted at 6% Off List

- 1.00 A.O.D (Air Operated Diaphragm) Water Pump with Washdown Hose & Gun - Requires Air Dryer
- 1.00 A.O.D. (Air Opened Diaphragm) Water Pump with Wash Down Hose
- 1.00 Abrasion Protection Package- Standard Hopper Screen With Hopper Baffle Curtains; Protective Hopper Wall Liners; Suction Nozzle Liner; Pressure Wear Pads; Heavy Duty Pressure Hose (Chip Seal/Milling Operations Require Chip Seal/Milling Hopper Screen Option)
- 1.00 Additional Nozzle Location(s) (Switched Separately)-Hopper Water Nozzle
- 1.00 Additional Nozzle Location(s) (Switched Separately)-Pick up Head Water Nozzles; (w/Low Emissions) (AQMD Rule 1186 non compliant)
- 1.00 Additional Nozzle Location(s) Pressure Transition
- 1.00 Additional Nozzle Locations(s) (Switched Separately)-Left gutter broom/Right gutter broom/Pressure transition (specify Location) (Each)
- 1.00 Air Dryer - Brakes
- 1.00 Air Horn
- 1.00 Air Purge- Facilitates Purging Dust Control System During Freezing Conditions
- 1.00 Amber Beacon Light - LED: SAE Class 1, cab mounted with limb guard
- 1.00 Amber Beacon Light- LED (Additional)- SAE Class 1 with Protective Limb Guard
- 1.00 Auto Sweep Interrupt (ASI)- Electronic Circuit Designed To Engage When The Transmission Gear Selector is Placed Into Reverse with the ASI Set in the Auto Mode
- 1.00 Auxiliary Engine Block Heater
- 1.00 Auxiliary Engine Heat Deflector (Standard with Quiet Pkg)
- 1.00 Auxiliary Engine Sound Package- Includes Auxiliary Engine Heat Deflector
- 1.00 Auxiliary Fuse Panel- a +12VDC fused power source panel for any needed additional electrical components or accessories i.e. radios, warning lights, controls, etc.
- 1.00 Auxiliary Hand Hose Extension- Additional 10' Hose With Quick Disconnect Coupler
Requires Auxiliary Hand Hose Option
- 1.00 Auxiliary Hand Hose Hydraulic Boom Remote Control- Power to control the boom (up/down), the auxiliary engine speed (up/down) and stop auxiliary engine utilizing a

| QTY | DESCRIPTION | UNIT PRICE | EXT PRICE |
|------|--|------------|-----------|
| | wireless control system. Includes receiver mounted in the truck cab and two (2) transmitters; one is a hand-held fob and the other is a box mounted on a quick release handle on the hand hose nozzle. Requires: Auxiliary Hand Hose w/Hydraulic Boom Assist Option | | |
| 1.00 | Auxiliary Hand Hose Nozzle Extension- Additional 42" Aluminum Extension with Quick Disconnect Coupler; **Requires Auxiliary Hand Hose Option** | | |
| 1.00 | Auxiliary Hand Hose with Catch Basin Cleaning Package: Includes Auxiliary Hand Hose with Hydraulic Boom Assist; A.O.D. Water Pump w/ Wash Down Hose & Gun (3/4" x 25" hose); Sweeper Mounted Washdown Hose Box; Nozzle Extension (42" w/ Quick Disconnect); Wireless Remote Control; REQUIRES AIR DRYER | | |
| 1.00 | Auxiliary Hand Hose with Catch Basin Cleaning Package: Includes Auxiliary Hand Hose with Hydraulic Boom Assist; Hi/Low Pressure Wash Down System; Hose Reel - 50' Automatic; Nozzle Extension 42" with Quick Disconnects; Wireless Remote Control Hand Hose | | |
| 1.00 | Auxiliary Hand Hose with Hydraulic Boom Assist-and Manhole Cover Lift **Recommend Hi/Low Pressure Washdown System** Power To Raise/Lower Boom with Hand Held Pendant Control (Includes Auxiliary Hydraulic System; Heavy Duty 8" Hand Hose, Remote Engine Throttle [Linear Actuator], Serrated Ring, Quick Coupler) | | |
| 1.00 | Auxiliary Hand Hose- 8" Diameter, 10' with 52" Nozzle | | |
| 1.00 | Auxiliary Hydraulic System- Electrically Operates Hydraulic System Without Auxiliary Engine | | |
| 1.00 | Auxillary Engine Air Intake Heater | | |
| 1.00 | Auxillary Engine Air Restriction Indicator - In Cab | | |
| 1.00 | Auxillary Engine: John Deere 4045T Tier iT4; 99HP | | |
| 1.00 | Battery Disconnect Switch-(standard on Peterbilt and Autocar | | |
| 1.00 | Broom Assist Pick-Up Head (BAH)- Exchange | | |
| 1.00 | Broom Assist Pick-Up Head Deluge | | |
| 1.00 | Camera/Monitor System: Alliance Wireless Technology (AWTI), slim line series with 7" color monitor mounted in cab with color camera. SINGLE Rear View Camera System | | |
| 1.00 | Camera/Monitor System: Single Rear View Camera System with One Additional Camera Alliance Wireless Technology (AWTI), slim line series with 7" color monitor mounted in cab with color camera. Choose Location of Second Camera: Pick-Up Head View from Right Side and/or Left and/or Right Gutter Broom. | | |
| 1.00 | Camera/Monitor System: Single Rear View Camera System with Two Additional Camera Alliance Wireless Technology (AWTI), slim line series with 7" color monitor mounted in cab with color camera. Choose Location of Second Camera: Pick-Up Head View from Right Side and/or Left and/or Right Gutter Broom. Choose Location of Third Camera: Pick-Up Head View from Right Side and/or Left and/or Right Gutter Broom. | | |
| 1.00 | CAT 290 Water Pump- **Not Available with Alternative Fuel** (In Lieu Of Standard) | | |
| 1.00 | CNG Conversion POR | | |
| 1.00 | COMDEX - Compact Design Extra Water; Total Water Capacity 330 gallons and Storage Box. | | |
| 1.00 | Customer Truck Charge - International (does not include dual steering) | | |
| 1.00 | DCVA - Water System Back Flow Protection Device | | |
| 1.00 | Deduct for one gutter broom light and mirror. Specify which side. | | |

| QTY | DESCRIPTION | UNIT PRICE | EXT PRICE |
|------|---|------------|-----------|
| 1.00 | Double Duo Skids (4" wide) with Skid Bumper Extension Set (3") | | |
| 1.00 | Dump Switch In Cab- Additional Dump Switch On Control Panel To Activate Dump Operation From Inside Cab | | |
| 1.00 | Engine Block Heater (Cabover Truck) | | |
| 1.00 | Engine Block Heater: Conventional Truck | | |
| 1.00 | Extra Water Capacity - Additional (2) 110 Gallons for a total of 440 Gallons- **Requires Cabover Chassis**; Deletes Storage Box (Autocar 171" WB Cabover Chassis) | | |
| 1.00 | Extra Water Capacity - Additional (2) 110 Gallons for a total of 440 Gallons- **Requires Cabover Chassis**; Deletes Storage Box (Peterbilt 168" WB Cabover Chassis) | | |
| 1.00 | Extra Water Capacity-Cabover style-Additional 110 gallon water tank for a total water capacity of 330 gallons located between chassis cab and sweeper. Includes two tool storage boxes. Peterbilt 220 (Required Option w/Chassis) | | |
| 1.00 | Extra Water Capacity-COMDEX-Additional 110 gallon water tank; total capacity of 330 gallons located between chassis cab and sweeper. Includes a right side mounted tool storage box | | |
| 1.00 | Fire Extinguisher- Refillable, Dry Chemical, Dot Approved, Cab Mounted | | |
| 1.00 | Floodlight (Additional-Each)- (Additional-Each) | | |
| 1.00 | Floodlight (LED) (additional) Specify Location (each) | | |
| 1.00 | Floodlight (LED) (Exchange) (each) | | |
| 1.00 | Front Bumper Spray Bar | | |
| 1.00 | Front Tow Hooks- 2 Steel Hooks Front Frame Mounted (Standard on Autocar & Peterbilt Chassis) | | |
| 1.00 | Gutter Broom - Drop Down- **Requires Gutter Broom Tilt Adjuster** (Each) | | |
| 1.00 | Gutter Broom Tilt Adjuster (Qty 2)- In Cab Control Allows Operator To Manipulate Pitch PF Vertical Diggers to Compensate for Changing Curb Line Depths/Angles (Each) | | |
| 1.00 | Gutter Broom Variable Speed | | |
| 1.00 | Hazard Reflectors - 3 Triangular Red Reflectors | | |
| 1.00 | Hi/Low Pressure Washdown System- **Not Available with Alternative Fuel** Self Contained Water Supply; High Pressure, Low Volume Washdown Hose, 20' (Includes CAT 290 Water Pump, a Spray Gun with Trigger Control & 2 Interchangeable Lance Lengths of 48" and 36") | | |
| 1.00 | High Capacity Dust Separator- (Included With Low Emission Package) | | |
| 1.00 | High Output Water System- Additional Nozzles & Deflectors Strategically Located to Control Extreme Dust (Included with Low Emission Package) | | |
| 1.00 | Hopper Deluge System- High Volume System Attaches To Fire Hydrant To Flush Hopper; Includes Quick Disconnect Fittings on Nozzle & Filler Hose | | |
| 1.00 | Hopper Drain System- Allows Sweeper To Operate In Wet Conditions By Draining Water Picked Up During Sweeper Operations; Mounts on Lower Right Dump Door Panel | | |
| 1.00 | Hopper Load Indicators- Sensor with Audible & Visual Indicators In Cab That Signals Full Load | | |
| 1.00 | Hopper Screen - Split | | |
| 1.00 | Hopper Screen Vibrator- Pneumatic | | |
| 1.00 | Hopper Screen-Chip Seal/Milling Hopper Screen- **Requires Abrasion Protection | | |

| QTY | DESCRIPTION | UNIT PRICE | EXT PRICE |
|------|--|------------|-----------|
| | Package** 1/4" Mesh High Carbon Steel Woven Wire, for Use in Milling and Chip Seal Applications - Includes Screen Baffles (Exchange) | | |
| 1.00 | Hopper Screen-Chip Seal/Milling Hopper Screen-Split- **Requires Abrasion Protection Package** 1/4" Mesh High Carbon Steel Woven Wire, for Use in Milling and Chip Seal Applications - Includes Screen Baffles and is Split Into Front and Rear Sections. Each Section can be Lowered or Removed Manually by Removing Lock Pins.(Exchange) | | |
| 1.00 | Hopper Suction Inlet Wear Flange | | |
| 1.00 | Hopper Suction Throat Liner and Inlet Wear Flange | | |
| 1.00 | Hose Reel- Automatic With 50' Retractable Hose | | |
| 1.00 | Hydrant Wrench | | |
| 1.00 | Hydraulic Level/Temperature Shutdown | | |
| 1.00 | Hydraulic Oil Level Shutdown System: (iT4 only) | | |
| 1.00 | Hydraulic Shutoff Valve | | |
| 1.00 | Lateral Air Flow Nozzle with Dual Gutter Brooms-Nozzle located on left side between the left gutter broom and rear axle; cab operated control to open diverter so full exhaust of blower is directed through nozzle. Nozzle orifice is manually adjustable and is 360 degree directional. Requires Special Order Chassis. Consult factory | | |
| 1.00 | Lateral Air Flow Nozzle- **Price Includes Left Side Gutter Broom Deletion** Located On Left Side Between Front & Rear Axle; Cab Operated Control to Open Diverter so Full Exhaust of Blower is Directed Through Nozzle; Nozzle Orifice is Manually Adj & is 360 Degree Directional | | |
| 1.00 | LED Lights: Alternate Warning Lights | | |
| 1.00 | LED Lights: Stop/Turn/Tail/Clearance/Side Markers | | |
| 1.00 | Light Bar - LED: Amber, SAE Class 1, 56" Long | | |
| 1.00 | Linear Actuator w/Guage - Pressure Bleeder | | |
| 1.00 | Liquid Recovery System Pump Kit | | |
| 1.00 | Liquid Recovery System- Hopper Conversion To Allow Capacity Of 700 Gallons of Liquid; Pump Suction Coupling, Suction Nozzle/Float with Filter Screen and In Cab Full Indicator | | |
| 1.00 | Low Emissions Package- AQMD Rule 1186 Compliant (Includes High Capacity Dust Separator, High Output Water Hopper Baffle Curtains, Pressure Transition Water Nozzle, and Deleted Pick-Up Head Water Nozzles | | |
| 1.00 | Magnet Assembly In-Cab Height Indicator | | |
| 1.00 | Magnet Assembly Light Duty Bumper Mounted, Chain Held 96" | | |
| 1.00 | Magnet Assembly, Electrically Controlled, Standard Duty- Full Width 84" Magnet, Mounted Where Front Bumper Attaches; Height 2-10 Inch Adjustment; Dump Control at Magnet.200 Gauss Magnetic Strength @ 2" Ground Clearance | | |
| 1.00 | Magnet Assembly, Electrically Controlled, Standard Duty-for Freightliner M2- Full Width 84" Magnet, Mounted Where Front Bumper Attaches; Height 2-10 Inch Adjustment); Dump Control at Magnet. 300 Gauss Magnetic Strength @ 2" Ground Clearance | | |
| 1.00 | Magnet Assembly, Electro-Mechanically Controlled, Heavy Duty-for Freighliner M2- Full Width 84" Magnet, Mounted Where Front Bumper Attaches; Electromechanically Activated with Hydraulic Height Control (2-10 Inch Adjustment) In Cab Controls and Height Indicator. 500 Gauss Magnetic Strenght @ 2" Ground Clearance. | | |

| QTY | DESCRIPTION | UNIT PRICE | EXT PRICE |
|------|---|------------|-----------|
| 1.00 | Magnet Assembly, Electro-Mechanically Controlled, Heavy Duty-Full Width 84" Magnet, Mounted Where Front Bumper Attaches; Electromechanically Activated with Hydraulic Height Control (2-10 Inch Adjustment) In Cab Controls and Height Indicator. 575 Gauss Magnetic Strenght @ 2" Ground Clearance. | | |
| 1.00 | Magnet Assembly, Light Duty, Bumper Mounted, Chain Held, 84" | | |
| 1.00 | Magnet, Remanufactured, Hydraulically Controlled, Heavy Duty- Six Months Warranty; In-Cab Controls & Height Indicator (Consult Factory for Availability) | | |
| 1.00 | Magnet, Remanufactured, Hydraulically Controlled, Heavy Duty-for Ferightliner M2- Six Months Warranty; In-Cab Controls & Height Indicator (Consult Factory for Availability) | | |
| 1.00 | Parabolic Mirror 12" | | |
| 1.00 | Pick-Up Head Curtain Lifter: Hydraulic Actuated And Retractable Roller Assembly That Provides The Pick-Up Head With The Ability To Sweep Large Volume Of Light Debris. Electronically Controlled In Cab. | | |
| 1.00 | Pick-Up Head Deluge with 6" Cleanout Port: Deluge Port(s) on pick-up head pressure inlet (and BAH Broom Chamber if applicable). Connects to Fire Hydrant to Flush Pick-Up Head. | | |
| 1.00 | Pick-Up Head Hour Meter- Records Hours Pick-Up Head Is Down | | |
| 1.00 | Pick-Up Head Pressure Inlet Cleanout Port: 6" Diameter | | |
| 1.00 | Pick-Up Head Pressure Inlet Water Injection System-Gravity flow water line connected to pick-up head pressure inlet. Cab controlled on/off solenoid valve; flow regulated by manual ball valve (inlcudes 6" cleanout port) | | |
| 1.00 | Pick-Up Head Pressure Transition Cleanout Port | | |
| 1.00 | Removable Front Curtain Set | | |
| 1.00 | Reverse Pick-Up Head Chains- Allows Unit To Back Up Without Damage To Pick-Up Head | | |
| 1.00 | Skid Bumper Extension - Set (3") | | |
| 1.00 | Slow Moving Vehicle Emblem | | |
| 1.00 | Spare Tire and Wheel (POR) | | |
| 1.00 | Spark Resistan Skids-Heavy duty, ultra high molecular weight (UHMW) polytheylene pick-up head skids, left and right side (exchange) | | |
| 1.00 | Stainless Steel Bolt-On Blower Housing- (Exchange With Carbon Steel Housing) | | |
| 1.00 | Stainless Steel Chip Seal/Milling Screen- Split-1/4" mesh high carbon steel woven wire, for use in milling and chip seal applications - includes screen baffles and is split into front and rear sections. Can be lowered or removed manually by removing lock pins. (REQUIRES ABRASION PROTECTION PACKAGE) | | |
| 1.00 | Stainless Steel Dust Separator | | |
| 1.00 | Stainless Steel High Capacity Dust Separator | | |
| 1.00 | Stainless Steel Hopper Drain | | |
| 1.00 | Stainless Steel Hopper Screen - Split-split into front and rear sections. Can be lowered or removed manually by removing lock pins. (upgrade from standard) | | |
| 1.00 | Stainless Steel Hopper Screen Upgrade-Upgrade any screen (standard/Chip Seal/Chip Seal-Split/Split) using stainless steel. | | |
| 1.00 | Stainless Steel Hopper Screen-High Capacity. Larger screen spanning the entire width of the dump door. | | |

| QTY | DESCRIPTION | UNIT PRICE | EXT PRICE |
|------|--|------------|-----------|
| 1.00 | Stainless Steel Hopper Screen-Standard size drain screen allowing for maximum payload in the hopper | | |
| 1.00 | Stainless Steel Hopper- For Maximum Corrosion & Salt Spray Resistance, All Interior Hopper Body Sheet Surfaces to be Fabricated with Low Carbon, High Chrome Stainless Steel; The Hopper Weldment, Hopper Door, Hopper Inspection Doors, Raker Plate, Skimmer Hood & Hopper Screen Assemblies are Included in this Option. Dust Separator Inlet Scroll and Door are not Stainless Steel. Stainless Steel Bolt-On Blower Housing NOT Included. (Exchange) | | |
| 1.00 | Storage Box with Work Platform: Large 6 ft storage box (12" W x 12" H x 69 L) with Street-Side and Curb-Side Accessible Lockable Doors Located Between Truck Cab and Sweeper. Comes with 2 Slide-Out Removable Drawers (10"W x 5.5"H x 33"L per drawer) and Easily Accessible Work Platform. (Only Available with an International 4300 Chassis with 165" WB and EGR Horizontal Exhaust, Autocar or Peterbilt with Minimum 98" CA) | | |
| 1.00 | Sweeper Deluge System: High volume system is mounted in the hopper with a water fill hose quick coupler for connection to a fire hydrant. Also included in the system is a pick-up head deluge system with a water fill hose quick coupler for connection to a fire hydrant. | | |
| 1.00 | Sweeper Odometer - Single Speed Chassis- Records Miles Swept When Pick-Up Head Is Down | | |
| 1.00 | Sweeper Odometer-2 Speed Chassis- Records Miles Swept When Pick-Up Head is Down | | |
| 1.00 | Sweeper Paint - Additional Color | | |
| 1.00 | Sweeper Paint - Solid Colors | | |
| 1.00 | Sweeper Paint - Special | | |
| 1.00 | Sweeper Paint - Tymco Standard White | | |
| 1.00 | Traffic Directing Light (Arrow Stick) LED: Whelen TACF85LH, SAE Calss 1 (44" Long) | | |
| 1.00 | Truck Paint: Additional Colors | | |
| 1.00 | Truck Paint: Additional Colors | | |
| 1.00 | Truck Paint: Additional Colors | | |
| 1.00 | Truck Paint: Additional Colors | | |
| 1.00 | Truck Paint: Additional Colors | | |
| 1.00 | Truck Paint: CNG Tanks/Back of Cab Solid Color on Tymco Stock Truck | | |
| 1.00 | Truck Paint: Solid Colors | | |
| 1.00 | Truck Paint: Solid Colors | | |
| 1.00 | Truck Parts Manual (Set) | | |
| 1.00 | Truck Shop Manual (Set) | | |
| 1.00 | Wall Liners- Standard with Abrasion Package | | |
| 1.00 | Water Tank Level Gauge | | |