

CONTAINER HANDLER OPTIONS

Option No.	Description
------------	-------------

HOIST MOUNTING HARDWARE

HUCK	SHIP OUT - Hoist Mounting Huck Bolts for Dealer Hoist Installation - PER HOIST
NOBO	DEDUCT - Remove Standard Mounting Bolt Kit from Ship Out Kit

VALVE CONTROL SYSTEMS

2SSE	UPCHARGE - (Single Axle <=25k lbs.) to upgrade from standard air controls to remote control, electric over hydraulic controls. 2-Spool Only non-integrated (saves space in cabs)
ADAIR1	SHIP OUT - Add-on air compressor for non-air trucks 1 gal tank (1.27 CFM @ 100 psi) - (parts only) - May be needed for inside controls, PTO, etc. - A4880 light duty
8834	FACTORY MOUNT - Add-on air compressor for non-air trucks 1 gal tank (1.27 CFM @ 100 psi) - (parts and labor) - May be needed for inside controls, PTO, etc. - A4880 light duty
ADAIR25	SHIP OUT - Add-on air compressor for non-air trucks 2.5 gal tank (2.62 CFM @ 100 psi) - (parts only) - May be needed for inside controls, PTO, etc. - 120820 med. duty
8834-2	FACTORY MOUNT - Add-on air compressor for non-air trucks 2.5 gal tank (2.62 CFM @ 100 psi) - (parts and labor) - May be needed for inside controls, PTO, etc. - 120820 med. duty

PTO & PUMP OPTIONS*Make, Model and Rotation of Transmission Needed when Ordering PTO*

PTO5	Single Axles - SHIP OUT - Muncie DS PTO for (Fuller direct mount) Manual Transmission - Electric over Air - 233318 (For factory mounting ADD option PTO INST)
PTO6	Single Axles - SHIP OUT - Muncie DS PTO for (Allison direct mount) Automatic Transmission - Hot Shift - 202663 (For factory mounting ADD option PTO INST)
PTO7	Ford F550/650/750 ONLY - SHIP OUT - Muncie DS PTO for (TorqShift direct mount) Automatic Transmission - Hot Shift - 202663 (241122 - diesel or 241123 - gas for F650/750) (For factory mounting ADD option PTO INST)
PTO13	SA HK Hoists - SHIP OUT - Bezares WS PTO for (Allison direct mount) Automatic Transmission - (includes pump upgrade Bezares bent axis piston pump) - 226835 (For factory mounting ADD option PTO INST)
WET	UPCHARGE for Muncie PTO to be Wet Spline (Most Chelsea/Parker PTO's are Wet Spline)
PTO INST	FACTORY MOUNT - Any PTO option pick (labor only)
13Y1	UPCHARGE FACTORY MOUNT - Front Mount Pump with Mounting Brackets in Place - A4890 - (parts and labor)
13D2	FACTORY MOUNT - Modify Brackets and Rerouting if Chassis is Not Front Mount Pump Ready - (parts and labor)

FOR NON AIR CHASSIS - USE OPTION 8834 OR 8834-2 - Add-On Air Compressor Kits

Manufacturers are Developing Engines and Transmissions that Communicate with Each Other to Gain Fuel Economy. These Newer Models may be Standard Transmission with a Hot Shift Type Feature. Contact Galbreath Inside Sales Department for Pricing

FENDERS

NFND	No Fenders Needed - place holder in order entry only
1/4FND	1/4 Poly Fenders - 24" for use with Lift Axles or in lieu of half round fenders
1/4FND2	1/4 Poly Fenders - 24" for use with Tandem Axle Trailers (2 sets)
PLST	Plastic Half Round Fenders 38"/16.5 Dually - A2425 (9616AO for brackets) - Single Axle Hoist
1PLY	Poly Half Round Fenders w/ Brackets - 5496BO - Single Axle Hoist
5B	Poly Half Round 44" Fenders - Specify Tire Size - A4531 (9616AO for brackets) - Single Axle Hoist
FD44	Steel Half Round 44" Fenders (3114) - w/ Mounting Brackets (9616AO) - Single Axle - 8486BO prev. p/n
FND4	Steel Half Round 48" Fenders for 22.5 Tires (9616AO for Brackets) - 171135 - Single Axle Hoist
HK44	Aluminum Half Round Fenders 44" - Specify Tire Size - A1042 uses 9616AO mounting brackets - Small Single Axle Cable/Hook Hoist/Container Handlers - Used w/ low profile tires
HK5A	Aluminum Half Round Diamond Plate Fenders (Large) 50" - Specify Tire Size - 9797 uses 9616AO mounting brackets - Single Axle Cable/Hook Hoist/Container Handlers & AC2 Trailer
1INFND	FACTORY MOUNT - Installation of Single Axle/Lift Axle Fenders - (labor only; add to option picked)

NO CUSTOMER SUPPLIED EQUIPMENT WILL BE INSTALLED AT THE GALBREATH FACTORY

CONTAINER HANDLER OPTIONS (continued)

Option No.	Description
------------	-------------

HYDRAULIC / WET KIT OPTIONS

HOS4	Four (4) Wire Hoses - For Low Pressure Systems
HSLV	UPCHARGE to Add Hose Protection Sleeves over Hydraulic Hoses

TOOLBOXES

17B	Aluminum Toolbox - 18" X 18" X 24" - Opens from the Front - A4819 - Toolbox Mounting Brackets Included
17F	Aluminum Toolbox - 18" X 18" X 36" - Opens from the Front - A4516 - Toolbox Mounting Brackets Included
17C	Aluminum Toolbox - 18" X 18" X 48" - Opens from the Front - A4820 - Toolbox Mounting Brackets Included
17E	Poly Toolbox - 19" X 20" X 36" - Opens from the Top - A4033 - Toolbox Mounting Brackets Included
G025	Steel Toolbox - 14" X 12" X 14" - Opens from the Front - 229309 - Standard Toolbox Option - Toolbox Mounting Brackets Included
G027	Steel Toolbox - 14" X 12" X 24" - Opens from the Front - 229311 - Standard Toolbox Option - Toolbox Mounting Brackets Included
G024	Steel Toolbox - 14" X 16" X 24" - Opens from the Front - 229310 - Standard Toolbox Option - Toolbox Mounting Brackets Included
17	Steel Toolbox - 16" X 20" X 24" - Opens from the Front - 0936AO - Galbreath Made - Toolbox Mounting Brackets Included
G018	Steel Toolbox - 16" X 20" X 24" - Opens from the Front (For High Mounts, includes mounting brackets) - 228969 - Standard Toolbox Option
17D	Steel Toolbox - 16" X 20" X 36" - Opens from the Front - 1573BO - Galbreath Made - Toolbox Mounting Brackets Included
17A	Steel Toolbox - 16" X 20" X 48" - Opens from the Front - 4395AO - Galbreath Made - Toolbox Mounting Brackets Included
G021	Steel Toolbox - 18" X 18" X 24" - Opens from the Front - 229306 - Standard Toolbox Option - Toolbox Mounting Brackets Included
G015	Steel Toolbox - 18" X 18" X 36" - Opens from the Front - 227987 - Buyers Brand Toolbox Option - Toolbox Mounting Brackets Included
G022	Steel Toolbox - 18" X 18" X 36" - Opens from the Front - 229307 - Standard Toolbox Option - Toolbox Mounting Brackets Included
G023	Steel Toolbox - 18" X 18" X 48" - Opens from the Front - 229308 - Standard Toolbox Option - Toolbox Mounting Brackets Included
G048	Steel Toolbox - 18" X 22" X 48" - Opens from the Front - 233774 - Diamond Plate Top w/ Rain Gutter - Toolbox Mounting Brackets Included
TINST	FACTORY MOUNT - Install Toolbox on Hoist when hoist comes with a Side Mount Oil Reservoir using Combo Brackets - (labor only) - 2260W & 0340BO - U/AH-Series Only
TINST1	FACTORY MOUNT - Install Toolbox (Side Mount), Mounting Brackets & Base when hoist comes with a BTC reservoir - (labor only) - 9554AO & 0340BO - Must be Used with all Trailers, AF/AFX Model Cable Hoist, WT-Cable Hoists and Container Handlers

BUMPERS & PINTLE HOOKS

B4	SHIP OUT - Reese Style Hitch on Pintle Ready Aprons - includes 7-spade pin Trailer Plug and harness - no air - w/o glad hands (Class V - 3,000 lbs. Vertical Load, 16,000 lbs. Gross Trailer Weight - Receiver Not Included) - 171062 (apron) - 171064 (Pintle plate) - 117189 or A2891 (2" hitch)
6A	FACTORY MOUNT - Install Reese Style Hitch Only (parts and labor) - includes 7-spade pin Trailer Plug and harness - no air - w/o glad hands (Class V - 3,000 lbs. Vertical Load, 16,000 lbs. GTW - (Individual Receivers Not Included) - A2891 - 117189 - 178258 - 171062
SAPH	SHIP OUT - Pintle Hook w/ 7-spade pin Trailer Plug and harness - no air - w/o glad hands 30k lb. GTW rating - Used On Single or Tandem Axle Cable Hoists w/ Pintle Adaptable Rear Aprons - 228735/8757BO (PH30)
SAPH INST	FACTORY MOUNT - Pintle Hook w/ 7-spade pin Trailer Plug and harness - no air - w/o glad hands 30k lb. GTW rating - (parts and labor) - Used On Single or Tandem Axle Cable Hoists w/ Pintle Adaptable Rear Apron - 228735/8757BO (PH30)
40U3	SHIP OUT - Pintle Hook w/ Glad Hands and Pintle Mounting Plate - 8617BO/8922BO/7898BO - 20K Vertical and 100K Tow Rating - 8922BO-H (Holland)
INST PH	FACTORY MOUNT - (labor only) Installation of Pintle Hook Options (ADD to option picks 40U3, 44U3)
FMPH	SHIP OUT - Fish Mount Pintle Hook - 2359 & 196981
INFMPH	FACTORY MOUNT - Installation of Option FMPH - Fish Mount Pintle Hook (parts and labor) - 2359 & 196981
HKSA AE	FACTORY MOUNT - Install Air and Electric for Pintle Hook if Available (parts and labor) - May Need to Add Option 8834 (A4880 - Add on Air Compressor) if Chassis is not Equipped
AELB	FACTORY MOUNT - Run Air and Electric for Pintle Hook if Pre-Wired and Plumbed (misc. parts and labor)

NO CUSTOMER SUPPLIED EQUIPMENT WILL BE INSTALLED AT THE GALBREATH FACTORY

CONTAINER HANDLER OPTIONS (continued)	
Option No.	Description
LIGHTING	
LIT2	Work Lights - (2) - 2" LED Mounted ON the Bumper OR (customer choice) On Tarper Gantry (1,790 Lumens) - 236458
LIT3	Work Lights - (2) - 4" LED Recessed Mounted IN the Bumper - (1,000 Lumens) - 232344
LIT4	Work Lights - (2) - 4" LED Mounted ON the Bumper OR Mounted On Tarper Gantry (1,600 Lumens) - 232356
INST WL	FACTORY MOUNT - Installation of Work/Mid Body Light Options (labor only) - 13A, LIT2, LIT3, & LIT4
SFTY	High Visibility Package - Requires Special Tower, Bumper and Wiring Harness - One (1) Beacon Light ON Tarper Gantry, (2) Work Lights ON Tarper Gantry and (2) Strobe Lights IN the Bumper (CANNOT add LIT3)
SFTY1	High Visibility Package - Requires Special Tower, Bumper and Wiring Harness - One (1) Beacon Light ON Tarper Gantry and (2) Strobe Lights IN the Bumper (CANNOT add LIT3)
IN SFTY	FACTORY MOUNT - Installation of a Safety Light Option (labor only) - SFTY, SFTY1, GSFY & GSFY1
MISC./SAFETY	
S047	SHIP OUT - 8 Gallon Hand Wash Station w/ Soap Dispenser
INS047	FACTORY MOUNT - Installation of 8 Gallon Hand Wash Station w/ Soap Dispenser- mounted on curb side behind the cab - 250649 (parts and labor)
J013	SHIP OUT - Rear View Camera System (3rd Eye) - 7" HD Display, Single Camera
IN RVC	FACTORY MOUNT - Installation of Any Single Rear View Camera System - (labor only) - ADD to Camera Option
619	SHIP OUT - (SLCH/CH Models Only) Behind the Cab (BTC) Lid Holder with Two Piece Rod Holder - Add 20" to Clear CA - OL0619 & 171054
IN 0619	FACTORY MOUNT - (CH8000 Only) Behind the Cab (BTC) Lid Holder with Two Piece Rod Holder - Add 20" to Clear CA - OL0619 + 181981 - (parts and labor)
1053	SHIP OUT - (SLCH/CH Models Only) Side Mount Lid Holder with Two Piece Rod Holder - 171053 & 171054
1053 INST	FACTORY MOUNT - (SLCH/CH Models Only) Side Mount Lid Holder with Two Piece Rod Holder - 171053 & 171054 - (parts and labor)
1981	SHIP OUT - (SLCH/CH Models Only) Solid Rod Holder in Lieu of Two Piece Rod Holder in Options 619 & 1053 - 181981 - (parts and labor)
1981 INST	FACTORY MOUNT - (SLCH/CH Models Only) Solid Rod Holder in Lieu of Two Piece Rod Holder in Options 619 & 1053 - 181981 - (parts and labor)
8261	SHIP OUT - (SLCH Models Only) Toter Cart Platform - Add 36" to Clear CA of Truck Chassis
8261 IN	FACTORY MOUNT - (SLCH Models Only) Toter Cart Platform - Add 36" to Clear CA of Truck Chassis - 178261 - (parts and labor)
AUTO	FACTORY MOUNT - SLCH Remote Control With Auto Load *factory programmed*
REMO	FACTORY MOUNT - UPCHARGE for SLCH Remote Control Without Auto Load *factory programmed
34CC	FACTORY MOUNT - 20 lb. Fire Extinguisher Mounted on Top Of Outside Controls Protective Cover - A4016 - (parts and labor)
34CJ	DOT Approved Roadside Reflector Kit - Required if the Vehicle Breaks Down - A4012
HAI	SHIP OUT - Hoist Up Alarm Audio Interrupter - Alarm Silenced When Parking Brake is Applied (Air Brake Systems Only) - 140868
IN HAI	FACTORY MOUNT - Hoist Up Alarm Audio Interrupter - Alarm Silenced When Parking Brake is Applied (Air Brake Systems Only) - 140868 - (parts and labor)
ROST	Remote Breather - Mounted on the Tarper Gantry, Driver's side - Keeps Snow and Ice Away from the Oil Reservoir Air Breather
SPEE1	FACTORY MOUNT - Hoist Up Ground Speed Control and PTO Rev Control Programming - This is for Software Programming Only - Chassis not Equipped with Proper Wiring Harnesses will Incur Additional Cost for Wiring
SPEE2	FACTORY MOUNT - Hoist Up Ground Speed Control Software Programming Only (Cummins Engine/Allison Transmission)
SAPT	UPCHARGE - Paint unit special color - Single Axle Hoists & OR Trail Hoist (indicate special paint code on order) - (parts and labor)
0131	SHIP OUT - Shovel Holder Assembly - 210131
0131IN	FACTORY MOUNT - Installation of Shovel Holder Assembly - 210131 (parts and labor)
S013	SHIP OUT - Hoist Up In Cab Audible Alarm
INS013	FACTORY MOUNT - Hoist Up In Cab Audible Alarm - (parts and labor)
TCC	Tire Chain Holder 24" long by 7.5" wide by 9" high - features aluminum diamond plate cover
INTCC	FACTORY MOUNT - Tire Chain Holder 24" long by 7.5" wide by 9" high - features aluminum diamond plate cover - (parts and labor)
381K	SHIP OUT - Retro Field Kit for Hydraulic Adjustable Fork Assembly Head - 24" of travel - Used to replace the original rotating head and hydraulic plumbing. - 236381K

NO CUSTOMER SUPPLIED EQUIPMENT WILL BE INSTALLED AT THE GALBREATH FACTORY

CONTAINER DELIVERY TRAILERS

CDT Trailers Include the Following Standard Features for Base Model:

20K lb. Suspension - 10,000 lbs. Capacity Axles	Eight (8) 235/80R 16 Tubeless Tires	7" x 16" Steel Rims
DOT Approved LED Lighting	2-speed 50,000 lb. Landing Gear	Ten (10) Leaf Springs
Pintle Lunette Eye on Trailer Tongue	Trailer Deck - (7) Gauge Tread Plate	Mud Flaps
Seven (7) Wire Electric Connection	Tongue Constructed of 10" I-Beam	Electric over Air Brakes or Electric Only Brakes
(2) Part Epoxy Primer and Paint	Outer Frame Constructed of (2) 5" Channels	Fixed Standard Tie Downs - 4 for 4 Bay Trailer, 5 for 5 Bay Trailer
Storage Bays for (4), or (5) Containers	4" x 30' Nylon Ratchet Hold Down - (per bay)	Operation & Maintenance Manual
Main Frame is wide flange 10" I-Beam	3/8" DOT Service & Emergency Air Lines w/ Glad Hands	1 year limited trailer warranty

CDT (Solid Floor) TRAILERS FOR FRONT & REAR LOAD CONTAINERS

Model	Description	Trailer Length
CDT-3	20K lb. Rated Capacity, (2) Axle Slip Spring Ride Suspension - (3) Bay Trailer - 252869	20' 8" Deck Length 30' 3" - Overall Length
CDT-4	20K lb. Rated Capacity, (2) Axle Slip Spring Ride Suspension - (4) Bay Trailer - 213450	27' 9" Deck Length 37' 4" - Overall Length
CDT-5	20K lb. Rated Capacity, (2) Axle Slip Spring Ride Suspension - (5) Bay Trailer - 217419	34' 6" Deck Length 44' 1" - Overall Length
CDT-3E	20K lb. Rated Capacity, (2) Axle Slip Spring Ride Suspension w/ Electric Brakes - (3) Bay Trailer - 252779	20' 8" Deck Length 30' 3" - Overall Length
CDT-4E	20K lb. Rated Capacity, (2) Axle Slip Spring Ride Suspension w/ Electric Brakes - (4) Bay Trailer - 252981	27' 9" Deck Length 37' 4" - Overall Length
CDT-5E	20K lb. Rated Capacity, (2) Axle Slip Spring Ride Suspension w/ Electric Brakes - (5) Bay Trailer - 252982	34' 6" Deck Length 44' 1" - Overall Length

CDT (Solid Floor) TRAILER OPTIONS

Model	Description
M008	FACTORY MOUNT - Sliding Ratchet Container Hold Down Assembly for Four (4) Bay Trailer
M009	FACTORY MOUNT - Sliding Ratchet Container Hold Down Assembly for Five (5) Bay Trailer
MLD	Manual Spring Loaded Drop Leg Assembly - CDT Trailers Only
RTHD	FACTORY MOUNT - Built with Extra Standard Nylon Ratchet Hold Down Assembly for Trailers (parts and labor) - (Priced Per Set, LH & RH) - 4537BO

SLCH - SINGLE LOADED CONTAINER HANDLER

SLCH Loaded Container Handler Includes the Following Standard Features:

5" x 3" Frame Assembly ASTM A500 Grade "C"	Inside Air Controls for Conventional Cab 3 Spool with Rotator; (Joystick)	Backup & Hoist Up Alarm w/ Signal Light in Cab
T1 1/2" Fabricated Pivot Assembly	4-Spool Manual Outside Control Valve (25 GPM)	Pintle Hitch Adaptable Apron/One Piece Bumper
4" x 3" x 1/4" Mast Assembly w/ 60" T1 Steel Forks (adjustable 24" of travel on 'X' models)	200 Degree Rotating Mast (On non-NR models) - 8k lb. max. lift, 4k lb. max. rotating	All In One - Rear Apron & Bumper w/ LED Recessed Lighting
(2) 6" x 3" DA Lift Cylinders	Main Frame Bolt-On Wear Strips	DOT Approved LED Lights for Stop, Turn, Reverse & Side Markers
(2) 5" x 2" DA Tilt Cylinders	Hydraulic Tube Plumbing w/ JIC Fittings	Fenders Not Included
Mounting Plates & Grade 5 Mounting Bolts (HUCK Bolts Optional)	Container Retainer Straps	Mud Flaps
Dual Hoist Safety Props	Polyurethane Container Bumpers	Ship-Outs in Black Primer
Gear Pump 1 1/4" 8-Tooth (23 GPM @ 3,800 psi)	Rear Load Container Attachment on Blunderbust Fork Assembly	Operation & Maintenance Manual
20 Gal. Oil Reservoir - Inside Frame w/ Dual Temp. & Sight Gauge	3/8" Chain w/ Grab Hook & Safety Hook for REL Container Securement	1 yr. limited warranty on Hoist / 2 yr. limited Hydraulic Warranty

Model	Description	Container Range
SLCH-93NR	Loaded container handler w/o rotator - 93" Clear CA	FEL (2 - 10 yd) / REL (2 - 6 yd)
SLCH-113NR	Loaded container handler w/o rotator - 113" Clear CA	FEL (2 - 10 yd) / REL (2 - 6 yd)
SLCH-93	Loaded container handler with rotator - 93" Clear CA	FEL (2 - 10 yd) / REL (2 - 6 yd)
SLCH-113	Loaded container handler with rotator - 113" Clear CA	FEL (2 - 10 yd) / REL (2 - 6 yd)
SLCH-93X	Loaded container handler with rotator - 93" Clear CA w/ Adjustable Fork Heights	FEL (2 - 10 yd) / REL (2 - 6 yd)
SLCH-113X	Loaded container handler with rotator - 113" Clear CA w/ Adjustable Fork Heights	FEL (2 - 10 yd) / REL (2 - 6 yd)
SLCH-93XNR	Loaded container handler w/o rotator - 93" Clear CA	FEL (2 - 10 yd) / REL (2 - 6 yd)
SLCH-113XNR	Loaded container handler w/o rotator - 113" Clear CA	FEL (2 - 10 yd) / REL (2 - 6 yd)

FACTORY MOUNTING

Factory Mounting to Include: Phosphate Wash, (2) Part Epoxy Primer and Paint and Dual Viscosity Oil.

SAMTG	FACTORY MOUNT - Single Axle Hoist--Includes Huck Bolts, Dual Viscosity Oil, Two Part Epoxy Primer & Paint
MTG2	FACTORY MOUNT - Any Hoist--on Used Chassis
SAMTG3	FACTORY MOUNT - Single Axle Hoist--on Cab Over Chassis
MTG4	FACTORY MOUNT - Any Hoist--Move the Chassis Air Tank Using the Existing Mounting Hardware
MTG5	FACTORY MOUNT - Any Hoist--Relocate: Air Tank; Air Dryer; Fuel Filter; Cross Member & Battery Box - Battery Cables NOT INCLUDED (priced per item)
MTG6	FACTORY MOUNT - Any Hoist--Install Galbreath Supplied Battery Box - Battery Cables NOT INCLUDED (priced per item)
BSLIDE	FACTORY MOUNT - Slide Camelback Bogie Suspension
BSLIDE1	FACTORY MOUNT - Slide M2 or T-Ride Bogie Suspension

Loaded Container Handler (SLCH) Minimum Truck Specifications: 163" Wheelbase, Clear CA of 93", After frame of 32", Frame Height based on 43" with a Section Modulus of 15.5 cubic inches - 50,000 PSI Minimum Steel Frame, 25,900 lbs GVWR, Dual Rear Wheels, 23GPM Pump with Operating Pressure of 3,800 PSI. Add 36" to Clear CA for Toter Platform.