

AR (Anthony RailTrac®) is a classic medium rail liftgate, with spring- assisted platform operation and an extensive list of available configurations.

Its durable roller chain drive allows all hydraulic components to be guarded safely within the liftgate housing. Lift cycle friction is minimized by advanced anti-wear pads which eliminate the need to lubricate or replace rollers, common in competitive models. Plus, AR offers a huge variety of steel and aluminum platforms, and three corrosion resistance finishes, including stainless steel.

RECOMMENDED APPLICATIONS


LIGHT/MEDIUM DUTY





MARINE DUTY CONTROLS

Inside every Anthony toggle control is a premium-quality, IP-67 rated, stainless steel switch. Its terminals are fully encased in a thick epoxy coating which guards against dust, moisture intrusion, and loose electrical connections that can lead to unwelcome downtime.





STANDARD MODELS				
MODEL	AR-1200	AR-1800	AR-2000	AR-2500
Capacity (lbs.)	1200	1800	2000	2500
Bed Height (Min-Max)	28" - 58"	28" - 58"	28" - 58"	28" - 58"
MODEL WIDTH	PLATFORM WIDTH			
90" (92" Body)		86"		
94" (96" Body)		90"		
100" (102" Body)		96"		
AVAILABLE PLATFORMS				
Single Piece Steel 36" or 42" + 6" Fixed				
Single Piece Steel 36" or 42" + 12" Fixed				
Single Piece Aluminum 33", 39", 44", 50", 60" + 12" Fixed				
Single Piece Aluminum 33", 39", 44", 50", 60" + 12" ARR				

Cart stops available on any platform

For mounting requirements, visit anthonyliftgates.com/mountingrequirements

78" wide models available

30