A DIFFFRENT POINT OF VIEW.

Get a better look at your high-quality work as you move onto the next job with the WESTERN® Low Profile tailgate spreaders. This high-density, single-stage, poly tailgate spreader sits lower on trucks to deliver top spreader performance without affecting the operator's view from behind the wheel.

ELECTRIC MOTOR

A fully enclosed, 12-volt electric, 1/3 hp motor is mounted inside a sealed housing, protecting it from corrosion.

CONTROLS

Choose between a variable-speed control with an "on/off" button and blast option to optimize material usage or a basic "on/off" toggle control (controls are sold separately).

COVER

A latching, molded polyethylene lid protects de-icing material from the elements.

SPINNER AND SPREADING WIDTH

Models 500 and 1000 both feature a durable 10" polyurethane spinner that delivers a spreading width of up to 30'. Model 2500 comes standard with a large, 15" polyurethane spinner that delivers a spreading width of up to 30'.

MATERIAL DELIVERY

Material is delivered by a powder coated, vertical, steel auger to provide long-lasting, reliable performance.

ADJUSTABLE FEED GATE

On Model 2500, a specialized "saw-tooth" feed gate and auger design combine to deliver complete, reliable flow control with positive shut-off, eliminating spillage and waste.

RATCHET STRAPS

Ratchet straps are provided standard for additional spreader stability on the Model 500 and 2500 spreaders only.

LOW PROFILE

ACCESSORIES

MODELS 500 AND 1000

Top Screen | Adjustable Deflector Truck Protector Flap (Model 1000 only)

MODEL 2500

Top Screen | 5 Flight Auger



CAPACITY AND MOUNT OPTIONS

MODEL 500 - 5.0 cu ft capacity Comes standard with a Class III receiver hitch mount.

MODEL 1000 - 8.0 cu ft capacity Available mount options include a Class IV receiver hitch mount, a fixed mount, or a dual-swing mount*.

MODEL 2500 - 8.5 cu ft capacity Comes standard with a Class IV receiver hitch mount.

*Mounts sold separately

