

## CONSISTENCY MEETS EFFICIENCY.

Designed to attach to a wide variety of vehicles, the WESTERN® PRO-FLO™ 525 and PRO-FLO™ 900 tailgate spreaders feature a two-stage, auger-fed delivery system and dual variable-speed control for consistent and efficient flow of all types of de-icing materials, including rock salt and sand.

### DUAL ELECTRIC MOTORS

Two instant-start, 12-volt electric motors provide quiet, reliable, independent control over the auger and spinner mechanisms. The spinner motor is sealed inside a weather-resistant housing, protecting it from corrosion.

### MATERIAL DELIVERY

Material is delivered by a heavy-duty, powder coated, horizontal steel auger that automatically backs itself in and out until an obstruction is cleared or a required adjustment has been made.

### DUAL VARIABLE-SPEED CONTROL

Enhanced, dual variable-speed control allows you to precisely match material delivery and spread patterns to conditions. Four standard accessory buttons and a dedicated blast button provide optimum in-cab efficiency. Easy-to-understand, digital self-diagnostics alert the operator when the spreader is empty or when adjustments are needed, and LEDs make the control easy to read. Its compact size compared to traditional controls fits easily into today's modern truck cab designs.

### SPINNER AND SPREADING WIDTH

PRO-FLO 525 spreader features a 10" nylon/glass-reinforced resin spinner that delivers a spreading width up to 30'. The PRO-FLO 900 spreader features a 12" steel spinner that delivers a spreading width up to 40'.

### INVERTED V / VIBRATOR

The standard inverted V helps keep sufficient material weight off of the auger, ensuring smooth startup and flow of material. The inverted V is directly connected to a 12-volt vibrator to help reduce bridging and keep material moving to the auger.

### ACCESSORY INTEGRATION

Conveniently connect accessories directly into the spreader module mounted in the spinner motor enclosure. Accessories automatically integrate with the tailgate control without having to run additional wires from the front of the truck.

### TOP SCREEN AND COVER

The steel rod top screen breaks up chunks of de-icing material and a molded polyethylene lid protects the materials from the elements.

### ACCESSORIES

Material Control Tube | Work Light Kit



### CAPACITY AND MOUNT OPTIONS

#### PRO-FLO 525 SPREADER

This 5.25 cu ft poly hopper holds up to 420 lb of bagged or bulk salt, sand, or a 50/50 mix; assumes dry, free-flowing materials. Comes standard with a 2" receiver hitch and 3-point hitch mount.

#### PRO-FLO 900 SPREADER

This 9.00 cu ft poly hopper holds up to 720 lb of bagged or bulk salt, sand, or a 50/50 mix; assumes dry, free-flowing materials. Available mount options include a pivot mount, 2" receiver hitch (requires additional adapter) and 3-point hitch mount.\*

\*Mounts sold separately

