

## O.M.G. NOZZLE

For cleaning commercial pipe where pressure on the pipe wall is not desirable

The OMG Nozzle is a Tier Three Fluid Mechanics large nozzle suitable for storm drain or sewer cleaning applications where pipe walls may be compromised and pressure on the pipe wall is not desired. The OMG is ideal for cleaning deteriorated pipe, corrugated metal pipe, or concrete pipe.

The OMG Nozzle offers superior performance in damaged or deteriorated pipe. The Tier Three design offers the ability to separate water coming into the nozzle and water coming from the nozzle. The large shape and design of the OMG provides optimal cleaning with minimal to no damage to the integrity of the pipe.

The OMG Nozzle is available with 13 titanium ceramic inserts. It has 12 jets; six jets at 8 degrees, and six jets at 12 degrees with an optional forward zero-degree jet. A blank can be inserted to remove flow in the forward jet.



## **ADVANTAGES**

- Tier Three Efficiency & Power
- High Thrust with 8° & 12° Jets
- Long Design Spans Holes in Pipe
- Minimal Force on Pipe Wall
- Replaceable Inserts

## **APPLICATIONS**

- SANITARY, STORM
- Pipe with No Bottom
- Concrete & Corrugated Metal
- Penetrating, Flushing, Pulling
- Clearing a Path for Other Nozzles
- \* See accessories section for Pulling Eye Option and other available products sold separately.

## KEG O.M.G. NOZZLE WITH FORWARD JET

Product Shown Above	Part Number	Hose Size	Number of Inserts	Insert Size	Weight (pounds)	Dimensions	Pipe Size
А	100266-C	1.5" down to .75"	12 Rear 1 Forward	M14	36	18.25" x 4.25"	From 8"

The OMG Nozzle is only available with titanium ceramic inserts