

Standard LX



The Standard LX, an E.H. Wachs exclusive valve maintenance trailer, comes with our industry-leading ERV-750 extended reach valve exerciser, our newest controller – the HC-100 wireless handheld computer / controller / datalogger with GPS and VITALS software, and our 500CFM-11in Hg vacuum with hydraulic slide, tilt & dump (rear discharge) with latching rear door spoils tank. Loaded with storage, and accessories this trailer is ready for serious valve exercising work.

FEATURES

- ERV-750 extended reach, 750 ft/lbs valve exerciser
- Ruggedized HC-100 controller/data logger with built in GPS
- Available in two types of engines:

Diesel: Tier 4 compliant Kubota 1.1 L, I-3 4-stroke, liquid cooled IDI. #77-000-38 Gas: 27HP Kohler overhead cam, air cooled, #77-000-36

- HTMA Class II circuit, 10 gal reservoir, fan cooled heat exchanger, 8gpm @1800psi
- Positive displacement blower provides 500 CFM-11in Hg vacuum
- 250 gal spoils tank utilizing exclusive hydraulic slide, tilt & dump (rear discharge) with latching rear door.
- 2.5 GPM@3000 psi pressure washer system with 95 gallon water tank.

INCLUDES

- 2 1/2in, 1 1/4in & 7/8in suction wands
- Short & long wash-down guns
- 20ft suction hose
- 50ft retractable water hose reel

LX PACKAGE BUNDLE

- LED light bar
- Auxiliary hose reel
- Bluetooth connectivity
- Job box



TRAILER

Designed for ease of use, the Standard LX rear-mounted spoils tank gets the job done



2.5GPM@3000 psi pressure washer with 95 gallon water tank makes clean-up easy

SPECIFICATIONS

- Gross Vehicle Weight: 7000 lb (3175 kg)
- Length: 15 ft, Height: 7 ft, Width: 7 1/2 ft