

VSA FVR 2022



Current report content is based on data as of 2021-07-12 08:30:50. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



VSA FVR 2022 (2022 FVR, MV1 152"WB, 127"CA, 33,000 GVWR. White, standard model specifications with power windows, power door locks, air conditioning, 5.57 final ratio, 11R22.5G tires, 21,000 multi leaf suspension, steel wheel, and 50 gallon aluminum fuel tank

	Code	Description	MSRI
Model		<u> </u>	
	MV1	FVR 152"WB, 127"CA	\$95,880.00
	G1	White, standard model specifications with power windows, power door locks, air conditioning, 5.57 final ratio, 11R22.5G tires, 21,000 multi leaf suspension, steel wheel, and 50 gallon aluminum fuel tank	\$0.0
Vehicle Applic	cation		
	RQ2	Truck Application	Inc
Emissions			
	YF5	California Emissions	Inc
Tires			
	I5H	LRR (low rolling resistance)	Inc
	5S8	11R22.5 G	Inc
Engine			
Ū	IE8	Cummins B6.7, diesel engine, 408 CID (6.7L), 260 HP at 2400 RPM, 660 lbft. gross torque at 1600 RPM, 6-cylinder, turbocharged, inter-cooled, EGR cooler, high pressure common rail fuel system, and single module aftertreatment.	Inc
Transmission			
	Y6T	Allison RDS 2500 / 6 speed trans w/ PTO gear	Inc
Wheelbase			
	39W	152" Wheelbase 127"CA	Inc
Air Cleaner			
	E6U	Dry paper single element. (Donaldson)	Inc
Alternator		, ,	
	KW1	160 AMP. with integral regulator.	Inc
Battery		100 / 1111 / 1110 / 1110 / 1100	
,	IX1	Dual 12-Volt maintenance free group 31 750 CCA batteries with threaded posts	Inc
Exhaust			
	I0B	Single module Cummins aftertreatment w/ DPF & SCR, exhaust cooler, and electronic exhuast restriction.	Inc
Front Axle			
	40C	Dana E1254-W 12,000 lbs. capacity	Inc
Rear Axle			
	M21	Dana S21-140 single-speed axle, 21,000 lbs. capacity	In
Ratio			
	011	5.571:1	Inc
Fuel Tank			
	70A	Left hand rail	Inc
	THF	50 Gallon Fuel Tank Capacity	In

Current report content is based on data as of 2021-07-12 08:30:50. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



VSA FVR 2022 (2022 FVR, MV1 152"WB, 127"CA, 33,000 GVWR. White, standard model specifications with power windows, power door locks, air conditioning, 5.57 final ratio, 11R22.5G tires, 21,000 multi leaf suspension, steel wheel, and 50 gallon aluminum fuel tank

	Code	Description	MSRF
Seat			
	A56	Level air suspension seat with RH armrest driver seat	Inc
Brakes			
	Z06	Full air dual circuit, s-cam, drum	Inc
Air Conditioning	l		
	C60	Air conditioner	Inc
Power Windows	& Door I	Locks	
	IL0	Yes	Inc
Floor Mats			
	IQ6	Standard Floor Mats	Inc
Model Option			
	G1	White, standard model specifications with power windows, power door locks, air conditioning, 5.57 final ratio, 11R22.5G tires, 21,000 multi leaf suspension, steel wheel, and 50 gallon aluminum fuel tank	Inc
CAB			
	729	Arc white color	Inc
Mirrors			
	DJ6	Black mirror head with black stays	Inc
Frame			
	7KJ	Straight frame, 80,000 PSI, 33.5 wide	Inc
Rear Springs			
	34L	21,000 lbs. capacity	Inc
	SAS	Multi leaf, bolted	Inc
Front Springs			
	34K	12,000 lbs. capacity	Inc
Accessories			
	8RP	Radio AM/FM/CD with Bluetooth	Inc
	IX2	Rear body dome lamp switch	Inc
Air Compressor			
	104	17 CFM turbocharged heavy duty.	Inc
Totals			
		Base Price	\$95,880.0
		Destination Charge	\$2,200.0
		DEF Fill Charge	\$10.0
		Total Options Price	
		Tire Weight Tax	\$151.6
		Total	\$98,241.6

Current report content is based on data as of 2021-07-12 08:30:50. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



VSA FVR 2022 (2022 FVR, MV1 152"WB, 127"CA, 33,000 GVWR. White, standard model specifications with power windows, power door locks, air conditioning, 5.57 final ratio, 11R22.5G tires, 21,000 multi leaf suspension, steel wheel, and 50 gallon aluminum fuel tank

Code	Description			
Vehicle App	•			
RQ2	Truck Application			
Emissions				
YF5	California Emissions			
Tires				
I5H	LRR (low rolling resistance)			
5S8	11R22.5 G			
Engine				
IE8	Cummins B6.7, diesel engine, 408 CID (6.7L), 260 HP at 2400 RPM, 660 lbft. gross torque at 1600 RPM, 6-cylinder, turbocharged, inter-cooled, EGR cooler, high pressure common rail fuel system, and single module aftertreatment.			
Transmissio	n			
Y6T	Allison RDS 2500 / 6 speed trans w/ PTO gear			
Wheelbase				
39W	152" Wheelbase 127"CA			
Air Cleaner				
E6U	Dry paper single element. (Donaldson)			
Alternator				
KW1	160 AMP. with integral regulator.			
Battery				
IX1	Dual 12-Volt maintenance free group 31 750 CCA batteries with threaded posts			
Exhaust				
I0B	Single module Cummins aftertreatment w/ DPF & SCR, exhaust cooler, and electronic exhuast restriction.			
Front Axle				
40C	Dana E1254-W 12,000 lbs. capacity			
Rear Axle				
M21	Dana S21-140 single-speed axle, 21,000 lbs. capacity			
Ratio				
011	5.571:1			
Fuel Tank				
70A	Left hand rail			
THF	50 Gallon Fuel Tank Capacity			
Seat				
A56	Level air suspension seat with RH armrest driver seat			
Brakes				
Z06	Full air dual circuit, s-cam, drum			
Air Condition	•			
C60	Air conditioner			
	ows & Door Locks			
IL0	Yes			
Floor Mats				
IQ6	Standard Floor Mats			
Model Optio				
G1	White, standard model specifications with power windows, power door locks, air conditioning, 5.57 final ratio, 11R22.5G tires 21,000 multi leaf suspension, steel wheel, and 50 gallon aluminum fuel tank			

Current report content is based on data as of 2021-07-12 08:30:50. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.

Initial:



VSA FVR 2022 (2022 FVR, MV1 152"WB, 127"CA, 33,000 GVWR. White, standard model specifications with power windows, power door locks, air conditioning, 5.57 final ratio, 11R22.5G tires, 21,000 multi leaf suspension, steel wheel, and 50 gallon aluminum fuel tank

Standard Equipment Summary					
Code	Description				
CAB					
729	Arc white color				
Mirrors					
DJ6	Black mirror head with black stays				
Frame					
7KJ	Straight frame, 80,000 PSI, 33.5 wide				
Rear Spring	S .				
34L	21,000 lbs. capacity				
SAS	Multi leaf, bolted				
Front Spring	js				
34K	12,000 lbs. capacity				
Accessories					
8RP	Radio AM/FM/CD with Bluetooth				
IX2	Rear body dome lamp switch				
Air Compres	ssor				
104	17 CFM turbocharged heavy duty.				

Current report content is based on data as of 2021-07-12 08:30:50. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.