

VSA NPR GAS REG CAB 2022



Current report content is based on data as of 2021-07-12 07:58:22. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



VTC ISUZU TRUCK

Logan Grimm

VSA NPR GAS REG CAB 2022 (2022 NPR Gas Cab Chassis, 1C1 109"WB, 86.5"CA, 12,000 GVWR.
White, Standard model specifications with power windows and door locks

Selected Model and Options

	Code	Description	MSRP
Model			
	1C1	NPR Gas Cab Chassis 109"WB, 86.5"CA	\$46,600.00
	04	White, Standard model specifications with power windows and door locks	\$0.00
Vehicle Application			
	RQ2	Truck Application	Inc.
Tires			
	I5H	LRR (low rolling resistance)	Inc.
Engine			
	L8T	GMPT 6.6L (400 CID) V8 gasoline engine; 350 HP at 4500 RPM; 425 lb-ft torque at 3800 RPM; precise fuel control direct injection technology; electronic throttle control; overhead valves with variable valve timing; heavy duty cast-iron cylinder block with six-bolt main-bearing cap; cast aluminum cylinder heads; forged steel crankshaft; stainless steel exhaust manifold.	Inc.
Transmission			
	MYD	6L90-E Hydra-Matic, 6-speed automatic with lock-up converter and overdrive. Ratios: Gear and Ratios 4.027, 2.364, 1.532, 1.152, 0.0852, 0.667, Rev. 3.064:1	Inc.
Wheelbase			
	IA8	109 inches, includes ladder type channel frame. Full C section straight frame 33.5 inches wide. Yield strength 44,000 psi; section modulus 7.20 in ³ RBM 316,800 lb./ft./in. per rail. 86.5"CA	Inc.
Air Cleaner			
	KNX	Dry paper single element. Air cleaner canister standard with air restriction gauge.	Inc.
Alternator			
	KW7	170 Amp. output with integral regulator.	Inc.
Battery			
	IL3	Single Delco 12-V maintenance free 750 CCA frame mounted battery box	Inc.
Exhaust			
	I41	Single horizontal aluminized steel with catalytic converter and oxygen sensor devices.	Inc.
Front Axle			
	ID2	"I"-beam rated at 6,830 lbs. Includes integral hydraulic power steering. Ratio 18.8-20.9:1.	Inc.
Front Suspension			
	I0K	7,220 lbs. Capacity semi elliptical tapered leaf spring. Includes shock absorbers and stabilizer bar.	Inc.
Front Wheels			
	RBY	16" X 6", 6-hole disc, painted white.	Inc.
Front Tires			

Current report content is based on data as of 2021-07-12 07:58:22. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



VTC ISUZU TRUCK

Logan Grimm

VSA NPR GAS REG CAB 2022 (2022 NPR Gas Cab Chassis, 1C1 109"WB, 86.5"CA, 12,000 GVWR.
White, Standard model specifications with power windows and door locks

Selected Model and Options

Code	Description	MSRP
I53I69	215/85R16E (10 ply) tubeless Radial, all season tread.	Inc.
Rear Suspension		
I8J	12,900 lbs. Capacity semi elliptical; main and auxiliary multi- leaf spring. Includes shock absorbers.	Inc.
Rear Axle		
ID3	Single-speed, 14,550 lb. capacity with oil lubricated rear wheel bearings.	Inc.
Ratio		
066	4.100:1	Inc.
Rear Wheels		
RBZ	16" X 6", 6-hole disc, painted white.	Inc.
Rear Tires		
I53I34	215/85R16E (10 ply) tubeless Radial, all season tread.	Inc.
Fuel Tank		
A17	38.6 gal. rectangular fuel tank. Mounted between frame rail with electric type fuel pump (mounted in tank). Through the rail fuel fill.	Inc.
Seat		
AQB	Driver seat is reclining high back. Two single occupant fold down seats with tray backs.	Inc.
Brakes		
IR8	Dual circuit, vacuum assisted hydraulic with EBD (Electronic Brake Distribution). Disc front and self-adjust outboard mounted drum rear. Mechanical, transmission mounted parking brake. Non-asbestos semi metallic linings are standard. 4 channel anti-lock brake system.	Inc.
Air Conditioning		
C60	Air conditioner	Inc.
Power Windows & Door Locks		
IL0	Yes	Inc.
Model Option		
04	White, Standard model specifications with power windows and door locks	Inc.
Accessories		
IX2	Rear body dome lamp switch	Inc.
8RP	AM/FM/CD radio with Aux input/USB port and Bluetooth RPO	Inc.
Totals		
	Base Price	\$46,600.00
	Destination Charge	\$1,325.00
	DEF Fill Charge	\$0.00
	Total Options Price	\$
	Tire Weight Tax	\$0.00
	Total	\$47,925.00

Current report content is based on data as of 2021-07-12 07:58:22. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



VTC ISUZU TRUCK

Logan Grimm

VSA NPR GAS REG CAB 2022 (2022 NPR Gas Cab Chassis, 1C1 109"WB, 86.5"CA, 12,000 GVWR.
White, Standard model specifications with power windows and door locks

Standard Equipment Summary

Code	Description
Vehicle Application	
RQ2	Truck Application
Tires	
I5H	LRR (low rolling resistance)
Engine	
L8T	GMPT 6.6L (400 CID) V8 gasoline engine; 350 HP at 4500 RPM; 425 lb-ft torque at 3800 RPM; precise fuel control direct injection technology; electronic throttle control; overhead valves with variable valve timing; heavy duty cast-iron cylinder block with six-bolt main-bearing cap; cast aluminum cylinder heads; forged steel crankshaft; stainless steel exhaust manifold.
Transmission	
MYD	6L90-E Hydra-Matic, 6-speed automatic with lock-up converter and overdrive. Ratios: Gear and Ratios 4.027, 2.364, 1.532, 1.152, 0.0852, 0.667, Rev. 3.064:1
Wheelbase	
IA8	109 inches, includes ladder type channel frame. Full C section straight frame 33.5 inches wide. Yield strength 44,000 psi; section modulus 7.20 in ³ RBM 316,800 lb./ft./in. per rail. 86.5"CA
Air Cleaner	
KNX	Dry paper single element. Air cleaner canister standard with air restriction gauge.
Alternator	
KW7	170 Amp. output with integral regulator.
Battery	
IL3	Single Delco 12-V maintenance free 750 CCA frame mounted battery box
Exhaust	
IA1	Single horizontal aluminized steel with catalytic converter and oxygen sensor devices.
Front Axle	
ID2	"I"-beam rated at 6,830 lbs. Includes integral hydraulic power steering. Ratio 18.8-20.9:1.
Front Suspension	
IOK	7,220 lbs. Capacity semi elliptical tapered leaf spring. Includes shock absorbers and stabilizer bar.
Front Wheels	
RBV	16" X 6", 6-hole disc, painted white.
Front Tires	
I53I69	215/85R16E (10 ply) tubeless Radial, all season tread.
Rear Suspension	
I8J	12,900 lbs. Capacity semi elliptical; main and auxiliary multi- leaf spring. Includes shock absorbers.
Rear Axle	
ID3	Single-speed, 14,550 lb. capacity with oil lubricated rear wheel bearings.
Ratio	
066	4.100:1
Rear Wheels	
RBZ	16" X 6", 6-hole disc, painted white.
Rear Tires	
I53I34	215/85R16E (10 ply) tubeless Radial, all season tread.
Fuel Tank	
A17	38.6 gal. rectangular fuel tank. Mounted between frame rail with electric type fuel pump (mounted in tank). Through the rail fuel fill.
Seat	
AQB	Driver seat is reclining high back. Two single occupant fold down seats with tray backs.

Current report content is based on data as of 2021-07-12 07:58:22. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



VTC ISUZU TRUCK

Logan Grimm

VSA NPR GAS REG CAB 2022 (2022 NPR Gas Cab Chassis, 1C1 109"WB, 86.5"CA, 12,000 GVWR.
White, Standard model specifications with power windows and door locks

Standard Equipment Summary

Code	Description
Brakes	
IR8	Dual circuit, vacuum assisted hydraulic with EBD (Electronic Brake Distribution). Disc front and self-adjust outboard mounted drum rear. Mechanical, transmission mounted parking brake. Non-asbestos semi metallic linings are standard. 4 channel anti-lock brake system.
Air Conditioning	
C60	Air conditioner
Power Windows & Door Locks	
IL0	Yes
Model Option	
04	White, Standard model specifications with power windows and door locks
Accessories	
IX2	Rear body dome lamp switch
8RP	AM/FM/CD radio with Aux input/USB port and Bluetooth RPO

Current report content is based on data as of 2021-07-12 07:58:22. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.