



## VTC ISUZU TRUCK

Logan Grimm

# VSA NPR-HD DSL CREW CAB 2022



Current report content is based on data as of 2021-07-12 08:07:01. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



# VTC ISUZU TRUCK

Logan Grimm

VSA NPR-HD DSL CREW CAB 2022 (2022 NPR-HD Crew Cab Chassis, 3G3 150"WB, 88.5"CA, 14,500 GVWR. White, 30 Gallon Stainless Steel In-Rail Fuel Tank with power windows, power door locks and air conditioning

## Selected Model and Options

|                         | Code   | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                    | MSRP        |
|-------------------------|--------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------|
| <b>Model</b>            |        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                |             |
|                         | 3G3    | NPR-HD Crew Cab Chassis 150"WB, 88.5"CA                                                                                                                                                                                                                                                                                                                                                                                                                        | \$62,864.00 |
|                         | 54     | White, 30 Gallon Stainless Steel In-Rail Fuel Tank with power windows, power door locks and air conditioning                                                                                                                                                                                                                                                                                                                                                   | \$0.00      |
| <b>Tires</b>            |        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                |             |
|                         | I5H    | LRR (low rolling resistance)                                                                                                                                                                                                                                                                                                                                                                                                                                   | Inc.        |
| <b>Engine</b>           |        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                |             |
|                         | I1B    | 4HK1-TC, diesel engine 317 CID (5.19L), 215 HP at 2550 RPM: 452 ft.-lb. gross torque at 1850 RPM. 4 cylinder, 16 valve, four cycle, overhead cam, turbocharged, inter-cooled, water cooled EGR valve, direct injection, electronically controlled common rail fuel system, engine cruise control function. Oil level check switch and light. Engine Warning system with audible warning for low oil pressure, high coolant temperature, and low coolant level. | Inc.        |
| <b>Transmission</b>     |        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                |             |
|                         | I1W    | Aisin A465id 6-speed automatic transmission, Ratios: 3.742, 2.003, 1.343,                                                                                                                                                                                                                                                                                                                                                                                      | Inc.        |
| <b>Wheelbase</b>        |        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                |             |
|                         | IH6    | 150 inches, includes ladder type channel frame. Full C section straight frame 33.5 inches wide. Yield strength 44,000 psi; section modulus 11.89 in3 RBM 523,160 lb./ft./in. per rail. 88.5"CA                                                                                                                                                                                                                                                                 | Inc.        |
| <b>Air Cleaner</b>      |        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                |             |
|                         | KNX    | Dry Paper single element. (Donaldson brand) Air cleaner canister standard with air restriction indicator in the driver's Multi-Information Display (MID).                                                                                                                                                                                                                                                                                                      | Inc.        |
| <b>Alternator</b>       |        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                |             |
|                         | I2C    | 140 AMP. with integral regulator.                                                                                                                                                                                                                                                                                                                                                                                                                              | Inc.        |
| <b>Battery</b>          |        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                |             |
|                         | IX1    | Dual 12-Volt maintenance free group 31 750 CCA batteries with threaded posts                                                                                                                                                                                                                                                                                                                                                                                   | Inc.        |
| <b>Exhaust</b>          |        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                |             |
|                         | IX7    | Single horizontal with DPF/SCR exhaust system                                                                                                                                                                                                                                                                                                                                                                                                                  | Inc.        |
| <b>Front Axle</b>       |        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                |             |
|                         | ID2    | "I"-beam rated at 6,830 lbs. Includes integral hydraulic power steering. Ratio 18.8-20.9:1.                                                                                                                                                                                                                                                                                                                                                                    | Inc.        |
| <b>Front Suspension</b> |        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                |             |
|                         | ID4    | 6,830 lb. capacity. Semi-elliptical tapered leaf springs. Includes shock absorbers and stabilizer bar.                                                                                                                                                                                                                                                                                                                                                         | Inc.        |
| <b>Front Wheels</b>     |        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                |             |
|                         | RBV    | 16" X 6", 6-hole disc, painted white.                                                                                                                                                                                                                                                                                                                                                                                                                          | Inc.        |
| <b>Front Tires</b>      |        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                |             |
|                         | I53I69 | 215/85R16E (10 ply) tubeless Radial, all season                                                                                                                                                                                                                                                                                                                                                                                                                | Inc.        |

Current report content is based on data as of 2021-07-12 08:07:01. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



# VTC ISUZU TRUCK

Logan Grimm

VSA NPR-HD DSL CREW CAB 2022 (2022 NPR-HD Crew Cab Chassis, 3G3 150"WB, 88.5"CA, 14,500 GVWR. White, 30 Gallon Stainless Steel In-Rail Fuel Tank with power windows, power door locks and air conditioning

## Selected Model and Options

| Code                                  | Description                                                                                                                                                               | MSRP        |
|---------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------|
|                                       | tread.                                                                                                                                                                    |             |
| <b>Rear Suspension</b>                |                                                                                                                                                                           |             |
| I27                                   | 9,880 lbs. capacity. Semi-elliptical main and auxiliary multi-leaf springs. Includes shock absorbers                                                                      | Inc.        |
| <b>Rear Axle</b>                      |                                                                                                                                                                           |             |
| I36                                   | R040, single-speed, 11,020 lb. capacity with oil lubricated rear wheel bearings.                                                                                          | Inc.        |
| <b>Ratio</b>                          |                                                                                                                                                                           |             |
| 005                                   | 4.56:1                                                                                                                                                                    | Inc.        |
| <b>Rear Wheels</b>                    |                                                                                                                                                                           |             |
| RBZ                                   | 16" X 6", 6-hole disc, painted white.                                                                                                                                     | Inc.        |
| <b>Rear Tires</b>                     |                                                                                                                                                                           |             |
| I53I34                                | 215/85R16E (10 ply) tubeless Radial, all season tread.                                                                                                                    | Inc.        |
| <b>Fuel Tank</b>                      |                                                                                                                                                                           |             |
| I4I                                   | 30 Gallon Stainless Steel In-Rail Fuel Tank                                                                                                                               | Inc.        |
| <b>Seat</b>                           |                                                                                                                                                                           |             |
| AQB                                   | Driver seat is reclining high back. Two single occupant fold down seats with tray backs.                                                                                  | Inc.        |
| <b>Brakes</b>                         |                                                                                                                                                                           |             |
| K40                                   | Butterfly valve type exhaust brake                                                                                                                                        | Inc.        |
| IE1                                   | Vacuum + Power Assist; hydraulic 4-wheel disc brakes with 4-channel ABS. Mechanical, transmission mounted parking brake. Non-asbestos semi metallic linings are standard. | Inc.        |
| <b>Air Conditioning</b>               |                                                                                                                                                                           |             |
| C60                                   | Air conditioner                                                                                                                                                           | Inc.        |
| <b>Power Windows &amp; Door Locks</b> |                                                                                                                                                                           |             |
| IL0                                   | Yes                                                                                                                                                                       | Inc.        |
| <b>Floor Mats</b>                     |                                                                                                                                                                           |             |
| IQ6                                   | Standard Floor Mats                                                                                                                                                       | Inc.        |
| <b>Model Option</b>                   |                                                                                                                                                                           |             |
| 54                                    | White, 30 Gallon Stainless Steel In-Rail Fuel Tank with power windows, power door locks and air conditioning                                                              | Inc.        |
| <b>Assistance System</b>              |                                                                                                                                                                           |             |
| I5I                                   | Electronic Vehicle Stability Control (EVSC) include ASR (Anti-Slip Regulation)                                                                                            | Inc.        |
| <b>Accessories</b>                    |                                                                                                                                                                           |             |
| IX2                                   | Rear body dome lamp switch                                                                                                                                                | Inc.        |
| 8RP                                   | AM/FM/CD radio with Aux input/USB port and Bluetooth RPO                                                                                                                  | Inc.        |
| <b>Totals</b>                         |                                                                                                                                                                           |             |
|                                       | Base Price                                                                                                                                                                | \$62,864.00 |
|                                       | Destination Charge                                                                                                                                                        | \$1,325.00  |

Current report content is based on data as of 2021-07-12 08:07:01. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



# VTC ISUZU TRUCK

Logan Grimm

VSA NPR-HD DSL CREW CAB 2022 (2022 NPR-HD Crew Cab Chassis, 3G3 150"WB, 88.5"CA, 14,500 GVWR. White, 30 Gallon Stainless Steel In-Rail Fuel Tank with power windows, power door locks and air conditioning

## Selected Model and Options

| Code | Description         | MSRP        |
|------|---------------------|-------------|
|      | DEF Fill Charge     | \$10.00     |
|      | Total Options Price | \$          |
|      | Tire Weight Tax     | \$0.00      |
|      | Total               | \$64,199.00 |

Current report content is based on data as of 2021-07-12 08:07:01. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



# VTC ISUZU TRUCK

Logan Grimm

VSA NPR-HD DSL CREW CAB 2022 (2022 NPR-HD Crew Cab Chassis, 3G3 150"WB, 88.5"CA, 14,500 GVWR. White, 30 Gallon Stainless Steel In-Rail Fuel Tank with power windows, power door locks and air conditioning

## Standard Equipment Summary

| Code                    | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|-------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Tires</b>            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| I5H                     | LRR (low rolling resistance)                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>Engine</b>           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| I1B                     | 4HK1-TC, diesel engine 317 CID (5.19L), 215 HP at 2550 RPM: 452 ft.-lb. gross torque at 1850 RPM. 4 cylinder, 16 valve, four cycle, overhead cam, turbocharged, inter-cooled, water cooled EGR valve, direct injection, electronically controlled common rail fuel system, engine cruise control function. Oil level check switch and light. Engine Warning system with audible warning for low oil pressure, high coolant temperature, and low coolant level. |
| <b>Transmission</b>     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| I1W                     | Aisin A465id 6-speed automatic transmission, Ratios: 3.742, 2.003, 1.343,                                                                                                                                                                                                                                                                                                                                                                                      |
| <b>Wheelbase</b>        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| IH6                     | 150 inches, includes ladder type channel frame. Full C section straight frame 33.5 inches wide. Yield strength 44,000 psi; section modulus 11.89 in3 RBM 523,160 lb./ft./in. per rail. 88.5"CA                                                                                                                                                                                                                                                                 |
| <b>Air Cleaner</b>      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| KNX                     | Dry Paper single element. (Donaldson brand) Air cleaner canister standard with air restriction indicator in the driver's Multi-Information Display (MID).                                                                                                                                                                                                                                                                                                      |
| <b>Alternator</b>       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| I2C                     | 140 AMP. with integral regulator.                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <b>Battery</b>          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| IX1                     | Dual 12-Volt maintenance free group 31 750 CCA batteries with threaded posts                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>Exhaust</b>          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| IX7                     | Single horizontal with DPF/SCR exhaust system                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>Front Axle</b>       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| ID2                     | "I"-beam rated at 6,830 lbs. Includes integral hydraulic power steering. Ratio 18.8-20.9:1.                                                                                                                                                                                                                                                                                                                                                                    |
| <b>Front Suspension</b> |                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| ID4                     | 6,830 lb. capacity. Semi-elliptical tapered leaf springs. Includes shock absorbers and stabilizer bar.                                                                                                                                                                                                                                                                                                                                                         |
| <b>Front Wheels</b>     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| RBV                     | 16" X 6", 6-hole disc, painted white.                                                                                                                                                                                                                                                                                                                                                                                                                          |
| <b>Front Tires</b>      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| I53I69                  | 215/85R16E (10 ply) tubeless Radial, all season tread.                                                                                                                                                                                                                                                                                                                                                                                                         |
| <b>Rear Suspension</b>  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| I27                     | 9,880 lbs. capacity. Semi-elliptical main and auxiliary multi-leaf springs. Includes shock absorbers                                                                                                                                                                                                                                                                                                                                                           |
| <b>Rear Axle</b>        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| I36                     | R040, single-speed, 11,020 lb. capacity with oil lubricated rear wheel bearings.                                                                                                                                                                                                                                                                                                                                                                               |
| <b>Ratio</b>            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| 005                     | 4.56:1                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <b>Rear Wheels</b>      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| RBZ                     | 16" X 6", 6-hole disc, painted white.                                                                                                                                                                                                                                                                                                                                                                                                                          |
| <b>Rear Tires</b>       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| I53I34                  | 215/85R16E (10 ply) tubeless Radial, all season tread.                                                                                                                                                                                                                                                                                                                                                                                                         |
| <b>Fuel Tank</b>        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| I4I                     | 30 Gallon Stainless Steel In-Rail Fuel Tank                                                                                                                                                                                                                                                                                                                                                                                                                    |
| <b>Seat</b>             |                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| AQB                     | Driver seat is reclining high back. Two single occupant fold down seats with tray backs.                                                                                                                                                                                                                                                                                                                                                                       |
| <b>Brakes</b>           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                |

Current report content is based on data as of 2021-07-12 08:07:01. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



# VTC ISUZU TRUCK

Logan Grimm

VSA NPR-HD DSL CREW CAB 2022 (2022 NPR-HD Crew Cab Chassis, 3G3 150"WB, 88.5"CA, 14,500 GVWR. White, 30 Gallon Stainless Steel In-Rail Fuel Tank with power windows, power door locks and air conditioning

## Standard Equipment Summary

| Code                                  | Description                                                                                                                                                               |
|---------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| K40                                   | Butterfly valve type exhaust brake                                                                                                                                        |
| IE1                                   | Vacuum + Power Assist; hydraulic 4-wheel disc brakes with 4-channel ABS. Mechanical, transmission mounted parking brake. Non-asbestos semi metallic linings are standard. |
| <b>Air Conditioning</b>               |                                                                                                                                                                           |
| C60                                   | Air conditioner                                                                                                                                                           |
| <b>Power Windows &amp; Door Locks</b> |                                                                                                                                                                           |
| IL0                                   | Yes                                                                                                                                                                       |
| <b>Floor Mats</b>                     |                                                                                                                                                                           |
| IQ6                                   | Standard Floor Mats                                                                                                                                                       |
| <b>Model Option</b>                   |                                                                                                                                                                           |
| 54                                    | White, 30 Gallon Stainless Steel In-Rail Fuel Tank with power windows, power door locks and air conditioning                                                              |
| <b>Assistance System</b>              |                                                                                                                                                                           |
| I5I                                   | Electronic Vehicle Stability Control (EVSC) include ASR (Anti-Slip Regulation)                                                                                            |
| <b>Accessories</b>                    |                                                                                                                                                                           |
| IX2                                   | Rear body dome lamp switch                                                                                                                                                |
| 8RP                                   | AM/FM/CD radio with Aux input/USB port and Bluetooth RPO                                                                                                                  |

Current report content is based on data as of 2021-07-12 08:07:01. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.