



## VTC ISUZU TRUCK

Logan Grimm

# VSA NPR-HD GAS CREW CAB 2022



Current report content is based on data as of 2021-07-12 08:03:17. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



# VTC ISUZU TRUCK

Logan Grimm

VSA NPR-HD GAS CREW CAB 2022 (2022 NPR-HD Gas Crew Cab, 1G3 150"WB, 88.5"CA, 14,500 GVWR. White, Standard model specifications with power windows and door locks

## Selected Model and Options

	Code	Description	MSRP
<b>Model</b>			
	1G3	NPR-HD Gas Crew Cab 150"WB, 88.5"CA	\$57,428.00
	04	White, Standard model specifications with power windows and door locks	\$0.00
<b>Vehicle Application</b>			
	RQ2	Truck Application	Inc.
<b>Tires</b>			
	I5H	LRR (low rolling resistance)	Inc.
<b>Engine</b>			
	L8T	GMPT 6.6L (400 CID) V8 gasoline engine; 350 HP at 4500 RPM; 425 lb-ft torque at 3800 RPM; precise fuel control direct injection technology; electronic throttle control; overhead valves with variable valve timing; heavy duty cast-iron cylinder block with six-bolt main-bearing cap; cast aluminum cylinder heads; forged steel crankshaft; stainless steel exhaust manifold.	Inc.
<b>Transmission</b>			
	MYD	6L90-E Hydra-Matic, 6-speed automatic with lock-up converter and overdrive. Ratios: Gear and Ratios 4.027, 2.364 ,1.532, 1.152, 0.0852, 0.667, Rev. 3.064:1	Inc.
<b>Wheelbase</b>			
	IB1	150 inches, includes ladder type channel frame. Full C section straight frame 33.5 inches wide. Yield strength 44,000 psi; section modulus 7.20in <sup>3</sup> RBM 316,800 lb./ft./in. per rail. 88.5"CA	Inc.
<b>Air Cleaner</b>			
	KNX	Dry paper single element. Air cleaner canister standard with air restriction gauge.	Inc.
<b>Alternator</b>			
	KW7	170 Amp. output with integral regulator.	Inc.
<b>Battery</b>			
	IL3	Single Delco 12-V maintenance free 750 CCA frame mounted battery box	Inc.
<b>Exhaust</b>			
	I41	Single horizontal aluminized steel with catalytic converter and oxygen sensor devices.	Inc.
<b>Front Axle</b>			
	ID2	"I"-beam rated at 6,830 lbs. Includes integral hydraulic power steering. Ratio 18.8-20.9:1.	Inc.
<b>Front Suspension</b>			
	I0K	7,220 lbs. Capacity semi elliptical tapered leaf spring. Includes shock absorbers and stabilizer bar.	Inc.
<b>Front Wheels</b>			
	IB9	19.5" x 6", 6-hole disc, painted white	Inc.
<b>Front Tires</b>			

Current report content is based on data as of 2021-07-12 08:03:17. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



# VTC ISUZU TRUCK

Logan Grimm

VSA NPR-HD GAS CREW CAB 2022 (2022 NPR-HD Gas Crew Cab, 1G3 150"WB, 88.5"CA, 14,500 GVWR. White, Standard model specifications with power windows and door locks

## Selected Model and Options

	Code	Description	MSRP
	I8B	225/70R19.5G (14 ply) tubeless Radial, all season tread	Inc.
<b>Rear Suspension</b>			
	I8J	12,900 lbs. Capacity semi elliptical; main and auxiliary multi- leaf spring. Includes shock absorbers.	Inc.
<b>Rear Axle</b>			
	ID3	Single-speed, 14,550 lb. capacity with oil lubricated rear wheel bearings.	Inc.
<b>Ratio</b>			
	092	4.300:1	Inc.
<b>Rear Wheels</b>			
	IC1	19.5" x 6", 6-hole disc, painted white	Inc.
<b>Rear Tires</b>			
	I9B	225/70R19.5G (14 ply) tubeless Radial, all season tread.	Inc.
<b>Fuel Tank</b>			
	A17	38.6 gal. rectangular fuel tank. Mounted between frame rail with electric type fuel pump (mounted in tank). Through the rail fuel fill.	Inc.
<b>Seat</b>			
	AQB	Driver seat is reclining high back. Two single occupant fold down seats with tray backs.	Inc.
<b>Brakes</b>			
	IR8	Dual circuit, vacuum assisted hydraulic with EBD (Electronic Brake Distribution). Disc front and self-adjust outboard mounted drum rear. Mechanical, transmission mounted parking brake. Non-asbestos semi metallic linings are standard. 4 channel anti-lock brake system.	Inc.
<b>Air Conditioning</b>			
	C60	Air conditioner	Inc.
<b>Power Windows &amp; Door Locks</b>			
	IL0	Yes	Inc.
<b>Model Option</b>			
	04	White, Standard model specifications with power windows and door locks	Inc.
<b>Accessories</b>			
	IX2	Rear body dome lamp switch	Inc.
	8RP	AM/FM/CD radio with Aux input/USB port and Bluetooth RPO	Inc.
<b>Totals</b>			
		Base Price	\$57,428.00
		Destination Charge	\$1,325.00
		DEF Fill Charge	\$0.00
		Total Options Price	\$
		Tire Weight Tax	\$26.64
		Total	\$58,779.64

Current report content is based on data as of 2021-07-12 08:03:17. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



# VTC ISUZU TRUCK

Logan Grimm

VSA NPR-HD GAS CREW CAB 2022 (2022 NPR-HD Gas Crew Cab, 1G3 150"WB, 88.5"CA, 14,500 GVWR. White, Standard model specifications with power windows and door locks

## Standard Equipment Summary

Code	Description
<b>Vehicle Application</b>	
RQ2	Truck Application
<b>Tires</b>	
I5H	LRR (low rolling resistance)
<b>Engine</b>	
L8T	GMPT 6.6L (400 CID) V8 gasoline engine; 350 HP at 4500 RPM; 425 lb-ft torque at 3800 RPM; precise fuel control direct injection technology; electronic throttle control; overhead valves with variable valve timing; heavy duty cast-iron cylinder block with six-bolt main-bearing cap; cast aluminum cylinder heads; forged steel crankshaft; stainless steel exhaust manifold.
<b>Transmission</b>	
MYD	6L90-E Hydra-Matic, 6-speed automatic with lock-up converter and overdrive. Ratios: Gear and Ratios 4.027, 2.364, 1.532, 1.152, 0.0852, 0.667, Rev. 3.064:1
<b>Wheelbase</b>	
IB1	150 inches, includes ladder type channel frame. Full C section straight frame 33.5 inches wide. Yield strength 44,000 psi; section modulus 7.20in <sup>3</sup> RBM 316,800 lb./ft./in. per rail. 88.5"CA
<b>Air Cleaner</b>	
KNX	Dry paper single element. Air cleaner canister standard with air restriction gauge.
<b>Alternator</b>	
KW7	170 Amp. output with integral regulator.
<b>Battery</b>	
IL3	Single Delco 12-V maintenance free 750 CCA frame mounted battery box
<b>Exhaust</b>	
I41	Single horizontal aluminized steel with catalytic converter and oxygen sensor devices.
<b>Front Axle</b>	
ID2	"I"-beam rated at 6,830 lbs. Includes integral hydraulic power steering. Ratio 18.8-20.9:1.
<b>Front Suspension</b>	
I0K	7,220 lbs. Capacity semi elliptical tapered leaf spring. Includes shock absorbers and stabilizer bar.
<b>Front Wheels</b>	
IB9	19.5" x 6", 6-hole disc, painted white
<b>Front Tires</b>	
I8B	225/70R19.5G (14 ply) tubeless Radial, all season tread
<b>Rear Suspension</b>	
I8J	12,900 lbs. Capacity semi elliptical; main and auxiliary multi- leaf spring. Includes shock absorbers.
<b>Rear Axle</b>	
ID3	Single-speed, 14,550 lb. capacity with oil lubricated rear wheel bearings.
<b>Ratio</b>	
092	4.300:1
<b>Rear Wheels</b>	
IC1	19.5" x 6", 6-hole disc, painted white
<b>Rear Tires</b>	
I9B	225/70R19.5G (14 ply) tubeless Radial, all season tread.
<b>Fuel Tank</b>	
A17	38.6 gal. rectangular fuel tank. Mounted between frame rail with electric type fuel pump (mounted in tank). Through the rail fuel fill.
<b>Seat</b>	
AQB	Driver seat is reclining high back. Two single occupant fold down seats with tray backs.

Current report content is based on data as of 2021-07-12 08:03:17. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



# VTC ISUZU TRUCK

Logan Grimm

VSA NPR-HD GAS CREW CAB 2022 (2022 NPR-HD Gas Crew Cab, 1G3 150"WB, 88.5"CA, 14,500 GVWR. White, Standard model specifications with power windows and door locks

## Standard Equipment Summary

Code	Description
<b>Brakes</b>	
IR8	Dual circuit, vacuum assisted hydraulic with EBD (Electronic Brake Distribution). Disc front and self-adjust outboard mounted drum rear. Mechanical, transmission mounted parking brake. Non-asbestos semi metallic linings are standard. 4 channel anti-lock brake system.
<b>Air Conditioning</b>	
C60	Air conditioner
<b>Power Windows &amp; Door Locks</b>	
IL0	Yes
<b>Model Option</b>	
04	White, Standard model specifications with power windows and door locks
<b>Accessories</b>	
IX2	Rear body dome lamp switch
8RP	AM/FM/CD radio with Aux input/USB port and Bluetooth RPO

Current report content is based on data as of 2021-07-12 08:03:17. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.