

VSA NPR-HD DSL REG CAB 2022



Current report content is based on data as of 2021-07-12 08:05:06. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



	Code	Description	MSRF
Model	Jour	Bootipion	Morti
Model	3F1	NPR-HD Cab Chassis 109"WB, 86.5"CA	\$57,248.00
	54	White, 30 Gallon Stainless Steel In-Rail Fuel Tank with power windows, power door locks and air conditioning	\$0.00
Tires			
	I5H	LRR (low rolling resistance)	Inc
Engine			
	I1B	4HK1-TC, diesel engine 317 CID (5.19L), 215 HP at 2550 RPM: 452 ftlb. gross torque at 1850 RPM. 4 cylinder, 16 valve, four cycle, overhead cam, turbocharged, inter-cooled, water cooled EGR valve, direct injection, electronically controlled common rail fuel system, engine cruise control function. Oil level check switch and light. Engine Warning system with audible warning for low oil pressure, high coolant temperature, and low coolant level.	Inc
Transmission			
	I1W	Aisin A465id 6-speed automatic transmission, Ratios: 3.742, 2.003, 1.343,	Inc
Wheelbase			
	IA8	109 inches, includes ladder type channel frame. Full C section straight frame 33.5 inches wide. Yield strength 44,000 psi; section modulus 7.20 in RBM 316,800 lb./ft./in. per rail. 86.5"CA	Inc
Air Cleaner			
	KNX	Dry Paper single element. (Donaldson brand) Air cleaner canister standard with air restriction indicator in the driver's Multi-Information Display (MID).	Inc
Alternator			
	I2C	140 AMP. with integral regulator.	Inc
Battery			
	IX1	Dual 12-Volt maintenance free group 31 750 CCA batteries with threaded posts	Inc
Exhaust			
	IX7	Single horizontal with DPF/SCR exhaust system	Inc
Front Axle			
	ID2	"I"-beam rated at 6,830 lbs. Includes integral hydraulic power steering. Ratio 18.8-20.9:1.	Inc
Front Suspens	ion	·	
	ID4	6,830 lb. capacity. Semi-elliptical tapered leaf springs. Includes shock absorbers and stabilizer bar.	Inc
Front Wheels			
	RBY	16" X 6", 6-hole disc, painted white.	Inc
Front Tires			
	153169	215/85R16E (10 ply) tubeless Radial, all season	Inc

Current report content is based on data as of 2021-07-12 08:05:06. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.

Initial:



Co	de Description	MSRP
	tread.	
Rear Suspension		
I	9,880 lbs. capacity. Semi-elliptical main and auxiliary multi-leaf springs. Includes shock absorbers	Inc.
Rear Axle		
I	R040, single-speed, 11,020 lb. capacity with oil lubricated rear wheel bearings.	Inc.
Ratio		
0	05 4.56:1	Inc.
Rear Wheels		
RI	3Z 16" X 6", 6-hole disc, painted white.	Inc.
Rear Tires		
1531	215/85R16E (10 ply) tubeless Radial, all season tread.	Inc.
Fuel Tank		
	4I 30 Gallon Stainless Steel In-Rail Fuel Tank	Inc.
Seat		
AC	QB Driver seat is reclining high back. Two single occupant fold down seats with tray backs.	Inc
Brakes		
K	40 Butterfly valve type exhaust brake	Inc.
II	Vacuum + Power Assist; hydraulic 4-wheel disc brakes with 4-channel ABS. Mechanical, transmission mounted parking brake. Non-asbestos semi metallic linings are standard.	Inc.
Air Conditioning	G. C.	
	60 Air conditioner	Inc.
Power Windows & Do	or Locks	
I	LO Yes	Inc.
Floor Mats		
IC	Q6 Standard Floor Mats	Inc.
Model Option		
	White, 30 Gallon Stainless Steel In-Rail Fuel Tank with power windows, power door locks and air conditioning	Inc.
Assistance System		
	5I Electronic Vehicle Stability Control (EVSC) include ASR (Anti-Slip Regulation)	Inc.
Accessories		
	K2 Rear body dome lamp switch	Inc.
8F	RP AM/FM/CD radio with Aux input/USB port and Bluetooth RPO	Inc.
Totals		
	Base Price	\$57,248.00
	Destination Charge	\$1,325.00

Current report content is based on data as of 2021-07-12 08:05:06. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.

Initial:



Selected Model and Options				
Code	Description	MSRP		
	DEF Fill Charge	\$10.00		
	Total Options Price	\$		
	Tire Weight Tax	\$0.00		
	Total	\$58,583.00		

Current report content is based on data as of 2021-07-12 08:05:06. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



Standard	Equipment Summary		
Code	Description		
Tires			
I5H	LRR (low rolling resistance)		
Engine			
I1B	4HK1-TC, diesel engine 317 CID (5.19L), 215 HP at 2550 RPM: 452 ftlb. gross torque at 1850 RPM. 4 cylinder, 16 valve, four cycle, overhead cam, turbocharged, inter-cooled, water cooled EGR valve, direct injection, electronically controlled common rail fuel system, engine cruise control function. Oil level check switch and light. Engine Warning system with audible warning for low oil pressure, high coolant temperature, and low coolant level.		
Transmissio	n		
I1W	Aisin A465id 6-speed automatic transmission, Ratios: 3.742, 2.003, 1.343,		
Wheelbase			
IA8	109 inches, includes ladder type channel frame. Full C section straight frame 33.5 inches wide. Yield strength 44,000 psi; section modulus 7.20 in RBM 316,800 lb./ft./in. per rail. 86.5"CA		
Air Cleaner			
KNX	Dry Paper single element. (Donaldson brand) Air cleaner canister standard with air restriction indicator in the driver's Multi-Information Display (MID).		
Alternator			
I2C	140 AMP. with integral regulator.		
Battery			
IX1	Dual 12-Volt maintenance free group 31 750 CCA batteries with threaded posts		
Exhaust			
IX7	Single horizontal with DPF/SCR exhaust system		
Front Axle			
ID2	"I"-beam rated at 6,830 lbs. Includes integral hydraulic power steering. Ratio 18.8-20.9:1.		
Front Suspe	nsion		
ID4	6,830 lb. capacity. Semi-elliptical tapered leaf springs. Includes shock absorbers and stabilizer bar.		
Front Wheels	8		
RBY	16" X 6", 6-hole disc, painted white.		
Front Tires			
153169	215/85R16E (10 ply) tubeless Radial, all season tread.		
Rear Suspen	sion		
127	9,880 lbs. capacity. Semi-elliptical main and auxiliary multi-leaf springs. Includes shock absorbers		
Rear Axle			
136	R040, single-speed, 11,020 lb. capacity with oil lubricated rear wheel bearings.		
Ratio			
005	4.56:1		
Rear Wheels			
RBZ	16" X 6", 6-hole disc, painted white.		
Rear Tires			
153134	215/85R16E (10 ply) tubeless Radial, all season tread.		
Fuel Tank			
141	30 Gallon Stainless Steel In-Rail Fuel Tank		
Seat			
AQB	Driver seat is reclining high back. Two single occupant fold down seats with tray backs.		
Brakes			

Current report content is based on data as of 2021-07-12 08:05:06. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



Standard Equipment Summary		
Code	Description	
K40	Butterfly valve type exhaust brake	
IE1	Vacuum + Power Assist; hydraulic 4-wheel disc brakes with 4-channel ABS. Mechanical, transmission mounted parking brake. Non-asbestos semi metallic linings are standard.	
Air Condition	oning	
C60	Air conditioner	
Power Wind	Power Windows & Door Locks	
IL0	Yes	
Floor Mats		
IQ6	Standard Floor Mats	
Model Option	on and the same of	
54	White, 30 Gallon Stainless Steel In-Rail Fuel Tank with power windows, power door locks and air conditioning	
Assistance	System	
151	Electronic Vehicle Stability Control (EVSC) include ASR (Anti-Slip Regulation)	
Accessories	s	
IX2	Rear body dome lamp switch	
8RP	AM/FM/CD radio with Aux input/USB port and Bluetooth RPO	

Current report content is based on data as of 2021-07-12 08:05:06. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.

Initial: