

NPR-XD DSL CREW CAB 2022



Current report content is based on data as of 2021-07-12 08:16:44. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.

NPR-XD DSL CREW CAB 2022 (2022 NPR-XD Crew Cab Chassis, 3Z3 150"WB, 88.5"CA, 16,000 GVWR. White, 30 Gallon Stainless Steel In-Rail Fuel Tank with power windows, power door locks and air conditioning

Selected Model and Options

	Code	Description	MSRP
Model			
	3Z3	NPR-XD Crew Cab Chassis 150"WB, 88.5"CA	\$64,600.00
	54	White, 30 Gallon Stainless Steel In-Rail Fuel Tank with power windows, power door locks and air conditioning	\$0.00
Tires			
	I5H	LRR (low rolling resistance)	Inc.
Engine			
	I1B	4HK1-TC, diesel engine 317 CID (5.19L), 215 HP at 2550 RPM: 452 ft.-lb. gross torque at 1850 RPM. 4 cylinder, 16 valve, four cycle, overhead cam, turbocharged, inter-cooled, water cooled EGR valve, direct injection, electronically controlled common rail fuel system, engine cruise control function. Oil level check switch and light. Engine Warning system with audible warning for low oil pressure, high coolant temperature, and low coolant level.	Inc.
Transmission			
	I1W	Aisin A465id 6-speed automatic transmission, Ratios: 3.742, 2.003, 1.343,	Inc.
Wheelbase			
	IH6	150 inches, includes ladder type channel frame. Full C section straight frame 33.5 inches wide. Yield strength 44,000 psi; section modulus 11.89 in3 RBM 523,160 lb./ft./in. per rail. 88.5"CA	Inc.
Air Cleaner			
	KNX	Dry Paper single element. (Donaldson brand) Air cleaner canister standard with air restriction indicator in the driver's Multi-Information Display (MID).	Inc.
Alternator			
	I2C	140 AMP. with integral regulator.	Inc.
Battery			
	IX1	Dual 12-Volt maintenance free group 31 750 CCA batteries with threaded posts	Inc.
Exhaust			
	IX7	Single horizontal with DPF/SCR exhaust system	Inc.
Front Axle			
	ID2	"I"-beam rated at 6,830 lbs. Includes integral hydraulic power steering. Ratio 18.8-20.9:1.	Inc.
Front Suspension			
	ID8	8440 lbs. Capacity semi elliptical tapered leaf spring. Includes shock absorbers and stabilizer bar	Inc.
Front Wheels			
	IB9	19.5" x 6", 6-hole disc, painted white	Inc.
Front Tires			
	XTN/R3M	225/70R19.5F (12 ply) tubeless Radial, all season	Inc.

Current report content is based on data as of 2021-07-12 08:16:44. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.

NPR-XD DSL CREW CAB 2022 (2022 NPR-XD Crew Cab Chassis, 3Z3 150"WB, 88.5"CA, 16,000 GVWR. White, 30 Gallon Stainless Steel In-Rail Fuel Tank with power windows, power door locks and air conditioning

Selected Model and Options

	Code	Description	MSRP
Rear Suspension			
	I9K	14,308 lbs. capacity. Semi-elliptical main and auxiliary multi-leaf springs. Includes shock absorbers.	Inc.
Rear Axle			
	I36	R040, single-speed, 11,020 lb. capacity with oil lubricated rear wheel bearings.	Inc.
Ratio			
	099	4.777	Inc.
Rear Wheels			
	IC1	19.5" x 6", 6-hole disc, painted white	Inc.
Rear Tires			
	YTN/S3M	225/70R19.5F (12 ply) tubeless Radial, all season tread.	Inc.
Fuel Tank			
	I4I	30 Gallon Stainless Steel In-Rail Fuel Tank	Inc.
Seat			
	AQB	Driver seat is reclining high back. Two single occupant fold down seats with tray backs.	Inc.
Brakes			
	K40	Butterfly valve type exhaust brake	Inc.
	IE1	Vacuum + Power Assist; hydraulic 4-wheel disc brakes with 4-channel ABS. Mechanical, transmission mounted parking brake. Non-asbestos semi metallic linings are standard.	Inc.
Air Conditioning			
	C60	Air conditioner	Inc.
Power Windows & Door Locks			
	IL0	Yes	Inc.
Floor Mats			
	IQ6	Standard Floor Mats	Inc.
Model Option			
	54	White, 30 Gallon Stainless Steel In-Rail Fuel Tank with power windows, power door locks and air conditioning	Inc.
Assistance System			
	I5I	Electronic Vehicle Stability Control (EVSC) include ASR (Anti-Slip Regulation)	Inc.
Accessories			
	IX2	Rear body dome lamp switch	Inc.
	8RP	AM/FM/CD radio with Aux input/USB port and Bluetooth RPO	Inc.
Totals			
		Base Price	\$64,600.00
		Destination Charge	\$1,325.00

Current report content is based on data as of 2021-07-12 08:16:44. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



VTC ISUZU TRUCK

Logan Grimm

NPR-XD DSL CREW CAB 2022 (2022 NPR-XD Crew Cab Chassis, 3Z3 150"WB, 88.5"CA, 16,000 GVWR. White, 30 Gallon Stainless Steel In-Rail Fuel Tank with power windows, power door locks and air conditioning

Selected Model and Options

Code	Description	MSRP
	DEF Fill Charge	\$10.00
	Total Options Price	\$
	Tire Weight Tax	\$7.94
	Total	\$65,942.94

Current report content is based on data as of 2021-07-12 08:16:44. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.

NPR-XD DSL CREW CAB 2022 (2022 NPR-XD Crew Cab Chassis, 3Z3 150"WB, 88.5"CA, 16,000 GVWR. White, 30 Gallon Stainless Steel In-Rail Fuel Tank with power windows, power door locks and air conditioning

Standard Equipment Summary

Code	Description
Tires	
I5H	LRR (low rolling resistance)
Engine	
I1B	4HK1-TC, diesel engine 317 CID (5.19L), 215 HP at 2550 RPM: 452 ft.-lb. gross torque at 1850 RPM. 4 cylinder, 16 valve, four cycle, overhead cam, turbocharged, inter-cooled, water cooled EGR valve, direct injection, electronically controlled common rail fuel system, engine cruise control function. Oil level check switch and light. Engine Warning system with audible warning for low oil pressure, high coolant temperature, and low coolant level.
Transmission	
I1W	Aisin A465id 6-speed automatic transmission, Ratios: 3.742, 2.003, 1.343,
Wheelbase	
IH6	150 inches, includes ladder type channel frame. Full C section straight frame 33.5 inches wide. Yield strength 44,000 psi; section modulus 11.89 in3 RBM 523,160 lb./ft./in. per rail. 88.5"CA
Air Cleaner	
KNX	Dry Paper single element. (Donaldson brand) Air cleaner canister standard with air restriction indicator in the driver's Multi-Information Display (MID).
Alternator	
I2C	140 AMP. with integral regulator.
Battery	
IX1	Dual 12-Volt maintenance free group 31 750 CCA batteries with threaded posts
Exhaust	
IX7	Single horizontal with DPF/SCR exhaust system
Front Axle	
ID2	"I"-beam rated at 6,830 lbs. Includes integral hydraulic power steering. Ratio 18.8-20.9:1.
Front Suspension	
ID8	8440 lbs. Capacity semi elliptical tapered leaf spring. Includes shock absorbers and stabilizer bar
Front Wheels	
IB9	19.5" x 6", 6-hole disc, painted white
Front Tires	
XTN/R3M	225/70R19.5F (12 ply) tubeless Radial, all season
Rear Suspension	
I9K	14,308 lbs. capacity. Semi-elliptical main and auxiliary multi-leaf springs. Includes shock absorbers.
Rear Axle	
I36	R040, single-speed, 11,020 lb. capacity with oil lubricated rear wheel bearings.
Ratio	
099	4.777
Rear Wheels	
IC1	19.5" x 6", 6-hole disc, painted white
Rear Tires	
YTN/S3M	225/70R19.5F (12 ply) tubeless Radial, all season tread.
Fuel Tank	
I4I	30 Gallon Stainless Steel In-Rail Fuel Tank
Seat	
AQB	Driver seat is reclining high back. Two single occupant fold down seats with tray backs.
Brakes	

Current report content is based on data as of 2021-07-12 08:16:44. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



VTC ISUZU TRUCK

Logan Grimm

NPR-XD DSL CREW CAB 2022 (2022 NPR-XD Crew Cab Chassis, 3Z3 150"WB, 88.5"CA, 16,000 GVWR. White, 30 Gallon Stainless Steel In-Rail Fuel Tank with power windows, power door locks and air conditioning

Standard Equipment Summary

Code	Description
K40	Butterfly valve type exhaust brake
IE1	Vacuum + Power Assist; hydraulic 4-wheel disc brakes with 4-channel ABS. Mechanical, transmission mounted parking brake. Non-asbestos semi metallic linings are standard.
Air Conditioning	
C60	Air conditioner
Power Windows & Door Locks	
IL0	Yes
Floor Mats	
IQ6	Standard Floor Mats
Model Option	
54	White, 30 Gallon Stainless Steel In-Rail Fuel Tank with power windows, power door locks and air conditioning
Assistance System	
I5I	Electronic Vehicle Stability Control (EVSC) include ASR (Anti-Slip Regulation)
Accessories	
IX2	Rear body dome lamp switch
8RP	AM/FM/CD radio with Aux input/USB port and Bluetooth RPO

Current report content is based on data as of 2021-07-12 08:16:44. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.