

VSA NQR DSL CREW CAB 2022



Current report content is based on data as of 2021-07-12 08:21:37. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



VSA NQR DSL CREW CAB 2022 (2022 NQR Crew Cab Chassis, 3S3 150"WB, 88.5"CA, 17,950 GVWR. White, 30 Gallon Stainless Steel In-Rail Fuel Tank with power windows, power door locks and air conditioning

	Code	Description	MSRF
Model			
	3S3 54	NQR Crew Cab Chassis 150"WB, 88.5"CA White, 30 Gallon Stainless Steel In-Rail Fuel Tank with power windows, power door locks and air conditioning	\$67,864.00 \$0.00
Tires			
	I5H	LRR (low rolling resistance)	Inc
Engine	I1B	4HK1-TC, diesel engine 317 CID (5.19L), 215 HP at 2550 RPM: 452 ftlb. gross torque at 1850 RPM. 4 cylinder, 16 valve, four cycle, overhead cam, turbocharged, inter-cooled, water cooled EGR valve, direct injection, electronically controlled common rail fuel system, engine cruise control function. Oil level check switch and light. Engine Warning system with audible warning for low oil pressure, high coolant townsorture, and low coolant lovel.	Inc
Transmission		temperature, and low coolant level.	
Transiliission	I1W	Aisin A465id 6-speed automatic transmission, Ratios: 3.742, 2.003, 1.343,	Inc
Wheelbase		Natios. 6.1 42, 2.000, 1.040,	
	IH6	150 inches, includes ladder type channel frame. Full C section straight frame 33.5 inches wide. Yield strength 44,000 psi; section modulus 11.89 in3 RBM 523,160 lb./ft./in. per rail. 88.5"CA	Inc
Air Cleaner			
	KNX	Dry Paper single element. (Donaldson brand) Air cleaner canister standard with air restriction indicator in the driver's Multi-Information Display (MID).	Inc
Alternator			
	I2C	140 AMP. with integral regulator.	Inc
Battery	IX1	Dual 12-Volt maintenance free group 31 750 CCA batteries with threaded posts	Inc
Exhaust			
Front Axle	IX7	Single horizontal with DPF/SCR exhaust system	Inc
	ID2	"I"-beam rated at 6,830 lbs. Includes integral hydraulic power steering. Ratio 18.8-20.9:1.	Inc
Front Suspension			
	ID8	8440 lbs. Capacity semi elliptical tapered leaf spring. Includes shock absorbers and stabilizer bar	Inc
Front Wheels			
	IB9	19.5" x 6", 6-hole disc, painted white	Inc
Front Tires			
	XTN/R3M	225/70R19.5F (12 ply) tubeless Radial, all season	Inc

Current report content is based on data as of 2021-07-12 08:21:37. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



VSA NQR DSL CREW CAB 2022 (2022 NQR Crew Cab Chassis, 3S3 150"WB, 88.5"CA, 17,950 GVWR. White, 30 Gallon Stainless Steel In-Rail Fuel Tank with power windows, power door locks and air conditioning

Code	Description	MSRI
Rear Suspension	· · · · · · · · · · · · · · · · · · ·	
ID9	14,550 lbs. capacity. Semi-elliptical main and auxiliary multi-leaf springs. Includes shock absorbers.	Inc
Rear Axle		
ID3	Single-speed, 14,550 lb. capacity with oil lubricated rear wheel bearings.	Ind
Ratio		
098	5.125:1	Ind
Rear Wheels		
IC1	19.5" x 6", 6-hole disc, painted white	Ind
Rear Tires		
YTN/S3M	225/70R19.5F (12 ply) tubeless Radial, all season tread.	In
Fuel Tank		
141	30 Gallon Stainless Steel In-Rail Fuel Tank	In
Seat		
AQB	Driver seat is reclining high back. Two single occupant fold down seats with tray backs.	In
Brakes		
K40	Butterfly valve type exhaust brake	In
IE1	Vacuum + Power Assist; hydraulic 4-wheel disc brakes with 4-channel ABS. Mechanical, transmission mounted parking brake. Non-asbestos semi metallic linings are standard.	ln:
Air Conditioning		
C60	Air conditioner	In
Power Windows & Door Locks		
ILO	Yes	In
Floor Mats		
IQ6	Standard Floor Mats	In
Model Option		
54	White, 30 Gallon Stainless Steel In-Rail Fuel Tank with power windows, power door locks and air conditioning	ln
Assistance System		
151	Electronic Vehicle Stability Control (EVSC) include ASR (Anti-Slip Regulation)	In
Accessories		
IX2	Rear body dome lamp switch	In
8RP	AM/FM/CD radio with Aux input/USB port and Bluetooth RPO	In
Totals		
	Base Price	\$67,864.0
	Destination Charge	\$1,325.0

Current report content is based on data as of 2021-07-12 08:21:37. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.

Initial:



VSA NQR DSL CREW CAB 2022 (2022 NQR Crew Cab Chassis, 3S3 150"WB, 88.5"CA, 17,950 GVWR. White, 30 Gallon Stainless Steel In-Rail Fuel Tank with power windows, power door locks and air conditioning

Selected Model and Options				
Code	Description	MSRP		
	DEF Fill Charge	\$10.00		
	Total Options Price	\$		
	Tire Weight Tax	\$7.94		
	Total	\$69,206.94		

Current report content is based on data as of 2021-07-12 08:21:37. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



VSA NQR DSL CREW CAB 2022 (2022 NQR Crew Cab Chassis, 3S3 150"WB, 88.5"CA, 17,950 GVWR. White, 30 Gallon Stainless Steel In-Rail Fuel Tank with power windows, power door locks and air conditioning

Code	Description			
Tires	Description			
III es I5H	LDD (low rolling resistance)			
Engine	LRR (low rolling resistance)			
I1B	4HK1-TC, diesel engine 317 CID (5.19L), 215 HP at 2550 RPM: 452 ftlb. gross torque at 1850 RPM. 4 cylinder, 16 valve, four cycle, overhead cam, turbocharged, inter-cooled, water cooled EGR valve, direct injection, electronically controlled common rail fuel system, engine cruise control function. Oil level check switch and light. Engine Warning system with audible warning for low oil pressure, high coolant temperature, and low coolant level.			
Transmissio	n			
I1W	Aisin A465id 6-speed automatic transmission, Ratios: 3.742, 2.003, 1.343,			
Wheelbase				
IH6	150 inches, includes ladder type channel frame. Full C section straight frame 33.5 inches wide. Yield strength 44,000 psi; section modulus 11.89 in RBM 523,160 lb./ft./in. per rail. 88.5"CA			
Air Cleaner				
KNX	Dry Paper single element. (Donaldson brand) Air cleaner canister standard with air restriction indicator in the driver's Multi-Information Display (MID).			
Alternator				
I2C	140 AMP. with integral regulator.			
Battery				
IX1	Dual 12-Volt maintenance free group 31 750 CCA batteries with threaded posts			
Exhaust				
IX7	Single horizontal with DPF/SCR exhaust system			
Front Axle				
ID2	"I"-beam rated at 6,830 lbs. Includes integral hydraulic power steering. Ratio 18.8-20.9:1.			
Front Suspe				
ID8	8440 lbs. Capacity semi elliptical tapered leaf spring. Includes shock absorbers and stabilizer bar			
Front Wheel				
IB9	19.5" x 6", 6-hole disc, painted white			
Front Tires				
XTN/R3M	225/70R19.5F (12 ply) tubeless Radial, all season			
Rear Susper				
ID9	14,550 lbs. capacity. Semi-elliptical main and auxiliary multi-leaf springs. Includes shock absorbers.			
Rear Axle				
ID3	Single-speed, 14,550 lb. capacity with oil lubricated rear wheel bearings.			
Ratio	F 40F 4			
098	5.125:1			
Rear Wheels				
IC1	19.5" x 6", 6-hole disc, painted white			
Rear Tires	205/70D10 55 (42 plu) tubologo Dodiol, all accessor tread			
YTN/S3M	225/70R19.5F (12 ply) tubeless Radial, all season tread.			
Fuel Tank	30 Gallon Stainless Steel In-Rail Fuel Tank			
Seat				
AQB	Driver seat is reclining high back. Two single occupant fold down seats with tray backs.			
Brakes	•			

Current report content is based on data as of 2021-07-12 08:21:37. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



VSA NQR DSL CREW CAB 2022 (2022 NQR Crew Cab Chassis, 3S3 150"WB, 88.5"CA, 17,950 GVWR. White, 30 Gallon Stainless Steel In-Rail Fuel Tank with power windows, power door locks and air conditioning

Standard Equipment Summary				
Code	Description			
K40	Butterfly valve type exhaust brake			
IE1	Vacuum + Power Assist; hydraulic 4-wheel disc brakes with 4-channel ABS. Mechanical, transmission mounted parking brake. Non-asbestos semi metallic linings are standard.			
Air Conditioning				
C60	Air conditioner			
Power Wind	Power Windows & Door Locks			
IL0	Yes			
Floor Mats	Floor Mats			
IQ6	Standard Floor Mats			
Model Optio	Model Option			
54	White, 30 Gallon Stainless Steel In-Rail Fuel Tank with power windows, power door locks and air conditioning			
Assistance	Assistance System			
151	Electronic Vehicle Stability Control (EVSC) include ASR (Anti-Slip Regulation)			
Accessories	Accessories			
IX2	Rear body dome lamp switch			
8RP	AM/FM/CD radio with Aux input/USB port and Bluetooth RPO			

Current report content is based on data as of 2021-07-12 08:21:37. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.

Initial: