

## **VSA NQR DSL REG CAB 2022**



Current report content is based on data as of 2021-07-12 08:20:06. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



VSA NQR DSL REG CAB 2022 (2022 NQR Cab Chassis, 3R1 109"WB, 86.5"CA, 17,950 GVWR. White, 30 Gallon Stainless Steel In-Rail Fuel Tank with power windows, power door locks and air conditioning

	0 - 1 -	Description	11000
Madal	Code	Description	MSRP
Model	004	NOD O LL OL 400MA/D. 00 FIIOA	#00.000.00
	3R1 54	NQR Cab Chassis 109"WB, 86.5"CA White, 30 Gallon Stainless Steel In-Rail Fuel Tank with power windows, power door locks and air conditioning	\$62,292.00 \$0.00
Tires			
	I5H	LRR (low rolling resistance)	Inc.
Engine			
	I1B	4HK1-TC, diesel engine 317 CID (5.19L), 215 HP at 2550 RPM: 452 ftlb. gross torque at 1850 RPM. 4 cylinder, 16 valve, four cycle, overhead cam, turbocharged, inter-cooled, water cooled EGR valve, direct injection, electronically controlled common rail fuel system, engine cruise control function. Oil level check switch and light. Engine Warning system with audible warning for low oil pressure, high coolant temperature, and low coolant level.	Inc.
Transmission			
	I1W	Aisin A465id 6-speed automatic transmission, Ratios: 3.742, 2.003, 1.343,	Inc.
Wheelbase			
	IA8	109 inches, includes ladder type channel frame. Full C section straight frame 33.5 inches wide. Yield strength 44,000 psi; section modulus 7.20 in RBM 316,800 lb./ft./in. per rail. 86.5"CA	Inc.
Air Cleaner			
	KNX	Dry Paper single element. (Donaldson brand) Air cleaner canister standard with air restriction indicator in the driver's Multi-Information Display (MID).	Inc.
Alternator			
	I2C	140 AMP. with integral regulator.	Inc
Battery			
	IX1	Dual 12-Volt maintenance free group 31 750 CCA batteries with threaded posts	Inc
Exhaust			
	IX7	Single horizontal with DPF/SCR exhaust system	Inc
Front Axle			
	ID2	"I"-beam rated at 6,830 lbs. Includes integral hydraulic power steering. Ratio 18.8-20.9:1.	Inc
Front Suspension			
	ID8	8440 lbs. Capacity semi elliptical tapered leaf spring. Includes shock absorbers and stabilizer bar	Inc.
Front Wheels			
	IB9	19.5" x 6", 6-hole disc, painted white	Inc
Front Tires			
	XTN/R3M	225/70R19.5F (12 ply) tubeless Radial, all season	Inc

Current report content is based on data as of 2021-07-12 08:20:06. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



VSA NQR DSL REG CAB 2022 (2022 NQR Cab Chassis, 3R1 109"WB, 86.5"CA, 17,950 GVWR. White, 30 Gallon Stainless Steel In-Rail Fuel Tank with power windows, power door locks and air conditioning

Code	Description	MSRF
Rear Suspension	· · · · · · · · · · · · · · · · · · ·	
ID9	14,550 lbs. capacity. Semi-elliptical main and auxiliary multi-leaf springs. Includes shock absorbers.	Inc
Rear Axle		
ID3	Single-speed, 14,550 lb. capacity with oil lubricated rear wheel bearings.	Inc
Ratio		
098	5.125:1	Inc
Rear Wheels		
IC1	19.5" x 6", 6-hole disc, painted white	Inc
Rear Tires		
YTN/S3M	225/70R19.5F (12 ply) tubeless Radial, all season tread.	Inc
Fuel Tank		
141	30 Gallon Stainless Steel In-Rail Fuel Tank	Inc
Seat		
AQB	Driver seat is reclining high back. Two single occupant fold down seats with tray backs.	Ind
Brakes		
K40 IE1	Butterfly valve type exhaust brake Vacuum + Power Assist; hydraulic 4-wheel disc brakes with 4-channel ABS. Mechanical, transmission mounted parking brake. Non-asbestos semi metallic linings are standard.	Inc Inc
Air Conditioning		
C60	Air conditioner	Inc
Power Windows & Door Locks		
IL0	Yes	Inc
Floor Mats		
IQ6	Standard Floor Mats	Inc
Model Option		
54	White, 30 Gallon Stainless Steel In-Rail Fuel Tank with power windows, power door locks and air conditioning	Inc
Assistance System		
151	Electronic Vehicle Stability Control (EVSC) include ASR (Anti-Slip Regulation)	Ind
Accessories		
IX2	Rear body dome lamp switch	Inc
8RP	AM/FM/CD radio with Aux input/USB port and Bluetooth RPO	Ind
Totals		
	Base Price	\$62,292.0
	Destination Charge	\$1,325.0

Current report content is based on data as of 2021-07-12 08:20:06. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.

Initial:



VSA NQR DSL REG CAB 2022 (2022 NQR Cab Chassis, 3R1 109"WB, 86.5"CA, 17,950 GVWR. White, 30 Gallon Stainless Steel In-Rail Fuel Tank with power windows, power door locks and air conditioning

Selected Model and Options				
Code	Description	MSRP		
	DEF Fill Charge	\$10.00		
	Total Options Price	\$		
	Tire Weight Tax	\$7.94		
	Total	\$63,634.94		

Current report content is based on data as of 2021-07-12 08:20:06. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



VSA NQR DSL REG CAB 2022 (2022 NQR Cab Chassis, 3R1 109"WB, 86.5"CA, 17,950 GVWR. White, 30 Gallon Stainless Steel In-Rail Fuel Tank with power windows, power door locks and air conditioning

Code	Description		
Tires	Description		
	LDD (low relling registance)		
I5H Engine	LRR (low rolling resistance)		
Engine	411/(4 TO 15 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1		
I1B	4HK1-TC, diesel engine 317 CID (5.19L), 215 HP at 2550 RPM: 452 ftlb. gross torque at 1850 RPM. 4 cylinder, 16 valve, four cycle, overhead cam, turbocharged, inter-cooled, water cooled EGR valve, direct injection, electronically controlled common rail fuel system, engine cruise control function. Oil level check switch and light. Engine Warning system with audible warning for low oil pressure, high coolant temperature, and low coolant level.		
Transmissio	n		
I1W	Aisin A465id 6-speed automatic transmission, Ratios: 3.742, 2.003, 1.343,		
Wheelbase			
IA8	109 inches, includes ladder type channel frame. Full C section straight frame 33.5 inches wide. Yield strength 44,000 psi; section modulus 7.20 in RBM 316,800 lb./ft./in. per rail. 86.5"CA		
Air Cleaner			
KNX	Dry Paper single element. (Donaldson brand) Air cleaner canister standard with air restriction indicator in the driver's Multi-Information Display (MID).		
Alternator			
I2C	140 AMP. with integral regulator.		
Battery			
IX1	Dual 12-Volt maintenance free group 31 750 CCA batteries with threaded posts		
Exhaust			
IX7	Single horizontal with DPF/SCR exhaust system		
Front Axle			
ID2	"I"-beam rated at 6,830 lbs. Includes integral hydraulic power steering. Ratio 18.8-20.9:1.		
Front Suspe	nsion		
ID8	8440 lbs. Capacity semi elliptical tapered leaf spring. Includes shock absorbers and stabilizer bar		
Front Wheel	S		
IB9	19.5" x 6", 6-hole disc, painted white		
Front Tires			
XTN/R3M	225/70R19.5F (12 ply) tubeless Radial, all season		
Rear Susper	• • • •		
ID9	14,550 lbs. capacity. Semi-elliptical main and auxiliary multi-leaf springs. Includes shock absorbers.		
Rear Axle			
ID3 Ratio	Single-speed, 14,550 lb. capacity with oil lubricated rear wheel bearings.		
098	5.125:1		
Rear Wheels			
IC1	19.5" x 6", 6-hole disc, painted white		
Rear Tires			
YTN/S3M	225/70R19.5F (12 ply) tubeless Radial, all season tread.		
Fuel Tank			
141	30 Gallon Stainless Steel In-Rail Fuel Tank		
Seat			
AQB	Driver seat is reclining high back. Two single occupant fold down seats with tray backs.		
Brakes	3 3		

Current report content is based on data as of 2021-07-12 08:20:06. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



VSA NQR DSL REG CAB 2022 (2022 NQR Cab Chassis, 3R1 109"WB, 86.5"CA, 17,950 GVWR. White, 30 Gallon Stainless Steel In-Rail Fuel Tank with power windows, power door locks and air conditioning

Standard	l Equipment Summary	
Code	Description	
K40	Butterfly valve type exhaust brake	
IE1	Vacuum + Power Assist; hydraulic 4-wheel disc brakes with 4-channel ABS. Mechanical, transmission mounted parking brake. Non-asbestos semi metallic linings are standard.	
Air Condition	ning	
C60	Air conditioner	
Power Wind	Power Windows & Door Locks	
IL0	Yes	
Floor Mats		
IQ6	Standard Floor Mats	
Model Option	on Control of the Con	
54	White, 30 Gallon Stainless Steel In-Rail Fuel Tank with power windows, power door locks and air conditioning	
Assistance	System	
151	Electronic Vehicle Stability Control (EVSC) include ASR (Anti-Slip Regulation)	
Accessories		
IX2	Rear body dome lamp switch	
8RP	AM/FM/CD radio with Aux input/USB port and Bluetooth RPO	

Current report content is based on data as of 2021-07-12 08:20:06. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.

Initial: