

## **VSA NQR GAS REG CAB 2022**



Current report content is based on data as of 2021-07-12 08:17:51. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



VSA NQR GAS REG CAB 2022 (2022 NQR Gas Cab Chassis, 1R2 132.5"WB, 110"CA, 17,950 GVWR. White, Standard model specifications with power windows and door locks

Madal	Code	Description	MSRP
Model			
	1R2	NQR Gas Cab Chassis 132.5"WB, 110"CA	\$53,008.00
	04	White, Standard model specifications with power	\$0.00
		windows and door locks	
Vehicle Applica	ation		
	RQ2	Truck Application	Inc
Tires			
	I5H	LRR (low rolling resistance)	Inc
Engine			
	LNJ	PSI 6.0L (366 CID) V8 gasoline engine; 311 HP at 4900 RPM; 353 lb-ft torque at 4150 RPM; sequential port fuel injection; electronic throttle control; overhead valves with variable valve timing; heavy duty cast-iron cylinder block with six-bolt mainbearing cap; cast aluminum cylinder heads.	Inc
Transmission			
	Y6V	Allison 1000 RDS 6-speed automatic transmission w/ PTO. Gear Ratios: 3.100, 1.810, 1.410, 1.000, 0.710, 0.610, Rev 4.490:1	Inc
Wheelbase			
	IA9	132.5 inches, includes ladder type channel frame. Full C section straight frame 33.5 inches wide. Yield strength 44,000 psi; section modulus 7.20 in3 RBM 316,800 lb./ft./in. per rail. 110"CA	Inc
Air Cleaner			
Rattory	KNX	Dry paper single element. Air cleaner canister standard with air restriction gauge.	Inc
Battery	IL3	Single Delco 12-V maintenance free 750 CCA frame mounted battery box	Inc
Exhaust		,	
	l41	Single horizontal aluminized steel with catalytic converter and oxygen sensor devices.	Inc
Front Axle			
	ID2	"I"-beam rated at 6,830 lbs. Includes integral hydraulic power steering. Ratio 18.8-20.9:1.	Inc
Front Wheels			
	IB9	19.5" x 6", 6-hole disc, painted white	Inc
Front Tires			
	I8B	225/70R19.5G (14 ply) tubeless Radial, all season tread	Ind
Rear Axle			
	ID3	Single-speed, 14,550 lb. capacity with oil lubricated rear wheel bearings.	Ind
Ratio			
	011	5.571:1	Inc

Current report content is based on data as of 2021-07-12 08:17:51. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



VSA NQR GAS REG CAB 2022 (2022 NQR Gas Cab Chassis, 1R2 132.5"WB, 110"CA, 17,950 GVWR. White, Standard model specifications with power windows and door locks

Selected Model a	nd Options	
Code	Description	MSRP
IC1	19.5" x 6", 6-hole disc, painted white	Inc.
Rear Tires		
I9B	225/70R19.5G (14 ply) tubeless Radial, all season tread.	Inc.
Fuel Tank		
A17	38.6 gal. rectangular fuel tank. Mounted between frame rail with electric type fuel pump (mounted in tank). Through the rail fuel fill.	Inc.
Seat		
AQB	Driver seat is reclining high back. Two single occupant fold down seats with tray backs.	Inc.
Air Conditioning		
C60	Air conditioner	Inc.
Power Windows & Door	Locks	
IL0	Yes	Inc.
Model Option		
04	White, Standard model specifications with power windows and door locks	Inc.
Accessories		
IX2	Rear body dome lamp switch	Inc.
8RP	AM/FM/CD radio with Aux input/USB port and Bluetooth RPO	Inc.
Totals		
	Base Price	\$53,008.00
	Destination Charge	\$1,325.00
	DEF Fill Charge	\$0.00
	Total Options Price	\$
	Tire Weight Tax	\$26.64
	Total	\$54,359.64

Current report content is based on data as of 2021-07-12 08:17:51. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



VSA NQR GAS REG CAB 2022 (2022 NQR Gas Cab Chassis, 1R2 132.5"WB, 110"CA, 17,950 GVWR. White, Standard model specifications with power windows and door locks

Standard	Equipment Summary	
Code	Description	
Vehicle Appl	ication	
RQ2	Truck Application	
Tires		
I5H	LRR (low rolling resistance)	
Engine		
LNJ	PSI 6.0L (366 CID) V8 gasoline engine; 311 HP at 4900 RPM; 353 lb-ft torque at 4150 RPM; sequential port fuel injection; electronic throttle control; overhead valves with variable valve timing; heavy duty cast-iron cylinder block with six-bolt main-bearing cap; cast aluminum cylinder heads.	
Transmissio		
Y6V	Allison 1000 RDS 6-speed automatic transmission w/ PTO. Gear Ratios: 3.100, 1.810, 1.410, 1.000, 0.710, 0.610, Rev 4.490:1	
Wheelbase		
IA9	132.5 inches, includes ladder type channel frame. Full C section straight frame 33.5 inches wide. Yield strength 44,000 psi; section modulus 7.20 in RBM 316,800 lb./ft./in. per rail. 110"CA	
Air Cleaner	Decrease the latest Atalana and the standard of the standard o	
KNX	Dry paper single element. Air cleaner canister standard with air restriction gauge.	
Battery	Cinala Dalas 43 V maintananas fuas 750 CCA fuerra maguntad battany hay	
IL3	Single Delco 12-V maintenance free 750 CCA frame mounted battery box	
Exhaust  41	Cinals having the classic includes a stable tip converted and average agency devices	
Front Axle	Single horizontal aluminized steel with catalytic converter and oxygen sensor devices.	
ID2	"I" hoom rated at 6 920 lbs. Includes integral hydraulic newer steering. Datic 19 9 20 0:1	
Front Wheels	"I"-beam rated at 6,830 lbs. Includes integral hydraulic power steering. Ratio 18.8-20.9:1.	
IB9	19.5" x 6", 6-hole disc, painted white	
Front Tires	19.5 X 0 , 0-hole disc, painted write	
I8B	225/70R19.5G (14 ply) tubeless Radial, all season tread	
Rear Axle	225/10/13:30 (14 pty) tubble33 readial, all 3ca30ff treat	
ID3	Single-speed, 14,550 lb. capacity with oil lubricated rear wheel bearings.	
Ratio	enigle opecu, 11,000 ib. capacity mai on abheatea real innear bearinge.	
011	5.571:1	
Rear Wheels		
IC1	19.5" x 6", 6-hole disc, painted white	
Rear Tires		
I9B	225/70R19.5G (14 ply) tubeless Radial, all season tread.	
Fuel Tank		
A17	38.6 gal. rectangular fuel tank. Mounted between frame rail with electric type fuel pump (mounted in tank). Through the rail fuel fill.	
Seat		
AQB Air Condition	Driver seat is reclining high back. Two single occupant fold down seats with tray backs.  ning	
C60	Air conditioner	
	ows & Door Locks	
ILO	Yes	

Current report content is based on data as of 2021-07-12 08:17:51. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.

White, Standard model specifications with power windows and door locks

Initial:

**Model Option** 



VSA NQR GAS REG CAB 2022 (2022 NQR Gas Cab Chassis, 1R2 132.5"WB, 110"CA, 17,950 GVWR. White, Standard model specifications with power windows and door locks

## **Standard Equipment Summary**

Code	Description	
Accessories		
IX2	Rear body dome lamp switch	
8RP	AM/FM/CD radio with Aux input/USB port and Bluetooth RPO	

Current report content is based on data as of 2021-07-12 08:17:51. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.