

# **VSA NRR GAS CREW CAB 2022**



**VTC ISUZU TRUCK** 

Logan Grimm

#### VSA NRR GAS CREW CAB 2022 (2022 NRR Gas Crew Cab, 1V3 150"WB, 88.5"CA, 19,500 GVWR. White, Standard model specifications with power windows and door locks

#### Selected Model and Options Code Description **MSRP** Model 1V3 NRR Gas Crew Cab 150"WB, 88.5"CA \$61,540.00 04 White, Standard model specifications with power \$0.00 windows and door locks Vehicle Application RQ2 **Truck Application** Inc. Tires 15H LRR (low rolling resistance) Inc. Engine LNJ PSI 6.0L (366 CID) V8 gasoline engine; 311 HP at Inc. 4900 RPM; 353 lb-ft torgue at 4150 RPM; seguential port fuel injection: electronic throttle control: overhead valves with variable valve timing; heavy duty cast-iron cylinder block with six-bolt mainbearing cap; cast aluminum cylinder heads. Transmission Y6V Allison 1000 RDS 6-speed automatic transmission w/ Inc. PTO. Gear Ratios: 3.100, 1.810, 1.410, 1.000, 0.710, 0.610, Rev 4.490:1 Wheelbase IB1 150 inches, includes ladder type channel frame. Full Inc. C section straight frame 33.5 inches wide. Yield strength 44,000 psi; section modulus 7.20in3 RBM 316,800 lb./ft./in. per rail. 88.5"CA **Air Cleaner** KNX Dry paper single element. Air cleaner canister Inc. standard with air restriction gauge. Battery IL3 Single Delco 12-V maintenance free 750 CCA frame Inc. mounted battery box Exhaust 141 Single horizontal aluminized steel with catalytic Inc. converter and oxygen sensor devices. **Front Axle** IZ6 "I"-beam rated at 7,275 lbs. Includes integral Inc. hydraulic power steering. Ratio 18.8-20.9:1. **Front Wheels** IB9 19.5" x 6", 6-hole disc, painted white Inc. **Front Tires** 18B 225/70R19.5G (14 ply) tubeless Radial, all season Inc. tread **Rear Axle** ID3 Single-speed, 14,550 lb. capacity with oil lubricated Inc. rear wheel bearings. Ratio 011 5.571:1 Inc. **Rear Wheels**

# **VTC ISUZU TRUCK**

Logan Grimm

#### VSA NRR GAS CREW CAB 2022 (2022 NRR Gas Crew Cab, 1V3 150"WB, 88.5"CA, 19,500 GVWR. White, Standard model specifications with power windows and door locks

Selected Model a	Ind Options	
Code	Description	MSRP
IC1	19.5" x 6", 6-hole disc, painted white	Inc.
Rear Tires		
I9B	225/70R19.5G (14 ply) tubeless Radial, all season tread.	Inc.
Fuel Tank		
A17	38.6 gal. rectangular fuel tank. Mounted between frame rail with electric type fuel pump (mounted in tank). Through the rail fuel fill.	Inc.
Seat		
AQB	Driver seat is reclining high back. Two single occupant fold down seats with tray backs.	Inc.
Air Conditioning		
C60	Air conditioner	Inc.
Power Windows & Door	Locks	
ILO	Yes	Inc.
Model Option		
04	White, Standard model specifications with power windows and door locks	Inc.
Accessories		
IX2	Rear body dome lamp switch	Inc.
8RP	AM/FM/CD radio with Aux input/USB port and Bluetooth RPO	Inc.
Totals		
	Base Price	\$61,540.00
	Destination Charge	\$1,325.00
	DEF Fill Charge	\$0.00
	Total Options Price	\$
	Tire Weight Tax	\$26.64
	Total	\$62,891.64

## **VTC ISUZU TRUCK**

Logan Grimm

> VSA NRR GAS CREW CAB 2022 (2022 NRR Gas Crew Cab, 1V3 150"WB, 88.5"CA, 19,500 GVWR. White, Standard model specifications with power windows and door locks

#### **Standard Equipment Summary**

Code	Description	
Vehicle App	lication	
RQ2	Truck Application	
Tires		
15H	LRR (low rolling resistance)	
Engine		
LNJ	PSI 6.0L (366 CID) V8 gasoline engine; 311 HP at 4900 RPM; 353 lb-ft torque at 4150 RPM; sequential port fuel injection; electronic throttle control; overhead valves with variable valve timing; heavy duty cast-iron cylinder block with six-bolt main-bearing cap; cast aluminum cylinder heads.	
Transmissic	n	
Y6V	Allison 1000 RDS 6-speed automatic transmission w/ PTO. Gear Ratios: 3.100, 1.810, 1.410, 1.000, 0.710, 0.610, Rev 4.490:1	
Wheelbase		
IB1	150 inches, includes ladder type channel frame. Full C section straight frame 33.5 inches wide. Yield strength 44,000 psi; section modulus 7.20in3 RBM 316,800 lb./ft./in. per rail. 88.5"CA	
Air Cleaner		
KNX	Dry paper single element. Air cleaner canister standard with air restriction gauge.	
Battery		
IL3	Single Delco 12-V maintenance free 750 CCA frame mounted battery box	
Exhaust		
l41	Single horizontal aluminized steel with catalytic converter and oxygen sensor devices.	
Front Axle		
IZ6	"I"-beam rated at 7,275 lbs. Includes integral hydraulic power steering. Ratio 18.8-20.9:1.	
Front Wheel	S	
IB9	19.5" x 6", 6-hole disc, painted white	
Front Tires		
18B	225/70R19.5G (14 ply) tubeless Radial, all season tread	
Rear Axle		
ID3	Single-speed, 14,550 lb. capacity with oil lubricated rear wheel bearings.	
Ratio		
011	5.571:1	
Rear Wheels		
IC1	19.5" x 6", 6-hole disc, painted white	
Rear Tires		
19B	225/70R19.5G (14 ply) tubeless Radial, all season tread.	
Fuel Tank		
A17	38.6 gal. rectangular fuel tank. Mounted between frame rail with electric type fuel pump (mounted in tank). Through the rail fuel fill.	
Seat		
AQB	Driver seat is reclining high back. Two single occupant fold down seats with tray backs.	
Air Conditio	ning	
C60	Air conditioner	
Power Wind	ows & Door Locks	
IL0	Yes	
Model Optio	n	
04	White, Standard model specifications with power windows and door locks	

# ISUZU VTC ISUZU TRUCK

Logan Grimm

TRUCK

VSA NRR GAS CREW CAB 2022 (2022 NRR Gas Crew Cab, 1V3 150"WB, 88.5"CA, 19,500 GVWR. White, Standard model specifications with power windows and door locks

### **Standard Equipment Summary**

Code	Description	
Accessories		
IX2	Rear body dome lamp switch	
8RP	AM/FM/CD radio with Aux input/USB port and Bluetooth RPO	