

VSA NRR GAS REG CAB 2022



Current report content is based on data as of 2021-07-12 08:22:39. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



VSA NRR GAS REG CAB 2022 (2022 NRR Gas Cab Chassis, 1U2 132.5"WB, 110"CA, 19,500 GVWR. White, Standard model specifications with power windows and door locks

	Code	Description	MSRP
Model			
	1U2	NRR Gas Cab Chassis 132.5"WB, 110"CA	\$54,340.00
	04	White, Standard model specifications with power	\$0.00
		windows and door locks	
Vehicle Applic	ation		
	RQ2	Truck Application	Inc
Tires			
	I5H	LRR (low rolling resistance)	Inc
Engine			
	LNJ	PSI 6.0L (366 CID) V8 gasoline engine; 311 HP at 4900 RPM; 353 lb-ft torque at 4150 RPM; sequential port fuel injection; electronic throttle control; overhead valves with variable valve timing; heavy duty cast-iron cylinder block with six-bolt main-bearing cap; cast aluminum cylinder heads.	Inc
Transmission			
	Y6V	Allison 1000 RDS 6-speed automatic transmission w/ PTO. Gear Ratios: 3.100, 1.810, 1.410, 1.000, 0.710, 0.610, Rev 4.490:1	lnc.
Wheelbase			
	IA9	132.5 inches, includes ladder type channel frame. Full C section straight frame 33.5 inches wide. Yield strength 44,000 psi; section modulus 7.20 in3 RBM 316,800 lb./ft./in. per rail. 110"CA	Inc
Air Cleaner			
Pattoni	KNX	Dry paper single element. Air cleaner canister standard with air restriction gauge.	Inc
Battery	IL3	Cingle Deleg 12 V maintenance from 750 CCA frame	lno
	ILS	Single Delco 12-V maintenance free 750 CCA frame mounted battery box	Inc
Exhaust		mounted battery box	
LANGUOT	l41	Single horizontal aluminized steel with catalytic converter and oxygen sensor devices.	Inc
Front Axle			
	IZ6	"I"-beam rated at 7,275 lbs. Includes integral hydraulic power steering. Ratio 18.8-20.9:1.	Inc
Front Wheels			
	IB9	19.5" x 6", 6-hole disc, painted white	Inc
Front Tires			
	I8B	225/70R19.5G (14 ply) tubeless Radial, all season tread	Inc
Rear Axle			
	ID3	Single-speed, 14,550 lb. capacity with oil lubricated rear wheel bearings.	Inc
Ratio			
	011	5.571:1	Inc

Current report content is based on data as of 2021-07-12 08:22:39. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



VSA NRR GAS REG CAB 2022 (2022 NRR Gas Cab Chassis, 1U2 132.5"WB, 110"CA, 19,500 GVWR. White, Standard model specifications with power windows and door locks

Code	Description	MSRP
IC1	19.5" x 6", 6-hole disc, painted white	Inc.
Rear Tires		
I9B	225/70R19.5G (14 ply) tubeless Radial, all season tread.	Inc.
Fuel Tank		
A17	38.6 gal. rectangular fuel tank. Mounted between frame rail with electric type fuel pump (mounted in tank). Through the rail fuel fill.	Inc.
Seat		
AQB	Driver seat is reclining high back. Two single occupant fold down seats with tray backs.	Inc.
Air Conditioning		
C60	Air conditioner	Inc.
Power Windows & Door	Locks	
IL0	Yes	Inc.
Model Option		
04	White, Standard model specifications with power windows and door locks	Inc.
Accessories		
IX2	Rear body dome lamp switch	Inc.
8RP	AM/FM/CD radio with Aux input/USB port and Bluetooth RPO	Inc.
Totals		
	Base Price	\$54,340.00
	Destination Charge	\$1,325.00
	DEF Fill Charge	\$0.00
	Total Options Price	\$
	Tire Weight Tax	\$26.64
	Total	\$55,691.64

Current report content is based on data as of 2021-07-12 08:22:39. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



VSA NRR GAS REG CAB 2022 (2022 NRR Gas Cab Chassis, 1U2 132.5"WB, 110"CA, 19,500 GVWR. White, Standard model specifications with power windows and door locks

Standard	Equipment Summary
Code	Description
Vehicle App	lication
RQ2	Truck Application
Tires	
I5H	LRR (low rolling resistance)
Engine	
LNJ	PSI 6.0L (366 CID) V8 gasoline engine; 311 HP at 4900 RPM; 353 lb-ft torque at 4150 RPM; sequential port fuel injection; electronic throttle control; overhead valves with variable valve timing; heavy duty cast-iron cylinder block with six-bolt main-bearing cap; cast aluminum cylinder heads.
Transmissio	yn
Y6V	Allison 1000 RDS 6-speed automatic transmission w/ PTO. Gear Ratios: 3.100, 1.810, 1.410, 1.000, 0.710, 0.610, Rev 4.490:1
Wheelbase	
IA9	132.5 inches, includes ladder type channel frame. Full C section straight frame 33.5 inches wide. Yield strength 44,000 psi; section modulus 7.20 in RBM 316,800 lb./ft./in. per rail. 110"CA
Air Cleaner	
KNX	Dry paper single element. Air cleaner canister standard with air restriction gauge.
Battery	
IL3	Single Delco 12-V maintenance free 750 CCA frame mounted battery box
Exhaust	
141	Single horizontal aluminized steel with catalytic converter and oxygen sensor devices.
Front Axle	
IZ6	"I"-beam rated at 7,275 lbs. Includes integral hydraulic power steering. Ratio 18.8-20.9:1.
Front Wheel	
IB9	19.5" x 6", 6-hole disc, painted white
Front Tires	
I8B	225/70R19.5G (14 ply) tubeless Radial, all season tread
Rear Axle	
ID3	Single-speed, 14,550 lb. capacity with oil lubricated rear wheel bearings.
Ratio	
011	5.571:1
Rear Wheels	
IC1	19.5" x 6", 6-hole disc, painted white
Rear Tires	005/70D40-50-/44L-V-L-L
19B	225/70R19.5G (14 ply) tubeless Radial, all season tread.
Fuel Tank	
A17	38.6 gal. rectangular fuel tank. Mounted between frame rail with electric type fuel pump (mounted in tank). Through the rail fuel fill.
Seat	
AQB	Driver seat is reclining high back. Two single occupant fold down seats with tray backs.
Air Conditio	
C60	Air conditioner
	ows & Door Locks
IL0	Yes

Current report content is based on data as of 2021-07-12 08:22:39. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.

Initial:

White, Standard model specifications with power windows and door locks

Model Option



VSA NRR GAS REG CAB 2022 (2022 NRR Gas Cab Chassis, 1U2 132.5"WB, 110"CA, 19,500 GVWR. White, Standard model specifications with power windows and door locks

Standard Equipment Summary

Code	Description	
Accessories	Accessories	
IX2	Rear body dome lamp switch	
8RP	AM/FM/CD radio with Aux input/USB port and Bluetooth RPO	

Current report content is based on data as of 2021-07-12 08:22:39. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.