

MACK MD7

Dependability, durability and steadfast support—everything you've come to expect from Mack is now available in a medium-duty truck. We're proud to introduce the Mack MD Series. These trucks, like the Mack MD7, are packed from the exterior to the driver environment with features to ensure a smooth, stress-free ride—and backed by our unmatched local dealer support. We've taken care of the details so you can focus on growing your business.

BORN READY.

KEY FEATURES

Cab air suspension (standard)

Full-width aluminum grated steps for easy entry and egress, horizontally offset for visibility (standard)

50-gallon fuel tank (standard), 90-gallon (optional)

Frame rails rated at 120,000 psi yield strength (standard)

34-inch assembled frame width

Rear leaf spring suspension (standard), Mack AirRide (optional)*

*Mack Maxlite air ride available on select wheelbases only.

Tires 11R22.5 All Season (standard), Rear Traction tires (optional)

Steel power coated white disc wheels (standard), aluminum wheels (optional)

Passenger door lower peep window (standard)

Flat back-of-cab and clear frame platform for easy body installation

Wheelbases to accommodate 10- to 26-foot typical van bodies

Clear space on driver and passenger side frame rails



Comfortable Interiors

The Mack MD7 brings heavy-duty levels of driver comfort and functionality to mediumduty trucks, to keep drivers comfortable and safe all day. Tilt/telescoping steering column, air suspension driver seat and all controls within reach keep drivers in control.


All Day Uptime

Mack uses Geotab to integrate the MD7 into our industry-leading Uptime Services. Mack's ASIST platform streamlines and shares all service communications among the customer, dealer and Mack's 24/7 Uptime Center.

		1	1	1	1	1			1
Typical Dry Van Body Length	(ft.)	10	12/14	16	18	20	22	24	26
Wheelbase*	WB (in.)	150	166	186	206	221	236	251	270
Cab to Rear Axle	CA (in.)	87	103	123	143	158	173	188	207
After Frame	AF (in.)	50	55	60	65	70	80	90	100
Overall Length Chassis	OL (in.)	240	261	286	311	341	356	381	410
GVWR	(lb.)	33,000	33,000	33,000	33,000	33,000	33,000	33,000	33,000
Front Axle Capacity	(lb.)	12,000	12,000	12,000	12,000	12,000	12,000	12,000	12,000
Rear Axle Capacity	(lb.)	21,000	21,000	21,000	21,000	21,000	21,000	21,000	21,000
Front Axle Weight	(lb.)	6,180	6,235	6,275	6,340	6,375	6,400	6,450	6,500
Rear Axle Weight	(lb.)	3,450	3,465	3,495	3,525	3,575	3,620	3,665	3,715
Total Chassis Weight**	(lb.)	9,630	9,700	9,770	9,865	9,950	10,020	10,115	10,215

 $^{{}^\}star Wheelbase \, selection \, should \, be \, based \, on \, specific \, weight \, distribution.$

^{**}Total Chassis Weight is for standard specifications EXCLUDING driver and fuel.



MACK® MD7

ENGINE	Cummins B6.7 Inline 6-cylinder, Turbo/Intercooled Diesel			CAB		Steel cab with Premium trim level					
				Air Conditioning	9	Standard					
	220 hp/600 lb. ft.						Audio		AM/FM with Bluetooth		
Horsepower/Torque –	240 hp/560 lb. ft.						Cab Lighting		Interior courtesy lights (2)		
	250 hp/660 lb. ft.						Cab Mirrors		Bright finish with lower convex mirror		
	260 hp/660 lb. ft.						Cab Suspension		Dual airbag cab suspension		
	280 hp/660 lb. ft.						Cruise Control		Standard		
	300 hp/660 lb. ft.										
Air Cleaner Type	11 inch						Cup Holders		Two large cup holders in console		
Alternator	Delco 12V, 145 amp						Passenger Door Window		Lower door window with lens		
Batteries	Dual 760CCA (1520 total CCA)					Power Outlets		12 volt and USB			
Engine Brake	Cummins with dash switch						Power Steering		Standard		
	Filter	and Wat	er Sepai	ator			Power Windows and Locks		Standard		
Fuel Filter -	Heated, Fuel and Water Separator				Pro Dash		Premium dash cluster				
Starter	Melco	12V					Seat Driver		High back, air suspension w/vinyl trim		
							Seat Passenge	r	High back, fixed base w/vinyl trim		
	STANDARD OPTIONAL Allison 2500HS Allison 2500RDS						Steering Column		Tilt and Telescopic		
TRANSMISSION							Steering Wheel		Flat-bottom steering wheel		
					6-speed, double OD rated to 660 lb. ft.		Sun Visors		Driver and Passenger		
	• *				, w/Fuel 2.0 Plus						
	BRAKE SYSTEM		Bendix Antilock Braking System "S" Cam Air Brake System								
Rear Axle Ratios	5.29	5.57	5.83	5.29	5.57	5.83	Front Brakes		Meritor S Cam, 16.5" x 5" in.		
Est Engine	1916	2018	2112	1916	2018	2112	Rear Brakes		Meritor S Cam, 16.5" x 7" in.		
RPM @ 65 mph									·		
							Parking Brake		Rear axle, spring brake		
FRONT AXLE								Round 22	in driver-eide 50 gallone		
GAWR	12,000 lbs.		FUEL TANK	Round 22 in, driver-side. 50 gallons							
Axle Type	М	eritor M	FS-12, I-	Beam			Round 22		in, driver-side. 90 gallons		
Suspension	Hendrickson Taper Leaf, 12,000 lbs.			DEF TANK	25 liter, passenger-side						
Shock Absorbers	Te	elescopio	type								
CHASSIS FRAME							WHEELS		steel powder coated white disc wheels 5 in., offset 6.6 in., 5-hole		
Rail Dimensions	260 x 70 x 8 mm					ride aluminum wheels x 22.5 in., offset 6.59 in.; 10-hole					
Yield Strength and RBN	1 12	20k psi,	1.547m l	RBM				Bridgestone R268 Ecopia radials			
Assembled Width	34 inches (864 mm)						TIRES	All season, all position, 11R22.5 (G)			
								Ü	ne M760 Ecopia radials		
							Tractio		ction, rear position, 11R22.5 (G)		

REAR AXLE	STANDARD	OPTIONAL		
GAWR (lb.)	21,000	21,000		
Axle Type – Meritor	MS-21-13x	MS-21-14x*		
Suspension - Taper Leaf (lb.)	21,000			
Suspension - Optional (lb.)	Mack Maxlite AL210 21,000**			

[☐] Shaded areas indicate optional equipment.

 $^{^{\}star}14x \text{ and driver controlled differential lock, Rear axle option equipped with driver controlled differential lock.}$

 $^{^{\}star\star}\textsc{Rear}$ air suspension available on 206-, 221-, 236-, 251- and 270-inch wheelbases only.



WARRANTY SUMMARY	MD Series Models MD6, MD7				
Typical Vocations	Distribution, Short Haul or P&D				
Axle Configuration	4 x 2				
Basic Coverage	24 months/unlimited miles*				
Batteries	12 months/unlimited miles*				
Chassis Towing	90 days or 5,000 miles (8 047 KM), whichever occurs first*				
Air Conditioning	24 months/unlimited miles – air conditioning (sealed system only)				
Engine/Emission	Warranty provided by Cummins Engine				
Transmission	Warranty provided by Allison Transmission				
Driveline, Rear Axle, Front Steer Axle	24 months/unlimited miles*				
Cab Structure and Internal Cab Corrosion	60 months/unlimited miles*				
Frame Rail/ Cross Members	60 months/unlimited miles*				
Noise Emission	Life of vehicle*				

^{*}See complete warranty certificate for details.

All illustrations, specifications and descriptions in this specification are based on the latest product information available at the time of this publication. The right is reserved to make changes in price, materials, equipment, design, specifications, diagrams and models, and to discontinue models of equipment at any time, without notice and without incurring any obligation whatsoever. For more information on additional options and accessories, contact Mack Trucks, Inc. (www.macktrucks.com).

UPTIME SUMMARY	MD Series Models MD6, MD7				
Mack OneCall™	12 months				
Mack ASIST	12 months				
Geotab Basic	12 months				
PURCHASE OPTIONS					
Mack OneCall	24-60 months, in 12 mo. increments				
Mack ASIST	24-60 months, in 12 mo. increments				
Geotab Basic	24-60 months, in 12 mo. increments				
Geotab Plus	12-60 months, in 12 mo. increments				
OTHER OPTIONS					
Allison Programming	Fuel Sense 2.0 MAX				
Battery Shut Off	Under cab, passenger side				
Engine Block Heater					
Air Filter Indicator	Under hood, restriction indicator mounted to air cleaner				
PTO Preparation Kit	Harness and switch kit				
Cab Mirrors	Chrome finish and convex mirror heated and motorized				
Seat Passenger	Two-person bench seat w/vinyl and under seat storage				
Drivers Seat Trim	Modura cloth upgrade seat upholstery				
Passenger Seat Trim	Modura cloth upgrade seat upholstery				
Passenger Bench Trim	Modura cloth upgrade seat upholstery				



[☐] Shaded areas indicate optional equipment.