



## LCT600

Kubota WSG3800 3.8L  
4-cylinder gasoline engine  
rated 87HP, EPA T2

- 28" suction impeller
- Hydraulic hose boom
- 16" dia. x 120" rubber intake hose

The LCT600 has the best  
suction of any unit in it's class.  
Contact your local Xtreme Vac  
dealer to order yours today!

\*Standard color is white.

\*Units may be shown with options.



Sold and Serviced by:

042220

## Specifications

## Tow-Behind Debris Collector-Trailer Mounted

### Engine - Gas

Kubota WSG3800 3.8L 4-cylinder gasoline engine, rated at 87HP, meets EPA T2 & CARB T3 standards.

### Engine Controls

Electronic engine controls with safety shut down.

### Drive

Belt driven via a 4-groove Kevlar power band.

### PTO

13" clutch assembly with 2.25" PTO shaft and safety engagement system.

### Trailer

1/4" thick trailer deck with channel members on ends.

### Axles

Single 6,000 lb. Torflex axle with EZ lube hubs. Equipped w/ electric brakes with break-away actuator.

### Tires

(2) ST225-75-R15 radial tires on steel wheels.

### Options

- 2 or 3-axis hose boom (up/dn, left/rt, in/out)
- Wireless boom controls (multi-axis boom only)
- 7,000lb Torflex axle and wireless belly pack (multi-axis boom only)
- Hydraulic parking jack in lieu of manual
- Fluid drive coupler in lieu of standard clutch
- Remote electric throttle for engine
- Remote electric clutch for engine
- 45 degree intake hose flange
- Urethane suction hose in lieu of rubber
- Urethane coated liners for blower housing
- Driver's side (street) pick up
- 38" Hydraulic curb nozzle
- Hydraulic agitator for curb nozzle
- Rotary self-cleaning radiator screen
- 30" fan

### Engine - Option

John Deere 4045TFC03 4-cylinder diesel engine rated at 74HP - Final T4

### Radiator Screen

Boxed corrugated radiator screen constructed from perforated steel to increase air flow for better cooling.

### Intake Hose

16" x 120" rubber suction hose with steel nozzle.

### Hose Boom

Hydraulic hose boom powered by 12v electric / hydraulic pump.

### Impeller

28" dia. suction impeller with six 3/8" thick T-1 AR steel plate blades. Replaceable 1/4" thick steel liners.

### Exhaust Hose

16" dia. x 48" long rubber exhaust hose.

### Fuel Tank

44-gallon polyethylene fuel tank.

### Pintle Eye

Heavy-duty height adjustable pintle eye with three quick release pins.

### Parking Jack

Manual parking jack with 5" swivel castor wheel.

### Lights

LED type DOT trailer lights. One amber LED flasher light at the rear.

### Paint

All components are pre-painted with PPG paint - Unit - standard white, Engine - Battleship grey. Other custom paint colors available as options.



Kubota  
Gas  
Engine  
Option



John Deere  
Diesel  
Engine  
Option