




LP61-G

Portable Litter Vacuum - Gasoline



LP61-G product video: <https://www.youtube.com/watch?v=fSPwxRsISM&t=12s>

Madvac website: www.madvac.com



Part No.	Description	
LP61-G	LP61 Gasoline Skid Includes the following standard features: <ul style="list-style-type: none">* 360° rotating vacuum hose support boom* Exhaust bag dust control system* Emergency stop button* Standard 25 ft. (7620 mm) vacuum hose	
K61T	Trailer conversion kit Available trailer attachment types: Ball 1-7/8" (K60344) Ball 2" (K60345) Pintle (K63117)	
K63087	Spare wheel mounted on trailer	
K9899	Additional 8 in. (203 mm) diameter X 15 ft. (4572 mm) hose extension	
K13063	Additional 8 in. (203 mm) diameter X 25 ft (7620 mm) hose extension	
K11793	2 micron interior cylindrical filter cartridge (for additional dust control)	
63271	Litter collector bags (100 bags)	



LP61-G Portable Litter Vacuum

Product Overview

<http://www.madvac.com>



Table of Contents



Application.....	3
Why the LP61-G.....	4-5
Specs, Characteristics & Performance.....	6-20
Vacuum System.....	21-23
Litter Collection System.....	24-26
Contact Us.....	27


LP61-G options:

Trailer conversion kit.....	6
Spare wheel.....	19
Hose extension.....	22
Litter collector bags.....	24
Filter cartridge.....	25



Application

Ideal for hard-to-reach soiled areas such as windblown trash at landfill and transfer station fence lines, parking lots, parks, cycling trails and industrial sites.




Why the LP61-G?

- Powerful vacuum litter collector: 5 times more efficient than manual picking
- Patented straight-through suction compacts litter
- No fan to jam technology

Why the LP61-G



- Compact, lightweight, easy to use
- 2 transport options:
 - standard pickup truck with 6-ft bed
 - tow behind trailer with standard hitch



Trailer attachment types available:

- 2 in. ball
- 1.78 in. ball
- pintle

Trailer jack

Trailer wiring harness (4 pin)




**Skid mount to trailer
option (or the reverse)
in 45 min**

Skid



Option Trailer Mounted



Dimensions

Skid Mount

- Length: 72 in. (1828 mm)
- Width: 47.2 in. (1198 mm)
- Height: 49.5 in. (1257 mm)
- Weight: 750 lbs (340 kg)

Trailer Mount

- Length: 130 in. (3300 mm)
- Width: 47.2 in. (1198 mm)
- Height: 57.5 in. (1460 mm)
- Weight: 952 lbs (425 kg)

Body / Frame

- Heavy gauge steel body on a weilded 1/4 in. structural steel frame
- Electrostatic powder-coated paint






Engine

- Model: HONDA TWIN GX630 (four stroke)
- Displacement: 0.630 L
- Gross rated power: 15.5 kW (20.8 HP)

Double Belt


Transmits engine power to
the fan



Cylinder Muffler


Suppresses engine noise





1 Oil inlet

2 Oil dipstick



1

Fuel filter

2

Spark plug

3

Oil filter

4

Oil drain

Fuel Tank

- Fuel type: gas (no diesel)
- Capacity: 6 gal. (9.5 L)
- Fuel gauge: displays fuel level in the tank
- Cap screw: releases gas pressure






Battery

12-volt heavy duty battery



Instruments


Hour-meter: displays the total operating hours of the machine.



Fuel: displays fuel level in the tank.



Emergency stop button



Control Panel

- 1 Throttle: sets engine revolution
- 2 Choke: set choke on and off for cold temperature engine start up
- 3 Ignition switch: 3 position rotary key switch controls ignition circuit of the machine



Lighting Package

Fully street legal

- Beacon
- 4 corner lights



Wheels



- 4-season radial tires
- 175/80 R 13
- Spare tire for trailer mount option



License Plate Holder

...



- Vacuum rating: 2900 CFM
- Air Flow: 8400 ft./min (237.8 M/min)
- Vacuum fan diameter: 14 in. (365 mm)
- Bottom mounted fan: no litter comes in contact with the fan
- Straight-through suction system compacts litter 2:1 ratio

Vacuum System

Hose Extension



Vacuum Hose

- Diameter: 8 in. (203 mm)
- Length: standard 25 ft. (7.62 m) including the handle
- Optional hose extension: 15 ft. (4.57 m) or 25 ft. (7.62 m)



Hose Support Arm



360-degree rotating vacuum hose support arm allows easy displacement and positioning of the hose



Container

- Litter capacity: 80 gal. (300 L)
- Material: 16-gauge powder-coated steel
- Bag: quick change reusable bag

Note: off-the-shelf bags not compatible with this machine



Dust Control

2-Micron Interior Cylindrical Filter Cartridge (Optional)

Offers additional dust control
(for high pedestrian areas)



Dust Control

Exhaust Filtration Bag

Retains fine particles
and dust before clean
air is expelled



To schedule a demo, request a quote, or for more information on the LP61-G portable vacuum:



855-651-0444 (USA/Canada)
450-651-0444 (International)



info@exprolink.com

http://



www.madvac.com



Madvac®
COMPACT SWEEPERS & VACUUMS

CONNECT WITH US

