

POWELL'S ISUZU TRUCK

Alayna Pickeral | 434-821-5935 | alaynap@powellstruck.com

VA Sheriff FTR base Spec 2023 (2023 FTR, MT4 200"WB, 175"CA, 25,950 GVWR. White, standard model specifications with power windows, power door locks, air conditioning, 5.57 final ratio, 11R22.5G tires, 21,000 multi leaf suspension, steel wheel type, and 50 gallon aluminum fuel tank

Standard	Equipment Summary	
Code	Description	
Vehicle Application		
RQ2	Truck Application	
Emissions		
NG5	50 State Emission	
Tires		
15H 5S8	LRR (low rolling resistance) 11R22.5 G	
Engine		
IE8	Cummins B6.7, diesel engine, 408 CID (6.7L), 260 HP at 2400 RPM, 660 lbft. gross torque at 1600 RPM, 6-cylinder, turbocharged, inter-cooled, EGR cooler, high pressure common rail fuel system, and single module aftertreatment.	
Transmissio		
Y6E	Allison RDS 2550 / 6 speed trans w/ PTO gear	
Wheelbase		
51W	200" Wheelbase 175"CA	
Air Cleaner		
E6U	Dry paper single element. (Donaldson)	
Alternator		
KW1	160 AMP. with integral regulator.	
Battery		
IX1	Dual 12-Volt maintenance free group 31 750 CCA batteries with threaded posts	
Exhaust		
I0B	Single module Cummins aftertreatment w/ DPF & SCR, exhaust cooler, and electronic exhuast restriction.	
Front Axle		
40C	Dana E1254-W 12,000 lbs. capacity	
Rear Suspen		
34L	21,000 lbs. capacity	
SAS	Multi leaf, bolted	
Rear Axle		
M20	Dana S19-140 single-speed axle, 19,000 lbs. capacity with synthetic lubricant	
Ratio		
011	5.571:1	
Fuel Tank		
70A	Left hand rail	
THF	50 Gallon Fuel Tank Capacity	
Seat		
A56	Level air suspension seat with RH armrest driver seat	
Brakes		
Z06	Full air dual circuit, s-cam, drum	
Air Condition	•	
C60	Air conditioner	
	ows & Door Locks	
ILO	Yes	
Floor Mats		
IQ6	Standard Floor Mats	
Model Option		

Current report content is based on data as of 2022-07-11 07:20:02. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.

Initial:



Page 4

POWELL'S ISUZU TRUCK

Alayna Pickeral | 434-821-5935 | alaynap@powellstruck.com

VA Sheriff FTR base Spec 2023 (2023 FTR, MT4 200"WB, 175"CA, 25,950 GVWR. White, standard model specifications with power windows, power door locks, air conditioning, 5.57 final ratio, 11R22.5G tires, 21,000 multi leaf suspension, steel wheel type, and 50 gallon aluminum fuel tank

Standard Equipment Summary		
Code	Description	
G1	White, standard model specifications with power windows, power door locks, air conditioning, 5.57 final ratio, 11R22.5G tires, 21,000 multi leaf suspension, steel wheel type, and 50 gallon aluminum fuel tank	
CAB		
729	Arc white color	
Mirrors		
DJ6	Black mirror head with black stays	
Frame		
7KJ	Straight frame, 80,000 PSI, 33.5 wide	
Front Springs		
34K	12,000 lbs. capacity	
Accessories		
8RP	Radio AM/FM/CD with Bluetooth	
IX2	Rear body dome lamp switch	
Air Compressor		
104	17 CFM turbocharged heavy duty.	

Current report content is based on data as of 2022-07-11 07:20:02. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.

Initial: