

Va Sheriff FVR base spec 2023 (2023 FVR, MV4 200"WB, 175"CA, 33,000 GVWR. White, standard model specifications with power windows, power door locks, air conditioning, 5.57 final ratio, 11R22.5G tires, 21,000 multi leaf suspension, steel wheel type, and 100 gallon aluminum fuel tank

Standard Equipment Summary

Code	Description
Vehicle Application	
RQ2	Truck Application
Emissions	
NG5	50 State Emission
Tires	
I5H	LRR (low rolling resistance)
5S8	11R22.5 G
Engine	
IE8	Cummins B6.7, diesel engine, 408 CID (6.7L), 260 HP at 2400 RPM, 660 lb.-ft. gross torque at 1600 RPM, 6-cylinder, turbocharged, inter-cooled, EGR cooler, high pressure common rail fuel system, and single module aftertreatment.
Transmission	
Y6T	Allison RDS 2500 / 6 speed trans w/ PTO gear
Wheelbase	
51W	200" Wheelbase 175"CA
Air Cleaner	
E6U	Dry paper single element. (Donaldson)
Alternator	
KW1	160 AMP. with integral regulator.
Battery	
IX1	Dual 12-Volt maintenance free group 31 750 CCA batteries with threaded posts
Exhaust	
I0B	Single module Cummins aftertreatment w/ DPF & SCR, exhaust cooler, and electronic exhaust restriction.
Front Axle	
40C	Dana E1254-W 12,000 lbs. capacity
Rear Suspension	
34L	21,000 lbs. capacity
SAS	Multi leaf, bolted
Rear Axle	
M21	Dana S21-140 single-speed axle, 21,000 lbs. capacity with synthetic lubricant
Ratio	
011	5.571:1
Fuel Tank	
70A	Left hand rail
EHC	100 Gallon Fuel Tank Capacity
Seat	
A56	Level air suspension seat with RH armrest driver seat
Brakes	
Z06	Full air dual circuit, s-cam, drum
Air Conditioning	
C60	Air conditioner
Power Windows & Door Locks	
IL0	Yes
Floor Mats	
IQ6	Standard Floor Mats
Model Option	

Current report content is based on data as of 2022-07-11 06:53:51. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



POWELL'S ISUZU TRUCK

Alayna Pickeral | 434-821-5935 | alaynap@powellstruck.com

Va Sheriff FVR base spec 2023 (2023 FVR, MV4 200"WB, 175"CA, 33,000 GVWR. White, standard model specifications with power windows, power door locks, air conditioning, 5.57 final ratio, 11R22.5G tires, 21,000 multi leaf suspension, steel wheel type, and 100 gallon aluminum fuel tank

Standard Equipment Summary

Code	Description
G2	White, standard model specifications with power windows, power door locks, air conditioning, 5.57 final ratio, 11R22.5G tires, 21,000 multi leaf suspension, steel wheel type, and 100 gallon aluminum fuel tank
CAB	
729	Arc white color
Mirrors	
DJ6	Black mirror head with black stays
Frame	
7KJ	Straight frame, 80,000 PSI, 33.5 wide
Front Springs	
34K	12,000 lbs. capacity
Accessories	
8RP	Radio AM/FM/CD with Bluetooth
IX2	Rear body dome lamp switch
Air Compressor	
I04	17 CFM turbocharged heavy duty.

Current report content is based on data as of 2022-07-11 06:53:51. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.