



# POWELL'S ISUZU TRUCK

Alayna Pickeral | 434-821-5935 | alaynap@powellstruck.com

Va Sheriff NPRHD crew Diesel 2023 (2023 NPR-HD Crew Cab Chassis, 3G4 176"WB, 114.5"CA, 14,500 GVWR. White, 30 Gallon Stainless Steel In-Rail Fuel Tank with power windows, power door locks and air conditioning

## Standard Equipment Summary

Code	Description
<b>Tires</b>	
I5H	LRR (low rolling resistance)
<b>Engine</b>	
I1B	4HK1-TC, diesel engine 317 CID (5.19L), 215 HP at 2550 RPM: 452 ft.-lb. gross torque at 1850 RPM. 4 cylinder, 16 valve, four cycle, overhead cam, turbocharged, inter-cooled, water cooled EGR valve, direct injection, electronically controlled common rail fuel system, engine cruise control function. Oil level check switch and light. Engine Warning system with audible warning for low oil pressure, high coolant temperature, and low coolant level.
<b>Transmission</b>	
I1W	Aisin A465id 6-speed automatic transmission, Ratios: 3.742, 2.003, 1.343,
<b>Wheelbase</b>	
IH7	176 inches, includes ladder type channel frame. Full C section straight frame 33.5 inches wide. Yield strength 44,000 psi; section modulus 11.89 in3 RBM 523,160 lb./ft./in. per rail. 114.5"CA
<b>Air Cleaner</b>	
KNX	Dry Paper single element. (Donaldson brand) Air cleaner canister standard with air restriction indicator in the driver's Multi-Information Display (MID).
<b>Alternator</b>	
I2C	140 AMP. with integral regulator.
<b>Battery</b>	
IX1	Dual 12-Volt maintenance free group 31 750 CCA batteries with threaded posts
<b>Exhaust</b>	
IX7	Single horizontal with DPF/SCR exhaust system
<b>Front Axle</b>	
ID2	"I"-beam rated at 6,830 lbs. Includes integral hydraulic power steering. Ratio 18.8-20.9:1.
<b>Front Suspension</b>	
ID4	6,830 lb. capacity. Semi-elliptical tapered leaf springs. Includes shock absorbers and stabilizer bar.
<b>Front Wheels</b>	
RBV	16" X 6", 6-hole disc, painted white.
<b>Front Tires</b>	
I53I69	215/85R16E (10 ply) tubeless Radial, all season tread.
<b>Rear Suspension</b>	
I27	9,880 lbs. capacity. Semi-elliptical main and auxiliary multi-leaf springs. Includes shock absorbers
<b>Rear Axle</b>	
I36	R040, single-speed, 11,020 lb. capacity with oil lubricated rear wheel bearings.
<b>Ratio</b>	
005	4.56:1
<b>Rear Wheels</b>	
RBZ	16" X 6", 6-hole disc, painted white.
<b>Rear Tires</b>	
I53I34	215/85R16E (10 ply) tubeless Radial, all season tread.
<b>Fuel Tank</b>	
I4I	30 Gallon Stainless Steel In-Rail Fuel Tank
<b>Seat</b>	
AQB	Driver seat is reclining high back. Two single occupant fold down seats with tray backs.
<b>Brakes</b>	
K40	Butterfly valve type exhaust brake
IE1	Vacuum + Power Assist; hydraulic 4-wheel disc brakes with 4-channel ABS. Mechanical, transmission mounted parking

Current report content is based on data as of 2022-07-11 07:18:32. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



# POWELL'S ISUZU TRUCK

Alayna Pickeral | 434-821-5935 | alaynap@powellstruck.com

Va Sheriff NPRHD crew Diesel 2023 (2023 NPR-HD Crew Cab Chassis, 3G4 176"WB, 114.5"CA, 14,500 GVWR. White, 30 Gallon Stainless Steel In-Rail Fuel Tank with power windows, power door locks and air conditioning

## Standard Equipment Summary

Code	Description
	brake. Non-asbestos semi metallic linings are standard.
<b>Air Conditioning</b>	
C60	Air conditioner
<b>Power Windows &amp; Door Locks</b>	
IL0	Yes
<b>Floor Mats</b>	
IQ6	Standard Floor Mats
<b>Model Option</b>	
54	White, 30 Gallon Stainless Steel In-Rail Fuel Tank with power windows, power door locks and air conditioning
<b>Assistance System</b>	
I5I	Electronic Vehicle Stability Control (EVSC) include ASR (Anti-Slip Regulation)
<b>Accessories</b>	
IX2	Rear body dome lamp switch
8RP	AM/FM/CD radio with Aux input/USB port and Bluetooth RPO

Current report content is based on data as of 2022-07-11 07:18:32. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.