



POWELL'S ISUZU TRUCK

Alayna Pickeral | 434-821-5935 | alaynap@powellstruck.com

VA Sheriff NPRHD Reg Cab Gas 2023 (2023 NPR-HD Gas Cab Chassis, 1F4 176"WB, 153.5"CA, 14,500 GVWR. White, Standard model specifications with power windows and door locks

Standard Equipment Summary

Code	Description
Vehicle Application	
RQ2	Truck Application
Tires	
I5H	LRR (low rolling resistance)
Engine	
L8T	GMPT 6.6L (400 CID) V8 gasoline engine; 350 HP at 4500 RPM; 425 lb-ft torque at 3800 RPM; precise fuel control direct injection technology; electronic throttle control; overhead valves with variable valve timing; heavy duty cast-iron cylinder block with six-bolt main-bearing cap; cast aluminum cylinder heads; forged steel crankshaft; stainless steel exhaust manifold.
Transmission	
MYD	6L90-E Hydra-Matic, 6-speed automatic with lock-up converter and overdrive. Ratios: Gear and Ratios 4.027, 2.364, 1.532, 1.152, 0.0852, 0.667, Rev. 3.064:1
Wheelbase	
FNW	176 inches, includes ladder type channel frame. Full C section straight frame 33.5 inches wide. Yield strength 44,000 psi; section modulus 7.20 in3 RBM 316,800 lb./ft./in per rail. 153.5"CA
Air Cleaner	
KNX	Dry paper single element. Air cleaner canister standard with air restriction gauge.
Alternator	
KW7	170 Amp. output with integral regulator.
Battery	
IL3	Single Delco 12-V maintenance free 750 CCA frame mounted battery box
Exhaust	
I41	Single horizontal aluminized steel with catalytic converter and oxygen sensor devices.
Front Axle	
ID2	"I"-beam rated at 6,830 lbs. Includes integral hydraulic power steering. Ratio 18.8-20.9:1.
Front Suspension	
ID4	6,830 lb. capacity. Semi-elliptical tapered leaf springs. Includes shock absorbers and stabilizer bar.
Front Wheels	
IB9	19.5" x 6", 6-hole disc, painted white
Front Tires	
I8B	225/70R19.5G (14 ply) tubeless Radial, all season tread
Rear Suspension	
I8J	12,900 lbs. Capacity semi elliptical; main and auxiliary multi- leaf spring. Includes shock absorbers.
Rear Axle	
ID3	Single-speed, 14,550 lb. capacity with oil lubricated rear wheel bearings.
Ratio	
092	4.300:1
Rear Wheels	
IC1	19.5" x 6", 6-hole disc, painted white
Rear Tires	
I9B	225/70R19.5G (14 ply) tubeless Radial, all season tread.
Fuel Tank	
A17	38.6 gal. rectangular fuel tank. Mounted between frame rail with electric type fuel pump (mounted in tank). Through the rail fuel fill.
Seat	
AQB	Driver seat is reclining high back. Two single occupant fold down seats with tray backs.
Brakes	
IE1	Vacuum + Power Assist; hydraulic 4-wheel disc brakes with 4-channel ABS. Mechanical, transmission mounted parking

Current report content is based on data as of 2022-07-11 07:34:21. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



POWELL'S ISUZU TRUCK

Alayna Pickeral | 434-821-5935 | alaynap@powellstruck.com

VA Sheriff NPRHD Reg Cab Gas 2023 (2023 NPR-HD Gas Cab Chassis, 1F4 176"WB, 153.5"CA, 14,500 GVWR. White, Standard model specifications with power windows and door locks

Standard Equipment Summary

Code	Description
	brake. Non-asbestos semi metallic linings are standard.
Air Conditioning	
C60	Air conditioner
Power Windows & Door Locks	
IL0	Yes
Model Option	
04	White, Standard model specifications with power windows and door locks
Accessories	
IX2	Rear body dome lamp switch
8RP	AM/FM/CD radio with Aux input/USB port and Bluetooth RPO

Current report content is based on data as of 2022-07-11 07:34:21. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.