

POWELL'S ISUZU TRUCK

Alayna Pickeral | 434-821-5935 | alaynap@powellstruck.com

Va Sheriff NPRHD reg cab Diesel 2023 (2023 NPR-HD Cab Chassis, 3F4 176"WB, 153.5"CA, 14,500 GVWR. White, 30 Gallon Stainless Steel In-Rail Fuel Tank with power windows, power door locks and air conditioning

Standard	Equipment Summary
Code	Description
Tires	
I5H	LRR (low rolling resistance)
Engine	
I1B	4HK1-TC, diesel engine 317 CID (5.19L), 215 HP at 2550 RPM: 452 ftlb. gross torque at 1850 RPM. 4 cylinder, 16 valve, four cycle, overhead cam, turbocharged, inter-cooled, water cooled EGR valve, direct injection, electronically controlled common rail fuel system, engine cruise control function. Oil level check switch and light. Engine Warning system with audible warning for low oil pressure, high coolant temperature, and low coolant level.
Transmission	
I1W	Aisin A465id 6-speed automatic transmission, Ratios: 3.742, 2.003, 1.343,
Wheelbase	
FNW	176 inches, includes ladder type channel frame. Full C section straight frame 33.5 inches wide. Yield strength 44,000 psi; section modulus 7.20 in RBM 316,800 lb./ft./in per rail. 153.5 CA
Air Cleaner	
KNX	Dry Paper single element. (Donaldson brand) Air cleaner canister standard with air restriction indicator in the driver's Multi-Information Display (MID).
Alternator	
I2C	140 AMP. with integral regulator.
Battery	
IX1	Dual 12-Volt maintenance free group 31 750 CCA batteries with threaded posts
Exhaust	
IX7	Single horizontal with DPF/SCR exhaust system
Front Axle	
ID2	"I"-beam rated at 6,830 lbs. Includes integral hydraulic power steering. Ratio 18.8-20.9:1.
Front Suspe	nsion
ID4	6,830 lb. capacity. Semi-elliptical tapered leaf springs. Includes shock absorbers and stabilizer bar.
Front Wheels	
RBY Front Tires	16" X 6", 6-hole disc, painted white.
153169	215/85R16E (10 ply) tubeless Radial, all season tread.
Rear Suspension	
127	9,880 lbs. capacity. Semi-elliptical main and auxiliary multi-leaf springs. Includes shock absorbers
Rear Axle	
136	R040, single-speed, 11,020 lb. capacity with oil lubricated rear wheel bearings.
Ratio	
005	4.56:1
Rear Wheels	
RBZ	16" X 6", 6-hole disc, painted white.
Rear Tires	
153134	215/85R16E (10 ply) tubeless Radial, all season tread.
Fuel Tank	
141	30 Gallon Stainless Steel In-Rail Fuel Tank
Seat	
AQB	Driver seat is reclining high back. Two single occupant fold down seats with tray backs.
Brakes	
K40 IE1	Butterfly valve type exhaust brake Vacuum + Power Assist; hydraulic 4-wheel disc brakes with 4-channel ABS. Mechanical, transmission mounted parking
Current reno	ort content is based on data as of 2022-07-11 07:33:35. Any performance-related calculations are offered solely as guidelines. Actual vehicle

Current report content is based on data as of 2022-07-11 07:33:35. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



POWELL'S ISUZU TRUCK

Alayna Pickeral | 434-821-5935 | alaynap@powellstruck.com

Va Sheriff NPRHD reg cab Diesel 2023 (2023 NPR-HD Cab Chassis, 3F4 176"WB, 153.5"CA, 14,500 GVWR. White, 30 Gallon Stainless Steel In-Rail Fuel Tank with power windows, power door locks and air conditioning

Code Description

brake. Non-asbestos semi metallic linings are standard.

Air Conditioning

C60 Air conditioner

Power Windows & Door Locks

IL0 Yes

Floor Mats

IQ6 Standard Floor Mats

Model Option

54 White, 30 Gallon Stainless Steel In-Rail Fuel Tank with power windows, power door locks and air conditioning

Assistance System

151 Electronic Vehicle Stability Control (EVSC) include ASR (Anti-Slip Regulation)

Accessories

IX2 Rear body dome lamp switch

8RP AM/FM/CD radio with Aux input/USB port and Bluetooth RPO

Current report content is based on data as of 2022-07-11 07:33:35. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.