

## **POWELL'S ISUZU TRUCK**

Alayna Pickeral | 434-821-5935 | alaynap@powellstruck.com

VA Sheriff NPRXD Crew Cab 2023 (2023 NPR-XD Crew Cab Chassis, 3Z4 176"WB, 114.5"CA, 16,000 GVWR. White, 30 Gallon Stainless Steel In-Rail Fuel Tank with power windows, power door locks and air conditioning

Standard	Equipment Summary		
Code	Description		
Tires			
I5H	LRR (low rolling resistance)		
Engine			
I1B	4HK1-TC, diesel engine 317 CID (5.19L), 215 HP at 2550 RPM: 452 ftlb. gross torque at 1850 RPM. 4 cylinder, 16 valve, four cycle, overhead cam, turbocharged, inter-cooled, water cooled EGR valve, direct injection, electronically controlled common rail fuel system, engine cruise control function. Oil level check switch and light. Engine Warning system with audible warning for low oil pressure, high coolant temperature, and low coolant level.		
Transmissio	n		
I1W	Aisin A465id 6-speed automatic transmission, Ratios: 3.742, 2.003, 1.343,		
Wheelbase			
IH7	176 inches, includes ladder type channel frame. Full C section straight frame 33.5 inches wide. Yield strength 44,000 psi; section modulus 11.89 in RBM 523,160 lb./ft./in. per rail. 114.5"CA		
Air Cleaner			
KNX	Dry Paper single element. (Donaldson brand) Air cleaner canister standard with air restriction indicator in the driver's Multi-Information Display (MID).		
Alternator			
I2C	140 AMP. with integral regulator.		
Battery			
IX1	Dual 12-Volt maintenance free group 31 750 CCA batteries with threaded posts		
Exhaust			
IX7	Single horizontal with DPF/SCR exhaust system		
Front Axle			
ID2	"I"-beam rated at 6,830 lbs. Includes integral hydraulic power steering. Ratio 18.8-20.9:1.		
Front Suspe			
ID8	8440 lbs. Capacity semi elliptical tapered leaf spring. Includes shock absorbers and stabilizer bar		
Front Wheels			
IB9	19.5" x 6", 6-hole disc, painted white		
Front Tires			
XTN/R3M	225/70R19.5F (12 ply) tubeless Radial, all season		
Rear Suspen			
I9K	14,308 lbs. capacity. Semi-elliptical main and auxiliary multi-leaf springs. Includes shock absorbers.		
Rear Axle			
136	R040, single-speed, 11,020 lb. capacity with oil lubricated rear wheel bearings.		
Ratio			
099	4.777		
Rear Wheels			
IC1	19.5" x 6", 6-hole disc, painted white		
Rear Tires			
YTN/S3M	225/70R19.5F (12 ply) tubeless Radial, all season tread.		
Fuel Tank			
141	30 Gallon Stainless Steel In-Rail Fuel Tank		
Seat			
AQB	Driver seat is reclining high back. Two single occupant fold down seats with tray backs.		
Brakes			
K40 IE1	Butterfly valve type exhaust brake Vacuum + Power Assist; hydraulic 4-wheel disc brakes with 4-channel ABS. Mechanical, transmission mounted parking		
0	ort content is based on data as of 2022.07-11 06:31:48. Any performance related calculations are offered solely as quidelines. Actual vehicle		

Current report content is based on data as of 2022-07-11 06:31:48. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.



## **POWELL'S ISUZU TRUCK**

Alayna Pickeral | 434-821-5935 | alaynap@powellstruck.com

VA Sheriff NPRXD Crew Cab 2023 (2023 NPR-XD Crew Cab Chassis, 3Z4 176"WB, 114.5"CA, 16,000 GVWR. White, 30 Gallon Stainless Steel In-Rail Fuel Tank with power windows, power door locks and air conditioning

Standard Equipment Summary	Standard	Equipment	Summary
----------------------------	----------	-----------	---------

Code Description

brake. Non-asbestos semi metallic linings are standard.

**Air Conditioning** 

C60 Air conditioner

**Power Windows & Door Locks** 

ILO Yes

**Floor Mats** 

IQ6 Standard Floor Mats

**Model Option** 

54 White, 30 Gallon Stainless Steel In-Rail Fuel Tank with power windows, power door locks and air conditioning

**Assistance System** 

151 Electronic Vehicle Stability Control (EVSC) include ASR (Anti-Slip Regulation)

**Accessories** 

IX2 Rear body dome lamp switch

8RP AM/FM/CD radio with Aux input/USB port and Bluetooth RPO

Current report content is based on data as of 2022-07-11 06:31:48. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.