## **POWELL'S ISUZU TRUCK**

Alayna Pickeral | 434-821-5935 | alaynap@powellstruck.com

### Va Sheriff NPRXD Reg Cab 2023 (2023 NPR-XD Cab Chassis, 3Y4 176"WB, 153.5"CA, 16,000 GVWR. White, 30 Gallon Stainless Steel In-Rail Fuel Tank with power windows, power door locks and air conditioning

### **Standard Equipment Summary**

Code	Description
Tires	
15H	LRR (low rolling resistance)
Engine	
I1B	4HK1-TC, diesel engine 317 CID (5.19L), 215 HP at 2550 RPM: 452 ftlb. gross torque at 1850 RPM. 4 cylinder, 16 valve, four cycle, overhead cam, turbocharged, inter-cooled, water cooled EGR valve, direct injection, electronically controlled common rail fuel system, engine cruise control function. Oil level check switch and light. Engine Warning system with audible warning for low oil pressure, high coolant temperature, and low coolant level.
Transmissio	n
I1W	Aisin A465id 6-speed automatic transmission, Ratios: 3.742, 2.003, 1.343,
Wheelbase	
FNW	176 inches, includes ladder type channel frame. Full C section straight frame 33.5 inches wide. Yield strength 44,000 psi; section modulus 7.20 in3 RBM 316,800 lb./ft./in per rail. 153.5"CA
Air Cleaner	
KNX	Dry Paper single element. (Donaldson brand) Air cleaner canister standard with air restriction indicator in the driver's Multi- Information Display (MID).
Alternator	
I2C	140 AMP. with integral regulator.
Battery	
IX1	Dual 12-Volt maintenance free group 31 750 CCA batteries with threaded posts
Exhaust	
IX7	Single horizontal with DPF/SCR exhaust system
Front Axle	
ID2	"I"-beam rated at 6,830 lbs. Includes integral hydraulic power steering. Ratio 18.8-20.9:1.
Front Suspe	nsion
ID8	8440 lbs. Capacity semi elliptical tapered leaf spring. Includes shock absorbers and stabilizer bar
Front Wheels	
IB9	19.5" x 6", 6-hole disc, painted white
Front Tires	
XTN/R3M	225/70R19.5F (12 ply) tubeless Radial, all season
<b>Rear Suspen</b>	sion
19K	14,308 lbs. capacity. Semi-elliptical main and auxiliary multi-leaf springs. Includes shock absorbers.
Rear Axle	
136	R040, single-speed, 11,020 lb. capacity with oil lubricated rear wheel bearings.
Ratio	
099	4.777
<b>Rear Wheels</b>	
IC1	19.5" x 6", 6-hole disc, painted white
Rear Tires	
YTN/S3M	225/70R19.5F (12 ply) tubeless Radial, all season tread.
Fuel Tank	
4	30 Gallon Stainless Steel In-Rail Fuel Tank
Seat	
AQB	Driver seat is reclining high back. Two single occupant fold down seats with tray backs.
Brakes	
	Butterfly valve type exhaust brake
K40	

Current report content is based on data as of 2022-07-11 06:30:57. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models. 

# **POWELL'S ISUZU TRUCK**

Alayna Pickeral | 434-821-5935 | alaynap@powellstruck.com

#### Va Sheriff NPRXD Reg Cab 2023 (2023 NPR-XD Cab Chassis, 3Y4 176"WB, 153.5"CA, 16,000 GVWR. White, 30 Gallon Stainless Steel In-Rail Fuel Tank with power windows, power door locks and air conditioning

Standard Equipment Summary		
Code	Description	
	brake. Non-asbestos semi metallic linings are standard.	
Air Conditioning		
C60	Air conditioner	
Power Windows & Door Locks		
IL0	Yes	
Floor Mats		
IQ6	Standard Floor Mats	
Model Option		
54	White, 30 Gallon Stainless Steel In-Rail Fuel Tank with power windows, power door locks and air conditioning	
Assistance System		
151	Electronic Vehicle Stability Control (EVSC) include ASR (Anti-Slip Regulation)	
Accessories		
IX2	Rear body dome lamp switch	
8RP	AM/FM/CD radio with Aux input/USB port and Bluetooth RPO	

Current report content is based on data as of 2022-07-11 06:30:57. Any performance-related calculations are offered solely as guidelines. Actual vehicle performance will depend on your operating conditions. All Information, specifications and pricing in this application are based on the latest information available. Isuzu Commercial Truck of America, Inc. reserves the right to discontinue or change, at any time, without prior notice, the pricing, specifications, options, materials, equipment, design and models.