

<b>Spray Patcher Street Max STANDARD EQUIPMENT</b>	
<b>HYDRAULIC SYSTEM</b>	<b>BOOM</b>
Pump, 12 volt power unit	Boom, rear mounted, spring suspension three segment
Hydraulic system pressure, 2000 psi	Balanced with leveling controls
	177" patch radius (4.5m)
<b>PAINT</b>	Manual nozzle tilt
One coat sealer / urethane primer	
Two coats of Imron Elite polyurethane, Yellow standard color	<b>FLUSH TANK</b>
	29 Gallon with sight level gauge
<b>HOPPER / CHUTE</b>	Tank mounted pressure gauge and shut-off valves
Construction, A36 Carbon Steel, 10 Gauge	Remote operated from cab, 3-way emulsion / flush valve
Capacity, 2.0 Cu.FT.	
Fill Opening, 30" x 14"	<b>ENGINE</b>
Forward trailer tongue mounted	Deutz Turbo Charged Tier 4 Final
Aggregate feed, Gravity from dump truck to trailer venturi	Displacement, 2.9L
	74 HP @2600 RPM / Max. Torque 192 LB-FT @ 1800 RPM
	Donaldson 2 element dry type air cleaner with restriction indicator
	Full flow spin-on oil filter
	Three point automatic safety shut down
<b>BLOWER</b>	<b>OPERATING CONTROLS</b>
670 CFM Output	Patcher controls & gauges on boom mounted console:
Positive displacement lobe type air pump	Keyed Ignition switch & Electronic Throttle
Direct Drive from engine	Horn for operator to driver alert
	Voltmeter, tach, oil pressure, water temp and hour meter
<b>EMULSION TANK</b>	Back lit sealed rocker switches with icon and text markings
70 PSI system pressure	Operator on/off emulsion valve and emulsion flow control valve
300 Gallon, R value 20 2-1/2" polyurethane foam installation	<b>MISC.</b>
Heating, Auxiliary engine or 115 volts (230 volt optional)	12 Volt 550 CCA
12" fill / service hatch	Axle Rating 14,400 LB
	Air Compressor 8.5 CFM @ 150 PSI
<b>AGGREGATE DELIVERY</b>	
Hose, 3-1/2" Rubber lined spiral reinforced	<b>SAFETY EQUIPMENT</b>
Nozzle, Heated eight hole spray ring	Wireless rear view camera system
	Amber LED Strobe

WARRANTY					Fire Extinguisher				
12 Months 1200 Hours					Optional Arrow Board				