

M6 SE AVALANCHE STANDARD EQUIPMENT	
HYDRAULIC SYSTEM	MAIN BROOM
Pump, Variable displacement load sense piston	Diameter, 36"; Length 58"
Hydraulic Tank, 35 gallon, w/ shut-off valve	Hydraulic Direct Drive / In Cab Adjustable Variable Speed
Tank & Cab mounted level and temperature indicator	In-Cab Adjustable Pneumatic lift w/ Positive lift Lock
Hydraulic pressure, 3200 psi	Brush type: Solid core, Wafer or poly strip broom
5 Micro Tank Breather Filter	2" wide Tungsten Carbide Trailing Arm Dirt Shoes
10 micron cartridge return filter	Self-Aligning Bearings, Triple Sealed & Shielded
100 Mesh Suction Strainer	GUTTER BROOMS
120,000 BTU oil to air twin fan oil cooler	49" Diameter
PNEUMATIC SYSTEM	5 Segment Wire Filled Vertical Digger
Electronic Digital Readout Air Regulators	Hydraulic Direct Drive / In Cab Adjustable Variable Speed
Auxiliary Air Tank - 1,488 cu. in. capacity	Free Floating Air Suspension & Air Extension
Electro-Pneumatic valves with push to connect fittings	DUST CONTROL SYSTEM
HOPPER	Heavy Duty Electric diaphragm water pump
Construction, A36 Carbon Steel, 10 Gauge, 3/16" Floor	50 PSI, 5.88 GPM
Roof skylights plus LED illumination & viewing window	Water tank capacity 350 gallons, polyethylene
Capacity, 5.0 Cu.Yd.	25-foot long fire hydrant fill hose
Lift Capacity, 14,000 LBS	50 mesh cleanable filter, with shut off valve
Twin Cylinder Scissor Lift and Dump	Five nozzles in front of main broom
Variable Dump Height, 16" to 138"	Seven nozzle front spray bar
Side Inspection Door with Ladder Access	Four nozzles per gutter broom
External weatherproof dump switches	Air purge system for flushing water lines
SQUEEGEE CONVEYOR	OPERATING CONTROLS
Heavy Duty, Constant-Radius Roller Chain	Six Sense - Six programmable sweep settings
Self-Aligning Bearings, Triple Sealed & Shielded	Swivel base console for left or right sweeping
Hydraulic Direct Drive / In Cab Adjustable Variable Speed	Keyed power switch
Bolt In 3/16" Abrasion Resisting Floor Plate	Voltmeter, tachometer, and hour meter
BELT CONVEYOR	Back lit sealed rocker switches with icon and text markings
Heavy Duty Multi-Ply Belt w/ Full Width Cleats	7" TFT LCD color display, 800 x 480 pixels
Self-Aligning Bearings, Triple Sealed & Shielded	SAFETY EQUIPMENT
Hydraulic Direct Drive / In Cab Adjustable Variable Speed	Two body props to lock hopper in raised position
SWEEPER WARRANTY	Rear view camera system
12 Months 1200 Hours	Slow moving vehicle emblem, backup alarm,
	5-lb fire extinguisher, and a warning triangle kit.