

<b>M6 AVALANCHE TE STANDARD EQUIPMENT</b>	
<b>HYDRAULIC SYSTEM</b>	<b>MAIN BROOM</b>
Pump, Variable displacement load sense piston	Diameter, 36"; Length 58"
Hydraulic Tank, 35 gallon, w/ shut-off valve	Hydraulic Direct Drive / In Cab Adjustable Variable Speed
Tank & Cab mounted level and temperature indicator	In-Cab Adjustable Pneumatic lift w/ Positive lift Lock
5 Micro Tank Breather Filter	Brush type: Solid core, Wafer or poly strip broom
10 micron cartridge return filter	2" wide Tungsten Carbide Trailing Arm Dirt Shoes
100 Mesh Suction Strainer	Self-Aligning Bearings, Triple Sealed & Shielded
120,000 BTU oil to air twin fan oil cooler	<b>GUTTER BROOMS</b>
<b>PNEUMATIC SYSTEM</b>	49" Diameter
Electronic Digital Readout Air Regulators	5 Segment Wire Filled Vertical Digger
Auxiliary Air Tank - 1,488 cu. in. capacity	Hydraulic Direct Drive / In Cab Adjustable Variable Speed
Electro-Pneumatic valves with push to connect fittings	Free Floating Air Suspension & Air Extension
<b>HOPPER</b>	<b>DUST CONTROL SYSTEM</b>
Construction, A36 Carbon Steel, 10 Gauge, 3/16" Floor	Heavy Duty Electric diaphragm water pump
Roof skylights plus LED illumination & viewing window	50 PSI, 5.88 GPM
Capacity, 5.0 Cu.Yd.	Water tank capacity 350 gallons, polyethylene
Lift Capacity, 14,000 LBS	25-foot long fire hydrant fill hose
Twin Cylinder Scissor Lift and Dump	50 mesh cleanable filter, with shut off valve
Variable Dump Height, 16" to 138"	Five nozzles in front of main broom
Side Inspection Door with Built In Ladder Access	Seven nozzle front spray bar
External weatherproof dump switches	Four nozzles per gutter broom
<b>ENGINE</b>	Air purge system for flushing water lines
Cummins QSF2.8 74 HP, Liquid Cooled	<b>OPERATING CONTROLS</b>
	Six Sense - Six programmable sweep settings
<b>SQUEEGEE CONVEYOR</b>	Swivel base console for left or right sweeping
Heavy Duty, Constant-Radius Roller Chain	Keyed Ignition switch & Electronic Throttle
Self-Aligning Bearings, Triple Sealed & Shielded	Voltmeter, tach, oil pressure, water temp and hour meter
Hydraulic Direct Drive / In Cab Adjustable Variable Speed	Back lit sealed rocker switches with icon and text markings
Bolt In 3/16" Abrasion Resisting Floor Plate	7" TFT LCD color display, 800 x 480 pixels
<b>BELT CONVEYOR</b>	<b>SAFETY EQUIPMENT</b>
Heavy Duty Multi-Ply Belt w/ Full Width Cleats	Two body props to lock hopper in raised position
Self-Aligning Bearings, Triple Sealed & Shielded	Rear view camera system
Hydraulic Direct Drive / In Cab Adjustable Variable Speed	Slow moving vehicle emblem, backup alarm,
<b>SWEEPER WARRANTY</b>	5-lb fire extinguisher, and a warning triangle kit.
12 Months 1200 Hours	5-lb fire extinguisher, and a warning triangle kit.

