

M5 Standard Unit:

Pump, Variable displacement load sense piston	Diameter, 36"; Length 58"
Hydraulic Tank, 35 gallon, w/ shut-off valve	Hydraulic Direct Drive / In Cab Adjustable Variable Speed
Tank & Cab mounted level and temperature indicator	In-Cab Adjustable Pneumatic lift w/ Positive lift Lock
5 Micro Tank Breather Filter	Brush type: Solid core, Wafer or poly strip broom
10 micron cartridge return filter	2" wide Tungsten Carbide Trailing Arm Dirt Shoes
100 Mesh Suction Strainer	Self-Aligning Bearings, Triple Sealed & Shielded
120,000 BTU oil to air twin fan oil cooler	GUTTER BROOMS
PNEUMATIC SYSTEM	42" Diameter
Electronic Digital Readout Air Regulators	5 Segment Wire Filled Vertical Digger
Auxiliary Air Tank - 1,488 cu. in. capacity	Hydraulic Direct Drive / In Cab Adjustable Variable Speed
Electro-Pneumatic valves with push to connect fittings	Free Floating Spring Suspension
HOPPER	DUST CONTROL SYSTEM
Construction, Stainless Steel (C12) ~LIFETIME WARRANTY~	Heavy Duty Electric diaphragm water pump
Capacity, 4.5 Cu.Yd. Usable	50 PSI, 5.88 GPM
Lift Capacity, 11,000 LBS	Water tank capacity 250 gallons, polyethylene
Twin Cylinder Scissor Lift and Dump	25-foot long fire hydrant fill hose
Variable Dump Height, 16" to 120"	50 mesh cleanable filter, with shut off valve
Side Inspection Door	Five nozzles in front of main broom
	Seven nozzle front spray bar
	Four nozzles per gutter broom
ENGINE	Air purge system for flushing water lines
Deutz 2.2 Turbo Charged 74 HP, Liquid Cooled Tier 4F	OPERATING CONTROLS
Tier Four Final, Non-DEF / No-Regen	Six Sense - Six programmable sweep settings
	Adjustable base console for left or right sweeping
SQUEEGEE CONVEYOR	Keyed Ignition switch & Electronic Throttle
Heavy Duty, Constant-Radius Roller Chain	Voltmeter, tach, oil pressure, water temp and hour meter
Self-Aligning Bearings, Triple Sealed & Shielded	Back lit sealed rocker switches with icon and text markings
Hydraulic Direct Drive / In Cab Adjustable Variable Speed	7" TFT LCD color display, 800 x 480 pixels
Bolt In Stainless Steel Abrasion Resisting Floor Plate	SAFETY EQUIPMENT
	Two body props to lock hopper in raised position
	Rear view camera system
SWEEPER WARRANTY	Slow moving vehicle emblem, backup alarm,
12 Months 1200 Hours	5-lb fire extinguisher, and warning triangle kit.

