

PR1500V Specs: - Recommended CA – 125”

1500 Gal. Vacuum Tank, Base, (54”)

Vac Pump, NVE Pro Liquid Could 607 w/ Max Package

Vacuum Pump Flush Kit

Liquid Cooled Vac Pump/Heated Valve – Coolant Kit

Drive Shaft, Power Transmission

Hot Shift PTO w/ Installation

20” Top Manway

Ladder To Manway w/ Safety Grip Tread

12” Low Profile Primary Shut-Off, 3” Internal

3” Internal Piping Through Tank

3” Dia. Hose Assy, Horiz. Traps

20” Rear Clean-Out MW, 4” Brass Lever Vlv & Cmlks

3” Intake Standpipe, TTMA Flange Connection w/ Brass Lever Vlv & Cmlks

Hose Hooks, Per Pair, as low as possible

Mud Flaps, Per Pair (2)

2” x 6” Tubular Rear Bumper

L.E.D. Running Light Kit w/ Fully Molded Wire Harness

L.E.D. Safety Beacon, Quad Flash Strobe, Clear w/ Yellow Flash

5” Site Eye (1/2,3/4,Full) (3)

Polished Aluminum Hose Trays, Short/Med

Mount Kit w/ Rubber Sill (Single Axle)

Mounting, Hook-Up & Wiring (Single Axle)

Super Liner, (Sides20”, Inside Hose Hooks)

Super Liner, (Hose Trays, Over Rail)

Paint, Custom Color (Code Provided By Customer)

Tool Box Installation, Each (2)

Toolbox, Alum Diamond Plt, 1 Door/Left Hinge, 24x24x24

Toolbox, Alum Diamond Plt, 2 Door/Right Hinge, 24x24x36