

PR3600V Specs: - Recommended CA – 159”

3600 Gal. Vacuum Tank, Base, (72”)

Vac Pump, 866 Max Package, Liquid Cooled

Vacuum Pump Flush Kit

Liquid Cooled Vac Pump/Heated Valve – Coolant Kit

Drive Shaft, Power Transmission

Hot Shift PTO w/ Installation

20” Top Manway

Ladder To Manway w/ Safety Grip Tread

12” Low Profile Primary Shut-Off, 4” Internal

4” Internal Piping Through Tank

4” Dia. Hose Assy, Horiz. Traps

20” Rear Clean-Out MW, 6” Brass Lever Vlv & Cmlks

4” Intake Standpipe, TTMA Flange Connection w/ Brass Lever Vlv & Cmlks

Hose Hooks, Per Pair, as low as possible

Mud Flaps, Per Pair (2)

2” x 6” Tubular Rear Bumper

L.E.D. Running Light Kit w/ Fully Molded Wire Harness

L.E.D. Safety Beacon, Quad Flash Strobe, Clear w/ Yellow Flash

5” Site Eye (1/2,3/4,Full) (3)

Polished Aluminum Hose Trays, Short/Med

Mount Kit w/ Rubber Sill (Tandem & Tri Axle)

Mounting, Hook-Up & Wiring (Tandem, Tri & Quad Axle)

Super Liner, (Sides 20”, Inside Hose Hooks)

Super Liner, (Hose Trays, Over Rail)

Paint, Custom Color (Code Provided By Customer)

Tool Box Installation, Each (2)

Toolbox, Alum Diamond Plt, 1 Door/Left Hinge, 24x24x24

Toolbox, Alum Diamond Plt, 2 Door/Right Hinge, 24x24x36