

2021 Vac Con 290-850 Standard Equipment

290/850	Includes: 2 Stage Vac-Con Blower, 9 CY Debris Tank, 850 Gal H2O, 4X2
---------	--

3/16" Corten Steel Debris Tank - (size as specified by model number)
Full opening rear door
Hydraulic rear door locks, with door grabber with safety latch
5" Butterfly valve with 10' layflat hose
Debris tank Dumping: minimum 50 deg., hydraulic scissors lift - power up/power down
Polyethylene water tank
Automatic Vacuum Breaker and overfill protection
8" vacuum intake hose
Boom travel tie down
4 Way hydraulic boom with 270 deg. Rotation and joystick controls
Front mounted 600' capacity (1" hose)/hydraulic hose reel
60 gpm/2000 psi water pump system
Water pump drive: Standard Aux Engine is GM 5.7L Gasoline, 140HP
400' high pressure jet rodder hose (1" or 3/4")
Manual hose rewind guide
Hose guide (Tiger Tail)
30" leader hose
20 gpm at 600 psi wash down hand gun with 25' of hose and nozzle
Sealed and locking tool box (es) {as indicated by model number}
1) each sanitary and penetrator nozzles
20.5' aluminum intake pipe(1-3', 1-5', 1-6', and 1-6.5' nozzle)
ICC lighting
DuPont Elite Polyurethane Paint
12 month standard warranty - see certificate for details
-
Note: PD Units Include Price for required Hydrostatic Drive Option.
5# Fire Extinguisher
Set Triangles
Hydrostatic Blower Drive