

Standard Specs & Features:

- Manufactured using only mill certified 50K (50,000 psi) high tensile steel
- High tensile 3/16" one piece steel floor (up to 20')
- Thermostat powder coated zinc primer with powder coated top coat (best in the industry)
- 3/8" x 2.5" flat bar rub rail with integral 2" x 4.25" ID outside pockets
- 10' to 13' platforms feature a heavy duty stacked understructure that utilizes 6" structural channel longitudinals, and 3" structural channel cross-members on 12" centers
- 14' to 26' platforms feature 7" structural channel longitudinals, and 4" structural channel cross-members on 12" centers
- Grommeted LED marker lights

Popular Options:

- 3/16" diamond tread floor seamed in 4' increments
- Removable steel sides
- Removable steel slated sides
- Permanent steel sides
- Barn doors
- Double acting tailgate
- Multiple headboard and headboard window options
- Multiple rear, and goose neck hitch options
- Cab protector
- Inside pocket design
- Conversion (Scissor), twin telescopic, direct mount hoist options
- Other options available by request



Godwin Manufacturing has built a reputation for engineering and manufacturing affordable and durable truck equipment that is easy to operate and service.

Phone: 800-892-0181 Fax: 910-892-7402
www.godwinmfg.com



Godwin

