



Peterbilt of Richmond (H830)
2800A Deepwater Terminal
Richmond, Virginia 23212

Virginia Sheriffs Association
901 East Byrd St Suite 1301
Richmond, Virginia 23219
United States of America

David Askew
Cell Phone:
Office Phone:
Email: daskew@thepetestore.com

Kaylyn Mitman
Office Phone: 919-459-6471
Email: kmitman@virginiasheriffs.org

Vehicle Summary

Unit		Chassis	
Model:	Model 220	Fr Axle Load (lbs):	12000
Type:	Full Truck	Rr Axle Load (lbs):	21000
Description 1:	220 Chassis	G.C.W. (lbs):	33000
Description 2:	Standard Chassis		
Application		Road Conditions:	
Intended Serv.:	City Delivery	Class A (Highway)	100
Commodity:	Household Goods	Class B (Hwy/Mtn)	0
		Class C (Off-Hwy)	0
		Class D (Off-Road)	0
Body			
Type:	Flatbed	Maximum Grade:	6
Length (ft):	20	Wheelbase (in):	170
Height (ft):	13.5	Overhang (in):	72
Max Laden Weight (lbs):	1000	Fr Axle to BOC (in):	11.4
Trailer			
No. of Trailer Axles:	0	Cab to Axle (in):	158.6
Type:		Cab to EOF (in):	230.6
Length (ft):	0	Overall Comb. Length (in):	293.6
Height (ft):	0	Special Req.	
Kingpin Inset (in):	0		
Corner Radius (in):	0		
Restrictions			
Length (ft):	40		
Width (in):	102		
Height (ft):	13.5		

Approved by: _____

Date: _____

Note: All sales are F.O.B. designated plant of manufacture.



Sales Code	Std/ Opt	Description	\$ List	Weight
Base Model				
0002201	S	Model 220 The Model 220 is a beautifully compact package offering driver comfort, easy service, entry safety features and vigorous power. The 220 is available with a GVW of 26,000-33,000 lbs. Designed for driver productivity, the Model 220 features 360-degree visibility, superior maneuverability, rugged protection and convenient storage. With low chassis weight, it's perfect for high-volume payloads while the standard Allison automatic transmission and air disc brakes help to provide a comfortable driver experience. The 220 is ideal for pickup and delivery as well as beverage and refuse applications, and it is available in a right-hand drive configuration for street sweepers and paint striper operations.	95,089	9,794
0070529	S	LFNA, Euro 6, LHD, Hi-HP, U.S. Registry	0	0
0091090	S	Household Goods	0	0
0093340	S	City Delivery Truck or tractor which hauls freight, typically operating within a 100-mile radius, on public streets and highways and other paved surfaces. Typically includes package and freight delivery.	0	0
0095020	S	Flatbed	0	0
0098170	S	United States Registry Canadian Registry Package Requires Air Conditioning Excise Tax Canada, Speedometer to be KPH ipo MPH, Daytime Running Lights and Rubber Battery Pad in Bottom of Battery Box.	0	0
Configuration				
0200700	S	Not Applicable Secondary Manufacturer	0	0
Frame & Equipment				
0510170	S	10-1/4" Steel Rails, Steel Crossmembers	0	0
0612410	S	170" Wheelbase, 72" Overhang Suitable for 18' body length	0	0
0644090	S	EOF Square without Crossmember End-of-frame square without crossmember. For use with body builder installed crossmember.	0	0
0651090	S	Omit Rear Mudflaps and Hangers	0	0
Front Axle & Equipment				
1011850	S	Dana Spicer E1202IR 12,000 Lb.	0	0
1111190	S	Taper Leaf Springs, Shocks 12,000 lb Hendrickson taper leaf springs, shocks for 12,000 lbs.	0	0

Price Level: January 1, 2022

Deal: 220 Chassis

Printed On: 7/6/2022 2:41:22 PM

Date: July 06, 2022

Quote Number: QUO-951381-M9B6J2



Sales Code	Std/ Opt	Description	\$ List	Weight
1233140	S	Power Steering, 12K Capacity, Single Power Supplier: Bosch	0	0
1354840	O	PHP10 Iron PreSet PLUS Hubs PHP10 iron PreSet PLUS hubs have a fully integrated spindle nut design, an optimized wheel spacer, magnetic fill plug on drive and trailer hubs for inspection of metal particles in lubricant, with a long life oil seal and bearings are pre-adjusted. Use with Front Axle.	-632	0
1391450	O	Meritor Q+ Air Cam Frt Drum Brks 15x5	-225	-35
Rear Axle & Equipment				
1512945	S	Dana Spicer S21-140 21,000 lb	0	0
1616300	O	PHP10 Iron PreSet PLUS Hubs	441	0
1680500	S	SBM Valve Full trucks require a spring brake modulation (SBM) system for emergency braking application. This system requires an SBM valve and a relay valve with spring brakes on the rear axles. The SBM valve allows the foot valve to operate the rear axle spring brakes if a failure exists in the rear air system.	0	0
1680750	O	Meritor Q+ Air Cam Rear Drum Brakes 16.5x7	-41	0
1680950	S	Stability System Not Selected Or Not Available	0	0
1683255	S	WABCO Electronic Braking System (EBS) With Antilock And Traction Control	0	0
1684200	S	Synthetic Axle Lubricant All Axles Peterbilt heavy duty models include Fuel Efficient Cognis EMGARD FE75W-90 which provides customers performance advantages over current synthetic lubricants with reduced gear wear and extended maintenance intervals, resulting in increased uptime. In addition, the lubricant provides improved fluid flow to protect gears in extreme cold conditions and withstand the stress from high temperatures, extending component life.	0	0
1706500	O	Ratio 6.50 Rear Axle	0	0
1816140	S	Reyco 79KB Taper Leaf 21,000 lb	0	0
Engine & Equipment				
2073117	S	PACCAR PX-7 220@2400 GOV@2600 520@1600 Efficiency (2021 Emissions) N21350 C121 75....Maximum Accelerator Pedal Ve N21370 C128 75....Maximum Cruise Speed (P059) N21460 C132 1400..Max PTO Speed (P046) N21520 C133 5.....Timer Setting (P030) N21610 C188 39....Low Ambient Temperature Thre N21620 C189 60....Intermediate Ambient Tempera N21630 C190 80....High Ambient Temperature Thr N21550 C206 35....Engine Load Threshold (P516)	0	0

Price Level: January 1, 2022

Deal: 220 Chassis

Printed On: 7/6/2022 2:41:22 PM

Date: July 06, 2022

Quote Number: QUO-951381-M9B6J2



Sales Code	Std/ Opt	Description	\$ List	Weight
		N21340 C209 120...Hard Maximum Speed Limit (P1		
		N21510 C225 YES...Enable Idle Shutdown Park Br		
		N21450 C231 NO....Gear Down Protection (P026)		
		N21570 C233 NO....Idle Shutdown Manual Overrul		
		N21440 C234 NO....Engine Protection Shutdown (
		N21480 C238 NO....Auto Engine Brake in Cruise		
		N21470 C239 NO....Cruise Control Auto Resume (
		N21430 C333 0.....Reserve Speed Limit Offset (
		N21410 C334 0.....Maximum Cycle Distance (N202		
		N21590 C382 YES...Enable Hot Ambient Automatic		
		N21500 C395 0.....Expiration Distance (N209)		
		N21530 C396 YES...Enable Impending Shutdown Wa		
		N21540 C397 60....Timer For Impending Shutdown		
		N21320 C399 120...Standard Maximum Speed Limit		
		N21400 C400 252...Reserve Speed Function Reset		
		N21420 C401 10....Maximum Active Distance (N20		
		N21330 C402 0.....Expiration Distance (N207)		
2091305	S	Engine Idle Shutdown Timer Enabled	0	0
2091315	O	Enable EIST Ambient Temp Overrule	0	0
2091372		Eff EIST NA Expiration Miles	0	0
2091640		Effective VSL Setting NA	0	0
2092016	O	Typical Operating Speed 62 MPH	0	0
2092033	O	Powertrain Optimized for Balance Best analysis for vehicles where service includes frequent start and stop cycles.	0	0
2140220	O	CARB Engine Idling Compliance DECLINED By Dealer/Customer	0	0
2140670	O	EPA Emission Warranty	0	0
2513050	S	160 Amp Alternator, Brushed 160 amp alternator is a brush style alternator is designed to address vehicle applications that require higher electrical output, but also want lower weight, improved temperature capability and fuel savings.	0	0
2521330	S	Cold Start Engine Grid Heater Effective to -4 F / -20 C	0	0
2522020	S	Delco 12V Starter PX-7 Engine. Delco Starter 12 volt used on utility/work trucks to power inverters, plug-in power tools, lights and other electrical equipment. Ideal for highway trucks with multiple battery auxiliary power units.	0	0
2538030	S	2 PACCAR Premium 12V Starting Batteries 2000 CCA Threaded stud type terminal. Stranded copper battery cables are double aught (00) or larger to reduce resistance.	0	0
2539740	S	Kissling Battery Disconnect Switch, 300 amp Mounted on battery box	0	0

Price Level: January 1, 2022

Deal: 220 Chassis

Printed On: 7/6/2022 2:41:22 PM

Date: July 06, 2022

Quote Number: QUO-951381-M9B6J2



Sales Code	Std/ Opt	Description	\$ List	Weight
2636030	S	Viscous Type Fan Clutch	0	0
2723210	S	18.7 CFM Air Compressor N/A X15. Furnished on engine. Teflon lined stainless steel braided compressor discharge line.	0	0
2921160	S	Spin-On Fuel/Water Separator	0	0
2921210	S	No Fluid Heat Option for Fuel Filter	0	0
2921310	S	No Electric Heat Option for Fuel Filter	0	0
3114270	S	High Efficiency Cooling System Cooling module is a combination of steel and aluminum components, with aluminum connections to maximize performance and cooling capability. Silicone radiator & heater hoses enhance value, durability, & reliability. Constant tension band clamps reduce leaks. Chevron Delo Extended Life Coolant (NOAT) extends maintenance intervals reducing maintenance costs. Anti-freeze effective to -30 degrees F helps protect the engine. Low coolant level sensor warns of low coolant condition to prevent engine damage. Radiator Size by Model: 579/367 FEPTO 1325 sq in, 567/365/367: 1440 sq in, 365 FEPTO: 1184 sq in, 389/367 HH: 1669 sq in, 348: 1000 sq in, 520: 1242 sq in.	0	0
3270020	S	(1) Air Cleaner Fender Mounted RH BOC	0	0
3280030	S	High Air Intake	0	0
3365290	S	Exhaust Single RH Horizontal DPF/SCR RH Under Frame.	0	0
Transmission & Equipment				
4051500	S	Allison 2500 HS Transmission, Gen 5 Highway Series. Includes Allison Shift Performance, Mobil Delvac Automatic Transmission Fluid, and Water-Oil Heat Exchange. Also includes dash mounted indicator light when the transmission fluid, filter or clutches need service. Meets the needs of on-highway vehicles that do not require PTO operation. The HS series provides no PTO provisions. Forward ratios: 1st-3.51, 2nd-1.90, 3rd-1.44, 4th-1.00, 5th-0.74, 6th-0.64. Reverse ratios: DR-(5.09).	0	0
4210930	S	SPL100 Driveline, 1 Midship Bearing	0	0
4252840	O	Allison FuelSense 2.0 Plus Features include: EcoCal shift technology keeps the engine speed at the most efficient level, DynActive Shifting system incorporates a learning algorithm that selects variable shift points to find the ideal balance of fuel economy and performance, based upon the vehicle specifications and environmental parameters. This is valuable for applications with heavy start-stop needs like refuse, city delivery, and construction and Neutral at Stop reduces or eliminates the load on the engine when vehicle is stopped, lowering fuel consumption and emissions.	0	0

Price Level: January 1, 2022

Deal: 220 Chassis

Printed On: 7/6/2022 2:41:22 PM

Date: July 06, 2022

Quote Number: QUO-951381-M9B6J2



Sales Code	Std/ Opt	Description	\$ List	Weight
4252940	S	Allison Neutral At Stop Neutral at Stop features and benefits: Reduces or eliminates the load on the engine when vehicle is stopped, can help lower fuel consumption and CO2 emissions, and is included in FuelSense 2.0 Plus and Max packages only.	0	0
4256020	S	Console Mounted Push Button Shifter Allison Automatic Transmissions or LFNA Electric Vehicle	0	0
4256780	O	Allison PTO Enable on Mode Button The PTO function C can be either on a remote wire, or mode button. It depends on the selected input/output package. This function is enabled with the MODE button. Enabling the function alerts the TCM that PTO operation has been requested by the operator. When the function is enabled and all of the required operating conditions exist, the TCM activates Output G: PTO Enable by switching power to wire 130. When this function is enabled, the TCM disables the variable modulated main pressure feature in the transmission, resulting in transmission operation at full main pressure. Required operating conditions for enabling this function are: throttle position is low, engine speed is within Customer Modifiable Constant limits, output speed is within Customer Modifiable Constant limits	0	0
4256880	O	Allison 6-Speed Configuration Wide ratio gears, 2500 series transmissions.	0	0
Air & Trailer Equipment				
4510830	S	WABCO SS1200 Plus Air Dryer, Heater Coalescing filter	0	0
4543320	S	Steel Painted Air Tanks All air tanks are steel with painted finish except when Code 4543330 Polish Aluminum Air Tanks is also selected (then exposed air tanks outside the frame rails will be polished aluminum). Peterbilt will determine the optimal size and location of required air tanks. Narratives requesting a specific air tank size or location will not be accepted for factory installation. See ECAT to determine number or location of air tanks installed.	0	0
Tires & Wheels				
5069600	S	FF: BR 14ply 11R22.5 R268 Ecopia Efficiency Rating: Poor R268 tread is not a Line Haul tire and is only for Pickup and Delivery or Regional use. Diameter = 41.5 inches; SLR = 19.3 inches	0	0
5169830	O	RR: BR 14 PLY 11R22.5 M760 Ecopia Efficiency Rating: Poor Diameter= 42.2 inches; SLR= 19.6 inches	328	32
5190004	S	Code-rear Tire Qty 04	0	0
5212020	S	FF: Accu-Lite Steel Armor 51487PK 22.5X8.25 PHP10-5 hand holes.	0	0

Price Level: January 1, 2022

Deal: 220 Chassis

Printed On: 7/6/2022 2:41:22 PM

Date: July 06, 2022

Quote Number: QUO-951381-M9B6J2



Sales Code	Std/ Opt	Description	\$ List	Weight
5312020	S	RR: Accu-Lite Steel Armor 51487PK 22.5X8.25 PHP10-5 hand holes.	0	0
5390004	S	Code-rear Rim Qty 04	0	0
Fuel Tanks				
5516050	S	22" Aluminum 56 Gal Fuel Tank LH BOC	0	0
5604056	S	Location LH BOC 56 Gallon	0	0
5652890	S	DEF Tank Mounted LH BOC Models 220 and 520 mounted left hand back-of-cab.	0	0
5652990	O	DEF To Fuel Ratio 2:1 Or Greater	0	0
5655059	S	DEF Tank Rectangular, 8 Gal	0	0
Battery Box & Bumper				
6020010	S	Steel Battery Box RH BOC Mounted on right-hand frame rail	0	0
6030630	S	Aluminum Battery Box Cover	0	0
6121210	S	Steel Bumper Painted Gray	0	0
Cab & Equipment				
6520020	S	Steel 63.5in BBC ProBilt Cab, LH Drive	0	0
6914130	S	Sears C2 Driver Seat	0	0
6923160	S	(2) Person Passenger Seat	0	0
6939400	S	Air Ride Driver	0	0
6939420	S	High Back Driver	0	0
6939460	S	Fabric Driver	0	0
6939510	S	Non-Air Ride Passenger	0	0
6939540	S	Low Back Passenger	0	0
6939560	S	Fabric Passenger	0	0
7000015	S	Adjustable Steering Column - Tilt Only	0	0
7001540	S	Rear Wall Storage	0	0
7001620	S	Steering Wheel With Peterbilt Logo Steering Wheel with embossed Peterbilt logo over horn button.	0	0

Price Level: January 1, 2022

Deal: 220 Chassis

Printed On: 7/6/2022 2:41:22 PM

Date: July 06, 2022

Quote Number: QUO-951381-M9B6J2



Sales Code	Std/ Opt	Description	\$ List	Weight
7039180	S	Interior Gray Includes view window in RH door and 18 inch 4-spoke foam soft-touch steering wheel.	0	0
7210540	S	Day Cab Rear Window Day cab rear window flush to back of cab.	0	0
7230060	S	1-Piece Curved Windshield	0	0
7230170	S	Electric Powered Window Lift, LH/RH Side	0	0
7322010	S	Combo Fresh Air Heater/Air Conditioner With radiator mounted condenser, dedicated side window defrosters, Bi-Level Heater/Defroster Controls, 54,500 BTU/HR, and silicone heater hoses.	0	0
7561170	S	LH/RH Driving Mirrors Heated/Motorized Heated and motorized mirrors for left and right sides.	0	0
7722120	S	ConcertClass, AM/FM, Weatherband, 3.5 Aux	0	0
7851480	S	Peterbilt Electric Windshield Wipers With Intermittent Feature.	0	0
8021380	S	Air Restriction Indicator Mounted on air cleaner, intake piping, or firewall	0	0
8041200	S	Dual Scale Speedometer MPH Over KPH	0	0
8111150	S	Headlights Dual Round Halogen, Integral Turn Signals	0	0
8121010	S	(5) Marker Lights	0	0
8133270	S	Fog / Driving Lights	0	0
8133960	S	Daytime Running Lights The brake interlock turns the daytime running lights off when the parking brakes are engaged. This is required on all Canadian vehicles.	0	0
8143270	S	Stop/Tail/Turn/Backup Lights RH/LH	0	0
Paint				
8530340	S	Axalta Single Stage Non-Metallic Cab/Hood (Solid Color Paint) N85020 A - M8870EA ICE WHITE DAF N85200 FRAME L0001EA BLACK	0	0
8531330	S	Medium Duty Paint Color M8870 Ice White Lead Time for Ice White Cab is 12 weeks.	0	0
Shipping Destination				
Options Not Subject To Discount				
9400091	S	Peterbilt Class 7 Standard Coverage 1 year/Unlimited Miles/km	0	0
9400093	S	PACCAR PX-7 Standard Coverage	0	0

Price Level: January 1, 2022

Deal: 220 Chassis

Printed On: 7/6/2022 2:41:22 PM

Date: July 06, 2022

Quote Number: QUO-951381-M9B6J2



Sales Code	Std/ Opt	Description	\$ List	Weight
		3 years/Unlimited Miles/Unlimited hrs		
9407103	O	Prepaid Freight Increase For 2022 Delivery	500	0
9408703	O	Base Warr: Emissions 5YR/100K MI-EPA Engine	0	0
Miscellaneous				
9409096	O	State Registry: Virginia	0	0

Promotions

Order Comments



Total List Price (W/O Freight & Warranty & Surcharges)	\$94,960
Marketing and Service Support Fee	\$670
Prepaid Freight	\$2,850
Total Surcharge/Options Not Subject To Discount	\$500
Total Weight	9,791

Prices and Specifications Subject to Change Without Notice.

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in CRM.

PRICING DISCLAIMER

While we make every effort to maintain the web site to preserve pricing accuracy, prices are subject to change without notice. Although the information in this price list is presented in good faith and believed to be correct at the time of printing, we make no representations or warranties as to the completeness or accuracy of this information. We reserve the right to change, delete or otherwise modify the pricing information which is represented herein without any prior notice. We carefully check pricing specifications, but occasionally errors can occur, therefore we reserve the right to change such prices without notice. We disclaim all liability for any errors or omissions in the materials. In no event will we be responsible for any damages of any nature whatsoever from the reliance upon information from these materials. Please check your order prebills to confirm your pricing information



Shipping Destinations

Intermediate Destination: NONE

Final Destinations	Quantity
--------------------	----------