



Peterbilt of Richmond (H830)  
2800A Deepwater Terminal  
Richmond, Virginia 23212

Virginia Sheriffs Association  
901 East Byrd St Suite 1301  
Richmond, Virginia 23219  
United States of America

David Askew  
Cell Phone:  
Office Phone:  
Email: daskew@thepetestore.com

Kaylyn Mitman  
Office Phone: 919-459-6471  
Email: kmitman@virginiasheriffs.org

## Vehicle Summary

Unit		Chassis	
Model:	Model 220	Fr Axle Load (lbs):	10000
Type:	Full Truck	Rr Axle Load (lbs):	23000
Description 1:	220 Chassis	G.C.W. (lbs):	41000
Description 2:	Option Chassis		
Application		Road Conditions:	
Intended Serv.:	City Delivery	Class A (Highway)	100
Commodity:	Household Goods	Class B (Hwy/Mtn)	0
		Class C (Off-Hwy)	0
		Class D (Off-Road)	0
Body			
Type:	Flatbed	Maximum Grade:	6
Length (ft):	18	Wheelbase (in):	170
Height (ft):	13.5	Overhang (in):	72
Max Laden Weight (lbs):	1000	Fr Axle to BOC (in):	11.4
		Cab to Axle (in):	158.6
		Cab to EOF (in):	230.6
Trailer		Overall Comb. Length (in):	293.6
No. of Trailer Axles:	0		
Type:			
Length (ft):	0	Special Req.	
Height (ft):	0		
Kingpin Inset (in):	0		
Corner Radius (in):	0		
Restrictions			
Length (ft):	40		
Width (in):	102		
Height (ft):	13.5		

Approved by: \_\_\_\_\_

Date: \_\_\_\_\_

Note: All sales are F.O.B. designated plant of manufacture.



Sales Code	Std/ Opt	Description	\$ List	Weight
<b>Base Model</b>				
0002201	S	<b>Model 220</b> The Model 220 is a beautifully compact package offering driver comfort, easy service, entry safety features and vigorous power. The 220 is available with a GVW of 26,000-33,000 lbs. Designed for driver productivity, the Model 220 features 360-degree visibility, superior maneuverability, rugged protection and convenient storage. With low chassis weight, it's perfect for high-volume payloads while the standard Allison automatic transmission and air disc brakes help to provide a comfortable driver experience. The 220 is ideal for pickup and delivery as well as beverage and refuse applications, and it is available in a right-hand drive configuration for street sweepers and paint striper operations.	95,089	<b>9,794</b>
0070549	O	<b>LFNA, Euro 6, LHD, Hi-HP, CRP, w/ Console, U.S. Registry</b>	0	<b>0</b>
0091090	S	<b>Household Goods</b>	0	<b>0</b>
0093340	S	<b>City Delivery</b> Truck or tractor which hauls freight, typically operating within a 100-mile radius, on public streets and highways and other paved surfaces. Typically includes package and freight delivery.	0	<b>0</b>
0095020	S	<b>Flatbed</b>	0	<b>0</b>
0098170	S	<b>United States Registry</b> Canadian Registry Package Requires Air Conditioning Excise Tax Canada, Speedometer to be KPH ipo MPH, Daytime Running Lights and Rubber Battery Pad in Bottom of Battery Box.	0	<b>0</b>
<b>Configuration</b>				
0200700	S	<b>Not Applicable</b> Secondary Manufacturer	0	<b>0</b>
<b>Frame &amp; Equipment</b>				
0510170	S	<b>10-1/4" Steel Rails, Steel Crossmembers</b>	0	<b>0</b>
0612920	O	<b>170" Wheelbase, 72" Overhang, Vertical Exhaust Only</b>	335	<b>0</b>
0623330	O	<b>Clear Rail Frame Package</b>	8,972	<b>0</b>
0644090	S	<b>EOF Square without Crossmember</b> End-of-frame square without crossmember. For use with body builder installed crossmember.	0	<b>0</b>
0651090	S	<b>Omit Rear Mudflaps and Hangers</b>	0	<b>0</b>
<b>Front Axle &amp; Equipment</b>				
1011825	O	<b>Dana Spicer E1002IR 10,000 Lb, 3.5" Drop</b>	96	<b>0</b>

Price Level: January 1, 2022

Deal: 220 Chassis

Printed On: 5/19/2022 8:23:17 AM

Date: May 19, 2022

Quote Number: QUO-847777-J9P8T2



Sales Code	Std/ Opt	Description	\$ List	Weight
1111190	S	<b>Taper Leaf Springs, Shocks 12,000 lb</b> Hendrickson taper leaf springs, shocks for 12,000 lbs.	0	0
1233140	S	<b>Power Steering, 12K Capacity, Single Power</b> Supplier: Bosch	0	0
1354850	O	<b>PHP10 Iron PreSet PLUS Hubs - Air Disc</b> Preset iron hub assemblies are designed for demanding conditions and require less maintenance while still offering dependability and superior performance. Precisely engineered to minimize roller stress under heavy loads and increase bearing life when used in demanding conditions such as wide-based single wheels and misalignment due to spindle wear.	279	0
1380290	S	<b>Bendix Air Disc Front Brakes</b> Bendix air disc front brakes use a floating caliper design to provide foundation braking on all axles and complies with reduced stopping distance regulations.	0	0
1391480	O	<b>Pad Dust Shields for Air Disc Brakes; Front Axle</b> Pad dust shields for air disc brakes can increase brake life. Brake dust shields reduce the buildup of road grime, extend brake system life and prevent premature failure.	28	2
<b>Rear Axle &amp; Equipment</b>				
1513280	O	<b>Dana Spicer S23-172, 23,000lb</b>	1,453	269
1616295	O	<b>PHP10 Aluminum Preset PLUS Hubs - Air Disc</b>	1,134	0
1660020	O	<b>Pad and Rotor Dust Shields For Air Disc Brakes, Drive Axle(s)</b>	809	15
1671040	O	<b>Differential Lock Rear-Rear Or Single Drive Axle</b> Air Rocker Switch Occupies the Space of One Gauge	1,015	0
1680500	S	<b>SBM Valve</b> Full trucks require a spring brake modulation (SBM) system for emergency braking application. This system requires an SBM valve and a relay valve with spring brakes on the rear axles. The SBM valve allows the foot valve to operate the rear axle spring brakes if a failure exists in the rear air system.	0	0
1680950	S	<b>Stability System Not Selected Or Not Available</b>	0	0
1683255	S	<b>WABCO Electronic Braking System (EBS)</b> With Antilock And Traction Control	0	0
1684200	S	<b>Synthetic Axle Lubricant All Axles</b> Peterbilt heavy duty models include Fuel Efficient Cognis EMGARD FE75W-90 which provides customers performance advantages over current synthetic lubricants with reduced gear wear and extended maintenance intervals, resulting in increased uptime. In addition, the lubricant provides improved fluid flow to protect gears in extreme cold conditions and withstand the stress from high temperatures, extending component life.	0	0
1687080	O	<b>Air Disc Rear Brakes, Single Drive Axle</b>	2,663	0

Price Level: January 1, 2022

Deal: 220 Chassis

Printed On: 5/19/2022 8:23:17 AM

Date: May 19, 2022

Quote Number: QUO-847777-J9P8T2



Sales Code	Std/Opt	Description	\$ List	Weight
1706140	O	Ratio 6.14 Rear Axle	0	0
1812030	O	Hendrickson HAS230L 23,000 LBS	783	90
1922260	O	Dash Mtd Dump Switch with Indicator Light Dash mounted dump switch with indicator light for suspension.	10	0

## Engine & Equipment

2073217	O	PACCAR PX-7 260@2400 GOV@2600 660@1600 EFFICIENCY (2021 EMISSIONS)	1,342	0
		N21350 C121 75....Maximum Accelerator Pedal Ve N21370 C128 75....Maximum Cruise Speed (P059) N21460 C132 1400..Max PTO Speed (P046) N21520 C133 5.....Timer Setting (P030) N21610 C188 39....Low Ambient Temperature Thre N21620 C189 60....Intermediate Ambient Tempera N21630 C190 80....High Ambient Temperature Thr N21550 C206 35....Engine Load Threshold (P516) N21340 C209 120...Hard Maximum Speed Limit (P1 N21510 C225 YES...Enable Idle Shutdown Park Br N21450 C231 NO....Gear Down Protection (P026) N21570 C233 NO....Idle Shutdown Manual Overrul N21440 C234 NO....Engine Protection Shutdown (N N21480 C238 NO....Auto Engine Brake in Cruise N21470 C239 NO....Cruise Control Auto Resume (N N21430 C333 0.....Reserve Speed Limit Offset (N N21410 C334 0.....Maximum Cycle Distance (N202 N21590 C382 YES...Enable Hot Ambient Automatic N21500 C395 0.....Expiration Distance (N209) N21530 C396 YES...Enable Impending Shutdown Wa N21540 C397 60....Timer For Impending Shutdown N21320 C399 120...Standard Maximum Speed Limit N21400 C400 252...Reserve Speed Function Reset N21420 C401 10....Maximum Active Distance (N20 N21330 C402 0.....Expiration Distance (N207)		
2091305	S	Engine Idle Shutdown Timer Enabled	0	0
2091315	O	Enable EIST Ambient Temp Overrule	0	0
2091372		Eff EIST NA Expiration Miles	0	0
2091640		Effective VSL Setting NA	0	0
2092016	O	Typical Operating Speed 62 MPH	0	0
2092033	O	Powertrain Optimized for Balance Best analysis for vehicles where service includes frequent start and stop cycles.	0	0

Price Level: January 1, 2022

Deal: 220 Chassis

Printed On: 5/19/2022 8:23:17 AM

Date: May 19, 2022

Quote Number: QUO-847777-J9P8T2



Sales Code	Std/ Opt	Description	\$ List	Weight
2140220	O	<b>CARB Engine Idling Compliance DECLINED By</b> Dealer/Customer	0	0
2140670	O	<b>EPA Emission Warranty</b>	0	0
2513050	S	<b>160 Amp Alternator, Brushed</b> 160 amp alternator is a brush style alternator is designed to address vehicle applications that require higher electrical output, but also want lower weight, improved temperature capability and fuel savings.	0	0
2521090	O	<b>Immersion Type Block Heater 110-120V</b> Standard location for 2.1M and 1.9M models is left-hand under cab, Model 520 is in bumper, and for Model 220 it is at the driver step. Plug includes a weather-proof cover that protects the receptacle. This pre-heater keeps the coolant in the engine block from freezing when the engine is not running.	53	2
2521110	O	<b>Oil Pan Heater 120V/300W</b> Oil Pan Heater 120V/300W operates via 120V ShorePower system and keeps oil warm and free flowing for instant lubrication with oil and transmission immersion heaters when the engine is not running. This option utilizes the same receptacle as the immersion pre-heater if specified together.	62	2
2521330	S	<b>Cold Start Engine Grid Heater</b> Effective to -4 F / -20 C	0	0
2522020	S	<b>Delco 12V Starter</b> PX-7 Engine. Delco Starter 12 volt used on utility/work trucks to power inverters, plug-in power tools, lights and other electrical equipment. Ideal for highway trucks with multiple battery auxiliary power units.	0	0
2538020	O	<b>2 PACCAR Premium 12V Dual Purpose Batt 1460 CCA</b> Threaded stud type terminal. Stranded copper battery cables are double aught (00) or larger to reduce resistance.	29	0
2539740	S	<b>Kissling Battery Disconnect Switch, 300 amp</b> Mounted on battery box	0	0
2636030	S	<b>Viscous Type Fan Clutch</b>	0	0
2723210	S	<b>18.7 CFM Air Compressor</b> N/A X15. Furnished on engine. Teflon lined stainless steel braided compressor discharge line.	0	0
2921160	S	<b>Spin-On Fuel/Water Separator</b>	0	0
2921210	S	<b>No Fluid Heat Option for Fuel Filter</b>	0	0
2921320	O	<b>12V Heat for Fuel Filter</b> Fuel filter heaters help ensure a seamless flow of diesel from the tank to the combustion chamber. Eliminating any possibility of moisture freezing within the fuel filter while simultaneously increasing the fuel temperature for atomization within the engine.	68	0
3114270	S	<b>High Efficiency Cooling System</b> Cooling module is a combination of steel and aluminum components, with aluminum connections to maximize performance and cooling capability. Silicone radiator & heater hoses enhance value, durability, & reliability. Constant tension band clamps reduce leaks. Chevron Delo	0	0

Price Level: January 1, 2022

Deal: 220 Chassis

Printed On: 5/19/2022 8:23:17 AM

Date: May 19, 2022

Quote Number: QUO-847777-J9P8T2



Sales Code	Std/ Opt	Description	\$ List	Weight
		Extended Life Coolant (NOAT) extends maintenance intervals reducing maintenance costs. Anti-freeze effective to -30 degrees F helps protect the engine. Low coolant level sensor warns of low coolant condition to prevent engine damage. Radiator Size by Model: 579/367 FEPTO 1325 sq in, 567/365/367: 1440 sq in, 365 FEPTO: 1184 sq in, 389/367 HH: 1669 sq in, 348: 1000 sq in, 520: 1242 sq in.		
3270020	S	<b>(1) Air Cleaner Fender Mounted RH BOC</b>	0	0
3280030	S	<b>High Air Intake</b>	0	0
3365350	O	<b>Exhaust Single RH Back of Cab Compact</b> DPF/SCR Vertical.	4,790	200
3381770	O	<b>Curved Tip Standpipe(s)</b>	89	0
3381890	O	<b>18" Ht, 4" Dia Standpipe(s) Aluminum, Steel Fin</b> Only available with clear rail frame package	36	1
<b>Transmission &amp; Equipment</b>				
4052110	O	<b>Allison 3000 RDS-P Transmission, Gen 5</b> Rugged Duty Series. Includes Rear Transmission Support except on MX engines, Mobil Delvac Automatic Transmission Fluid, and Water-Oil Heat Exchange. Also includes features that monitor the transmission fluid, filter and clutch condition. Will display percent life remaining for the transmission fluid, filter and clutches on the shift selector. This information may be displayed using the Mode and Up and Down buttons. A wrench icon will also be included to indicate when the transmission fluid, filter or clutches need servicing. Suited for vehicles operating on/off highway and/or requiring PTO operation. Forward ratios: 1st-3.49, 2nd-1.86, 3rd-1.41, 4th-1.00, 5th-0.75, 6th-0.65. Reverse ratios: DR-(5.03).	7,731	361
4210320	O	<b>1710 HD Driveline, 2 Midship Bearings</b>	895	175
4252170	O	<b>Auto Neutral Activates With Parking Brake</b> Auto Neutral helps improve jobsite safety by reducing the possibility of the truck moving due to throttle application.	19	0
4252840	O	<b>Allison FuelSense 2.0 Plus</b> Features include: EcoCal shift technology keeps the engine speed at the most efficient level, DynActive Shifting system incorporates a learning algorithm that selects variable shift points to find the ideal balance of fuel economy and performance, based upon the vehicle specifications and environmental parameters. This is valuable for applications with heavy start-stop needs like refuse, city delivery, and construction and Neutral at Stop reduces or eliminates the load on the engine when vehicle is stopped, lowering fuel consumption and emissions.	0	0
4252940	S	<b>Allison Neutral At Stop</b> Neutral at Stop features and benefits: Reduces or eliminates the load on the engine when vehicle is stopped, can help lower fuel consumption and CO2 emissions, and is included in FuelSense 2.0 Plus and Max	0	0

Price Level: January 1, 2022

Deal: 220 Chassis

Printed On: 5/19/2022 8:23:17 AM

Date: May 19, 2022

Quote Number: QUO-847777-J9P8T2



Sales Code	Std/ Opt	Description	\$ List	Weight
		packages only.		
4256020	S	<b>Console Mounted Push Button Shifter</b> Allison Automatic Transmissions or LFNA Electric Vehicle	0	0
4256640	O	<b>Allison 6-Speed Configuration, Close Ratio Gears</b> 3000 Series Transmissions.	0	0
4256780	O	<b>Allison PTO Enable on Mode Button</b> The PTO function C can be either on a remote wire, or mode button. It depends on the selected input/output package. This function is enabled with the MODE button. Enabling the function alerts the TCM that PTO operation has been requested by the operator. When the function is enabled and all of the required operating conditions exist, the TCM activates Output G: PTO Enable by switching power to wire 130. When this function is enabled, the TCM disables the variable modulated main pressure feature in the transmission, resulting in transmission operation at full main pressure. Required operating conditions for enabling this function are: throttle position is low, engine speed is within Customer Modifiable Constant limits, output speed is within Customer Modifiable Constant limits	0	0
<b>Air &amp; Trailer Equipment</b>				
4510830	S	<b>WABCO SS1200 Plus Air Dryer, Heater</b> Coalescing filter	0	0
4543340	O	<b>Aluminum Painted Air Tanks</b> All air tanks are aluminum with painted finish except when Code 4543330 Polish Aluminum Air Tanks is also selected (then exposed air tanks outside the frame rails will be polished aluminum). Peterbilt will determine the optimal size and location of required air tanks. Narratives requesting a specific air tank size or location will not be accepted for factory installation. See ECAT to determine number or location of air tanks installed.	622	-45
4543580	O	<b>Install Frame Mounted Air Tank As Far Forward</b> As possible (only available with Clear Rail Frame Package)	511	0
4611280	O	<b>Body Connections Harness, 34'</b>	97	0
<b>Tires &amp; Wheels</b>				
5058840	O	<b>FF: MN 14ply 11R22.5 XZE2</b> Efficiency Rating: Poor A regional, all-position radial with extra-wide, extra-deep tread designed to help deliver exceptional wear in high scrub regional and urban applications. Diameter = 41.3 inches; SLR = 19.2 inches.	277	4
5168400	O	<b>RR: BR 16Ply 11R22.5 M770</b>	992	52
5190004	S	<b>Code-rear Tire Qty 04</b>	0	0
5220720	O	<b>FF: Alcoa ULT397 22.5X8.25 High Polish</b> Aluminum. Built for heavy-duty applications and are light weight. Available with polished and Dura-Bright finishes.	325	-52

Price Level: January 1, 2022

Deal: 220 Chassis

Printed On: 5/19/2022 8:23:17 AM

Date: May 19, 2022

Quote Number: QUO-847777-J9P8T2



<b>Sales Code</b>	<b>Std/ Opt</b>	<b>Description</b>	<b>\$ List</b>	<b>Weight</b>
5320720	O	<b>RR: Alcoa ULT397 22.5X8.25 High Polish</b> Aluminum. Built for heavy-duty applications and are light weight. Available with polished and Dura-Bright finishes.	650	<b>-104</b>
5390004	S	<b>Code-rear Rim Qty 04</b>	0	<b>0</b>
5407640	O	<b>FF: Mirror Polish Wheels, Outer Surface</b> Single/tandem steer. Mirror Polish outer surface of outer wheel. Without chrome wheel nuts.	75	<b>0</b>
5407650	O	<b>RR: Mirror Polish Wheels, Outer Surface, Single</b> Drive without chrome wheel nuts. Mirror polish outer surface of outer wheel.	289	<b>0</b>
5410140	O	<b>FF: Dura-Bright Finish</b> Outer Surface of Outer Wheel, requires Polished Option	268	<b>0</b>
5410150	O	<b>RR: Dura-Bright Finish-Single Axle</b> Outer Surface of Outer Wheel, requires Polished Option.	268	<b>0</b>
<b>Fuel Tanks</b>				
5516050	S	<b>22" Aluminum 56 Gal Fuel Tank LH BOC</b>	0	<b>0</b>
5604056	S	<b>Location LH BOC 56 Gallon</b>	0	<b>0</b>
5652930	O	<b>DEF Tank Mounted LH BOC Raised</b> Use in addition to DEF tank option	477	<b>0</b>
5652990	O	<b>DEF To Fuel Ratio 2:1 Or Greater</b>	0	<b>0</b>
5655059	S	<b>DEF Tank Rectangular, 8 Gal</b>	0	<b>0</b>
<b>Battery Box &amp; Bumper</b>				
6010700	O	<b>Aluminum Battery Box Vertical Above Rail BOC</b>	488	<b>0</b>
6030630	S	<b>Aluminum Battery Box Cover</b>	0	<b>0</b>
6121210	S	<b>Steel Bumper Painted Gray</b>	0	<b>0</b>
<b>Cab &amp; Equipment</b>				
6520020	S	<b>Steel 63.5in BBC ProBilt Cab, LH Drive</b>	0	<b>0</b>
6914130	S	<b>Sears C2 Driver Seat</b>	0	<b>0</b>
6924130	O	<b>Sears C2 Passenger Seat</b>	129	<b>0</b>
6931120	O	<b>Seat Belt Color Orange IPO Standard Black</b>	10	<b>0</b>
6934000	O	<b>Driver Armrest - Inboard Only</b>	104	<b>2</b>
6934010	O	<b>Passenger Armrest - Inboard Only</b>	104	<b>2</b>

Price Level: January 1, 2022

Deal: 220 Chassis

Printed On: 5/19/2022 8:23:17 AM

Date: May 19, 2022

Quote Number: QUO-847777-J9P8T2



<b>Sales Code</b>	<b>Std/ Opt</b>	<b>Description</b>	<b>\$ List</b>	<b>Weight</b>
6939385	O	<b>Seat Belt Alarm Provisions Driver Only</b>	52	0
6939400	S	<b>Air Ride Driver</b>	0	0
6939420	S	<b>High Back Driver</b>	0	0
6939460	S	<b>Fabric Driver</b>	0	0
6939500	O	<b>Air Ride Passenger</b>	0	0
6939520	O	<b>High Back Passenger</b>	0	0
6939560	S	<b>Fabric Passenger</b>	0	0
7000015	S	<b>Adjustable Steering Column - Tilt Only</b>	0	0
7001540	S	<b>Rear Wall Storage</b>	0	0
7001620	S	<b>Steering Wheel With Peterbilt Logo</b> Steering Wheel with embossed Peterbilt logo over horn button.	0	0
7039180	S	<b>Interior Gray</b> Includes view window in RH door and 18 inch 4-spoke foam soft-touch steering wheel.	0	0
7210540	S	<b>Day Cab Rear Window</b> Day cab rear window flush to back of cab.	0	0
7230060	S	<b>1-Piece Curved Windshield</b>	0	0
7230170	S	<b>Electric Powered Window Lift, LH/RH Side</b>	0	0
7322010	S	<b>Combo Fresh Air Heater/Air Conditioner</b> With radiator mounted condenser, dedicated side window defrosters, Bi-Level Heater/Defroster Controls, 54,500 BTU/HR, and silicone heater hoses.	0	0
7561170	S	<b>LH/RH Driving Mirrors Heated/Motorized</b> Heated and motorized mirrors for left and right sides.	0	0
7722120	S	<b>ConcertClass, AM/FM, Weatherband, 3.5 Aux</b>	0	0
7728040	O	<b>Bluetooth Phone and Audio Requires USB Port</b>	62	0
7728050	O	<b>USB Port</b>	62	0
7851480	S	<b>Peterbilt Electric Windshield Wipers</b> With Intermittent Feature.	0	0
7853030	O	<b>Center Console with Storage &amp; 2 Cup Holders</b>	190	0
7900040	O	<b>Fire Extinguisher, Ship Loose</b> Hazmat approved UL listed/rated ABC.	53	7
7901130	O	<b>Backup Alarm (107 DB)</b>	46	3

Price Level: January 1, 2022

Deal: 220 Chassis

Printed On: 5/19/2022 8:23:17 AM

Date: May 19, 2022

Quote Number: QUO-847777-J9P8T2



Sales Code	Std/ Opt	Description	\$ List	Weight
8021380	S	<b>Air Restriction Indicator</b> Mounted on air cleaner, intake piping, or firewall	0	0
8041200	S	<b>Dual Scale Speedometer MPH Over KPH</b>	0	0
8111150	S	<b>Headlights Dual Round Halogen, Integral Turn Signals</b>	0	0
8121010	S	<b>(5) Marker Lights</b>	0	0
8133270	S	<b>Fog / Driving Lights</b>	0	0
8133960	S	<b>Daytime Running Lights</b> The brake interlock turns the daytime running lights off when the parking brakes are engaged. This is required on all Canadian vehicles.	0	0
8143270	S	<b>Stop/Tail/Turn/Backup Lights RH/LH</b>	0	0
<b>Paint</b>				
8530340	S	<b>Axalta Single Stage Non-Metallic Cab/Hood</b> (Solid Color Paint) N85020 A - M8870EA ICE WHITE DAF N85200 FRAME L0001EA BLACK	0	0
8531330	S	<b>Medium Duty Paint Color M8870 Ice White</b> Lead Time for Ice White Cab is 12 weeks.	0	0
<b>Shipping Destination</b>				
<b>Options Not Subject To Discount</b>				
9400091	S	<b>Peterbilt Class 7 Standard Coverage</b> 1 year/Unlimited Miles/km	0	0
9400093	S	<b>PACCAR PX-7 Standard Coverage</b> 3 years/Unlimited Miles/Unlimited hrs	0	0
9407103	O	<b>Prepaid Freight Increase For 2022 Delivery</b>	500	0
9408703	O	<b>Base Warr: Emissions 5YR/100K MI-EPA Engine</b>	0	0
<b>Miscellaneous</b>				
9409096	O	<b>State Registry: Virginia</b>	0	0

## Promotions

## Order Comments



Total List Price (W/O Freight & Warranty & Surcharges )	\$133,931
Marketing and Service Support Fee	\$670
Prepaid Freight	\$2,850
Total Surcharge/Options Not Subject To Discount	\$500
Total Weight	10,780

## Prices and Specifications Subject to Change Without Notice.

---

Unpublished options may require review/approval.  
Dimensional and performance data for unpublished options may vary from that displayed in CRM.

---

### **PRICING DISCLAIMER**

*While we make every effort to maintain the web site to preserve pricing accuracy, prices are subject to change without notice. Although the information in this price list is presented in good faith and believed to be correct at the time of printing, we make no representations or warranties as to the completeness or accuracy of this information. We reserve the right to change, delete or otherwise modify the pricing information which is represented herein without any prior notice. We carefully check pricing specifications, but occasionally errors can occur, therefore we reserve the right to change such prices without notice. We disclaim all liability for any errors or omissions in the materials. In no event will we be responsible for any damages of any nature whatsoever from the reliance upon information from these materials. Please check your order prebills to confirm your pricing information*



**Shipping Destinations**

**Intermediate Destination:** NONE

Final Destinations	Quantity
--------------------	----------