



Peterbilt of Richmond (H830)
2800A Deepwater Terminal
Richmond, Virginia 23212

Virginia Sheriffs Association
901 East Byrd St Suite 1301
Richmond, Virginia 23219
United States of America

David Askew
Cell Phone:
Office Phone:
Email: daskew@thepetestore.com

Kaylyn Mitman
Office Phone: 919-459-6471
Email: kmitman@virginiasheriffs.org

Vehicle Summary

Unit		Chassis	
Model:	Model 337	Fr Axle Load (lbs):	13200
Type:	Full Truck	Rr Axle Load (lbs):	23000
Description 1:	337 Chassis	G.C.W. (lbs):	36200
Description 2:	337 Option Specs		
Application		Road Conditions:	
Intended Serv.:	Snowplow	Class A (Highway)	100
Commodity:	Other Commodity	Class B (Hwy/Mtn)	0
		Class C (Off-Hwy)	0
		Class D (Off-Road)	0
Body		Maximum Grade:	
Type:	End Dump		6
Length (ft):	24	Wheelbase (in):	190
Height (ft):	13.5	Overhang (in):	74.8
Max Laden Weight (lbs):	33000	Fr Axle to BOC (in):	69.8
Trailer		Cab to Axle (in):	
No. of Trailer Axles:	0	Cab to EOF (in):	120.2
Type:		Overall Comb. Length (in):	195
Length (ft):	0		303
Height (ft):	0	Special Req.	
Kingpin Inset (in):	0		
Corner Radius (in):	0		
Restrictions			
Length (ft):	40		
Width (in):	102		
Height (ft):	13.5		

Approved by: _____

Date: _____

Note: All sales are F.O.B. designated plant of manufacture.



Sales Code	Std/ Opt	Description	\$ List	Weight
Base Model				
0003371	S	Model 337 The Peterbilt Model 337 is built to take on the big jobs. That's why it's available as a Class 7 truck or tractor with a GVW up to 33,000 lbs. With a full range of suspensions and in an all-wheel-drive configuration, the 337 delivers an ideal match for applications such as wrecker, tanker, beverage delivery, municipal utilities – just about any job you can throw at it.	97,368	10,070
0091200	S	Other Commodity	0	0
0093150	O	Snowplow Truck which is configured for mounting a snowplow to the front. May also have dump or other body.	0	0
0095170	O	End Dump	0	0
0098170	S	United States Registry Canadian Registry Package Requires Air Conditioning Excise Tax Canada, Speedometer to be KPH ipo MPH, Daytime Running Lights and Rubber Battery Pad in Bottom of Battery Box.	0	0
Configuration				
0200700	S	Not Applicable Secondary Manufacturer	0	0
Frame & Equipment				
0514000	O	10-3/4" Steel Rails To 354" 10.75x3.5x.375 Dimension, 2,136,000 RBM; Yield Strength: 120,000 psi. Section Modulus: 17.8 cubic inches. Weight: 1.74 lbs/inch pair	572	367
0601500	O	Full Steel Inner Liner	1,237	551
0611330	O	Zinc Coated Anti Corrosion Treated Frame Rails Requires Frame Rail Code. Zinc Phosphate coating will replace the standard frame rail primer and provide added corrosion prevention for your customer's operating in severe conditions or in climates where vehicle rust is common.	348	4
0613090	O	Three-Piece Crossmembers	583	58
0644090	S	EOF Square without Crossmember End-of-frame square without crossmember. For use with body builder installed crossmember.	0	0
0651090	S	Omit Rear Mudflaps and Hangers	0	0
Front Axle & Equipment				
1012160	O	Meritor MFS+13B 13,200 lb, 3.5 in. Drop Axle is designed for applications with a gross axle weight rating (GAWR) of 13,200 pounds. Axles include special low-friction bushings, double draw keys and integral thrust bearing and seal design for durability, low maintenance and ease of service.	310	43

Price Level: April 1, 2021

Deal: 337 Chassis

Printed On: 7/20/2021 6:30:49 PM

Date: July 21, 2021

Quote Number: QUO-847897-J4N0W7



Sales Code	Std/ Opt	Description	\$ List	Weight
1111200	O	Taper Leaf Springs, Shocks 13,200 lb Hendrickson taper leaf springs for 13,200 lbs. offer high value to weight ratio.	263	9
1233100	O	Power Steering TRW THP60 TRW THP60 Power Steering is for use with 10,000 to 13,200 lb. axle ratings. Glidekote splines on steering shaft extend service life of components.	119	-19
1250180	O	Power Steering Reservoir Frame Mounted The power steering reservoir is a steering system that eases drivability by applying hydraulic pressure to the steering gear.	0	0
1354850	O	PHP10 Iron PreSet PLUS Hubs-Air Disc Preset iron hub assemblies are designed for demanding conditions and require less maintenance while still offering dependability and superior performance. Precisely engineered to minimize roller stress under heavy loads and increase bearing life when used in demanding conditions such as wide-based single wheels and misalignment due to spindle wear.	871	56
1380070	O	Greasable Front Spring Pins	65	0
1380290	O	Bendix Air Disc Front Brakes Bendix air disc front brakes use a floating caliper design to provide foundation braking on all axles and complies with reduced stopping distance regulations.	-170	30
1380470	O	Meritor Wide Track IPO Standard, Front Axle Meritor wide track front axle offers greater turning radius and ease of service. MFS+ 3.5" Drop / MFS 3.74" Drop. 71in KPI IPO 69in with MFS and MFS+ axles.	0	15
Rear Axle & Equipment				
1513210	O	Dana Spicer S26-190 26,000 lb Laser factory axle alignment to improve handling & reduce tire wear. Magnetic rear axle oil drain plug captures & holds any metal fragments in drive axle lube to extend service life. Parking brakes on all drive axles for optimal performance. Cognis EMGARD® FE 75W-90 synthetic axle lube provides over 1% fuel economy improvement. Reduces wear & extends maintenance intervals, resulting in increased uptime. Provides improved fluid flow to protect components in extreme cold conditions & withstand the stress from high temperatures, extending component life.	2,275	387
1616370	S	PHP10 Iron PreSet Hubs	0	0
1680450	O	Rear Brake Camshaft Reinforcement Rear brake camshaft reinforcement helps guard against wear and corrosion.	93	9
1680490	O	Gusseted Cam Brackets, Drive Axle(s)	24	2
1680500	S	SBM Valve Full trucks require a spring brake modulation (SBM) system for emergency braking application. This system requires an SBM valve and a relay valve with spring brakes on the rear axles. The SBM valve	0	0

Price Level: April 1, 2021

Deal: 337 Chassis

Printed On: 7/20/2021 6:30:49 PM

Date: July 21, 2021

Quote Number: QUO-847897-J4N0W7



Sales Code	Std/Opt	Description	\$ List	Weight
		allows the foot valve to operate the rear axle spring brakes if a failure exists in the rear air system.		
1680550	O	Upsize Parking Brakes	81	0
1680795	O	Diff Lock, Single Drive Axle with Speed Interlock	875	30
1680950	S	Stability System Not Selected Or Not Available	0	0
1681337	S	Single Drive Axle (Model 337)	0	0
1682430	S	Anti-Lock Braking System (ABS) 4S4M ABS-6. Includes air braking system.	0	0
1684200	S	Synthetic Axle Lubricant All Axles Peterbilt heavy duty models include Fuel Efficient Cognis EMGARD FE75W-90 which provides customers performance advantages over current synthetic lubricants with reduced gear wear and extended maintenance intervals, resulting in increased uptime. In addition, the lubricant provides improved fluid flow to protect gears in extreme cold conditions and withstand the stress from high temperatures, extending component life.	0	0
1687020	O	Bendix Air Cam Rear Drum Brakes 16.5x8.6 Bendix Air Cam Rear Drum Brakes to fit all heavy haul, construction, refuse and highway truck and tractor applications. Includes Automatic Slack Adjusters & Outboard Mounted Brake Drums. Refer to TSB 11-57 for more information.	104	0
1705380	O	Ratio 5.38 Rear Axle	0	0
1816040	O	Reyco 102AR 23,000 Lb Tracking Rods, Single Drive 8.25in Low Mount. Includes Heavy Duty Shock Absorbers.	1,332	40
1922260	O	Dash Mtd Dump Switch with Indicator Light Dash mounted dump switch with indicator light for suspension.	35	2
Engine & Equipment				
2074307	O	PACCAR PX-9 300@2000 GOV@2200 860@1200 Productivity (2021 Emissions)	1,943	0
		N21350 C121 65....Maximum Accelerator Pedal Ve		
		N21370 C128 65....Maximum Cruise Speed (P059)		
		N21460 C132 1400..Max PTO Speed (P046)		
		N21520 C133 5.....Timer Setting (P030)		
		N21610 C188 39....Low Ambient Temperature Thre		
		N21620 C189 60....Intermediate Ambient Tempera		
		N21630 C190 80....High Ambient Temperature Thr		
		N21550 C206 35....Engine Load Threshold (P516)		
		N21340 C209 120...Hard Maximum Speed Limit (P1		
		N21510 C225 YES...Enable Idle Shutdown Park Br		
		N21450 C231 NO....Gear Down Protection (P026)		
		N21570 C233 NO....Idle Shutdown Manual Overrul		
		N21440 C234 NO....Engine Protection Shutdown (
		N21480 C238 NO....Auto Engine Brake in Cruise		

Price Level: April 1, 2021

Deal: 337 Chassis

Printed On: 7/20/2021 6:30:49 PM

Date: July 21, 2021

Quote Number: QUO-847897-J4N0W7



Sales Code	Std/ Opt	Description	\$ List	Weight
		N21470 C239 NO....Cruise Control Auto Resume (
		N21430 C333 0.....Reserve Speed Limit Offset (
		N21410 C334 0.....Maximum Cycle Distance (N202		
		N21590 C382 YES...Enable Hot Ambient Automatic		
		N21500 C395 0.....Expiration Distance (N209)		
		N21530 C396 YES...Enable Impending Shutdown Wa		
		N21540 C397 60....Timer For Impending Shutdown		
		N21320 C399 120...Standard Maximum Speed Limit		
		N21400 C400 252...Reserve Speed Function Reset		
		N21420 C401 10....Maximum Active Distance (N20		
		N21330 C402 0.....Expiration Distance (N207)		
2091305	O	Engine Idle Shutdown Timer Enabled	0	0
2091315	O	Enable EIST Ambient Temp Override	0	0
2091372		Eff EIST NA Expiration Miles	0	0
2091640		Effective VSL Setting NA	0	0
2092016	O	Typical Operating Speed 62 MPH	0	0
2092033	O	Powertrain Optimized for Balance Best analysis for vehicles where service includes frequent start and stop cycles.	0	0
2140150	O	Remote PTO and Throttle Provision 12-pin connector on engine harness.	17	0
2140200	S	CARB Engine Idling Compliance PACCAR PX-7, PX-9 and MX, Cummins X15 and ISX diesel engines will include the required factory installed serialized sticker on the drivers door to identify them as meeting the NOx idling standard.	0	0
2140320	O	Remote Throttle/PTO Control Switch & Wiring EOF W/ Park Brake	75	4
2513060	S	PACCAR 160 Amp Alternator, Brushed PACCAR 160 AMP alternator, brushed producing 160 Amps at road speed and 100 Amps at idle.	0	0
2521090	O	Immersion Type Block Heater 110-120V Standard location for 2.1M and 1.9M models is left-hand under cab, Model 520 is in bumper, and for Model 220 it is at the driver step. Plug includes a weather-proof cover that protects the receptacle. This pre-heater keeps the coolant in the engine block from freezing when the engine is not running.	86	2
2522110	S	PACCAR 12V Starter, N/A PACCAR MX Engines PACCAR 12-volt electrical system. With centralized power distribution incorporating plug-in style relays. Circuit protection for serviceability, 12-volt light system w/circuit protection circuits number & color coded.	0	0
2538040	O	3 PACCAR Premium 12V Dual Purpose Batt 2190 CCA Threaded stud type terminal. Stranded copper battery cables are double aught (00) or larger to reduce resistance.	224	62
2539410	O	Battery Jumper Terminal Mounted Under Hood	100	4

Price Level: April 1, 2021

Deal: 337 Chassis

Printed On: 7/20/2021 6:30:49 PM

Date: July 21, 2021

Quote Number: QUO-847897-J4N0W7



Sales Code	Std/ Opt	Description	\$ List	Weight
		LH Frame Rail. Not available with PX-7 engines.		
2539740	O	Kissling Battery Disconnect Switch, 300 amp Mounted on battery box	221	3
2621000	O	2-Speed Fan Clutch For Frequent Start/Stops A 2-speed fan clutch is ideal for vocational applications where the fan clutch engagement time exceeds 10% of the engine run time. When the fan clutch is disengaged, the fan still rotates at 15-25% of the engine RPM. This fan rotation provides crucial airflow to the engine and draws virtually no horsepower.	374	0
2723210	S	18.7 CFM Air Compressor N/A X15. Furnished on engine. Teflon lined stainless steel braided compressor discharge line.	0	0
2812210	O	VGT Exhaust Brake (Variable Geometry Turbo). Provides approximately 90-100 HP of retardation and is part of the turbocharger.	66	0
2921160	S	Spin-On Fuel/Water Separator	0	0
2921210	S	No Fluid Heat Option for Fuel Filter	0	0
2921310	S	No Electric Heat Option for Fuel Filter	0	0
3010400	O	Engine Protection Shutdown w/ Label Includes oil pressure, oil temperature, coolant temperature, and intake manifold temperature.	4	0
3114270	S	High Efficiency Cooling System Cooling module is a combination of steel and aluminum components, with aluminum connections to maximize performance and cooling capability. Silicone radiator & heater hoses enhance value, durability, & reliability. Constant tension band clamps reduce leaks. Chevron Delo Extended Life Coolant (NOAT) extends maintenance intervals reducing maintenance costs. Anti-freeze effective to -30 degrees F helps protect the engine. Low coolant level sensor warns of low coolant condition to prevent engine damage. Radiator Size by Model: 579/367 FEPTO 1325 sq in, 567/365/367: 1440 sq in, 365 FEPTO: 1184 sq in, 389/367 HH: 1669 sq in, 348: 1000 sq in, 520: 1242 sq in.	0	0
3211120	S	Radial Seal, Dry Type Air Cleaner, Frontal Air Intake. Molded rubber air intake connections with lined stainless steel clamps seal to prevent contaminants in air intake.	0	0
3365270	O	Exhaust Single RH Side of Cab DPF/SCR right-hand Under Cab.	351	29
3381770	O	Curved Tip Standpipe(s)	41	0
3383040	O	DPF Regeneration Switch Remove Stop Position	0	0
3387880	O	7" Dia Chrome Plated Steel Standpipe(s) IPO 5"	156	0
3387890	O	36" Ht, 5" Dia Chrome, Clear Coat Standpipe(s)	523	4

Transmission & Equipment

Price Level: April 1, 2021
Deal: 337 Chassis
Printed On: 7/20/2021 6:30:49 PM

Date: July 21, 2021
Quote Number: QUO-847897-J4N0W7



Sales Code	Std/ Opt	Description	\$ List	Weight
4052110	O	Allison 3000 RDS-P Transmission, Gen 5 Rugged Duty Series. Includes Rear Transmission Support except on MX engines, Mobil Delvac Automatic Transmission Fluid, and Water-Oil Heat Exchange. Also includes features that monitor the transmission fluid, filter and clutch condition. Will display percent life remaining for the transmission fluid, filter and clutches on the shift selector. This information may be displayed using the Mode and Up and Down buttons. A wrench icon will also be included to indicate when the transmission fluid, filter or clutches need servicing. Suited for vehicles operating on/off highway and/or requiring PTO operation. Forward ratios: 1st-3.49, 2nd-1.86, 3rd-1.41, 4th-1.00, 5th-0.75, 6th-0.65. Reverse ratios: DR-(5.03).	10,737	195
4210320	O	1710 HD Driveline, 2 Midship Bearings	626	100
4252170	O	Auto Neutral Activates With Parking Brake Auto Neutral helps improve jobsite safety by reducing the possibility of the truck moving due to throttle application.	16	0
4252890	O	Allison FuelSense 2.0 Not Desired	0	0
4252940	O	Allison Neutral At Stop Neutral at Stop features and benefits: Reduces or eliminates the load on the engine when vehicle is stopped, can help lower fuel consumption and CO2 emissions, and is included in FuelSense 2.0 Plus and Max packages only.	0	0
4256640	O	Allison 6-Speed Configuration, Close Ratio Gears 3000 Series Transmissions.	0	0
4256920	O	Dash Mounted Push Button Shifter Available with Allison transmissions	626	0
4256990	O	Rolling Direction Change Shift Inhibit Feature Allison transmissions. A programmable feature that keeps the transmission from shifting from Drive to Reverse or from Reverse to Drive above a preset speed. This wireless function is enabled when a switch is closed to complete the circuit between input wire 101 and ground. Frequently the function is interfaced with a switch indicating activation of another vehicle function, such as application of the service brakes. When the function is enabled, the TCM will recognize the request for a direction change shift, Reverse-to-Drive or Drive-to-Reverse. If all other operating conditions are acceptable, the TCM will command the requested shift. The enable remains in effect until the switch is opened, followed by the selection of a different direction, Reverse or Drive, at the shift selector. This could be used for doc spotters and refuse. If the function is not enabled, any shift which results in a change of direction is inhibited.	0	0
Air & Trailer Equipment				
4510210	O	Bendix AD-HF EP Air Dryer, Heater	186	-2

Price Level: April 1, 2021

Deal: 337 Chassis

Printed On: 7/20/2021 6:30:49 PM

Date: July 21, 2021

Quote Number: QUO-847897-J4N0W7



Sales Code	Std/ Opt	Description	\$ List	Weight
		Coalescing filter, extended purge. Bendix AD-HF air filters protects the life of your engine system and components. Proven PuraGuard oil coalescing technology in the the air dryer cartridge. This oil coalescing filter ensures the removal of oil and oil aerosols before they can contaminate the moisture removing desiccant.		
4540420	S	Nylon Chassis Hose	0	0
4542330	O	Central Location For Air Tank Drain Valves Frame mounted BOC tanks, includes pull cords. Only available horizontal/transverse tanks	251	4
4543320	S	Steel Painted Air Tanks All air tanks are steel with painted finish except when Code 4543330 Polish Aluminum Air Tanks is also selected (then exposed air tanks outside the frame rails will be polished aluminum). Peterbilt will determine the optimal size and location of required air tanks. Narratives requesting a specific air tank size or location will not be accepted for factory installation. See ECAT to determine number or location of air tanks installed.	0	0
4543330	O	Aluminum Polished Air Tanks Outside Frame Rails Exposed air tanks outside the frame rails will be polished aluminum. Air tanks mounted inside the frame rails or covered by other components will be either painted aluminum (4543340) or painted steel (4543320) air tanks depending on air tank option selected.	248	0
4543390	O	High Mount Air Tanks BOC/BOS Where Possible Subject to frame review	0	0
4611930	O	Body Connections 5' BOC Junction box contains light and power circuits for body connections located 5' from back-of-cab	134	4
4612900	O	AE Connection EOF, 7-Way Socket, Connection EOF Strapped to the rail	438	15
Tires & Wheels				
5056540	O	FF: MN 20ply 315/80R22.5 X Line Energy Z Efficiency Rating: Optimal The MICHELIN X LINE ENERGY Z tire is a line haul steer tire built for high miles and better rolling resistance. Diameter= 42.3 inches; SLR= 19.6 inches	708	36
5158970	O	RR: MN 20ply 315/80R22.5 XZUS2 Efficiency Rating: Fair All-position, wide base single designed for significant weight and fuel savings in urban regional applications. Diameter = 42.9 inches; SLR = 19.8 inches.	1,758	192
5190004	O	Code-rear Tire Qty 04	0	0
5220530	O	FF: Alcoa 89U647 22.5X9.00 High Polish Aluminum, Ultra ONE wheels with MagnaForce alloy.	445	-20
5320530	O	RR: Alcoa 89U647 22.5X9.00 High Polish Aluminum. Ultra ONE wheels with MagnaForce alloy.	890	-40
5390004	O	Code-rear Rim Qty 04	0	0

Price Level: April 1, 2021

Deal: 337 Chassis

Printed On: 7/20/2021 6:30:49 PM

Date: July 21, 2021

Quote Number: QUO-847897-J4N0W7



Sales Code	Std/ Opt	Description	\$ List	Weight
Fuel Tanks				
5554070	O	26" Aluminum 60 Gallon Fuel Tank LH U/C Includes steps for cab access. Paddle handle filler cap with threadless filler neck. Top draw fuel plumbing reduces chance of introducing air into the fuel system during low fuel level conditions due to the central placement of fuel pickup tube. Wire braid fuel lines increase durability & reduce potential for leaks.	127	-117
5602060	O	Location LH U/C 60 Gallon	0	0
5652890	S	DEF Tank Mounted LH BOC Models 220 and 520 mounted left hand back-of-cab.	0	0
5652990	O	DEF To Fuel Ratio 2:1 Or Greater	0	0
5655019	O	DEF Tank Small, HD 14 Gal 2.1M MD 5.5 Gal	-174	0
Battery Box & Bumper				
6010780	O	Aluminum Space Saver Battery Box RH BOC Battery access from side	208	-84
6030540	O	Polish Battery/Tool Box(s), Aftertreatment Cab Entry complete	426	0
6040550	S	Aftertreatment Aluminum Non-Slip Cab Entry Aftertreatment right-hand under cab step. DPF/SCR for diesel engines, catalyst for natural gas engines. On Models 579 specifying chassis fairings, the box is aerodynamic.	0	0
6113050	O	Aluminum Channel Bumper Stainless Steel Clad Two tow points	613	-4
Cab & Equipment				
6510110	S	Alum Cab 108in BBC Metton Hood w/Bright Crown Includes view window RH door and convex mirror over RH door.	0	0
6540120	O	Severe Service Cab Package #1 Includes Aluminum side skins, aluminum rear skin, steel windshield mask, steel firewall, and steel front floor sheet on all cabs, and additional reinforcement structure on the back wall of the day cab.	155	39
6540720	O	10" Extension for Ultra Day Cab Add additional 10" to the loadspace dimension-- refer to the horizontal dimension workscreen.	4,728	163
6800360	O	Rubber Fender Lips 2" Wide	97	8
6911710	O	National Premium Driver Seat Increased comfort with more foam in critical areas, better lumbar support, improved adjustability and suspension with toggle link design.	410	4
6921710	O	National Premium Passenger Seat Increased comfort with more foam in critical areas, better lumbar support, improved adjustability and suspension with toggle link design.	319	0
6930580	O	Drivers Armrests - LH & RH	73	4



Sales Code	Std/ Opt	Description	\$ List	Weight
6931120	O	Seat Belt Color Orange IPO Standard Black	10	0
6939400	O	Air Ride Driver	225	0
6939420	S	High Back Driver	0	0
6939480	O	Mordura Driver	55	0
6939500	O	Air Ride Passenger	203	43
6939520	O	High Back Passenger	28	0
6939580	O	Mordura Passenger	54	0
7001520	O	Adjustable Steering Column - Tilt/Telescope	114	11
7001620	S	Steering Wheel With Peterbilt Logo Steering Wheel with embossed Peterbilt logo over horn button.	0	0
7036120	S	Interior Gray/Black Includes rugged charcoal instrument panels, glare-resistant gray dash, black bezels on gauges, (2) power ports, monochromatic molded door pads with durable in-mold color, gray molded back wall, 18 inch 4-spoke soft-touch steering wheel, soft-touch steering column cover, power lift passenger window, extruded rubber floor covering, header-mounted dome light, foot well lighting, integrated "dead pedal", (4) inside entry grab handles, (2) inside sunvisors, (2) coat hooks, (2) cup holders and map bin in dash.	0	0
7210540	S	Day Cab Rear Window Day cab rear window flush to back of cab.	0	0
7230060	S	1-Piece Curved Windshield	0	0
7322010	S	Combo Fresh Air Heater/Air Conditioner With radiator mounted condenser, dedicated side window defrosters, Bi-Level Heater/Defroster Controls, 54,500 BTU/HR, and silicone heater hoses.	0	0
7322130	O	Cup Holder (Floor Mounted) Includes two standard-size drink holders and one extra-large jugholder, coin tray, and clipboard-size storage area.	89	4
7410040	O	Outside Sunvisor - Stainless Steel Not available with 2.1M high roof sleeper.	223	4
7561180	O	Aero Mirrors Ea Side Htd & Mtrzd 4-Way Adjustable Bright Finish with Convex	521	4
7564110	S	Power Package Includes power door locks and power windows.	0	0
7620620	O	(2) Air Horns 24.5" Chrome - Round w/Horn Shields	465	16
7725720	S	No Head Unit or Audio Speakers Selected	0	0
7850210	O	Plug-In Auto Reset Circuit Breaker	40	0

Price Level: April 1, 2021

Deal: 337 Chassis

Printed On: 7/20/2021 6:30:49 PM

Date: July 21, 2021

Quote Number: QUO-847897-J4N0W7



Sales Code	Std/ Opt	Description	\$ List	Weight
		in place of fuses in junction box.		
7851100	O	Stationary Grille w/o Fepto Extension	228	4
7851480	S	Peterbilt Electric Windshield Wipers With Intermittent Feature.	0	0
7851780	O	CabMate Cab Air Suspension Mfg by Link. The class 8 conventionals (except Model 348) includes (2) airbags, (2) shock absorbers, (1) leveling valve, radius rod, and height limiter. The Models 330, 337, and 348 includes (1) airbag and (1) shock absorber.	1,297	15
8021380	S	Air Restriction Indicator Mounted on air cleaner, intake piping, or firewall	0	0
8071870	S	Main Instrumentation Panel, Graphics Display Includes speedometer with trip odometer, tachometer with hourmeter and outside air temperature display, voltmeter, engine oil pressure, engine coolant temperature, fuel level, primary and secondary air pressure gauges. Includes standard warning light package: high water temperature, low oil pressure, and low air pressure warning lights with audible alarms, high beam, turn signal, low fuel, parking brake, and ice warning indicators; seat belt reminder; rocker switches with long-life LED indicators; multi-function turn stalk with flash-to-pass feature (night mode flashes headlights and marker lights; day mode flashes headlights only), intermittent windshield wiper and headlamp beam control. Hydraulic braked trucks do not include air pressure gauges.	0	0
8111110	S	Headlights Composite Fender Mounted Integral park, turn, and side marker	0	0
8120980	S	(5) Marker Lights, Aero LED	0	0
8134070	O	(2) Additional Dome/Reading Lights, Ceiling Mtd	49	0
8140120	S	Incandescent Square Stop/Turn/Tail/Backup Left-hand / right-hand square end of frame or dropped a-brace	0	0
Paint				
8500710	O	Standard Paint Color Selection	-200	0
8530770	S	(1) Color Axalta Two Stage - Cab/Hood Base Coat/Clear Coat N85020 A - L0006EY WHITE N85500 CAB ROOF L0006EY WHITE N85300 FENDER L0006EY WHITE N85200 FRAME L0001EA BLACK N85400 HOOD TOP L0006EY WHITE	0	0
Shipping Destination				
Options Not Subject To Discount				
9400091	S	Peterbilt Class 7 Standard Coverage 1 year/Unlimited Miles/km	0	0

Price Level: April 1, 2021

Deal: 337 Chassis

Printed On: 7/20/2021 6:30:49 PM

Date: July 21, 2021

Quote Number: QUO-847897-J4N0W7



<i>Sales Code</i>	<i>Std/ Opt</i>	<i>Description</i>	<i>\$ List</i>	<i>Weight</i>
Miscellaneous				
9409831	O	2021 EPA Emissions Engine Warranty Only	0	0

Promotions

Order Comments



Total List Price (W/O Freight & Warranty & Surcharges)	\$138,012
Marketing and Service Support Fee	\$895
Prepaid Freight	\$2,800
Total Surcharge/Options Not Subject To Discount	\$0
Total Weight	12,360

Prices and Specifications Subject to Change Without Notice.

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in CRM.

PRICING DISCLAIMER

While we make every effort to maintain the web site to preserve pricing accuracy, prices are subject to change without notice. Although the information in this price list is presented in good faith and believed to be correct at the time of printing, we make no representations or warranties as to the completeness or accuracy of this information. We reserve the right to change, delete or otherwise modify the pricing information which is represented herein without any prior notice. We carefully check pricing specifications, but occasionally errors can occur, therefore we reserve the right to change such prices without notice. We disclaim all liability for any errors or omissions in the materials. In no event will we be responsible for any damages of any nature whatsoever from the reliance upon information from these materials. Please check your order prebills to confirm your pricing information



Shipping Destinations

Intermediate Destination: none

Final Destinations	Quantity
--------------------	----------

337



337

BUILT STRONG FOR TOUGH JOBS.

The Peterbilt Model 337 is built to take on the big jobs. That's why it's available as a Class 7 truck or tractor with a GVW up to 33,000 lbs. It can be configured to meet the demands of virtually any work application and spec'd to meet the needs of any business. The 337 earned its durable reputation from features such as the all-aluminum cab, Metton® hood and stainless steel grille. Plus, the sloping aerodynamic hood enhances driver visibility and productivity. A multiplex electrical system offers diagnostic simplicity and reliability with clearly numbered, color-coded wiring. The 337 is available with the fuel-efficient PACCAR PX-9 and PX-7 engines that deliver superior performance, minimize operational costs and maximize uptime for medium duty customers. The Peterbilt Model 337 proves its value every day with every mile.

For more information on the Model 337, contact your local Peterbilt dealer or visit www.peterbilt.com



The Model 337 delivers a signature combination of comfort, serviceability, visibility and versatility. It's ideal for truck and tractor applications such as wrecker, tanker, beverage delivery and municipal utilities.



DURABILITY

Stamped from a single piece of steel, with no seams or fasteners, the 337 bumper is as durable as it is protective.



MANEUVERABILITY

Featuring a 53-degree wheel cut, the 337 allows drivers to maneuver in congested urban environments as well as tight loading and unloading conditions.



EFFICIENCY

The durable and ergonomic dash features LED backlit gauges that are easy to read, a driver information display for critical vehicle data and rocker switches within easy reach.



VERSATILITY

Available as a truck or tractor and with a full range of suspension options, the 337 delivers the ideal match for your particular application.



PACCAR
FINANCIAL

PACLEASE & PACCAR FINANCIAL PLANS TAILORED TO YOUR NEEDS.



PETE-9885 REV. 7/15 • PRINTED IN U.S.A. • FOR MORE INFORMATION, CALL 1-800-552-0024 • BUCKLE-UP FOR SAFETY



CLASS PAYS



FEATURES & BENEFITS: MODEL 337

Model 337 Standard Features

(Base Model Option Code 0003371)



FRAME

- Steel rails with gussets to maximize RBM.
- Huck bobtail fasteners provide a consistent and durable clamping force up to 600% greater than bolted frames. Tamper resistant round head and collar offers improved paint adhesion and corrosion resistance. Swage indicating features on collar allows for visual inspection of clamped joint.
- Rubber-lined clamps along frame rail to protect air & electric lines routed in frame.
- Chassis hose and wiring bundles conveniently routed through gussets provides protection for lines.
- Front wheel mudflaps reduce road spray, help maintain a cleaner truck and better visibility.

STEER AXLE

- Factory front axle alignment to improve handling and reduce tire wear.
- Zerk fittings on tie rod ends, kingpins, and draglink ball joints for ease of maintenance and help extend service life of components.
- Standard oil seals for long lasting leak protection.
- Cognis EMGARD® Synthetic Axle Lube reduces wear and extends maintenance intervals, resulting in increased uptime. Provides improved fluid flow to protect components in extreme cold conditions and withstand the stress from high temperatures, extending component life.
- Glidekote splines on steering shaft extend service life of components.

DRIVE AXLE

- Laser factory axle alignment (accurate to .030 of an inch) to improve handling and reduce tire wear.

- Magnetic rear axle oil drain plug captures and holds any metal fragments in drive axle lube to extend service life.
- Parking brakes on all drive axles for optimal performance.
- Cognis EMGARD® Synthetic Axle Lube reduces wear and extends maintenance intervals, resulting in increased uptime. Provides improved fluid flow to protect components in extreme cold conditions and withstand the stress from high temperatures, extending component life.

ENGINES & RELATED SYSTEMS

- Selective Catalytic Reduction (SCR) System provides the most fuel efficient, reliable and cost effective solution to the 2010 EPA regulations. The SCR system consists of several new standard components on the truck - a dosing pump, a DEF tank, an injector and the SCR ammonia catalyst.
- Chevron Delo 400 LE SAE 10W30 engine oil is specially formulated for new low emissions engines.
- Magnetic engine oil drain plug captures and holds any metal fragments in engine oil to extend service life.
- Silicone radiator and heater hoses enhance value, durability and reliability.
- ClimaTech extended life coolant extends maintenance intervals which reduces maintenance costs.
- Low coolant level sensor warns of low coolant condition to prevent engine damage.
- Constant tension and torque band clamps reduce leaks.
- Thermal fuse in the air conditioning compressor clutch allows the pulley to free spin in the event of a compressor failure, thus reducing belt wear and vehicle downtime.
- Weather pack silicone sealed electrical chassis connectors enhance value, durability and reliability.
- 12 Volt System with circuit protection for reliable easy maintenance and service.
- 1000 sq. in. frontal area cooling system provides a large surface area for heat exchange.
- PENCOOL with Stabil-Aid supplemental coolant additive
- Composite fan is light-weight but strong and corrosion resistant.
- Full fan shroud, ring and rubber boot improves under hood airflow and provides a robust fan-to-radiator shroud interface for greater cooling capacity.
- Anti-freeze effective to -30 degrees F helps protect the engine.
- Maintenance free 12V batteries provide reliable power for starting and accessories.
- Stranded copper battery cables are double aught (00) or larger to reduce resistance.
- Molded rubber air intake connections with stainless steel clamps seal to prevent contaminants in air intake.
- Washer bottle with 1.3 gallon capacity extends maintenance intervals to refill.
- Polished stainless steel grille with a distinctive punched oval grille pattern provides a durable bright finish.
- Stainless steel flex exhaust tubing & clamps provide durability.
- Optimized exhaust routing to simplify the truck order process and provide optimal performance.

TRANSMISSION & RELATED SYSTEMS

- Synthetic lubricant to reduce friction, improve efficiency and extend component life.
- Magnetic transmission oil drain plug captures and holds any metal fragments in transmission oil to extend service life.
- Coated driveshaft splines extend service life.
- Configured clutch on manual transmission to simplify the truck order process and provide optimal performance.

FUEL TANKS

- Under cab fuel tanks include steps for cab access.
- Single fuel tank will receive a single draw / single return fuel system.
- Dual fuel tanks will receive dual draw / dual return fuel system equalizes fuel load.
- Top draw fuel plumbing reduces chance of introducing air into the fuel system during low fuel level conditions due to the central placement of the fuel pickup tube.
- Optimized filler neck location on under cab fuel tanks optimizes access and safety.
- Paddle handle filler cap
- Wire braid fuel lines increase durability and reduce potential for leaks.

ELECTRICAL SYSTEM

- Multiplex electrical design utilizing the industry standard J1939 data bus that sends multiple signals over a single wire instead of having an individual wire for each function. This allows each component (engine, transmission and instrumentation) to communicate to each other. This design improves reliability and offers increased functionality.
- Proprietary Electronic Service Analyst (ESA) allows dealer to monitor the electrical system, isolate sensors and gauges, and keep a log of service history.
- Automatically resetting circuit breakers in selected circuits.
- Braided chassis harness cover provides durability.
- Convoluted tube covering on harnesses protects from chaffing.
- Wires numbered every 4 inches or less for ease of serviceability.
- Power distribution center in cab is centrally located in a protected environment for easy access.

CAB / HOOD

- Proprietary all-aluminum cab is light weight and durable for long service life.
- Durable Metton® hood with 108" BBC is lightweight but strong, withstanding impacts that would shatter or crack fiberglass.
- Torsional hood pivot with tilt assist for serviceability.
- Proprietary anti-blow-down locking mechanism that keeps the hood open during servicing and prevents unintentional closing.
- Hood latch on each side secures the hood to the cowl.
- Three point rubber cab mounting
- One piece roof reduces potential for leaks.
- Lap seam construction and aircraft fasteners has greater clamp load than rivets.

- Bulkhead style doors provide virtually water-tight, rattle-free performance.
- Extruded aluminum door frames for strength and durability.
- Full length, heavy-duty piano-type stainless steel door hinges and pins provide durability.
- View window in RH door for safety.
- Electric windshield wipers and washers with intermittent wiper function
- Grab handles mounted on cab LH & RH for cab access.
- Convex mirror over RH door and below each rear view mirror for improved visibility and safety.

CAB INTERIOR

- Vinyl padded headliner and back panels
- Contoured door pads featuring integrated ergonomic armrests for driver comfort.
- Door pads include the “in-mold” color process to reduce the visibility of scratches and scuffs, important in medium duty applications where drivers frequently enter and exit the cab.
- Power lift passenger window controls integrated into the door panel are within easy reach of the driver for safe and convenient operation.
- Two inside sunvisors with map straps provide driver and passenger comfort and convenience.
- Two coat hooks for driver and passenger convenience.
- Cast rubber flooring with integral sound barrier.
- Integrated "dead pedal" for driver comfort.
- Heater / air conditioner with dedicated side window defroster
- 18" black four-spoke soft touch steering wheel
- Key start ignition for an automotive feel.
- Ignition and doors keyed alike for driver convenience.
- Single electric horn
- Cigar lighter
- Dual cup holders with 12-volt power outlet
- 2-way dome light
- Retractable three-point seatbelts
- Two entry / egress grab handles
- Non-slip threshold plate for safety.

LIGHTS

- High-intensity forward lighting system integrated into the fenders provides outstanding visibility and aerodynamic efficiency.
- 'Headlight on Warning' when headlights are active with door open and ignition off. The high beam headlamp icon flashes and sounds an audible alarm.
- Lighting system is protected by an impact resistant Lexan® lens and requires no special tools for lamp adjustment or bulb replacement.
- Rear combination stop / turn / tail lights
- Self-cancelling turn signals for driver convenience (full truck applications only).

DASH & INSTRUMENTATION

- Driver Information Display that allows the driver to view diagnostic information and monitor truck system behavior. Information such as fuel economy, optimum engine speed and engine and transmission system management provides driver feedback and improves operating performance.
- Dash features an "in-mold" color process that imbeds the color into the material making the color permanent and eliminating peeling and fading. Ergonomic dash provides enhanced driver comfort and productivity.
- Removable dash panels provide easy access to electrical and HVAC components.
- Ergonomic dash provides enhanced driver comfort and productivity.
- LED backlit gauges to prevent eye fatigue.
- Electronic speedometer with trip odometer
- Electronic tachometer
- Air pressure gauge
- Engine oil pressure gauge
- Engine coolant temperature gauge
- Engine fan clutch override switch
- Fuel level gauge
- DPF Regeneration display
- Standard warning lights with audible alarm for high coolant temperature, low oil pressure and low air pressure
- Warning indicators for high beam, parking brake, turn signals
- Cruise control for driver convenience.
- Multi-function turn stalk with flash-to-pass feature intermittent windshield wiper and headlamp beam control.
- Marker lights, hazard lights, regeneration (DPF), and dimmer switches
- Integrated storage tray

PAINT

- DuPont Imron Elite single stage non-metallic paint, one color cab / hood

337



337

BUILT STRONG FOR TOUGH JOBS.

The Peterbilt Model 337 is built to take on the big jobs. That's why it's available as a Class 7 truck or tractor with a GVW up to 33,000 lbs. It can be configured to meet the demands of virtually any work application and spec'd to meet the needs of any business. The 337 earned its durable reputation from features such as the all-aluminum cab, Metton® hood and stainless steel grille. Plus, the sloping aerodynamic hood enhances driver visibility and productivity. A multiplex electrical system offers diagnostic simplicity and reliability with clearly numbered, color-coded wiring. The 337 is available with the fuel-efficient PACCAR PX-9 and PX-7 engines that deliver superior performance, minimize operational costs and maximize uptime for medium duty customers. The Peterbilt Model 337 proves its value every day with every mile.

For more information on the Model 337, contact your local Peterbilt dealer or visit www.peterbilt.com



The Model 337 delivers a signature combination of comfort, serviceability, visibility and versatility. It's ideal for truck and tractor applications such as wrecker, tanker, beverage delivery and municipal utilities.



DURABILITY

Stamped from a single piece of steel, with no seams or fasteners, the 337 bumper is as durable as it is protective.



MANEUVERABILITY

Featuring a 53-degree wheel cut, the 337 allows drivers to maneuver in congested urban environments as well as tight loading and unloading conditions.



EFFICIENCY

The durable and ergonomic dash features LED backlit gauges that are easy to read, a driver information display for critical vehicle data and rocker switches within easy reach.



VERSATILITY

Available as a truck or tractor and with a full range of suspension options, the 337 delivers the ideal match for your particular application.



PACCAR
FINANCIAL

PACLEASE & PACCAR FINANCIAL PLANS TAILORED TO YOUR NEEDS.



PETE-9885 REV. 7/15 • PRINTED IN U.S.A. • FOR MORE INFORMATION, CALL 1-800-552-0024 • BUCKLE-UP FOR SAFETY



CLASS PAYS