

Peterbilt of Richmond (H830) 2800A Deepwater Terminal Richmond, Virginia 23212

Email: daskew@thepetestore.com

David Askew

Cell Phone: Office Phone: Virginia Sheriffs Association 901 East Byrd St Suite1301 Richmond, Virginia 23219 United States of America

Kaylyn Mitman

Office Phone: 919-459-6471 Email: kmitman@virginiasheriffs.org

Vehicle Summary

	Unit		Ch	assis
Model:		Model 389	Fr Axle Load (lbs):	12000
Туре:		Tractor	Rr Axle Load (lbs):	38000
Description 1:		389 Tractor	G.C.W. (lbs):	125000
Description 2:	:	389 Standard Specs		
	Application		Road Conditions:	
Intended Serv .:		General Freight	Class A (Highway)	100
Commodity:		Other Commodity	Class B (Hwy/Mtn)	0
			Class C (Off-Hwy)	0
	Body		Class D (Off-Road)	0
Туре:			Maximum Grade:	6
Length (ft):		0	Wheelbase (in):	195
Height (ft):		0	Overhang (in):	54.7
Max Laden Weight (lbs):		0	Fr Axle to BOC (in):	92.8
(100).			Cab to Axle (in):	102.2
	Trailer		Cab to EOF (in):	156.9
No. of Trailer Axles:		2	Overall Comb. Length (in):	826
Type:		Flatbed	3 ()	
Length (ft):		53	Spec	ial Reg.
Height (ft):		13.5	••••	
Kingpin Inset (in):		36		
Corner Radius (in):		2		
	Restrictions			
Length (ft):		65		
Width (in):		102		
Height (ft):		13.5		
Approved by:			Date:	

Note: All sales are F.O.B. designated plant of manufacture.



Sales Code	Std/ Opt	Description	\$ List	Weight
Base Mo	odel			
0003891	S	Model 389 The Model 389 embodies the Peterbilt heritage and merges it with a proven design to create a legendary classic for vocational applications. The lightweight, all-aluminum cab with lap seam construction, aircraft grade fasteners and bulkhead style doors is legendary for its durability. The pod-mounted headlamps are durable, corrosion-resistant and cost-effective to replace. Peterbilt's all-aluminum cab is not only extremely durable, it's also lightweight to allow for increased payloads to maximize performance and profitability.	191,702	14,915
0091200	S	Other Commodity	0	0
0093170	S	General Freight Truck or tractor used in over-the-road hauling of general freight. Pickup to delivery distance is typically over 100 miles and annual mileage is typically over 60,000 miles per year. Operation is typically on-highway.	0	0
0096060	0	Flatbed A flat trailer with no enclosure or doors. Can be loaded/unloaded from the sides or above, and does not require elevated access for forklifts.	0	0
0098170	S	United States Registry Canadian Registry PackageRequires Air Conditioning Excise Tax Canada, Speedometer to be KPH ipo MPH, Daytime Running Lights and Rubber Battery Pad in Bottom of Battery Box.	0	0
Configu	ration			
0200700	0	Not Applicable Secondary Manufacturer	0	0
Frame &	k Equip	oment		
0515030	S	10-5/8" Steel Rails to 285" 10.625 x 3.45 x .313 Dimension, 1,776,000 RBM; Yield Strength: 120,000 psi. Section Modulus: 14.8 cubic inches. Weight: 1.44 lbs/inch pair	0	0
0644000	S	EOF Tractor Tapered with Crossmember Includes Kingpin Cutout	0	0
0651010	S	Peterbilt Rear Mudflaps and Straight Hangers Mudflaps aid in protecting the frame and undercarriage from road salt, grime and debris that can cause rust and corrosion. Mud flaps also shield other vehicles from gravel, rocks and road spray.	0	0
0854110	0	JOST JSK37 Fifth Wheel Top Plate JOSTs fifth wheels are the simplest and safest design in the market, with only four moving parts. JOSTs simple mechanism allows infinite adjustments versus competitors' notched adjustments.	2,001	240
0870000		Rear Or Fixd Setting Centerline Bogie	0	0
0890090	0	LH Fifth Wheel Release	0	0
0890550	0	7.6in - 8in Fifth Wheel Height	0	95



Sales Code	Std/ Opt	Description	\$ List	Weight
0890665	0	Jost Lightweight Inboard Slider	0	0
0891240	0	24" Air Slide	115	216
0940330	S	No Access Package or Deckplate Desired Use with tractors without access package or deckplate	0	0
Front Ax	de & E	quipment		
1012140	S	Meritor MFS+12E 12,500 lb, 3.5 in. Drop Axle is designed for applications with a gross axle weight rating (GAWR) of 13,000 pounds. Axles include special low-friction bushings, double draw keys and integral thrust bearing and seal design for durability, low maintenance and ease of service.	0	0
1111190	S	Taper Leaf Springs, Shocks 12,000 lb	0	0
1243000	S	Hendrickson taper leaf springs, shocks for 12,000 lbs. Power Steering Sheppard M100 For use with 10,000 to 13,200 lb. axle ratings. Glidekote splines on steering shaft extend service life of components.	0	0
1250180	S	Power Steering Reservoir Frame Mounted The power steering reservoir is a steering system that eases drivability by applying hydraulic pressure to the steering gear.	0	0
1353550	S	PHP10 Aluminum PreSet PLUS Hubs Air Disc PHP10 aluminum PreSet PLUS hubs air disc have a fully integrated spindle nut design, an optimized wheel spacer, magnetic fill plug, with a seal and bearings. Use with Front Axle.	0	0
1380290	S	Bendix Air Disc Front Brakes Bendix air disc front brakes use a floating caliper design to provide foundation braking on all axles and complies with reduced stopping distance regulations.	0	0
1380470	0	Meritor Wide Track IPO Standard, Front Axle Meritor wide track front axle offers greater turning radius and ease of service. MFS+ 3.5" Drop / MFS 3.74" Drop. 71in KPI IPO 69in with MFS and MFS+ axles.	0	15
1390630		80mm Front Spring Spacer Blocks	0	0
Rear Ax	le & Eo	quipment		
1527050	S	PACCAR DX-40 40K Tandem Axle	0	0
1616290	S	PHP10 Aluminum PreSet PLUS Hubs	0	0
1680390	S	Bendix ESP Electronic Stability Program With ATC Tractor service only. The Bendix ESP system is designed to continuously monitor a variety of vehicle parameters and sensors to determine if the vehicle is reaching a critical stability threshold. If such a situation develops, the system will quickly and automatically intervene to assist the driver by selectively applying tractor and trailer brakes, and de-throttling the engine.	0	0
1682710	S	Anti-Lock Braking System (ABS) 6S6M	0	0

Date: July 21, 2021 Quote Number: QUO-847808-H0V9G6



Sales Code	Std/ Opt	Description	\$ List	Weight
		ABS-6. Includes air braking system.		
1684200	S	Synthetic Axle Lubricant All Axles Peterbilt heavy duty models include Fuel Efficient Cognis EMGARD FE75W-90 which provides customers performance advantages over current synthetic lubricants with reduced gear wear and extended maintenance intervals, resulting in increased uptime. In addition, the lubricant provides improved fluid flow to protect gears in extreme cold conditions and withstand the stress from high temperatures, extending component life.	0	0
1687010	S	Bendix Air Cam Rear Drum Brakes 16.5x7 Bendix Air Cam Rear Drum Brakes to fit all heavy haul, contruction, refuse and highway truck and tractor applications. Includes Automatic Slack Adjusters & Outboard Mounted Brake Drums.	0	0
1703550	0	Ratio 3.55 Rear Axle	0	0
1821700	S	Peterbilt Air Leaf 38,000 lb, 52in Axle Spacing Light Weight with Tracking Rods.	0	0
Engine a	& Equi	pment		
2072828	S	PACCAR MX-13 455@1600 GV@2200 1650@900 (2021 Emissions) N20700 AA003 75CC MAX TARGET SPEED N20800 AA004 10CC MIN ENABLE SPEED N22000 AA005 OFFDYNAMIC CC ENABLE N20830 AA006 MTMULTI TORQUE IN CC N21930 AA009 0DRIVER REWARD VEH SPD BONUS N21940 AA010 -5DRIVER REWARD VEH SPD PNLTY N21920 AA013 BOTHOFFSET MODE N21950 AA015 3MIN SPEED FOR DR SHIFT AID N21960 AA016 1DSA LOWEST ACTV GEAR N21970 AA017 10DSA HIGHEST ACTV GEAR N21970 AA017 10DSA HIGHEST ACTV GEAR N21910 AA022 30EIST PARK BRAKE RESET ENABLE N21910 AA023 80EIST DARK BRAKE RESET ENABLE N20870 AA023 80EIST HI AMBAIR TEMP OVRRDE N20860 AA024 39EIST PTO MAX IDLE TIME N20860 AA025 5EIST PARKED MAX IDLE TIME N20850 AA027 5EIST PARKED MAX IDLE TIME N20850 AA027 5EIST PARKED MAX IDLE TIME N20850 AA027 5EIST PARKED FROM ENG LOAD N21170 AA030 NOEIST OVERRIDE FROM ENG LOAD N21170 AA031 0EIST EXPIRATION DISTANCE N21230 AA032 YESEIST ACCEL PEDAL RESET N21240 AA033 YESEIST SERVICE BRK RESET N21240 AA033 YESEIST PTO OVERRIDE N2070 AA037 4DSL SPD OFFSET N21260 AA034 YESEIST PTO OVERRIDE N20760 AA038 2AUTO RTRDR VEH SPD OFFSET N20760 AA039 0.1TIME DELAY FOR RTRDR ACT	0	0



Sales Code	Std/ Opt	Description	\$ List	Weight
		N22090 AA044 750CAB/REM: CUSTOM PRESET 1 N22100 AA045 CNCLCAB/REM: CUSTOM PRESET 2 FUN N22110 AA046 850CAB/REM: CUSTOM PRESET 3 FUN N22130 AA047 CNCLCAB/REM: CUSTOM PRESET 3 N22010 AA048 950CAB/REM: CUSTOM PRESET 1 N22010 AA049 CNCLCAB: CUSTOM PRESET 1 N22020 AA050 0CAB: CUSTOM PRESET 1 N22020 AA051 CNCLCAB: CUSTOM PRESET 2 N22040 AA052 0CAB: CUSTOM PRESET 2 N22050 AA053 CNCLCAB: CUSTOM PRESET 3 N22010 AA054 0CAB: CUSTOM PRESET 3 N22060 AA054 0CAB: CUSTOM PRESET 3 N20900 AA055 ON ACAB: CUSTOM PRESET 3 N20900 AA055 ON ACAB: CUSTOM PRESET 3 N20900 AA055 ON ACAB: RUTRAL INTLK N21010 AA058 ON ACAB: NEUTRAL INTLK N21101 AA059 ON ACAB: NEUTRAL INTLK N21100 AA059 ON ACAB: NEUTRAL INTLK N21100 AA059 ON ACAB: NEUTRAL INTLK N21100 AA060 OFFCAB: PRESET +/- SWITCH TYPE N21180 AA061 2000CAB: MAX ENG SPD - ACCEL CTRL N21120 AA062 2000CAB: MAX ENG SPD SW CTRL N21200 AA064 650CAB: MNX VEH SPEED N21200 AA066 600CAB: DEDICATED PRESET (-) N21220 AA066 600CAB: DEDICATED PRESET (-) N21220 AA066 900CAB: ACCEL PEDAL TYPE IN PTO N21140 AA068 YESCAB: ACCEL PEDAL TYPE IN PTO N21140 AA068 YESCAB: ACCEL ACTV IN CAB PTO N21140 AA068 YESCAB: ACCEL ACTV IN CAB PTO N21140 AA069 YESPTO REM PEDAL ENABLE N21600 AA071 OFFREM: CUSTOM INTLK N21700 AA072 ON AD.REM: NEUTRAL INTLK N21700 AA072 ON AD.REM: NEUTRAL INTLK N21710 AA073 ON AD.REM: SER BRK INTLK: NO PTO N21490 AA076 650REM: MIN ENG SPD N21320 AA076 650REM: MIN ENG SPD N21320 AA076 650REM: MIN ENG SPD N21320 AA076 650REM: MAX ENG SPD-ACCEL CTRL N21110 AA075 2000REM: MAX ENG SPD-SW/TSC1 CT N21320 AA076 650REM: MIN ENG SPD N21320 AA076 650REM: MIN ENG SPD N21320 AA077 000REM: DEDICATED PRESET (-) N21490 AA078 000REM: DEDIC		
2091130	S	VMUX Electronics Architecture	0	0
2091310	0	Engine Idle Shutdown Timer Disabled	0	0
2091372		Eff EIST NA Expiration Miles	0	0
2091638		Effective VSL Setting 65.0 MPH or Greater (USA)	0	0



Sales Code	Std/ Opt	Description	\$ List	Weight
2092014	S	Typical Operating Speed 65 MPH	0	0
2092027	0	MX Retarder State Cruise Control On (Manual Mode Engine Parameter)	0	0
2092032	0	Powertrain Optimized for Performance Best analysis for vehicles used in vocational applications or with heavy GCWRs.	0	0
2092082	S	Engine Monitoring Protection - Derate (PACCAR MX) A warning is provided in the A-Panel display when DPF regeneration is required. Continued operation without regeneration will initiate automate derating of the engine's power and can result in damage to the engine.	0	0
2140200	S	CARB Engine Idling Compliance PACCAR PX-7, PX-9 and MX, Cummins X15 and ISX diesel engines will include the required factory installed serialized sticker on the drivers door to identify them as meeting the NOx idling standard.	0	0
2140410	S	Engine Brake Controls Located on RH Column	0	0
2513060	S	PACCAR 160 Amp Alternator, Brushed PACCAR 160 AMP alternator, brushed producing 160 Amps at road speed and 100 Amps at idle.	0	0
2521090	S	Immersion Type Block Heater 110-120V Standard location for 2.1M and 1.9M models is left-hand under cab, Model 520 is in bumper, and for Model 220 it is at the driver step. Plug includes a weather-proof cover that protects the receptacle. This pre- heater keeps the coolant in the engine block from freezing when the engine is not running.	0	0
2522080	S	PACCAR Premium Starter - MX Engines Only PACCAR Premium 12 volt. Better cranking power, lower current draw and improved warranty to 5-yr/500K miles.	0	0
2538040	S	3 PACCAR Premium 12V Dual Purpose Batt 2190 CCA Threaded stud type terminal. Stranded copper battery cables are double aught (00) or larger to reduce resistance.	0	0
2621090	S	DM Advantage ON/OFF Fan Clutch Horton DM Advantage Two-Speed Fan Clutch On/Off for heavy-duty, medium-duty and a variety of off-highway equipment.	0	0
2738410	S	WABCO 25.9 CFM Air Compressor, MX only WABCO 25.9 CFM air compressor, MX only, provides greater air output aiding in cleaner operation, higher efficiency, and durability.	0	0
2811160	S	Compression Brake, MX The Mx brake features a Jacobs Brake with an integrated compression- release brake and engine overhead. the specially designed exhaust came lobe provides both exhaust cam motion and deicated Compression release timing. This results in precise timing of the valve opening, unleashing higher retarding performance with minimum loading on the engine.	0	0
2921180	S	PACCAR Fuel/Water Separator On Engine Extended life fuel filter, optimized for MX engines and Includes fuel heat, 12V electric heat and WIF sensor.	0	0
3114270	S	High Efficiency Cooling System	0	0

Price Level: April 1, 2021 Deal: 389 Tractor Printed On: 7/21/2021 4:23:32 AM Date: July 21, 2021 Quote Number: QUO-847808-H0V9G6



ales ode	Std/ Opt	Description	\$ List	Weigh
		Cooling module is a combination of steel and aluminum components,		
		with aluminum connections to maximize performance and cooling		
		capability. Silicone radiator & heater hoses enhance value, durability, &		
		reliability. Constant tension band clamps reduce leaks. Chevron Delo		
		Extended Life Coolant (NOAT) extends maintenance intervals reducing		
		maintenance costs. Anti-freeze effective to -30 degrees F helps protect		
		the engine. Low coolant level sensor warns of low coolant condition to		
		prevent engine damage. Radiator Size by Model: 579/367 FEPTO		
		1325 sq in, 567/365/367: 1440 sq in, 365 FEPTO: 1184 sq in, 389/367		
		HH: 1669 sq in, 348: 1000 sq in, 520: 1242 sq in.		
3213500	S	(1) 15" Painted Air Cleaner Cowl Mtd, Painted Cap	0	
		Molded rubber air intake connections with lined stainless steel clamps		
		seal to prevent contaminants in air intake. Stainless steel air cleaner		
		straps, brackets, & fasteners provide a durable bright finish.		
3365270	S	Exhaust Single RH Side of Cab	0	
0000040		DPF/SCR right-hand Under Cab.	0	
3383040	0	DPF Regeneration Switch	0	
3387870	S	Remove Stop Position 24" Ht, 5" Dia Chrome, Clear Coat Standpipe(s)	0	
	ission	& Equipment		
4040760	S	Eaton FRO16210C 10-Speed	0	
1010100	U	Includes oil-to-water cooler and internal pump, direct shift pattern.	Ũ	
		Synthetic lubricant to reduce friction, improve efficiency, & extend		
		component life. Magnetic transmission oil drain plug captures & holds		
		any metal fragments in transmission oil to extend service life. Torque		
		limiting clutch brake. Forward ratios: 1st-12.69, 2nd-9.29, 9th-1.00,		
		10th-0.74. Reverse ratios: L-13.75, H-2.80		
	-	SPL250 Lite HT Driveline, Without Midship Bearing		-2
4211510	0		-407	-
4211510 4216330	0	SPL170 XL Driveline Interaxle	-407 647	
		SPL170 XL Driveline Interaxle		
		SPL170 XL Driveline Interaxle Dana Spicer Life Series heavy-duty drive shafts are built for heavy		
4216330	0	SPL170 XL Driveline Interaxle Dana Spicer Life Series heavy-duty drive shafts are built for heavy loads over the long haul. For tandem rear axles.	647	
4216330 4216660 4256100	0 0 S	SPL170 XL Driveline Interaxle Dana Spicer Life Series heavy-duty drive shafts are built for heavy loads over the long haul. For tandem rear axles. Service Free Driveline Service free driveline for SPL350, SPL250, SPL170, SPL100. Manual Shifter, Black	647	
4216330 4216660 4256100	0 0 S	 SPL170 XL Driveline Interaxle Dana Spicer Life Series heavy-duty drive shafts are built for heavy loads over the long haul. For tandem rear axles. Service Free Driveline Service free driveline for SPL350, SPL250, SPL170, SPL100. 	647	
4216330 4216660 4256100	0 0 S	SPL170 XL Driveline Interaxle Dana Spicer Life Series heavy-duty drive shafts are built for heavy loads over the long haul. For tandem rear axles. Service Free Driveline Service free driveline for SPL350, SPL250, SPL170, SPL100. Manual Shifter, Black quipment Bendix AD-HF Air Dryer, Heater	647	
4216330 4216660 4256100 Air & Tra	0 0 S ailer E	SPL170 XL Driveline Interaxle Dana Spicer Life Series heavy-duty drive shafts are built for heavy loads over the long haul. For tandem rear axles. Service Free Driveline Service free driveline for SPL350, SPL250, SPL170, SPL100. Manual Shifter, Black quipment Bendix AD-HF Air Dryer, Heater Bendix AD-HF air filters protects the life of your engine system and	647 0 0	
4216330 4216660 4256100 Air & Tra	0 0 S ailer E	SPL170 XL Driveline Interaxle Dana Spicer Life Series heavy-duty drive shafts are built for heavy loads over the long haul. For tandem rear axles. Service Free Driveline Service free driveline for SPL350, SPL250, SPL170, SPL100. Manual Shifter, Black quipment Bendix AD-HF Air Dryer, Heater Bendix AD-HF air filters protects the life of your engine system and components. Proven PuraGuard oil coalescing technonlgy in the the air	647 0 0	
4216330 4216660 4256100 Air & Tra	0 0 S ailer E	SPL170 XL Driveline Interaxle Dana Spicer Life Series heavy-duty drive shafts are built for heavy loads over the long haul. For tandem rear axles. Service Free Driveline Service free driveline for SPL350, SPL250, SPL170, SPL100. Manual Shifter, Black quipment Bendix AD-HF Air Dryer, Heater Bendix AD-HF air filters protects the life of your engine system and components. Proven PuraGuard oil coalescing technonlgy in the the air dryer catridge. This oil coalescing filter ensures the removal of oil and	647 0 0	
4216330 4216660 4256100 Air & Tra	0 0 S ailer E	SPL170 XL Driveline Interaxle Dana Spicer Life Series heavy-duty drive shafts are built for heavy loads over the long haul. For tandem rear axles. Service Free Driveline Service free driveline for SPL350, SPL250, SPL170, SPL100. Manual Shifter, Black quipment Bendix AD-HF Air Dryer, Heater Bendix AD-HF air filters protects the life of your engine system and components. Proven PuraGuard oil coalescing technonlgy in the the air dryer catridge. This oil coalescing filter ensures the removal of oil and oil aerosols before they can contaminate the moisture removing	647 0 0	
4216330 4216660 4256100 Air & Tra	0 0 S ailer E	SPL170 XL Driveline Interaxle Dana Spicer Life Series heavy-duty drive shafts are built for heavy loads over the long haul. For tandem rear axles. Service Free Driveline Service free driveline for SPL350, SPL250, SPL170, SPL100. Manual Shifter, Black quipment Bendix AD-HF Air Dryer, Heater Bendix AD-HF air filters protects the life of your engine system and components. Proven PuraGuard oil coalescing technonlgy in the the air dryer catridge. This oil coalescing filter ensures the removal of oil and	647 0 0	
4216330 4216660 4256100 Air & Tr 4510190	O S ailer E S	SPL170 XL Driveline Interaxle Dana Spicer Life Series heavy-duty drive shafts are built for heavy loads over the long haul. For tandem rear axles. Service Free Driveline Service free driveline for SPL350, SPL250, SPL170, SPL100. Manual Shifter, Black quipment Bendix AD-HF Air Dryer, Heater Bendix AD-HF air filters protects the life of your engine system and components. Proven PuraGuard oil coalescing technonlgy in the the air dryer catridge. This oil coalescing filter ensures the removal of oil and oil aerosols before they can contaminate the moisture removing desiccant. Nylon Chassis Hose	647 0 0	
4216330 4216660 4256100 Air & Tr 4510190	O S ailer E S	SPL170 XL Driveline Interaxle Dana Spicer Life Series heawy-duty drive shafts are built for heavy loads over the long haul. For tandem rear axles. Service Free Driveline Service free driveline for SPL350, SPL250, SPL170, SPL100. Manual Shifter, Black quipment Bendix AD-HF Air Dryer, Heater Bendix AD-HF air filters protects the life of your engine system and components. Proven PuraGuard oil coalescing technonly in the the air dryer catridge. This oil coalescing filter ensures the removal of oil and oil aerosols before they can contaminate the moisture removing desiccant. Nylon Chassis Hose Steel Painted Air Tanks	647 0 0	
4216330 4216660 4256100 Air & Tr 4510190	O S ailer E S	SPL170 XL Driveline Interaxle Dana Spicer Life Series heavy-duty drive shafts are built for heavy loads over the long haul. For tandem rear axles. Service Free Driveline Service free driveline for SPL350, SPL250, SPL170, SPL100. Manual Shifter, Black quipment Bendix AD-HF Air Dryer, Heater Bendix AD-HF air filters protects the life of your engine system and components. Proven PuraGuard oil coalescing technonlgy in the the air dryer catridge. This oil coalescing filter ensures the removal of oil and oil aerosols before they can contaminate the moisture removing desiccant. Nylon Chassis Hose	647 0 0 0	-



Sales Code	Std/ Opt	Description		Weight
		outside the frame rails will be polished aluminum). Peterbilt will determine the optimal size and location of required air tanks. Narratives requesting a specific air tank size or location will not be accepted for factory installation. See ECAT to determine number or location of air tanks installed.		
4543390	0	High Mount Air Tanks BOC/BOS Where Possible Subject to frame review	0	0
4610920	S	Self-Returning Brake Hand Valve Dash mounted controls	0	0
4611440	0	Hose Tenna Mounted On LH Rail		0
4614810	S	AE Connections BOC/BOS, Hose Tenna	0	0
4614850	0	12' AE Lines Straight, (2) 7-Way Plugs	260	8
4614870	0	AE Connections 41-54" BOC/BOS	0	0
Tires &	Wheel	S		
5066100	S	FF: BR 14ply 295/75R22.5 R213 Ecopia	0	0
5166100	S	RR: BR 14ply 295/75R22.5 R213 Ecopia		0
5190008	S	Code-rear Tire Qty 08	0	0
5211990	S	FF: Accu-Lite Steel Armor 51408PK 22.5X8.25 PHP10-2 hand holes		0
5311990	S	RR: Accu-Lite Steel Armor 51408PK 22.5X8.25 PHP10-2 hand holes	0	0
5390008	S	Code-rear Rim Qty 08	0	0
Fuel Ta	nks			
5552070	S	26" Aluminum 60 Gallon Fuel Tank RH BOC Paddle handle filler cap with threadless filler neck. Top draw fuel plumbing reduces chance of introducing air into the fuel system during low fuel level conditions due to the central placement of fuel pickup tube. Wire braid fuel lines increase durability & reduce potential for leaks.	0	0
5556070	S	26" Aluminum 60 Gallon Fuel Tank LH BOC Paddle handle filler cap with threadless filler neck. Top draw fuel plumbing reduces chance of introducing air into the fuel system during low fuel level conditions due to the central placement of fuel pickup tube. Wire braid fuel lines increase durability & reduce potential for leaks.	0	0
5603060	S	Location RH BOC 60 Gallon	0	0
5604060	S	Location LH BOC 60 Gallon	0	0



Sales Code	Std/ Opt	Description	\$ List	Weight
5652890	S	DEF Tank Mounted LH BOC Models 220 and 520 mounted left hand back-of-cab.	0	0
5652990	0	DEF To Fuel Ratio 2:1 Or Greater	0	0
5655019	S	DEF Tank Small, HD 14 Gal 2.1M MD 5.5 Gal	0	0
Battery	Box &	Bumper		
6010030	S	Aluminum Battery Box LH Under Cab, Non-Slip Step Includes diamond pattern block shaped cover in traditional/vocational models and a smooth finish tapered cover on aerodynamic models	0	0
6040550	S	Aftertreatment Aluminum Non-Slip Cab Entry Aftertreatment right-hand under cab step. DPF/SCR for diesel engines, catalyst for natural gas engines. On Models 579 specifying chassis fairings, the box is aerodynamic.	0	0
6121090	S	Steel Bumper Deep Tapered Chromed Two tow points	0	0
Cab & E	quipm	ent		
6510140	S	Alum Cab 123in BBC Alum Hood SFFA fenders w/polished crown, spring tilt assist. Proprietary anti-blow-down locking mechanism that keeps hood open during servicing & prevents unintentional closing. Hood latch each side secures hood to cowl. Proprietary all-alum cab is light weight & durable for long service life. One-piece roof reduces potential for leaks. Two-piece windshield for cost effective windshield replacement. Lap seam construction & aircraft fasteners has greater clamp load than rivets. Bulkhead style doors provide virtually water-tight, rattle-free performance. Extruded alum door frames for strength & durability. Full length, heavy-duty piano-type stainless steel door hinges & pins provide durability. View window in RH door for safety. Electric windshield wipers & washers w/intermittent wiper function. Grab handles mtd on cab LH & RH for cab access. Convex mirror over RH door & below each rear view mirror for improved visibility & safety.	0	0
6700000	S	No Sleeper Selected	0	0
6911170	S	Sears Driver Seat Increased comfort with more foam in critical areas, better lumbar support, improved adjustability and suspension with toggle link design.	0	0
6921170	S	Sears Passenger Seat Increased comfort with more foam in critical areas, better lumbar support, improved adjustability and suspension with toggle link design.	0	0
6939400	S	Air Ride Driver	0	0
6939420	S	High Back Driver	0	0
6939470	S	Vinyl Driver	0	0
6939510	S	Non-Air Ride Passenger	0	0



Sales Code	Std/ Opt	Description	\$ List	Weigh
6939520	S	High Back Passenger	0	(
6939570	S	Vinyl Passenger	0	
7000025	S	Steering Wheel With Multi-Function Includes Peterbilt logo on horn button, audio volume, seek, mute and mode button on LH pod with cruise control on/off/cancel, set/resume and accelerate/coast on the right pod.	0	
7000350	S	Power Door Locks Both Doors	0	
7001520	S	Adjustable Steering Column - Tilt/Telescope	0	
7039050	S	ProBilt Interior - Arctic Gray Includes rugged charcoal instrument panels, gray dash with glare- resistant, charcoal soft-touch upper, dark gray hard trim, black bezels on gauges, cigar lighter and ashtray with power port, monochromatic dark gray durable doorpads with map pocket on driver's side, dark gray molded back wall, 18 inch 4-spoke soft-touch steering wheel, soft-touch steering column cover, power lift passenger window, extruded rubber floor covering, header-mounted domelight, driver and passenger dome/reading lights, footwell lighting, integrated "dead pedal", (5) inside entry grab handles, (2) inside sunvisors, (2) coat hooks, cup holder and map bin in dash.	0	
7210540	S	Day Cab Rear Window Day cab rear window flush to back of cab.	0	
7230060	S	1-Piece Curved Windshield		
7230680	S	Power Lift Windows - Both Doors For use with ProBilt or Prestige Interior	0	
7322010	S	Combo Fresh Air Heater/Air Conditioner With radiator mounted condenser, dedicated side window defrosters, Bi-Level Heater/Defroster Controls, 54,500 BTU/HR, and silicone heater hoses.	0	
7330700	S	Peterbilt Comfort Control - Cab	0	
7510010	S	Stainless Steel Mirrors 7 x 16	0	
7560850	S	(2) Convex 8 Inch SSTL Mirrors Center mounted under mirror bracket. If rear view mirrors are heated, the convex mirrors will be heated. Option includes dual door stops.	0	
7610470	S	(1) Air Horn 24.5" Chrome - Round w/Horn Shield	0	
7725720	S	No Head Unit or Audio Speakers Selected	0	
7788055	S	SmartLINQ Remote Diagnostics SmartLINQ is Peterbilts proprietary remote diagnostics service which monitors the engine and aftertreatment for diagnostic codes providing real-time code analysis maximizing vehicle uptime and strengthening the fleets partnership with their dealer. SmartLINQ provides fault coverage for over 800 codes, a customizable email notification for 116	0	
e Level: A		2021	Date: Ju	J .
al: 389 Trad		Quote Number: 21 4:23:32 AM	QUO-8478	08-H0



Sales Code	Std/ Opt	Description	\$ List	Weight
		codes plus a web portal to manage your entire fleet included at no additional charge. SmartLINQ is compatible with any telematics system and doesnt require a specific fleet management system. For those whose customers utilize PeopleNet, the pre-wire with remote diagnostics will provide a more integrated solution utilizing the existing SmartLINQ modem. For those whose customers utilize other fleet		
		services products, the existing pre-wire option for the other fleet service devices will continue to be available. Standard on Class 8 engines and available on Models 348, 337, 330 and 325 with a PX-9, PX-7 or		
7788056	S	Cummins Westport natural gas engine. 24 Months SmartLINQ Subscription With OTA Functionality - PACCAR MX Engines	0	0
7851480	S	Peterbilt Electric Windshield Wipers0With Intermittent Feature.0		0
8011830	S	Engine Oil Temperature0Located in Digital Cluster Display.0		0
8021380	S	Air Restriction Indicator Mounted on air cleaner, intake piping, or firewall	0	0
8021810	S	Brake Application Air Pressure (Tractor) Located in Digital Cluster Display.	0	0
8070810	S	Engine Manifold Pressure (Turbo Boost) Located in Digital Cluster Display	0	0
8070820	S	Engine Percent Torque Located in Digital Cluster Display	0	0
8070830	0	Main Instrumentation Panel Digital Cluster 15" Display includes: Speedometer, Tachometer, Primary Air Pressure, Secondary Air Pressure, Fuel Level, DEF Level, DPF Filter Status, Fuel Economy, Oil Pressure, Coolant Temp, OAT and Voltmeter.		0
8111140	S	Headlights Projector Module Pod Integral Turn Signals	0	0
8120980	S	(5) Marker Lights, Aero LED	0	0
8134160	0	Self-Canceling Turn Signal	0	0
8140000	S	Incandescent Oval Stop/Turn/Tail/Backup In tractor taper end of frame crossmember	0	0
Paint				
8500710	0	Standard Paint Color Selection	-200	0
8530770	S	(1) Color Axalta Two Stage - Cab/Hood Base Coat/Clear Coat N85020 A - L0006EY WHITE N85500 CAB ROOF L0006EY WHITE N85300 FENDER L0006EY WHITE N85200 FRAME L0001EA BLACK N85400 HOOD TOP L0006EY WHITE N85720 SK FAIRINGS L0006EY WHITE	0	0

Price Level: April 1, 2021 Deal: 389 Tractor Printed On: 7/21/2021 4:23:32 AM Date: July 21, 2021 Quote Number: QUO-847808-H0V9G6



Sales Code	Std/ Opt	Description	\$ List	Weight						
Shippin	Shipping Destination									
Options	Not S	Subject To Discount								
9400090	S	Peterbilt Class 8 Standard Coverage 1 year/100,000 Miles (160,000 km)	0	0						
9400092	S	PACCAR MX Standard Coverage 2 yrs/250,000 mi (400,000 km)/6,250 hrs	0	0						
Miscella	neous	3								
9409000	S	Day Cab / ProBilt Interior (DB)	0	0						
9409831	S	2021 EPA Emissions Engine Warranty Only	0	0						
Promoti	ons									

Order Comments



Total List Price (W/O Freight & Warranty & Surcharges) Marketing and Service Support Fee Prepaid Freight Total Surcharge/Options Not Subject To Discount

Total Weight

\$194,165 \$895 \$2,825 \$0

15,466

Prices and Specifications Subject to Change Without Notice.

Unpublished options may require review/approval. Dimensional and performance data for unpublished options may vary from that displayed in CRM.

PRICING DISCLAIMER

While we make every effort to maintain the web site to preserve pricing accuracy, prices are subject to change without notice. Although the information in this price list is presented in good faith and believed to be correct at the time of printing, we make no representations or warranties as to the completeness or accuracy of this information. We reserve the right to change, delete or otherwise modify the pricing information which is represented herein without any prior notice. We carefully check pricing specifications, but occasionally errors can occur, therefore we reserve the right to change such prices without notice. We disclaim all liability for any errors or omissions in the materials. In no event will we be responsible for any damages of any nature whatsoever from the reliance upon information from these materials. Please check your order prebills to confirm your pricing information



Shipping Destinations

Intermediate Destination: none

Final Destinations	Quantity



THE **ICON** OF THE HIGHWAY.



The Model 389 embodies Peterbilt heritage and merges it with a proven design to create a legendary classic. Lightweight components, such as the all-aluminum cab and the industry's only aluminum hood, as well as a variety of lightweight front and rear suspensions, allow for increased load capacity. Aerodynamic enhancements for increased fuel savings all combine to ensure that your investment in the Model 389 pays dividends long after the initial purchase. An optional fuel-efficiency package as well as Peterbilt's exceptional reliability and performance translate into an overall low cost of operation. The Model 389 is available with the fuel-efficient PACCAR MX-13 engine with power ratings up to 510 hp and 1,850 lb.-ft. torque for maximum performance. The Model 389 continues to be an industry leader in quality, styling, performance and enduring value.



The Model 389 features conventional styling, plus a selection of components and options for efficiency and performance. Peterbilt's lightweight and durable hood is the industry's only all-aluminum hood with a distinctive punched oval grille and one-piece aluminum crown.

For more information on the Model 389, contact your local Peterbilt dealer or visit **www.peterbilt.com**



CAB INTERIOR

The Model 389 features an ergonomic dash that puts everything within reach of the driver and improves visibility. The charcoal finish reduces glare and resists scratches and fading.



SLEEPER INTERIOR Peterbilt's unique sleepers are built to deliver unparalleled fit and finish, quality and comfort. They feature plenty of storage, shelving, ample overhead lighting and a powerful HVAC. Available in 44", 58", 72" & 78" configurations.



VISIBILITY Halogen projectors, aluminum headlamps and long-life LED directional signals are protected with an impact-resistant lens and contribute to overall exceptional visibility.



DURABILITY

A lightweight all-aluminum cab is huck-bolted with lap seam construction and bulkhead style doors for toughness and corrosion resistance. The Model 389 cab offers years of virtually watertight, rattle-free performance.



PACLEASE & PACCAR FINANCIAL PLANS TAILORED TO YOUR NEEDS.

PETE-9888 REV. 3/17 • PRINTED IN U.S.A. • FOR MORE INFORMATION, CALL 1-800-552-0024 • BUCKLE-UP FOR SAFETY





Model 389 Standard Features

(Base Model Option Code 0003891)



FRAME

- Steel rails with gussets to maximize RBM.
- Huck bobtail fasteners provide a consistent and durable clamping force up to 600% greater than bolted frames. Tamper resistant round head and collar offers improved paint adhesion and corrosion resistance. Swage indicating features on collar allows for visual inspection of clamped joint.
- 3-piece C-Channel cross member with cast gussets.
- Rubber-lined clamps along frame rail to protect air & electric lines routed in frame.
- Chassis hose and wiring bundles conveniently routed through gussets provides protection for lines.
- Front wheel mud flaps reduce road spray, help maintain a cleaner truck and better visibility.
- Two frame mounted tow pins.

STEER AXLE

- Set forward front axle configuration uses longer springs to deliver a smooth and comfortable ride.
- Factory front axle alignment to improve handling and reduce tire wear.
- Zerk fittings on tie rod ends, kingpins, and draglink ball joints for ease of maintenance and help extend service life of components.
- Greaseless spring pins reduce maintenance and improve ride quality.
- Standard oil seals for long lasting leak protection.
- Cognis EMGARD[®] Synthetic Axle Lube reduces wear and extends maintenance intervals, resulting in increased uptime. Provides improved fluid flow to protect components in extreme cold conditions and withstand the stress from high temperatures, extending component life.
- Glidekote splines on steering shaft extend service life of components.

DRIVE AXLE

- Laser factory axle alignment (accurate to .030 of an inch) to improve handling and reduce tire wear.
- Magnetic rear axle oil drain plug captures and holds any metal fragments in drive axle lube to extend service life.
- Parking brakes on all drive axles for optimal performance.
- Cognis EMGARD[®] Synthetic Axle Lube reduces wear and extends maintenance intervals, resulting in increased uptime. Provides improved fluid flow to protect components in extreme cold conditions and withstand the stress from high temperatures, extending component life.

ENGINES & RELATED SYSTEMS

- Selective Catalytic Reduction (SCR) System provides the most fuel efficient, reliable and cost effective solution to the 2010 EPA regulations. The SCR system consists of several new standard components on the truck - a dosing pump, a DEF tank, an injector and the SCR ammonia catalyst.
- Chevron Delo 400 LE SAE 10W30 engine oil is specially formulated for new low emissions engines.
- Magnetic engine oil drain plug captures and holds any metal fragments in engine oil to extend service life.
- Silicone radiator and heater hoses enhance value, durability and reliability.
- ClimaTech extended life coolant extends maintenance intervals which reduces maintenance costs.
- Low coolant level sensor warns of low coolant condition to prevent engine damage.
- Constant tension and torque band clamps reduce leaks.
- Stainless steel hardline manifold reduces coolant hoses in the engine compartment to improve durability and appearance.
- Thermal fuse in the air conditioning compressor clutch allows the pulley to free spin in the event of a compressor failure, thus reducing belt wear and vehicle downtime.
- Weather pack silicone sealed electrical chassis connectors enhance value, durability and reliability.
- 12 Volt System with circuit protection for reliable easy maintenance and service.
- 1669 sq. in. frontal area cooling system provides a large surface area for heat exchange.
- Composite fan is light-weight but strong and corrosion resistant.
- Full fan shroud, ring and rubber boot improves under hood airflow and provides a robust fan-to-radiator shroud interface for greater cooling capacity.
- Anti-freeze effective to -30 degrees F helps protect the engine.
- Maintenance free 12V batteries provide reliable power for starting and accessories.
- Stranded copper battery cables are double aught (00) or larger to reduce resistance.
- Stainless steel air cleaner straps, brackets and fasteners provide a durable bright finish.
- Molded rubber air intake connections with lined stainless steel clamps seal to prevent contaminants in air intake.
- Washer bottle with 1.3 gallon capacity extends maintenance intervals to refill.

- Stainless steel grille with a distinctive punched oval grille pattern provides a durable bright finish
- Stainless steel flex exhaust tubing & clamps provide durability.
- Optimized exhaust routing to simplify the truck order process and provide optimal performance.
- 5" diameter chrome plated steel standpipe cools exhaust for safety.

TRANSMISSION & RELATED SYSTEMS

- Synthetic lubricant to reduce friction, improve efficiency and extend component life.
- Magnetic transmission oil drain plug captures and holds any metal fragments in transmission oil to extend service life.
- Coated driveshaft splines extends service life.
- Configured Clutch to simplify the truck order process and provide optimal performance.
- Torque limiting clutch brake

AIR SYSTEM

- Engine mounted air compressor with remote mounted air system filter dryer to reduce moisture in air system components.
- Teflon-lined, stainless steel braided compressor discharge hose provides long service life in high operating temperatures.
- Schrader valve for charging of air system from external source.

FUEL TANKS

- Aluminum fuel tanks with heavy-duty aluminum brackets and stainless steel straps.
- Under cab fuel tanks include steps for cab access.
- Single fuel tank will receive a single draw / single return fuel system.
- Dual fuel tanks will receive dual draw / dual return fuel system equalizes fuel load.
- Top draw fuel plumbing reduces chance of introducing air into the fuel system during low fuel level conditions due to the central placement of the fuel pickup tube.
- Optimized filler neck location on under cab fuel tanks optimizes access and safety.
- Paddle handle filler cap with threadless filler neck
- Wire braid fuel lines increase durability and reduce potential for leaks.

ELECTRICAL SYSTEM

- Multiplex electrical design utilizing the industry standard J1939 data bus that sends multiple signals over a single wire instead of having an individual wire for each function. This allows each component (engine, transmission and instrumentation) to communicate to each other. This design improves reliability and offers increased functionality.
- Proprietary Electronic Service Analyst (ESA) allows dealer to monitor the electrical system, isolate sensors and gauges, and keep a log of service history.
- Automatically resetting circuit breakers in selected circuits
- Braided chassis harness cover provides durability.
- Convoluted tube covering on harnesses protects from chaffing.

- Wires numbered every 4 inches or less for ease of serviceability.
- Power distribution center in cab is centrally located in a protected environment for easy access.

CAB / HOOD

- Proprietary all-aluminum cab is light weight and durable for long service life.
- Light-weight all-aluminum hood with 131" BBC and one-piece grille crown improves air flow.
- Removable aluminum fenders with polished aluminum reinforcements to expedite repairs and minimize downtime.
- Fender liners with pre-molded features to facilitate quicker installation of mirrors and protect fenders from rock damage.
- Spring assisted 90 degree hood opening for serviceability.
- Proprietary anti-blow-down locking mechanism that keeps the hood open during servicing and prevents unintentional closing.
- Hood latch on each side secures the hood to the cowl.
- Aerodynamic hood ornament
- Three point rubber cab mounting
- One piece roof reduces potential for leaks.
- Lap seam construction and aircraft fasteners has greater clamp load than rivets.
- Bulkhead style doors provide virtually water-tight, rattle-free performance.
- Extruded aluminum door frames for strength and durability.
- Full length, heavy-duty piano-type stainless steel door hinges and pins provide durability.
- View window in RH door for safety.
- Electric windshield wipers and washers with intermittent wiper function
- Grab handles mounted on cab LH & RH for cab access.
- Convex mirror over RH door and below each rear view mirror for improved visibility and safety.

CAB INTERIOR

Standard Features	Interior Level		
	Platinum	Prestige	ProBilt
Upper and lower dash panels in a dark charcoal color that is not only easier to clean and shows less scratches and scuffs, but also improves driver visibility due to less glare.			•
Top-of-dash panels in a dark charcoal grey that reduces driver glare, is less likely to scratch and scuff and is easier to clean, while the lower dash panels are perfectly matched to your cab's interior color.		•	
Top-of-dash panels in a dark charcoal grey that reduces driver glare, is scratch resistant and is less likely to fade or show dirt with elegant woodgrain on the lower dash panels.	•		

Monochromatic dash with soft touch upper			•
Two-toned color coordinated dash with soft touch upper	•	•	
Black bezels on gauges	•	•	
Bright bezels on gauges	•		
Contoured door pads featuring integrated ergonomic armrests for driver	•	•	•
comfort			
Satin burlwood insert on contoured door pads		•	
High gloss burlwood insert on contoured door pads with vinyl inserts	•		
LH & RH door mounted map pockets with built-in courtesy lights	•	•	
Power lift passenger window controls integrated into the door panel are		•	•
within easy reach of the driver for safe and convenient operation.			
Power windows and door locks on both doors integrated into the door	•		
panel are within easy reach of the driver for safe and convenient operation.			
Padded vinyl headliner is easy to clean.		•	•
Padded vinyl headliner with premium insert	•		
Two inside sunvisors with map straps provide driver and passenger comfort		•	•
and convenience.			
Two inside sunvisors with integral vanity mirrors provide driver and	•		
passenger comfort and convenience.			
Two coat hooks for driver and passenger convenience with daycabs only.	•	•	•
Integrated cup holder in dash	•	•	•
Cast rubber flooring with integral sound barrier.	•	•	
Fully carpeted floor covering with integral sound barrier.	•		
Heater / air conditioner with dedicated side window defroster	•	•	•
18" soft touch steering wheel	•	•	•
Adjustable steering column	•		
Key start ignition for an automotive feel.	•	•	•
Ignition and doors keyed alike for driver convenience.	•	•	•
Single electric horn	•	•	•
Cigar lighter and ashtray with power port	•	•	•
Integrated "dead pedal" for driver comfort.	•	•	•
Five ergonomically positioned entry / egress grab handles	•	•	•
Proprietary non-slip threshold plate accented with a chrome inset and	•	•	•
Peterbilt Red Oval adds a touch of Peterbilt class to safety and convenience.			
Header mounted dome light	•	•	•
Driver and passenger dome and reading lights	•	•	•
Retractable three-point seatbelts on driver and passenger seats	•	•	•
Footwell lighting	•	•	•
12-volt power outlet in dash	٠		
Peterbilt in-dash Navigation System	•		

<u>LIGHTS</u>

• State-of-the-art halogen projector module pod headlights increase visibility.

- 'Headlight on Warning' when headlights are active with door open and ignition off. The high beam headlamp icon flashes and sounds an audible alarm.
- Headlights turn on automatically when windshield wiper blades are activated.
- Polished cast aluminum headlight pod housing with LED side-turn indicators and an impact resistant lens matches durability with style.
- Rear combination stop / turn / tail lights

DASH & INSTRUMENTATION

- Driver Information Display that allows the driver to view diagnostic information and monitor truck system behavior. Information such as fuel economy, optimum engine speed and engine and transmission system management provides driver feedback and improves operating performance.
- Dash features an "in-mold" color process that imbeds the color into the material making the color permanent and eliminating peeling and fading.
- Electronic speedometer with trip odometer
- LED backlit gauges to prevent eye fatigue.
- Electronic tachometer with hour meter and outside air temperature display
- Voltmeter
- Primary and secondary air pressure gauges
- Engine oil pressure gauge
- Engine coolant temperature gauge
- Fuel level gauge with low fuel warning.
- Standard warning lights with audible alarm for high coolant temperature, low oil pressure and low air pressure
- Warning indicators for high beam, parking brake, turn signals, low fuel, road surface ice potential
- Seat belt reminder
- Cruise control for driver convenience.
- Head lights, marker lights, hazard lights, regeneration (DPF) and dimmer switches.
- Rocker switches with long-life LED indicators that are easy to reach for driver safety and convenience.
- Multi-function turn stalk with flash-to-pass feature intermittent windshield wiper and headlamp beam control.

<u>PAINT</u>

• DuPont Imron Elite two-stage non-metallic paint, one color cab / hood



THE **PRIDE** & **CLASS** OF THE HIGHWAY

Jaw dropping! Pulse pounding! Peterbilt's new Model 389 Pride & Class package is a stunning display of chrome and sophistication. No one can miss this awe-inspiring truck as it commands the highways. With its eye-popping, head-turning features like the distinct louvered grille and brightly polished accessories, this exceptional truck truly impresses from every angle. Exclusive, chic accents surround the driver in touches of understated elegance and comfort. The Pride & Class package demands the attention of everyone who sees it while its driver instantly becomes the envy of all others. Elevate the driving experience from ordinary to extraordinary with the Model 389 Pride & Class.

For more information on the Model 389 Pride & Class, contact your nearest Peterbilt dealer or visit www.peterbilt.com.



The Pride & Class interior features a dark charcoal top and Blackwood finish trim throughout the cab and sleeper. Exclusive details include black leather seats with red contract stitching, a special steering wheel and a chrome interior handle. A bright logo'd shifter plate and shift lever with a Blackwood finish shifter knob are available with manual transmissions. The distinctive Pride & Class emblem is located on the dash, in the seat headrest and on the shifter plate.



2892

HIDOR P

CLASSIC DESIGN Reminiscent of Peterbilt's traditionally styled products of the 1950's, the Model 389 Pride & Class features a new louvered grille with a highly polished hood crown and spine.



BRIGHT FEATURES Polished aluminum fenders, a large sunvisor, bumper, and exhaust stacks are impressive and easily identify this model as being in a Class of its own.



DISTINCTIVE STYLING A stylized, side-hood air intake bezel is a unique design exclusive to the Pride & Class package.



CHROME ACCENTS Bright rocker panels complement the cowl skirts, battery box, fuel tanks and mud flaps providing sleek accents that are clearly visible from every angle of the truck.



PACLEASE & PACCAR FINANCIAL PLANS TAILORED TO YOUR NEEDS.

PETE-9902-US 7/14 • PRINTED IN U.S.A. • FOR MORE INFORMATION, CALL 1-800-552-0024 • BUCKLE-UP FOR SAFETY

