



Peterbilt of Richmond (H830)
2800A Deepwater Terminal
Richmond, Virginia 23212

Virginia Sheriffs Association
901 East Byrd St Suite 1301
Richmond, Virginia 23219
United States of America

David Askew
Cell Phone:
Office Phone:
Email: daskew@thepetestore.com

Kaylyn Mitman
Office Phone: 919-459-6471
Email: kmitman@virginiasheriffs.org

Vehicle Summary

| Unit | | Chassis | |
|-------------------------|------------------|----------------------------|--------|
| Model: | Model 389 | Fr Axle Load (lbs): | 14600 |
| Type: | Tractor | Rr Axle Load (lbs): | 46000 |
| Description 1: | 389 Tractor | G.C.W. (lbs): | 125000 |
| Description 2: | 389 Option Specs | | |
| Application | | Road Conditions: | |
| Intended Serv.: | Heavy Equipment | Class A (Highway) | 100 |
| Commodity: | Machinery | Class B (Hwy/Mtn) | 0 |
| | | Class C (Off-Hwy) | 0 |
| | | Class D (Off-Road) | 0 |
| Body | | Maximum Grade: | 6 |
| Type: | | Wheelbase (in): | 250 |
| Length (ft): | 0 | Overhang (in): | 56 |
| Height (ft): | 0 | Fr Axle to BOC (in): | 100.6 |
| Max Laden Weight (lbs): | 0 | | |
| Trailer | | Cab to Axle (in): | 149.4 |
| No. of Trailer Axles: | 2 | Cab to EOF (in): | 205.4 |
| Type: | Dropped Deck | Overall Comb. Length (in): | 881 |
| Length (ft): | 53 | Special Req. | |
| Height (ft): | 13.5 | | |
| Kingpin Inset (in): | 36 | | |
| Corner Radius (in): | 2 | | |
| Restrictions | | | |
| Length (ft): | 65 | | |
| Width (in): | 102 | | |
| Height (ft): | 13.5 | | |

Approved by: _____

Date: _____

Note: All sales are F.O.B. designated plant of manufacture.



| Sales Code | Std/ Opt | Description | \$ List | Weight |
|------------------------------|----------|---|---------|---------------|
| Base Model | | | | |
| 0003891 | S | Model 389 The Model 389 embodies the Peterbilt heritage and merges it with a proven design to create a legendary classic for vocational applications. The lightweight, all-aluminum cab with lap seam construction, aircraft grade fasteners and bulkhead style doors is legendary for its durability. The pod-mounted headlamps are durable, corrosion-resistant and cost-effective to replace. Peterbilt's all-aluminum cab is not only extremely durable, it's also lightweight to allow for increased payloads to maximize performance and profitability. | 191,702 | 14,915 |
| 0091160 | O | Machinery | 0 | 0 |
| 0093030 | O | Heavy Equipment Tractor used to transport heavy, non-divisible loads, such as earth moving equipment, electrical transformers, pressure vessels, etc. GCW can be from 80,000 lb. to extremely heavy. | 0 | 0 |
| 0096190 | O | Dropped Deck A flatbed with a lowered deck, featuring a raised step at the front, where the trailer connects to the fifth wheel. | 0 | 0 |
| 0098170 | S | United States Registry Canadian Registry Package Requires Air Conditioning Excise Tax Canada, Speedometer to be KPH ipo MPH, Daytime Running Lights and Rubber Battery Pad in Bottom of Battery Box. | 0 | 0 |
| Configuration | | | | |
| 0200700 | O | Not Applicable Secondary Manufacturer | 0 | 0 |
| Frame & Equipment | | | | |
| 0514000 | O | 10-3/4" Steel Rails To 354" 10.75x3.5x.375 Dimension, 2,136,000 RBM; Yield Strength: 120,000 psi. Section Modulus: 17.8 cubic inches. Weight: 1.74 lbs/inch pair | 358 | 357 |
| 0601500 | O | Full Steel Inner Liner | 1,367 | 677 |
| 0611250 | O | Heavy-Duty Iron Front Spring Brackets With Front Air Leaf the front spring bracket is iron but not the shackle bracket | 316 | 35 |
| 0611330 | O | Zinc Coated Anti Corrosion Treated Frame Rails Requires Frame Rail Code. Zinc Phosphate coating will replace the standard frame rail primer and provide added corrosion prevention for your customer's operating in severe conditions or in climates where vehicle rust is common. | 387 | 0 |
| 0644000 | S | EOF Tractor Tapered with Crossmember Includes Kingpin Cutout | 0 | 0 |
| 0651540 | O | Peterbilt Rear Mudflaps,SSTL Flt Engr FB27 Hanger 45 Degree, Spring-loaded (requires two additional inches of overhang for tractors). | 258 | -2 |
| 0672080 | O | Hogebuilt 27" SS Quarter Fender Tube Mount | 364 | 50 |

Price Level: April 1, 2021

Deal: 389 Tractor

Printed On: 7/21/2021 4:25:30 AM

Date: July 19, 2021

Quote Number: QUO-847809-C7L8T7



| Sales Code | Std/ Opt | Description | \$ List | Weight |
|-----------------------------------|----------|--|---------|--------|
| | | White Peterbilt Top Flap, Single Post Mount. Hogebuilt 27" Stainless Steel quarter fenders, are composed of premium 304 stainless steel with a mirror finish that provides a lasting image. | | |
| 0674100 | O | Locate Quarter Fender Ahead of Pusher Axle Requires Quarter Fender Option | 0 | 0 |
| 0854110 | O | JOST JSK37 Fifth Wheel Top Plate JOST's fifth wheels are the simplest and safest design in the market, with only four moving parts. JOST's simple mechanism allows infinite adjustments versus competitors' notched adjustments. | 2,001 | 240 |
| 0870000 | | Rear Or Fixd Setting Centerline Bogie | 0 | 0 |
| 0890090 | O | LH Fifth Wheel Release | 0 | 0 |
| 0890550 | O | 7.6in - 8in Fifth Wheel Height | 0 | 95 |
| 0890665 | O | Jost Lightweight Inboard Slider | 0 | 0 |
| 0891260 | O | 36" Air Slide | 268 | 246 |
| 0960020 | O | Frame Mounted Deckplate And Access Pkg,Both Sides | 568 | 68 |
| Front Axle & Equipment | | | | |
| 1012300 | O | Meritor MFS14 14,600 lb, 3.5 in. Drop Axle is designed for applications with a gross axle weight rating (GAWR) of 14,600 pounds. Axle includes special low-friction bushings, double draw keys and integral thrust bearing and seal design for durability, low maintenance and ease of service. Combination of Meritor Easy Steer king pin bushings, computer-designed and optimized I-beam construction and stiff axle assembly delivering a tight turning radius, superior vehicle control and longer tire life. | 576 | 29 |
| 1112150 | O | Taper Leaf Springs, Shocks 14,600 lb Hendrickson Taper Leaf Springs, shocks 14,600 lb. | 293 | 57 |
| 1233050 | O | Power Steering TRW TAS85 TRW TA85 Power Steering for use with 14,600 lb. axle ratings. Glidekote splines on steering shaft extend service life of components. | 372 | 7 |
| 1250180 | S | Power Steering Reservoir Frame Mounted The power steering reservoir is a steering system that eases drivability by applying hydraulic pressure to the steering gear. | 0 | 0 |
| 1354840 | O | PHP10 Iron PreSet PLUS Hubs PHP10 iron PreSet PLUS hubs have a fully integrated spindle nut design, an optimized wheel spacer, magnetic fill plug on drive and trailer hubs for inspection of metal particles in lubricant, with a long life oil seal and bearings are pre-adjusted. Use with Front Axle. | -844 | -113 |
| 1380070 | O | Greasable Front Spring Pins | 78 | 0 |
| 1380360 | O | Bendix Air Cam Front HP Drum Brakes 16.5x6 Complies with reduced stopping distance regulations. For use with 13,201 - 18,000 lb steer axles in combination with 40,001 to 52,000 lb drive axles, or 20,001-23,000 lift axles. Includes high performance | 527 | -20 |

Price Level: April 1, 2021

Deal: 389 Tractor

Printed On: 7/21/2021 4:25:30 AM

Date: July 19, 2021

Quote Number: QUO-847809-C7L8T7



| Sales Code | Std/ Opt | Description | \$ List | Weight |
|----------------------------------|----------|--|---------|--------|
| | | drum brakes, automatic slack adjusters, outboard mounted brake drums. | | |
| 1380470 | O | Meritor Wide Track IPO Standard, Front Axle Meritor wide track front axle offers greater turning radius and ease of service. MFS+ 3.5" Drop / MFS 3.74" Drop. 71in KPI IPO 69in with MFS and MFS+ axles. | 0 | 15 |
| 1390620 | | 60mm Front Spring Spacer Blocks | 0 | 0 |
| 1391410 | O | Gusseted Cam Brackets, Steer Axle | 27 | 0 |
| 1392970 | O | Heavy Duty Cam Bushings, Steer Axle | 30 | 0 |
| Rear Axle & Equipment | | | | |
| 1526120 | O | Meritor RT46-160 46,000 lb Interaxle diff lock air rocker occupies space of one gauge. Laser factory axle alignment to improve handling & reduce tire wear. Magnetic rear axle oil drain plug captures & holds any metal fragments in drive axle lube to extend service life. Parking brakes on all drive axles for optimal performance. Cognis EMGARD FE 75W-90 synthetic axle lube provides over 1% fuel economy improvement. Reduces wear & extends maintenance intervals, resulting in increased uptime. Provides improved fluid flow to protect components in extreme cold conditions & withstand the stress from high temperatures, extending component life. If code 1526120 (RT46-160) is ordered with 1680460 (Heavy Wall), you will get the 16 mm wall, but not the improved carrier that is in 1526130 code (RT46-160E) that also has a 16 mm wall. This could affect Heavy Haul service warranty length in Canada per Meritor. | 1,810 | 634 |
| 1604196 | O | Hendrickson EXS20 Self-Str Pusher 20K Lb, Includes (1) Air Tank | 13,621 | 1,672 |
| 1607154 | O | 54in Pusher Axle Spacing From Centerline of Forward Drive Axle | 0 | 0 |
| 1615170 | O | PHP10 Aluminum PreSet PLUS Hubs, Cast Drums With 13.5K or 20K Self-Steering Pusher Axles | 0 | 0 |
| 1616300 | O | PHP10 Iron PreSet PLUS Hubs | -63 | 0 |
| 1680390 | S | Bendix ESP Electronic Stability Program With ATC Tractor service only. The Bendix ESP system is designed to continuously monitor a variety of vehicle parameters and sensors to determine if the vehicle is reaching a critical stability threshold. If such a situation develops, the system will quickly and automatically intervene to assist the driver by selectively applying tractor and trailer brakes, and de-throttling the engine. | 0 | 0 |
| 1680450 | O | Rear Brake Camshaft Reinforcement Rear brake camshaft reinforcement helps guard against wear and corrosion. | 124 | 9 |
| 1680470 | O | Lube Pump, Drive Axle(s) Used to circulate oil within the axle housing. Recommended for use on 46,000 or greater axles used in refuse or severe service applications. | 502 | 36 |
| 1680490 | O | Gusseted Cam Brackets, Drive Axle(s) | 70 | 2 |

Price Level: April 1, 2021

Deal: 389 Tractor

Printed On: 7/21/2021 4:25:30 AM

Date: July 19, 2021

Quote Number: QUO-847809-C7L8T7



| Sales Code | Std/ Opt | Description | \$ List | Weight |
|------------|----------|---|---------|--------|
| 1682710 | S | Anti-Lock Braking System (ABS) 6S6M ABS-6. Includes air braking system. | 0 | 0 |
| 1684200 | S | Synthetic Axle Lubricant All Axles Peterbilt heavy duty models include Fuel Efficient Cognis EMGARD FE75W-90 which provides customers performance advantages over current synthetic lubricants with reduced gear wear and extended maintenance intervals, resulting in increased uptime. In addition, the lubricant provides improved fluid flow to protect gears in extreme cold conditions and withstand the stress from high temperatures, extending component life. | 0 | 0 |
| 1685090 | O | Lift Axle Regulator(s) Mounted LH Of Driver Seat Switches & gauges in dash | 111 | 2 |
| 1687020 | O | Bendix Air Cam Rear Drum Brakes 16.5x8.6 Bendix Air Cam Rear Drum Brakes to fit all heavy haul, construction, refuse and highway truck and tractor applications. Includes Automatic Slack Adjusters & Outboard Mounted Brake Drums. Refer to TSB 11-57 for more information. | 293 | 0 |
| 1703910 | O | Ratio 3.91 Rear Axle | 0 | 0 |
| 1821640 | O | Peterbilt Air Trac 46,000 lbs, 54in Axle Spacing Light Weight | 1,675 | 291 |
| 1922260 | O | Dash Mtd Dump Switch with Indicator Light Dash mounted dump switch with indicator light for suspension. | 47 | 2 |

Engine & Equipment

| | | | | |
|---------|---|--|--------|-----|
| 2059922 | O | X15 565@1900 GOV@1900 1850@1000 Performance Series (2021 Emissions) N21350 C121 64....Maximum Accelerator Vehicle N21370 C128 64....Maximum Cruise Control Speed N21460 C132 1400..PTO Maximum Engine Speed N21520 C133 5.....Idle Shutdown Timer N21610 C188 39....Idle Shutdown Cold Ambient A N21620 C189 60....Idle Shutdown Intermediate A N21630 C190 80....Idle Shutdown Hot Ambient Ai N21550 C206 35....Idle Shutdown Percent Engine N21340 C209 120...Maximum Vehicle Speed N21510 C225 NO....Idle Shutdown with Parking B N21450 C231 NO....Gear Down Protection N21570 C233 NO....Idle Shutdown Manual Overrid N21440 C234 NO....Engine Protection Shutdown N21480 C238 NO....Cruise Control and Engine Br N21470 C239 NO....Cruise Control Auto-Resume N21430 C333 0.....Driver Initiated OverrideMax N21410 C334 0.....Driver Initiated Override Ma N21590 C382 YES...Idle Shutdown Hot Ambient Au N21500 C395 3.....Green House Gas Automatic En N21530 C396 NO....Idle Shutdown Warning Period N21540 C397 60....Idle Shutdown Warning Period N21320 C399 120...Green House Gas Vehicle Spee N21400 C400 252...Driver Initiated Override Re | 12,000 | 465 |
|---------|---|--|--------|-----|

Price Level: April 1, 2021

Deal: 389 Tractor

Printed On: 7/21/2021 4:25:30 AM

Date: July 19, 2021

Quote Number: QUO-847809-C7L8T7



| Sales Code | Std/ Opt | Description | \$ List | Weight |
|------------|----------|--|---------|--------|
| | | N21420 C401 10....Green House Gas Vehicle Spee | | |
| | | N21330 C402 0.....Green House Gas Vehicle Spee | | |
| 2091130 | S | VMUX Electronics Architecture | 0 | 0 |
| 2091305 | S | Engine Idle Shutdown Timer Enabled | 0 | 0 |
| 2091638 | | Effective VSL Setting 65.0 MPH or Greater (USA) | 0 | 0 |
| 2092015 | O | Typical Operating Speed 70 MPH | 0 | 0 |
| 2092032 | O | Powertrain Optimized for Performance Best analysis for vehicles used in vocational applications or with heavy GCWRs. | 0 | 0 |
| 2120160 | O | Cummins TRV For DAVCO Only For Fuel Filter, X15 | 48 | 0 |
| 2140200 | S | CARB Engine Idling Compliance PACCAR PX-7, PX-9 and MX, Cummins X15 and ISX diesel engines will include the required factory installed serialized sticker on the drivers door to identify them as meeting the NOx idling standard. | 0 | 0 |
| 2140410 | S | Engine Brake Controls Located on RH Column | 0 | 0 |
| 2513060 | S | PACCAR 160 Amp Alternator, Brushed PACCAR 160 AMP alternator, brushed producing 160 Amps at road speed and 100 Amps at idle. | 0 | 0 |
| 2521090 | S | Immersion Type Block Heater 110-120V Standard location for 2.1M and 1.9M models is left-hand under cab, Model 520 is in bumper, and for Model 220 it is at the driver step. Plug includes a weather-proof cover that protects the receptacle. This pre-heater keeps the coolant in the engine block from freezing when the engine is not running. | 0 | 0 |
| 2522090 | O | PACCAR Premium Starter - X15 Engines Only PACCAR Premium 12 volt. Better cranking power, lower current draw and improved warranty to 5-yr/500K miles. | 405 | 0 |
| 2538040 | S | 3 PACCAR Premium 12V Dual Purpose Batt 2190 CCA Threaded stud type terminal. Stranded copper battery cables are double aught (00) or larger to reduce resistance. | 0 | 0 |
| 2539715 | O | Kissling Battery Disconnect Switch Terminals Mounted Inside Battery Box | 433 | 0 |
| 2621000 | O | 2-Speed Fan Clutch For Frequent Start/Stops A 2-speed fan clutch is ideal for vocational applications where the fan clutch engagement time exceeds 10% of the engine run time. When the fan clutch is disengaged, the fan still rotates at 15-25% of the engine RPM. This fan rotation provides crucial airflow to the engine and draws virtually no horsepower. | 345 | 0 |
| 2723220 | O | Naturally Aspirated 18.7 CFM Air Compressor X15 Only | 0 | 17 |
| 2812170 | O | Intebrate (Furnished on Engine) Features a dedicated cam lobe design for optimum power and three-stage engine brake operation. | 0 | 0 |

Price Level: April 1, 2021

Deal: 389 Tractor

Printed On: 7/21/2021 4:25:30 AM

Date: July 19, 2021

Quote Number: QUO-847809-C7L8T7



| Sales Code | Std/ Opt | Description | \$ List | Weight |
|-------------------------------------|----------|---|---------|--------|
| 2921130 | O | DAVCO 382 Fuel/Water Separator The Fuel Pro 382 is a combination of diesel fuel filtration and water separator that is recommended for heavy-duty diesel engines with flow rates up to 180 gallon/hour. | 601 | 0 |
| 2921310 | O | No Electric Heat Option for Fuel Filter | 0 | 0 |
| 3010400 | O | Engine Protection Shutdown w/ Label Includes oil pressure, oil temperature, coolant temperature, and intake manifold temperature. | 6 | 0 |
| 3114270 | S | High Efficiency Cooling System Cooling module is a combination of steel and aluminum components, with aluminum connections to maximize performance and cooling capability. Silicone radiator & heater hoses enhance value, durability, & reliability. Constant tension band clamps reduce leaks. Chevron Delo Extended Life Coolant (NOAT) extends maintenance intervals reducing maintenance costs. Anti-freeze effective to -30 degrees F helps protect the engine. Low coolant level sensor warns of low coolant condition to prevent engine damage. Radiator Size by Model: 579/367 FEPTO 1325 sq in, 567/365/367: 1440 sq in, 365 FEPTO: 1184 sq in, 389/367 HH: 1669 sq in, 348: 1000 sq in, 520: 1242 sq in. | 0 | 0 |
| 3211040 | O | (2) 15" Premium SS Air Cleaners, Cowl Mtd SS Cap | 1,906 | 68 |
| 3365320 | O | Exhaust Dual Side of Cab DPF/SCR right-hand under cab. | 2,493 | 146 |
| 3381770 | O | Curved Tip Standpipe(s) | 51 | 1 |
| 3381790 | O | Chrome Finish Over Elbows for Dual Exhaust Requires DPF tool box right-hand under cab, and battery box left-hand under cab. | 489 | 13 |
| 3387500 | O | 48" Ht, 5" Dia Chrome, Clear Coat Standpipe(s) | 165 | 8 |
| Transmission & Equipment | | | | |
| 4024130 | O | Eaton FO18E313A-MHP 13-Speed Ultrashift Plus Multi-Purpose High Performance. Includes oil-to-water cooler. Features two-pedal operation for driver convenience. A Hill Start Aid (HSA) feature is included to prevent roll back or roll forward while launching on grades by employing the trucks foundation brakes. Synthetic lubricant to reduce friction, improve efficiency, and extend component life. Magnetic transmission oil drain plug captures and holds any metal fragments in transmission oil to extend service life. Torque limiting clutch brake. Forward ratios: 1st-12.29, 2nd-8.51, 11th-1.00, 12th-0.86, 13th-0.73. Reverse ratios: R1-15.06, R2-12.85, R3-4.03. | 7,751 | 145 |
| 4210280 | O | 1810 HD Driveline, 2 Midship Bearings 4.5in x .180 wall tubing | 1,578 | 215 |
| 4216590 | O | 1710 Driveline Interaxle For tandem rear axles | 288 | 0 |
| 4240540 | O | Eaton Transmission Oil Cooler, Oil-to-Water For use with 1450 torque Fuller transmission, except 18-speed Fuller transmission | 839 | 13 |

Price Level: April 1, 2021

Deal: 389 Tractor

Printed On: 7/21/2021 4:25:30 AM

Date: July 19, 2021

Quote Number: QUO-847809-C7L8T7



| Sales Code | Std/ Opt | Description | \$ List | Weight |
|------------------------------------|-----------------|--|----------------|---------------|
| 4252610 | O | Column Mounted Shifter RH Side | 451 | 0 |
| Air & Trailer Equipment | | | | |
| 4510190 | S | Bendix AD-HF Air Dryer, Heater Bendix AD-HF air filters protects the life of your engine system and components. Proven PuraGuard oil coalescing technonlgy in the the air dryer catridge. This oil coalescing filter ensures the removal of oil and oil aerosols before they can contaminate the moisture removing desiccant. | 0 | -8 |
| 4540420 | S | Nylon Chassis Hose | 0 | 0 |
| 4543320 | S | Steel Painted Air Tanks All air tanks are steel with painted finish except when Code 4543330 Polish Aluminum Air Tanks is also selected (then exposed air tanks outside the frame rails will be polished aluminum). Peterbilt will determine the optimal size and location of required air tanks. Narratives requesting a specific air tank size or location will not be accepted for factory installation. See ECAT to determine number or location of air tanks installed. | 0 | 0 |
| 4543390 | O | High Mount Air Tanks BOC/BOS Where Possible Subject to frame review | 0 | 0 |
| 4610920 | S | Self-Returning Brake Hand Valve Dash mounted controls | 0 | 0 |
| 4611440 | O | Hose Tenna Mounted On LH Rail | 47 | 0 |
| 4614810 | S | AE Connections BOC/BOS, Hose Tenna | 0 | 0 |
| 4614850 | O | 12' AE Lines Straight, (2) 7-Way Plugs | 260 | 8 |
| 4614870 | O | AE Connections 41-54" BOC/BOS | 0 | 0 |
| Tires & Wheels | | | | |
| 5056540 | O | FF: MN 20ply 315/80R22.5 X Line Energy Z Efficiency Rating: Optimal The MICHELIN X LINE ENERGY Z tire is a line haul steer tire built for high miles and better rolling resistance. Diameter= 42.3 inches; SLR= 19.6 inches | 743 | 44 |
| 5156120 | O | RR: MN 16ply 11R22.5 X Multi D Efficiency Rating: Poor Diameter= 41.4 inches; SLR= 19.4 inches | 2,276 | 112 |
| 5190008 | S | Code-rear Tire Qty 08 | 0 | 0 |
| 5220520 | O | FF: Alcoa 89U637 22.5 X 9.00 High Polish Aluminum, Ultra ONE technology that saves more than 50 lbs. versus a comparable steel wheel. Built for refuse, logging, mining and other | 478 | -36 |



| Sales Code | Std/ Opt | Description | \$ List | Weight |
|-------------------|----------|--|---------|--------|
| | | heavy haul applications that demand a tough wheel. Each wheel offers a 10,000 lbs. load rating. | | |
| 5320710 | O | RR: Alcoa 882677 22.5X8.25 High Polish Aluminum. High polish finish on both sides as applicable. Finish options for heavy-duty trucks, 2.5 lbs. weight savings, new hub bore with less metal to metal contact to hinder corrosion with a maintained half dual space and load rating. | 1,336 | -200 |
| 5390008 | S | Code-rear Rim Qty 08 | 0 | 0 |
| 5407640 | O | FF: Mirror Polish Wheels, Outer Surface Single/tandem steer. Mirror Polish outer surface of outer wheel. Without chrome wheel nuts. | 73 | 0 |
| 5407660 | O | RR: Mirror Polish Wheels, Outer Surface, Tandem Drive Mirror polish outer surface of outer wheels (4). Without chrome wheel nuts. | 565 | 0 |
| 5407700 | O | PR: Mirror Polish Wheels, Outer Surface All pusher axles. Mirror polish outer surface of outer wheel. | 283 | 0 |
| 5409320 | O | Wheel Guards, Tandem Axle Wheel guards provide a protective barrier to maintain the integrity between the brake drums and wheels to ensure the maximum life for your polished wheels. | 31 | 0 |
| 5455897 | O | PR: (2) MN 20ply 315/80R22.5 XZUS2 All-position, wide base single designed for significant weight and fuel savings in urban regional applications. For use with single 20,000 lb self-steering pusher axle. Diameter= 43.3 inches; SLR= 20.0 inches | 2,053 | 326 |
| 5482052 | O | PR: (2) Alcoa 89U637 22.5X9.00 High Polish Aluminum, (1) self-steering pusher axle. Ultra ONE technology. | 770 | 98 |
| Fuel Tanks | | | | |
| 5554190 | O | 26" Aluminum 100 Gallon Fuel Tank LH U/C Includes steps for cab access. Paddle handle filler cap with threadless filler neck. Top draw fuel plumbing reduces chance of introducing air into the fuel system during low fuel level conditions due to the central placement of fuel pickup tube. Wire braid fuel lines increase durability & reduce potential for leaks. | 574 | 22 |
| 5602100 | O | Location LH U/C 100 Gallon | 0 | 0 |
| 5650810 | O | Polish (1) Aluminum Fuel Tank | 234 | 0 |
| 5652830 | O | Polish All Fuel / Hydraulic Tank Straps Does not apply to rectangular DEF tank straps | 83 | 0 |
| 5652840 | O | Locking Fuel Tank Cap(s) | 30 | 0 |
| 5652890 | S | DEF Tank Mounted LH BOC Models 220 and 520 mounted left hand back-of-cab. | 0 | 0 |
| 5652990 | O | DEF To Fuel Ratio 2:1 Or Greater | 0 | 0 |



| Sales Code | Std/ Opt | Description | \$ List | Weight |
|---------------------------------|-----------------|--|----------------|---------------|
| 5653000 | O | Polished Stainless Steel Cover For DEF Tank | 199 | 0 |
| 5655029 | O | DEF Tank Medium, 24 Gal | 93 | 22 |
| 5760010 | O | RH Tank None Furnished | -540 | -86 |
| Battery Box & Bumper | | | | |
| 6010780 | O | Aluminum Space Saver Battery Box RH BOC Battery access from side | 44 | -20 |
| 6030540 | O | Polish Battery/Tool Box(s), Aftertreatment Cab Entry complete | 325 | 0 |
| 6034620 | O | Heavy Duty Battery Box Step Reinforcement | 61 | 2 |
| 6040550 | S | Aftertreatment Aluminum Non-Slip Cab Entry Aftertreatment right-hand under cab step. DPF/SCR for diesel engines, catalyst for natural gas engines. On Models 579 specifying chassis fairings, the box is aerodynamic. | 0 | 0 |
| 6121090 | S | Steel Bumper Deep Tapered Chromed Two tow points | 0 | 0 |
| Cab & Equipment | | | | |
| 6510130 | O | Alum Cab 131in BBC Alum Hood SFFA fenders w/polished crown, spring tilt assist. Proprietary anti-blow-down locking mechanism that keeps hood open during servicing & prevents unintentional closing. Hood latch each side secures hood to cowl. Proprietary all-alum cab is light weight & durable for long service life. One-piece roof reduces potential for leaks. Two-piece windshield for cost effective windshield replacement. Lap seam construction & aircraft fasteners has greater clamp load than rivets. Bulkhead style doors provide virtually water-tight, rattle-free performance. Extruded alum door frames for strength & durability. Full length, heavy-duty piano-type stainless steel door hinges & pins provide durability. View window in RH door for safety. Electric windshield wipers & washers w/intermittent wiper function. Grab handles mtd on cab LH & RH for cab access. Convex mirror over RH door & below each rear view mirror for improved visibility & safety. | 2,173 | 90 |
| 6540120 | O | Severe Service Cab Package #1 Includes Aluminum side skins, aluminum rear skin, steel windshield mask, steel firewall, and steel front floor sheet on all cabs, and additional reinforcement structure on the back wall of the day cab. | 235 | 48 |
| 6540720 | O | 10" Extension for Ultra Day Cab Add additional 10" to the loadspace dimension-- refer to the horizontal dimension workscreen. | 5,338 | 163 |
| 6700000 | S | No Sleeper Selected | 0 | 0 |
| 6800360 | O | Rubber Fender Lips 2" Wide | 116 | 8 |
| 6911710 | O | National Premium Driver Seat | 391 | 4 |



| Sales Code | Std/ Opt | Description | \$ List | Weight |
|------------|----------|---|---------|--------|
| | | Increased comfort with more foam in critical areas, better lumbar support, improved adjustability and suspension with toggle link design. | | |
| 6921710 | O | National Premium Passenger Seat | 571 | 4 |
| | | Increased comfort with more foam in critical areas, better lumbar support, improved adjustability and suspension with toggle link design. | | |
| 6930580 | O | Drivers Armrests - LH & RH | 95 | 4 |
| 6939400 | S | Air Ride Driver | 0 | 0 |
| 6939420 | S | High Back Driver | 0 | 0 |
| 6939450 | O | Leather Driver | 256 | 0 |
| 6939500 | O | Air Ride Passenger | 387 | 43 |
| 6939520 | S | High Back Passenger | 0 | 0 |
| 6939550 | O | Leather Passenger | 256 | 0 |
| 7000350 | S | Power Door Locks Both Doors | 0 | 0 |
| 7001520 | S | Adjustable Steering Column - Tilt/Telescope | 0 | 0 |
| 7001630 | O | Premium Steering Wheel with Multi Function | 148 | 5 |
| | | Premium Multi-functional Leather Wrapped Steering Wheel with Peterbilt logo over horn button. Includes audio volume, seek, mute and mode button on LH pod with cruise control on/off/cancel, set/resume and accelerate/coast on the right pod. | | |
| 7039070 | O | Prestige Interior - Arctic Gray | 493 | 22 |
| | | Includes innovative charcoal A & B instrument panels and color-matched C & D instrument panels, monochromatic color-coordinated dash with glare-resistant, charcoal soft-touch upper, black bezel on gauges, cigar lighter and ashtray with power port, burlwood insert on contoured doorpads, LH and RH door mounted map pockets with built-in courtesy lights, 18 inch 4-spoke soft-touch steering wheel, soft-touch steering column cover, power lift passenger window, padded vinyl headliner and wall panels, extruded rubber floor covering, (2) inside sunvisors, (2) coat hooks, header-mounted domelight, driver and passenger dome/reading lights, footwell lighting, integrated "dead pedal", (5) inside entry grab handles, cup holder and map bin in dash. | | |
| 7040330 | O | Woodgrain A & B Dash Panels IPO Charcoal | 1,780 | 0 |
| | | Requires Prestige/Mid-Level Interior and Bright Bezel Gauges OR Platinum/Premium Interior. | | |
| 7040370 | O | Rubber Floor IPO Carpet - Cab/Sleeper | 283 | 3 |
| | | 58 inch, 72 inch, 78 inch or 80 inch sleepers only. | | |
| 7210540 | S | Day Cab Rear Window | 0 | 0 |
| | | Day cab rear window flush to back of cab. | | |
| 7230350 | O | 2-Piece Flat Windshield | 33 | 0 |

Price Level: April 1, 2021

Deal: 389 Tractor

Printed On: 7/21/2021 4:25:30 AM

Date: July 19, 2021

Quote Number: QUO-847809-C7L8T7



| Sales Code | Std/ Opt | Description | \$ List | Weight |
|-------------------|-----------------|--|----------------|---------------|
| 7230680 | S | Power Lift Windows - Both Doors For use with ProBilt or Prestige Interior | 0 | 0 |
| 7322010 | S | Combo Fresh Air Heater/Air Conditioner With radiator mounted condenser, dedicated side window defrosters, Bi-Level Heater/Defroster Controls, 54,500 BTU/HR, and silicone heater hoses. | 0 | 0 |
| 7322130 | O | Cup Holder (Floor Mounted) Includes two standard-size drink holders and one extra-large jugholder, coin tray, and clipboard-size storage area. | 97 | 4 |
| 7330700 | S | Peterbilt Comfort Control - Cab | 0 | 0 |
| 7410040 | O | Outside Sunvisor - Stainless Steel Not available with 2.1M high roof sleeper. | 436 | 4 |
| 7560100 | O | Mirrors SSTL Each Side Heated and Motorized with Switch on Door. | 350 | 2 |
| 7560320 | O | Convex 8 Inch SSTL LH/RH Hood with adjustable bent arm for downward visibility. | 219 | 8 |
| 7560850 | S | (2) Convex 8 Inch SSTL Mirrors Center mounted under mirror bracket. If rear view mirrors are heated, the convex mirrors will be heated. Option includes dual door stops. | 0 | 0 |
| 7620630 | O | (2) Air Horns 30" Chrome - Round w/Horn Shields | 546 | 10 |
| 7721050 | O | Satellite Radio Requires USB port and bluetooth for phone and audio. | 227 | 0 |
| 7722120 | O | ConcertClass, AM/FM, Weatherband, 3.5 Aux | 316 | 10 |
| 7725740 | O | Midlevel Speaker Package For Cab (4) Speakers | 205 | 6 |
| 7728030 | O | Radio Mute When In Reverse For automatic or automated transmission | 0 | 0 |
| 7728040 | O | Bluetooth Phone and Audio Requires USB Port | 56 | 0 |
| 7728050 | O | USB Port | 56 | 0 |
| 7740100 | O | Cobra 40 Channel CB Radio w/Integral Speaker Includes illuminated front panel | 251 | 11 |
| 7748520 | O | CB Antenna Mounting, Vertical, Center BOC/BOS | 84 | 1 |
| 7788055 | S | SmartLINQ Remote Diagnostics SmartLINQ is Peterbilts proprietary remote diagnostics service which monitors the engine and aftertreatment for diagnostic codes providing real-time code analysis maximizing vehicle uptime and strengthening the fleets partnership with their dealer. SmartLINQ provides fault coverage for over 800 codes, a customizable email notification for 116 codes plus a web portal to manage your entire fleet included at no additional charge. SmartLINQ is compatible with any telematics system and doesnt require a specific fleet management system. For those whose customers utilize PeopleNet, the pre-wire with remote diagnostics will provide a more integrated solution utilizing the existing | 0 | 0 |

Price Level: April 1, 2021

Deal: 389 Tractor

Printed On: 7/21/2021 4:25:30 AM

Date: July 19, 2021

Quote Number: QUO-847809-C7L8T7



| Sales Code | Std/ Opt | Description | \$ List | Weight |
|------------|----------|---|---------|--------|
| | | SmartLINQ modem. For those whose customers utilize other fleet services products, the existing pre-wire option for the other fleet service devices will continue to be available. Standard on Class 8 engines and available on Models 348, 337, 330 and 325 with a PX-9, PX-7 or Cummins Westport natural gas engine. | | |
| 7788058 | O | 24 Months SmartLINQ Subscription Cummins Engines. | 0 | 0 |
| 7850210 | O | Plug-In Auto Reset Circuit Breaker in place of fuses in junction box. | 109 | 0 |
| 7851040 | O | Removable Bugscreen Behind Grille | 180 | 2 |
| 7851480 | S | Peterbilt Electric Windshield Wipers With Intermittent Feature. | 0 | 0 |
| 7851970 | O | Unibilt Cab Air Suspension Includes dual air bag suspension, leveling valve, and tracking rod. Provides a more ergonomic installation, higher EAU, easier serviceability and fewer parts. | 658 | 25 |
| 7900090 | O | Triangle Reflector Kit, Ship Loose Florescent triangle emergency road flares are designed to meet and exceed all DOT standards. | 18 | 13 |
| 7900270 | O | Fire Extinguisher, Cab Mounted Hazmat approved UL listed/rated ABC | 59 | 8 |
| 7901130 | O | Backup Alarm (107 DB) | 66 | 3 |
| 8011100 | O | Main Transmission Temperature Gauge 52mm Round, backlit. If this option is selected on a truck with VMUX electrical architecture, the gauge will be included in the digital display. | 46 | 0 |
| 8011410 | O | Drive Axle #1 Front Oil Temperature Gauge 52mm round, backlit. Physical gauges must be ordered in pairs and are limited to a total of 6. If this option is selected on a truck with VMUX electrical architecture, the gauge will be included in the digital display. | 125 | 0 |
| 8011470 | O | Engine Oil Temperature Gauge 52mm round, backlit. These physical gauges must be ordered in pairs and are limited to a total of 6. If this option is selected on a truck with VMUX electrical architecture, the gauge will be included in the digital display. | 125 | 0 |
| 8021050 | O | Air Restriction Pressure Gauge 52mm Round, backlit. If this option is selected on a truck with VMUX electrical architecture, the gauge will be included in the digital display. | 190 | 0 |
| 8021810 | S | Brake Application Air Pressure (Tractor) Located in Digital Cluster Display. | 0 | 0 |
| 8021860 | O | Suspension Air Pressure 1 (Load) Located in Digital Cluster Display | 71 | 0 |
| 8022160 | O | Fuel Filter Restriction Gauge 52mm Round, backlit. Physical gauges must be ordered in pairs and are limited to a total of 6. If this option is selected on a truck with VMUX electrical architecture, the gauge will be included in the digital display. | 154 | 0 |
| 8070100 | O | (4) Additional Dash Switches With Wiring Located on dash panel C. Availability subject to dash space. Includes 4" 14 gauge wire with butt splice at rear of each additional switch. | 175 | 3 |

Price Level: April 1, 2021

Deal: 389 Tractor

Printed On: 7/21/2021 4:25:30 AM

Date: July 19, 2021

Quote Number: QUO-847809-C7L8T7



| Sales Code | Std/ Opt | Description | \$ List | Weight |
|-------------------|-----------------|--|----------------|---------------|
| 8070820 | S | Engine Percent Torque Located in Digital Cluster Display | 0 | 0 |
| 8070830 | O | Main Instrumentation Panel Digital Cluster 15" Display includes: Speedometer, Tachometer, Primary Air Pressure, Secondary Air Pressure, Fuel Level, DEF Level, DPF Filter Status, Fuel Economy, Oil Pressure, Coolant Temp, OAT and Voltmeter. | 0 | 0 |
| 8071340 | O | Bright Bezel Gauges 52mm Round Gauges Only- B Panel | 50 | 0 |
| 8071900 | O | Manifold Pressure Gauge 52mm Round, backlit. Physical gauges must be ordered in pairs and are limited to a total of 6. If this option is selected on a truck with VMUX electrical architecture, the gauge will be included in the digital display. | 106 | 0 |
| 8111140 | S | Headlights Projector Module Pod Integral Turn Signals | 0 | 0 |
| 8120980 | S | (5) Marker Lights, Aero LED | 0 | 0 |
| 8131560 | O | (2) Peterbilt Fog Lights Recessed in bumper | 148 | 6 |
| 8132210 | O | (1) 6 in Spotlight, Round Halogen LH (1) 6" spotlight, round halogen left hand side. | 131 | 4 |
| 8132215 | O | (2) LED Strobe Lights Roof Mounted (2) LED strobe lights roof mounted on each side of the cab with stainless steel brackets. LED technology provides continual heavy-duty use in the toughest conditions with a weatherproof and vibration resistant design for external use. Offering four times the brightness in a more compact housing, 4.5" shorter and 3" smaller in diameter. Classified as a Class 1 light incandescent light. | 455 | 10 |
| 8133110 | O | Switch & Wiring F/O Auxiliary Light Under cab/sleeper (15 amp max), includes switch on the dash that will power metri-pack sealed connections at the left-hand / right-hand side of cab at base of the firewall. Bundle panel light harness break outs with firewall harness. | 61 | 2 |
| 8133120 | O | Switch & Wiring F/O Aux Light On Air Cleaners Includes switch on the dash which will power metri-pack sealed connections at the left-hand / right-hand air cleaner outlets | 102 | 2 |
| 8134160 | O | Self-Canceling Turn Signal | 0 | 0 |
| 8140060 | O | LED Oval Stop/Turn/Tail/Backup In tractor taper end of frame crossmember | 27 | -7 |
| 8140490 | O | Additional LED Round Turn Signal Mirror mounted | 165 | 2 |
| 8151130 | O | (2) Load Lights, Flush Mounted Low Inboard Loc A | 114 | 4 |
| 8151140 | O | (2) Load Lights, Flush Mounted Low Outboard Loc B | 114 | 4 |
| Paint | | | | |
| 8500710 | O | Standard Paint Color Selection | -200 | 0 |

Price Level: April 1, 2021

Deal: 389 Tractor

Printed On: 7/21/2021 4:25:30 AM

Date: July 19, 2021

Quote Number: QUO-847809-C7L8T7



| Sales Code | Std/ Opt | Description | \$ List | Weight |
|------------|----------|---|---------|--------|
| 8530770 | S | (1) Color Axalta Two Stage - Cab/Hood Base Coat/Clear Coat N85020 A - L0006EY WHITE N85500 CAB ROOF L0006EY WHITE N85300 FENDER L0006EY WHITE N85200 FRAME L0001EA BLACK N85400 HOOD TOP L0006EY WHITE N85720 SK FAIRINGS L0006EY WHITE | 0 | 0 |

Shipping Destination

Options Not Subject To Discount

| | | | | |
|---------|---|---|---|---|
| 9400090 | S | Peterbilt Class 8 Standard Coverage 1 year/100,000 Miles (160,000 km) | 0 | 0 |
|---------|---|---|---|---|

Miscellaneous

| | | | | |
|---------|---|---|---|---|
| 9409001 | O | Day Cab / Prestige Interior (DM) | 0 | 0 |
| 9409831 | S | 2021 EPA Emissions Engine Warranty Only | 0 | 0 |

Promotions

Order Comments



| | |
|---|-----------|
| Total List Price (W/O Freight & Warranty & Surcharges) | \$275,352 |
| Marketing and Service Support Fee | \$895 |
| Prepaid Freight | \$2,825 |
| Total Surcharge/Options Not Subject To Discount | \$0 |
| Total Weight | 21,210 |

Prices and Specifications Subject to Change Without Notice.

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in CRM.

PRICING DISCLAIMER

While we make every effort to maintain the web site to preserve pricing accuracy, prices are subject to change without notice. Although the information in this price list is presented in good faith and believed to be correct at the time of printing, we make no representations or warranties as to the completeness or accuracy of this information. We reserve the right to change, delete or otherwise modify the pricing information which is represented herein without any prior notice. We carefully check pricing specifications, but occasionally errors can occur, therefore we reserve the right to change such prices without notice. We disclaim all liability for any errors or omissions in the materials. In no event will we be responsible for any damages of any nature whatsoever from the reliance upon information from these materials. Please check your order prebills to confirm your pricing information



Shipping Destinations

Intermediate Destination: none

| Final Destinations | Quantity |
|--------------------|----------|
|--------------------|----------|

389



Peterbilt

389

THE **ICON** OF THE HIGHWAY.

The Model 389 embodies Peterbilt heritage and merges it with a proven design to create a legendary classic. Lightweight components, such as the all-aluminum cab and the industry's only aluminum hood, as well as a variety of lightweight front and rear suspensions, allow for increased load capacity. Aerodynamic enhancements for increased fuel savings all combine to ensure that your investment in the Model 389 pays dividends long after the initial purchase. An optional fuel-efficiency package as well as Peterbilt's exceptional reliability and performance translate into an overall low cost of operation. The Model 389 is available with the fuel-efficient PACCAR MX-13 engine with power ratings up to 510 hp and 1,850 lb.-ft. torque for maximum performance. The Model 389 continues to be an industry leader in quality, styling, performance and enduring value.

For more information on the Model 389, contact your local Peterbilt dealer or visit www.peterbilt.com



The Model 389 features conventional styling, plus a selection of components and options for efficiency and performance. Peterbilt's lightweight and durable hood is the industry's only all-aluminum hood with a distinctive punched oval grille and one-piece aluminum crown.



CAB INTERIOR

The Model 389 features an ergonomic dash that puts everything within reach of the driver and improves visibility. The charcoal finish reduces glare and resists scratches and fading.



SLEEPER INTERIOR

Peterbilt's unique sleepers are built to deliver unparalleled fit and finish, quality and comfort. They feature plenty of storage, shelving, ample overhead lighting and a powerful HVAC. Available in 44", 58", 72" & 78" configurations.



VISIBILITY

Halogen projectors, aluminum headlamps and long-life LED directional signals are protected with an impact-resistant lens and contribute to overall exceptional visibility.



DURABILITY

A lightweight all-aluminum cab is huck-bolted with lap seam construction and bulkhead style doors for toughness and corrosion resistance. The Model 389 cab offers years of virtually watertight, rattle-free performance.



PACCAR
FINANCIAL

PACLEASE & PACCAR FINANCIAL PLANS TAILORED TO YOUR NEEDS.



PETE-9888 REV. 3/17 • PRINTED IN U.S.A. • FOR MORE INFORMATION, CALL 1-800-552-0024 • BUCKLE-UP FOR SAFETY



CLASS PAYS



FEATURES & BENEFITS: MODEL 389

Model 389 Standard Features

(Base Model Option Code 0003891)



FRAME

- Steel rails with gussets to maximize RBM.
- Huck bobtail fasteners provide a consistent and durable clamping force up to 600% greater than bolted frames. Tamper resistant round head and collar offers improved paint adhesion and corrosion resistance. Swage indicating features on collar allows for visual inspection of clamped joint.
- 3-piece C-Channel cross member with cast gussets.
- Rubber-lined clamps along frame rail to protect air & electric lines routed in frame.
- Chassis hose and wiring bundles conveniently routed through gussets provides protection for lines.
- Front wheel mud flaps reduce road spray, help maintain a cleaner truck and better visibility.
- Two frame mounted tow pins.

STEER AXLE

- Set forward front axle configuration uses longer springs to deliver a smooth and comfortable ride.
- Factory front axle alignment to improve handling and reduce tire wear.
- Zerk fittings on tie rod ends, kingpins, and draglink ball joints for ease of maintenance and help extend service life of components.
- Greaseless spring pins reduce maintenance and improve ride quality.
- Standard oil seals for long lasting leak protection.
- Cognis EMGARD® Synthetic Axle Lube reduces wear and extends maintenance intervals, resulting in increased uptime. Provides improved fluid flow to protect components in extreme cold conditions and withstand the stress from high temperatures, extending component life.
- Glidekote splines on steering shaft extend service life of components.

DRIVE AXLE

- Laser factory axle alignment (accurate to .030 of an inch) to improve handling and reduce tire wear.
- Magnetic rear axle oil drain plug captures and holds any metal fragments in drive axle lube to extend service life.
- Parking brakes on all drive axles for optimal performance.
- Cognis EMGARD® Synthetic Axle Lube reduces wear and extends maintenance intervals, resulting in increased uptime. Provides improved fluid flow to protect components in extreme cold conditions and withstand the stress from high temperatures, extending component life.

ENGINES & RELATED SYSTEMS

- Selective Catalytic Reduction (SCR) System provides the most fuel efficient, reliable and cost effective solution to the 2010 EPA regulations. The SCR system consists of several new standard components on the truck - a dosing pump, a DEF tank, an injector and the SCR ammonia catalyst.
- Chevron Delo 400 LE SAE 10W30 engine oil is specially formulated for new low emissions engines.
- Magnetic engine oil drain plug captures and holds any metal fragments in engine oil to extend service life.
- Silicone radiator and heater hoses enhance value, durability and reliability.
- ClimaTech extended life coolant extends maintenance intervals which reduces maintenance costs.
- Low coolant level sensor warns of low coolant condition to prevent engine damage.
- Constant tension and torque band clamps reduce leaks.
- Stainless steel hardline manifold reduces coolant hoses in the engine compartment to improve durability and appearance.
- Thermal fuse in the air conditioning compressor clutch allows the pulley to free spin in the event of a compressor failure, thus reducing belt wear and vehicle downtime.
- Weather pack silicone sealed electrical chassis connectors enhance value, durability and reliability.
- 12 Volt System with circuit protection for reliable easy maintenance and service.
- 1669 sq. in. frontal area cooling system provides a large surface area for heat exchange.
- Composite fan is light-weight but strong and corrosion resistant.
- Full fan shroud, ring and rubber boot improves under hood airflow and provides a robust fan-to-radiator shroud interface for greater cooling capacity.
- Anti-freeze effective to -30 degrees F helps protect the engine.
- Maintenance free 12V batteries provide reliable power for starting and accessories.
- Stranded copper battery cables are double aught (00) or larger to reduce resistance.
- Stainless steel air cleaner straps, brackets and fasteners provide a durable bright finish.
- Molded rubber air intake connections with lined stainless steel clamps seal to prevent contaminants in air intake.
- Washer bottle with 1.3 gallon capacity extends maintenance intervals to refill.

- Stainless steel grille with a distinctive punched oval grille pattern provides a durable bright finish
- Stainless steel flex exhaust tubing & clamps provide durability.
- Optimized exhaust routing to simplify the truck order process and provide optimal performance.
- 5" diameter chrome plated steel standpipe cools exhaust for safety.

TRANSMISSION & RELATED SYSTEMS

- Synthetic lubricant to reduce friction, improve efficiency and extend component life.
- Magnetic transmission oil drain plug captures and holds any metal fragments in transmission oil to extend service life.
- Coated driveshaft splines extends service life.
- Configured Clutch to simplify the truck order process and provide optimal performance.
- Torque limiting clutch brake

AIR SYSTEM

- Engine mounted air compressor with remote mounted air system filter dryer to reduce moisture in air system components.
- Teflon-lined, stainless steel braided compressor discharge hose provides long service life in high operating temperatures.
- Schrader valve for charging of air system from external source.

FUEL TANKS

- Aluminum fuel tanks with heavy-duty aluminum brackets and stainless steel straps.
- Under cab fuel tanks include steps for cab access.
- Single fuel tank will receive a single draw / single return fuel system.
- Dual fuel tanks will receive dual draw / dual return fuel system equalizes fuel load.
- Top draw fuel plumbing reduces chance of introducing air into the fuel system during low fuel level conditions due to the central placement of the fuel pickup tube.
- Optimized filler neck location on under cab fuel tanks optimizes access and safety.
- Paddle handle filler cap with threadless filler neck
- Wire braid fuel lines increase durability and reduce potential for leaks.

ELECTRICAL SYSTEM

- Multiplex electrical design utilizing the industry standard J1939 data bus that sends multiple signals over a single wire instead of having an individual wire for each function. This allows each component (engine, transmission and instrumentation) to communicate to each other. This design improves reliability and offers increased functionality.
- Proprietary Electronic Service Analyst (ESA) allows dealer to monitor the electrical system, isolate sensors and gauges, and keep a log of service history.
- Automatically resetting circuit breakers in selected circuits
- Braided chassis harness cover provides durability.
- Convuluted tube covering on harnesses protects from chaffing.

- Wires numbered every 4 inches or less for ease of serviceability.
- Power distribution center in cab is centrally located in a protected environment for easy access.

CAB / HOOD

- Proprietary all-aluminum cab is light weight and durable for long service life.
- Light-weight all-aluminum hood with 131" BBC and one-piece grille crown improves air flow.
- Removable aluminum fenders with polished aluminum reinforcements to expedite repairs and minimize downtime.
- Fender liners with pre-molded features to facilitate quicker installation of mirrors and protect fenders from rock damage.
- Spring assisted 90 degree hood opening for serviceability.
- Proprietary anti-blow-down locking mechanism that keeps the hood open during servicing and prevents unintentional closing.
- Hood latch on each side secures the hood to the cowl.
- Aerodynamic hood ornament
- Three point rubber cab mounting
- One piece roof reduces potential for leaks.
- Lap seam construction and aircraft fasteners has greater clamp load than rivets.
- Bulkhead style doors provide virtually water-tight, rattle-free performance.
- Extruded aluminum door frames for strength and durability.
- Full length, heavy-duty piano-type stainless steel door hinges and pins provide durability.
- View window in RH door for safety.
- Electric windshield wipers and washers with intermittent wiper function
- Grab handles mounted on cab LH & RH for cab access.
- Convex mirror over RH door and below each rear view mirror for improved visibility and safety.

CAB INTERIOR

| Standard Features | Interior Level | | |
|---|----------------|----------|---------|
| | Platinum | Prestige | ProBilt |
| Upper and lower dash panels in a dark charcoal color that is not only easier to clean and shows less scratches and scuffs, but also improves driver visibility due to less glare. | | | • |
| Top-of-dash panels in a dark charcoal grey that reduces driver glare, is less likely to scratch and scuff and is easier to clean, while the lower dash panels are perfectly matched to your cab's interior color. | | • | |
| Top-of-dash panels in a dark charcoal grey that reduces driver glare, is scratch resistant and is less likely to fade or show dirt with elegant woodgrain on the lower dash panels. | • | | |

| | | | |
|---|---|---|---|
| Monochromatic dash with soft touch upper | | | • |
| Two-toned color coordinated dash with soft touch upper | • | • | |
| Black bezels on gauges | • | • | |
| Bright bezels on gauges | • | | |
| Contoured door pads featuring integrated ergonomic armrests for driver comfort | • | • | • |
| Satin burlwood insert on contoured door pads | | • | |
| High gloss burlwood insert on contoured door pads with vinyl inserts | • | | |
| LH & RH door mounted map pockets with built-in courtesy lights | • | • | |
| Power lift passenger window controls integrated into the door panel are within easy reach of the driver for safe and convenient operation. | | • | • |
| Power windows and door locks on both doors integrated into the door panel are within easy reach of the driver for safe and convenient operation. | • | | |
| Padded vinyl headliner is easy to clean. | | • | • |
| Padded vinyl headliner with premium insert | • | | |
| Two inside sunvisors with map straps provide driver and passenger comfort and convenience. | | • | • |
| Two inside sunvisors with integral vanity mirrors provide driver and passenger comfort and convenience. | • | | |
| Two coat hooks for driver and passenger convenience with daycabs only. | • | • | • |
| Integrated cup holder in dash | • | • | • |
| Cast rubber flooring with integral sound barrier. | • | • | |
| Fully carpeted floor covering with integral sound barrier. | • | | |
| Heater / air conditioner with dedicated side window defroster | • | • | • |
| 18" soft touch steering wheel | • | • | • |
| Adjustable steering column | • | | |
| Key start ignition for an automotive feel. | • | • | • |
| Ignition and doors keyed alike for driver convenience. | • | • | • |
| Single electric horn | • | • | • |
| Cigar lighter and ashtray with power port | • | • | • |
| Integrated "dead pedal" for driver comfort. | • | • | • |
| Five ergonomically positioned entry / egress grab handles | • | • | • |
| Proprietary non-slip threshold plate accented with a chrome inset and Peterbilt Red Oval adds a touch of Peterbilt class to safety and convenience. | • | • | • |
| Header mounted dome light | • | • | • |
| Driver and passenger dome and reading lights | • | • | • |
| Retractable three-point seatbelts on driver and passenger seats | • | • | • |
| Footwell lighting | • | • | • |
| 12-volt power outlet in dash | • | | |
| Peterbilt in-dash Navigation System | • | | |

LIGHTS

- State-of-the-art halogen projector module pod headlights increase visibility.

- 'Headlight on Warning' when headlights are active with door open and ignition off. The high beam headlamp icon flashes and sounds an audible alarm.
- Headlights turn on automatically when windshield wiper blades are activated.
- Polished cast aluminum headlight pod housing with LED side-turn indicators and an impact resistant lens matches durability with style.
- Rear combination stop / turn / tail lights

DASH & INSTRUMENTATION

- Driver Information Display that allows the driver to view diagnostic information and monitor truck system behavior. Information such as fuel economy, optimum engine speed and engine and transmission system management provides driver feedback and improves operating performance.
- Dash features an "in-mold" color process that imbeds the color into the material making the color permanent and eliminating peeling and fading.
- Electronic speedometer with trip odometer
- LED backlit gauges to prevent eye fatigue.
- Electronic tachometer with hour meter and outside air temperature display
- Voltmeter
- Primary and secondary air pressure gauges
- Engine oil pressure gauge
- Engine coolant temperature gauge
- Fuel level gauge with low fuel warning.
- Standard warning lights with audible alarm for high coolant temperature, low oil pressure and low air pressure
- Warning indicators for high beam, parking brake, turn signals, low fuel, road surface ice potential
- Seat belt reminder
- Cruise control for driver convenience.
- Head lights, marker lights, hazard lights, regeneration (DPF) and dimmer switches.
- Rocker switches with long-life LED indicators that are easy to reach for driver safety and convenience.
- Multi-function turn stalk with flash-to-pass feature intermittent windshield wiper and headlamp beam control.

PAINT

- DuPont Imron Elite two-stage non-metallic paint, one color cab / hood

389
Pride & Class





THE **PRIDE & CLASS** OF THE HIGHWAY

Jaw dropping! Pulse pounding! Peterbilt's new **Model 389 Pride & Class** package is a stunning display of chrome and sophistication. No one can miss this awe-inspiring truck as it commands the highways. With its eye-popping, head-turning features like the distinct louvered grille and brightly polished accessories, this exceptional truck truly impresses from every angle. Exclusive, chic accents surround the driver in touches of understated elegance and comfort. The Pride & Class package demands the attention of everyone who sees it while its driver instantly becomes the envy of all others. Elevate the driving experience from ordinary to extraordinary with the Model 389 Pride & Class.

For more information on the Model 389 Pride & Class, contact your nearest Peterbilt dealer or visit www.peterbilt.com.



The Pride & Class interior features a dark charcoal top and Blackwood finish trim throughout the cab and sleeper. Exclusive details include black leather seats with red contract stitching, a special steering wheel and a chrome interior handle. A bright logo'd shifter plate and shift lever with a Blackwood finish shifter knob are available with manual transmissions. The distinctive Pride & Class emblem is located on the dash, in the seat headrest and on the shifter plate.



CLASSIC DESIGN

Reminiscent of Peterbilt's traditionally styled products of the 1950's, the Model 389 Pride & Class features a new louvered grille with a highly polished hood crown and spine.



BRIGHT FEATURES

Polished aluminum fenders, a large sunvisor, bumper, and exhaust stacks are impressive and easily identify this model as being in a Class of its own.



DISTINCTIVE STYLING

A stylized, side-hood air intake bezel is a unique design exclusive to the Pride & Class package.



CHROME ACCENTS

Bright rocker panels complement the cowl skirts, battery box, fuel tanks and mud flaps providing sleek accents that are clearly visible from every angle of the truck.



PACCAR
FINANCIAL

PACLEASE & PACCAR FINANCIAL PLANS TAILORED TO YOUR NEEDS.



PETE-9902-US 7/14 • PRINTED IN U.S.A. • FOR MORE INFORMATION, CALL 1-800-552-0024 • BUCKLE-UP FOR SAFETY



CLASS PAYS