



Peterbilt of Richmond (H830)
2800A Deepwater Terminal
Richmond, Virginia 23212

Virginia Sheriffs Association
901 East Byrd St Suite 1301
Richmond, Virginia 23219
United States of America

David Askew
Cell Phone:
Office Phone:
Email: daskew@thepetestore.com

Kaylyn Mitman
Office Phone: 919-459-6471
Email: kmitman@virginiasheriffs.org

Vehicle Summary

| Unit | | Chassis | |
|-------------------------|-----------------|----------------------------|-------|
| Model: | Model 535 | Fr Axle Load (lbs): | 8000 |
| Type: | Full Truck | Rr Axle Load (lbs): | 13500 |
| Description 1: | 535 Chassis | G.C.W. (lbs): | 21500 |
| Description 2: | | | |
| Application | | Road Conditions: | |
| Intended Serv.: | City Delivery | Class A (Highway) | 100 |
| Commodity: | Other Commodity | Class B (Hwy/Mtn) | 0 |
| | | Class C (Off-Hwy) | 0 |
| | | Class D (Off-Road) | 0 |
| Body | | Maximum Grade: | 6 |
| Type: | Van | Wheelbase (in): | 175 |
| Length (ft): | 20 | Overhang (in): | 60 |
| Height (ft): | 13.5 | Fr Axle to BOC (in): | 67.5 |
| Max Laden Weight (lbs): | 1000 | | |
| Trailer | | Cab to Axle (in): | 107.5 |
| No. of Trailer Axles: | 0 | Cab to EOF (in): | 167.5 |
| Type: | | Overall Comb. Length (in): | 275 |
| Length (ft): | 0 | Special Req. | |
| Height (ft): | 0 | | |
| Kingpin Inset (in): | 0 | | |
| Corner Radius (in): | 0 | | |
| Restrictions | | | |
| Length (ft): | 40 | | |
| Width (in): | 102 | | |
| Height (ft): | 13.5 | | |

Approved by: _____

Date: _____

Note: All sales are F.O.B. designated plant of manufacture.



| Sales Code | Std/ Opt | Description | \$ List | Weight |
|-----------------------------------|----------|---|---------|--------------|
| Base Model | | | | |
| 0005351 | S | Model 535 Available exclusively as a truck, and perfect for light- and medium-duty applications, the Model 535 is a hardworking Class 5 powerhouse with no commercial drivers license required for operation. With a GVW of 19,500 lbs., its ideal for pickup and delivery, landscaping and municipal utility applications. | 93,445 | 7,620 |
| 0091200 | S | Other Commodity | 0 | 0 |
| 0093340 | S | City Delivery Truck or tractor which hauls freight, typically operating within a 100-mile radius, on public streets and highways and other paved surfaces. Typically includes package and freight delivery. | 0 | 0 |
| 0095040 | S | Van | 0 | 0 |
| 0098170 | S | United States Registry Canadian Registry Package Requires Air Conditioning Excise Tax Canada, Speedometer to be KPH ipo MPH, Daytime Running Lights and Rubber Battery Pad in Bottom of Battery Box. | 0 | 0 |
| Configuration | | | | |
| 0200700 | S | Not Applicable Secondary Manufacturer | 0 | 0 |
| Frame & Equipment | | | | |
| 0510100 | S | 9-7/8" Steel Rails 120,000 PSI, 9.875 x 3.5 x .25 Dimension, 1,250,000 RBM | 0 | 45 |
| 0611350 | S | 1-Piece Steel Frame Rail Xmbr Excludes Suspension | 0 | 0 |
| 0612035 | S | 175" Wheelbase | 0 | 0 |
| 0613230 | S | Steel BOC Xmbr | 0 | 0 |
| 0644090 | S | EOF Square without Crossmember End-of-frame square without crossmember. For use with body builder installed crossmember. | 0 | 0 |
| 0651090 | S | Omit Rear Mudflaps and Hangers | 0 | 0 |
| Front Axle & Equipment | | | | |
| 1011290 | S | Dana Spicer D800F 8,000 lb 3.5" drop. Factory front axle alignment to improve handling & reduce tire wear. Zerk fittings on tie rod ends, king pins, & draglink ball joints for ease of maintenance & help extend service life of components. Cognis EMGARD® FE 75W-90 synthetic axle lube provides over 1% fuel economy improvement. Reduces wear & extends maintenance intervals, resulting in increased uptime. Provides improved fluid flow to protect components in extreme cold conditions & withstand the stress from high temperatures, extending component life. | 0 | 0 |

Price Level: January 1, 2022

Deal: 535 Chassis

Printed On: 7/6/2022 4:30:38 PM

Date: July 06, 2022

Quote Number: QUO-970229-V8Y0N0



| Sales Code | Std/ Opt | Description | \$ List | Weight |
|------------|----------|--|---------|--------|
| 1111150 | S | Mono-Leaf Springs, Shocks, 8,000 LBS. | 0 | 0 |
| 1243170 | S | Power Steering Sheppard MD83 For use with 8,000 lb. axle ratings. The MD83 is a lighter duty power steering gear designed to handle up to 8,000 lbs. This gear is currently used in utility vans/package delivery trucks and other Class 6 & 7 applications. | 0 | 0 |
| 1354885 | S | 8-Stud Iron Hubs For Hydraulic Brakes | 0 | 0 |
| 1380440 | S | Hydraulic Front Brakes | 0 | 0 |

Rear Axle & Equipment

| | | | | |
|---------|---|--|---|---|
| 1513080 | S | Dana Spicer S14 14,000 lb, Hydraulic Brakes Axle Package. Inc Bosch 12x3 driveline parking brakes, standard oil seals, omit slack adjusters. Laser factory axle alignment to improve handling & reduce tire wear. Magnetic rear axle oil drain plug captures & holds any metal fragments in drive axle lube to extend service life. Parking brakes on all drive axles for optimal performance. Cognis EMGARD® FE 75W-90 synthetic axle lube provides over 1% fuel economy improvement. Reduces wear & extends maintenance intervals, resulting in increased uptime. Provides improved fluid flow to protect components in extreme cold conditions & withstand the stress from high temperatures, extending component life. | 0 | 0 |
| 1616325 | S | 8-Stud Iron Hubs for Hydraulic Brakes | 0 | 0 |
| 1680805 | S | Hydraulic Rear Brakes | 0 | 0 |
| 1682700 | S | WABCO Hydraulic ABS Anti-Lock Brake System. HABS-E Technology | 0 | 0 |
| 1684200 | S | Synthetic Axle Lubricant All Axles Peterbilt heavy duty models include Fuel Efficient Cognis EMGARD FE75W-90 which provides customers performance advantages over current synthetic lubricants with reduced gear wear and extended maintenance intervals, resulting in increased uptime. In addition, the lubricant provides improved fluid flow to protect gears in extreme cold conditions and withstand the stress from high temperatures, extending component life. | 0 | 0 |
| 1703730 | S | Ratio 3.73 Rear Axle | 0 | 0 |
| 1811180 | S | Peterbilt Taper Leaf, 13,500 LBS | 0 | 0 |

Engine & Equipment

| | | | | |
|---------|---|---|---|---|
| 2073116 | S | PACCAR PX-7 200@2400 GOV@2600 520@1600 Efficiency (2021 Emissions) N21350 C121 75....Maximum Accelerator Pedal Ve N21370 C128 75....Maximum Cruise Speed (P059) N21460 C132 1400..Max PTO Speed (P046) N21520 C133 5.....Timer Setting (P030) N21610 C188 39....Low Ambient Temperature Thre | 0 | 0 |
|---------|---|---|---|---|

Price Level: January 1, 2022

Deal: 535 Chassis

Printed On: 7/6/2022 4:30:38 PM

Date: July 06, 2022

Quote Number: QUO-970229-V8Y0N0



| Sales Code | Std/ Opt | Description | \$ List | Weight |
|------------|----------|--|---------|--------|
| | | N21620 C189 60....Intermediate Ambient Tempera | | |
| | | N21630 C190 80....High Ambient Temperature Thr | | |
| | | N21550 C206 35....Engine Load Threshold (P516) | | |
| | | N21340 C209 120....Hard Maximum Speed Limit (P1 | | |
| | | N21510 C225 YES...Enable Idle Shutdown Park Br | | |
| | | N21450 C231 NO....Gear Down Protection (P026) | | |
| | | N21570 C233 NO....Idle Shutdown Manual Overrul | | |
| | | N21440 C234 NO....Engine Protection Shutdown (| | |
| | | N21480 C238 NO....Auto Engine Brake in Cruise | | |
| | | N21470 C239 NO....Cruise Control Auto Resume (| | |
| | | N21430 C333 0.....Reserve Speed Limit Offset (| | |
| | | N21410 C334 0.....Maximum Cycle Distance (N202 | | |
| | | N21590 C382 YES...Enable Hot Ambient Automatic | | |
| | | N21500 C395 0.....Expiration Distance (N209) | | |
| | | N21530 C396 YES...Enable Impending Shutdown Wa | | |
| | | N21540 C397 60....Timer For Impending Shutdown | | |
| | | N21320 C399 120....Standard Maximum Speed Limit | | |
| | | N21400 C400 252....Reserve Speed Function Reset | | |
| | | N21420 C401 10....Maximum Active Distance (N20 | | |
| | | N21330 C402 0.....Expiration Distance (N207) | | |
| 2091130 | S | VMUX Electronics Architecture | 0 | 0 |
| 2091305 | S | Engine Idle Shutdown Timer Enabled | 0 | 0 |
| 2091315 | O | Enable EIST Ambient Temp Override | 0 | 0 |
| 2091372 | | Eff EIST NA Expiration Miles | 0 | 0 |
| 2091640 | | Effective VSL Setting NA | 0 | 0 |
| 2092016 | O | Typical Operating Speed 62 MPH | 0 | 0 |
| 2092031 | S | Powertrain Optimized for Fuel Economy Best analysis for vehicles which operate at or near cruise speed 90 plus percent of time. | 0 | 0 |
| 2140220 | S | CARB Engine Idling Compliance DECLINED By Dealer/Customer | 0 | 0 |
| 2140670 | O | EPA Emission Warranty | 0 | 0 |
| 2513060 | S | PACCAR 160 Amp Alternator, Brushed PACCAR 160 AMP alternator, brushed producing 160 Amps at road speed and 100 Amps at idle. | 0 | 0 |
| 2522160 | S | PACCAR 12V Starter PX-7 Engine Only | 0 | 0 |
| 2538030 | S | 2 PACCAR Premium 12V Starting Batteries 2000 CCA Threaded stud type terminal. Stranded copper battery cables are double aught (00) or larger to reduce resistance. | 0 | 0 |
| 2621130 | S | Belt Driven Variable Speed Fan Clutch PX9 Engine | 0 | 0 |

Price Level: January 1, 2022

Deal: 535 Chassis

Printed On: 7/6/2022 4:30:38 PM

Date: July 06, 2022

Quote Number: QUO-970229-V8Y0N0



| Sales Code | Std/ Opt | Description | \$ List | Weight |
|-------------------------------------|----------|---|---------|--------|
| | | PX7/ PX9/L9N/B6.7N. The belt-driven fully variable speed fan drives communicate directly with the PX9 ECM through the included electronic controller, managing the fan speed to match the exact amount of cooling required. The optimized setup creates smoother engagements, reduces noise and frees up available horsepower. These fan drives are also maintenance-free. A belt, additional pulleys, idlers, tensioners, and a drive hub are included to drive the fan. | | |
| 2711200 | S | Compressor Not Required (Hydraulic Brakes) | 0 | 0 |
| 2812210 | S | VGT Exhaust Brake (Variable Geometry Turbo). Provides approximately 90-100 HP of retardation and is part of the turbocharger. | 0 | 0 |
| 2921110 | S | PACCAR Fuel/Water Separator Standard Service PACCAR Fuel/Water separator standard service intervals. High efficiency media protects critical engine components. | 0 | 0 |
| 2921210 | S | No Fluid Heat Option for Fuel Filter | 0 | 0 |
| 2921310 | S | No Electric Heat Option for Fuel Filter | 0 | 0 |
| 3114270 | S | High Efficiency Cooling System Cooling module is a combination of steel and aluminum components, with aluminum connections to maximize performance and cooling capability. Silicone radiator & heater hoses enhance value, durability, & reliability. Constant tension band clamps reduce leaks. Chevron Delo Extended Life Coolant (NOAT) extends maintenance intervals reducing maintenance costs. Anti-freeze effective to -30 degrees F helps protect the engine. Low coolant level sensor warns of low coolant condition to prevent engine damage. Radiator Size by Model: 579/367 FEPTO 1325 sq in, 567/365/367: 1440 sq in, 365 FEPTO: 1184 sq in, 389/367 HH: 1669 sq in, 348: 1000 sq in, 520: 1242 sq in. | 0 | 0 |
| 3211140 | S | (1) Air Cleaner Engine Mounted | 0 | 0 |
| 3365290 | S | Exhaust Single RH Horizontal DPF/SCR RH Under Frame. | 0 | 0 |
| Transmission & Equipment | | | | |
| 4058010 | S | PACCAR TX-8AP560 Automatic 8-Speed, No Cooler | 0 | 0 |
| 4210930 | S | SPL100 Driveline, 1 Midship Bearing | 0 | 0 |
| 4252610 | S | Column Mounted Shifter RH Side | 0 | 0 |
| 4256365 | O | TP-650 Torque Converter PACCAR 8 Speed Transmission | 0 | 0 |
| Air & Trailer Equipment | | | | |
| 4540270 | S | Hydraulic Brake Package | 0 | 0 |
| Tires & Wheels | | | | |

Price Level: January 1, 2022

Deal: 535 Chassis

Printed On: 7/6/2022 4:30:38 PM

Date: July 06, 2022

Quote Number: QUO-970229-V8Y0N0



| Sales Code | Std/ Opt | Description | \$ List | Weight |
|---------------------------------|----------|--|---------|--------|
| 5004220 | S | FF: CN 14ply 245/70R19.5 Conti Hybrid HS3 | 0 | 0 |
| 5104220 | S | RR: CN 14ply 245/70R19.5 Conti Hybrid HS3 | 0 | 0 |
| 5190004 | S | Code-rear Tire Qty 04 | 0 | 0 |
| 5210590 | S | FF: Accur Stl Armor 50180PK 19.5X6.75 Hydraulic Brakes, PHP8-4 Hand Holes | 0 | 0 |
| 5310590 | S | RR: Accur Steel Armor 50180PK 19.5X6.75 Hydraulic Brakes, PHP8-4 Hand Holes | 0 | 0 |
| 5390004 | O | Code-rear Rim Qty 04 | 0 | 0 |
| Fuel Tanks | | | | |
| 5581040 | S | D-Shaped Aluminum 50 Gallon Fuel Tank RH U/C Non-slip step RH under cab | 0 | 0 |
| 5601050 | S | Location RH U/C 50 Gallon | 0 | 0 |
| 5652890 | S | DEF Tank Mounted LH BOC Models 220 and 520 mounted left hand back-of-cab. | 0 | 0 |
| 5652990 | O | DEF To Fuel Ratio 2:1 Or Greater | 0 | 0 |
| 5655019 | S | DEF Tank Small, HD 14 Gal 2.1M MD 5.5 Gal | 0 | 0 |
| Battery Box & Bumper | | | | |
| 6020030 | S | MD Battery Box, Non-Slip Step LH Under Cab | 0 | 0 |
| 6030660 | S | Plastic Battery Box Cover | 0 | 0 |
| 6121790 | S | Aero Bumper Molded One Piece Gray ***Warning*** Due to a new legal regulations, all New Medium Duty trucks require headlights to be located in the bumper when the chassis height is GREATER than the following chassis height: Measurement to bottom of frame at front of frame: for the 107 Aero Hood 32.6, for the 109 Aero Hood 31.4, for the 109 Vocational Hood 26.7. Work with applications if your chassis height is unacceptable. | 0 | 0 |
| Cab & Equipment | | | | |
| 6510150 | S | Aerodynamic 107in BBC Aluminum Cab & SMC Hood With molded gray crown. | 0 | 0 |
| 6917350 | S | Seats Inc. Non-Adjustable Driver Seat | 0 | 0 |
| 6923160 | S | (2) Person Passenger Seat | 0 | 0 |
| 6939110 | S | Toolbox Under Passenger Seat Non-Suspension Seat | 0 | 0 |
| 6939410 | S | Non-Air Ride Driver | 0 | 0 |

Price Level: January 1, 2022

Deal: 535 Chassis

Printed On: 7/6/2022 4:30:38 PM

Date: July 06, 2022

Quote Number: QUO-970229-V8Y0N0



| Sales Code | Std/ Opt | Description | \$ List | Weight |
|-------------------|-----------------|---|----------------|---------------|
| 6939430 | S | Mid Back Driver | 0 | 0 |
| 6939470 | S | Vinyl Driver | 0 | 0 |
| 6939510 | S | Non-Air Ride Passenger | 0 | 0 |
| 6939540 | S | Low Back Passenger | 0 | 0 |
| 6939570 | S | Vinyl Passenger | 0 | 0 |
| 7001520 | S | Adjustable Steering Column - Tilt/Telescope | 0 | 0 |
| 7001620 | S | Steering Wheel With Peterbilt Logo Steering Wheel with embossed Peterbilt logo over horn button. | 0 | 0 |
| 7036140 | S | Probilt Interior Gray/Black - Flat Roof | 0 | 0 |
| 7210540 | S | Day Cab Rear Window Day cab rear window flush to back of cab. | 0 | 0 |
| 7210550 | S | 1-Piece Glass Rear Cab Window Fixed | 0 | 0 |
| 7230060 | S | 1-Piece Curved Windshield | 0 | 0 |
| 7230360 | S | Power Door Locks and Power Window Lifts Standard | 0 | 0 |
| 7322010 | S | Combo Fresh Air Heater/Air Conditioner With radiator mounted condenser, dedicated side window defrosters, Bi-Level Heater/Defroster Controls, 54,500 BTU/HR, and silicone heater hoses. | 0 | 0 |
| 7510070 | S | Aero Rear View Mirror Housing, Molded Black | 0 | 0 |
| 7514050 | S | Look Down Mirror Over Passenger Door with Black Housing | 0 | 0 |
| 7514090 | S | Peterbilt Aero Rear View Mirror, Non-Motorized Includes top mirror with non-motorized, adjustable dual axis non-heated glass. Bottom mirror is an integrated convex surface. Includes black textured arms with breakaway feature. | 0 | 0 |
| 7725720 | S | No Head Unit or Audio Speakers Selected | 0 | 0 |
| 7851480 | S | Peterbilt Electric Windshield Wipers With Intermittent Feature. | 0 | 0 |
| 7852060 | S | Solid Rear Day Cab Mounts | 0 | 0 |
| 8021380 | S | Air Restriction Indicator Mounted on air cleaner, intake piping, or firewall | 0 | 0 |
| 8070860 | S | Main Instrumentation Panel Digital Cluster 7" Display includes: Physical (Analog) - Speedometer, Tachometer, Oil Pressure, Coolant Temp and Display Gauges - Fuel | 0 | 0 |

Price Level: January 1, 2022

Deal: 535 Chassis

Printed On: 7/6/2022 4:30:38 PM

Date: July 06, 2022

Quote Number: QUO-970229-V8Y0N0



| Sales Code | Std/ Opt | Description | \$ List | Weight |
|--|----------|---|---------|--------|
| | | Level, DEF Level, DPF Filter Status, Fuel Economy, Volts Telltale, OAT and Primary Air Pressure, Secondary Air Pressure for air brake trucks. | | |
| 8111110 | S | Headlights Composite Fender Mounted Integral park, turn, and side marker | 0 | 0 |
| 8120980 | S | (5) Marker Lights, Aero LED | 0 | 0 |
| 8134160 | S | Self-Canceling Turn Signal | 0 | 0 |
| 8140080 | S | LED Stop/Turn/Tail/Backup Bracket mounted left-hand / right-hand end of frame | 0 | 0 |
| Paint | | | | |
| 8500710 | O | Standard Paint Color Selection | -200 | 0 |
| 8530770 | S | (1) Color Axalta Two Stage - Cab/Hood Base Coat/Clear Coat N85020 A - L0006EY WHITE N85500 CAB ROOF L0006EY WHITE N85300 FENDER L0006EY WHITE N85200 FRAME L0001EA BLACK N85400 HOOD TOP L0006EY WHITE | 0 | 0 |
| Shipping Destination | | | | |
| Options Not Subject To Discount | | | | |
| 9400091 | S | Peterbilt Class 7 Standard Coverage 1 year/Unlimited Miles/km | 0 | 0 |
| 9400093 | S | PACCAR PX-7 Standard Coverage 3 years/Unlimited Miles/Unlimited hrs | 0 | 0 |
| 9407103 | O | Prepaid Freight Increase For 2022 Delivery | -500 | 0 |
| 9408703 | O | Base Warr: Emissions 5YR/100K MI-EPA Engine | 0 | 0 |
| Miscellaneous | | | | |
| 9409040 | S | Aero Hood (MODEL 535) | 0 | 0 |
| 9409096 | O | State Registry: Virginia | 0 | 0 |
| Promotions | | | | |
| Order Comments | | | | |



| | |
|---|----------|
| Total List Price (W/O Freight & Warranty & Surcharges) | \$93,245 |
| Marketing and Service Support Fee | \$670 |
| Prepaid Freight | \$2,800 |
| Total Surcharge/Options Not Subject To Discount | \$-500 |
| Total Weight | 7,665 |

Prices and Specifications Subject to Change Without Notice.

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in CRM.

PRICING DISCLAIMER

While we make every effort to maintain the web site to preserve pricing accuracy, prices are subject to change without notice. Although the information in this price list is presented in good faith and believed to be correct at the time of printing, we make no representations or warranties as to the completeness or accuracy of this information. We reserve the right to change, delete or otherwise modify the pricing information which is represented herein without any prior notice. We carefully check pricing specifications, but occasionally errors can occur, therefore we reserve the right to change such prices without notice. We disclaim all liability for any errors or omissions in the materials. In no event will we be responsible for any damages of any nature whatsoever from the reliance upon information from these materials. Please check your order prebills to confirm your pricing information



Shipping Destinations

Intermediate Destination: NONE

| Final Destinations | Quantity |
|--------------------|----------|
|--------------------|----------|