



Peterbilt of Richmond (H830)
2800A Deepwater Terminal
Richmond, Virginia 23212

Virginia Sheriffs Association
901 East Byrd St Suite1301
Richmond, Virginia 23219
United States of America

David Askew
Cell Phone:
Office Phone:
Email: daskew@thepetestore.com

Kaylyn Mitman
Office Phone: 919-459-6471
Email: kmitman@virginiasheriffs.org

Vehicle Summary

Unit		Chassis	
Model:	Model 535	Fr Axle Load (lbs):	8000
Type:	Full Truck	Rr Axle Load (lbs):	13500
Description 1:	535 Chassis	G.C.W. (lbs):	21500
Description 2:	535 Chassis Options		
Application		Road Conditions:	
Intended Serv.:	City Delivery	Class A (Highway)	100
Commodity:	Other Commodity	Class B (Hwy/Mtn)	0
		Class C (Off-Hwy)	0
		Class D (Off-Road)	0
Body		Maximum Grade:	6
Type:	Van	Wheelbase (in):	175
Length (ft):	20	Overhang (in):	60
Height (ft):	13.5	Fr Axle to BOC (in):	67.5
Max Laden Weight (lbs):	1000		
Trailer		Cab to Axle (in):	107.5
No. of Trailer Axles:	0	Cab to EOF (in):	167.5
Type:		Overall Comb. Length (in):	275
Length (ft):	0	Special Req.	
Height (ft):	0		
Kingpin Inset (in):	0		
Corner Radius (in):	0		
Restrictions			
Length (ft):	40		
Width (in):	102		
Height (ft):	13.5		

Approved by: _____

Date: _____

Note: All sales are F.O.B. designated plant of manufacture.



Sales Code	Std/ Opt	Description	\$ List	Weight
Base Model				
0005351	S	Model 535 Available exclusively as a truck, and perfect for light- and medium-duty applications, the Model 535 is a hardworking Class 5 powerhouse with no commercial drivers license required for operation. With a GVW of 19,500 lbs., its ideal for pickup and delivery, landscaping and municipal utility applications.	93,445	7,620
0091200	S	Other Commodity	0	0
0093340	S	City Delivery Truck or tractor which hauls freight, typically operating within a 100-mile radius, on public streets and highways and other paved surfaces. Typically includes package and freight delivery.	0	0
0095040	S	Van	0	0
0098170	S	United States Registry Canadian Registry Package Requires Air Conditioning Excise Tax Canada, Speedometer to be KPH ipo MPH, Daytime Running Lights and Rubber Battery Pad in Bottom of Battery Box.	0	0
Configuration				
0200700	S	Not Applicable Secondary Manufacturer	0	0
Frame & Equipment				
0510100	S	9-7/8" Steel Rails 120,000 PSI, 9.875 x 3.5 x .25 Dimension, 1,250,000 RBM	0	45
0611330	O	Zinc Coated Anti Corrosion Treated Frame Rails Requires Frame Rail Code. Zinc Phosphate coating will replace the standard frame rail primer and provide added corrosion prevention for your customer's operating in severe conditions or in climates where vehicle rust is common.	362	2
0611350	S	1-Piece Steel Frame Rail Xmbr Excludes Suspension	0	0
0612035	S	175" Wheelbase	0	0
0613230	S	Steel BOC Xmbr	0	0
0644090	S	EOF Square without Crossmember End-of-frame square without crossmember. For use with body builder installed crossmember.	0	0
0651090	S	Omit Rear Mudflaps and Hangers	0	0
Front Axle & Equipment				
1011290	S	Dana Spicer D800F 8,000 lb 3.5" drop. Factory front axle alignment to improve handling & reduce tire wear. Zerk fittings on tie rod ends, king pins, & draglink ball joints for ease of maintenance & help extend service life of components. Cognis	0	0

Price Level: January 1, 2022

Deal: 535 Chassis

Printed On: 7/6/2022 4:40:07 PM

Date: July 06, 2022

Quote Number: QUO-970231-G2L5K9



Sales Code	Std/ Opt	Description	\$ List	Weight
		EMGARD® FE 75W-90 synthetic axle lube provides over 1% fuel economy improvement. Reduces wear & extends maintenance intervals, resulting in increased uptime. Provides improved fluid flow to protect components in extreme cold conditions & withstand the stress from high temperatures, extending component life.		
1111150	S	Mono-Leaf Springs, Shocks, 8,000 LBS.	0	0
1243170	S	Power Steering Sheppard MD83 For use with 8,000 lb. axle ratings. The MD83 is a lighter duty power steering gear designed to handle up to 8,000 lbs. This gear is currently used in utility vans/package delivery trucks and other Class 6 & 7 applications.	0	0
1354885	S	8-Stud Iron Hubs For Hydraulic Brakes	0	0
1380440	S	Hydraulic Front Brakes	0	0
Rear Axle & Equipment				
1513080	S	Dana Spicer S14 14,000 lb, Hydraulic Brakes Axle Package. Inc Bosch 12x3 driveline parking brakes, standard oil seals, omit slack adjusters. Laser factory axle alignment to improve handling & reduce tire wear. Magnetic rear axle oil drain plug captures & holds any metal fragments in drive axle lube to extend service life. Parking brakes on all drive axles for optimal performance. Cognis EMGARD® FE 75W-90 synthetic axle lube provides over 1% fuel economy improvement. Reduces wear & extends maintenance intervals, resulting in increased uptime. Provides improved fluid flow to protect components in extreme cold conditions & withstand the stress from high temperatures, extending component life.	0	0
1616325	S	8-Stud Iron Hubs for Hydraulic Brakes	0	0
1680805	S	Hydraulic Rear Brakes	0	0
1682700	S	WABCO Hydraulic ABS Anti-Lock Brake System. HABS-E Technology	0	0
1683225	O	SmarTire Tire Pressure Monitoring System Next generation TPMS.	923	25
1684200	S	Synthetic Axle Lubricant All Axles Peterbilt heavy duty models include Fuel Efficient Cognis EMGARD FE75W-90 which provides customers performance advantages over current synthetic lubricants with reduced gear wear and extended maintenance intervals, resulting in increased uptime. In addition, the lubricant provides improved fluid flow to protect gears in extreme cold conditions and withstand the stress from high temperatures, extending component life.	0	0
1703730	S	Ratio 3.73 Rear Axle	0	0
1811180	S	Peterbilt Taper Leaf, 13,500 LBS	0	0

Engine & Equipment

Price Level: January 1, 2022

Deal: 535 Chassis

Printed On: 7/6/2022 4:40:07 PM

Date: July 06, 2022

Quote Number: QUO-970231-G2L5K9



Sales Code	Std/ Opt	Description	\$ List	Weight
2073306	O	PACCAR PX-7 300@2600 GOV@2600 660@1600 PERFORMANCE (2021 EMISSIONS)	2,142	0
		N21350 C121 75....Maximum Accelerator Pedal Ve		
		N21370 C128 75....Maximum Cruise Speed (P059)		
		N21460 C132 1400..Max PTO Speed (P046)		
		N21520 C133 5.....Timer Setting (P030)		
		N21610 C188 39....Low Ambient Temperature Thre		
		N21620 C189 60....Intermediate Ambient Tempera		
		N21630 C190 80....High Ambient Temperature Thr		
		N21550 C206 35....Engine Load Threshold (P516)		
		N21340 C209 120....Hard Maximum Speed Limit (P1		
		N21510 C225 YES...Enable Idle Shutdown Park Br		
		N21450 C231 NO....Gear Down Protection (P026)		
		N21570 C233 NO....Idle Shutdown Manual Overrul		
		N21440 C234 NO....Engine Protection Shutdown (
		N21480 C238 NO....Auto Engine Brake in Cruise		
		N21470 C239 NO....Cruise Control Auto Resume (
		N21430 C333 0.....Reserve Speed Limit Offset (
		N21410 C334 0.....Maximum Cycle Distance (N202		
		N21590 C382 YES...Enable Hot Ambient Automatic		
		N21500 C395 0.....Expiration Distance (N209)		
		N21530 C396 YES...Enable Impending Shutdown Wa		
		N21540 C397 60....Timer For Impending Shutdown		
		N21320 C399 120....Standard Maximum Speed Limit		
		N21400 C400 252....Reserve Speed Function Reset		
		N21420 C401 10....Maximum Active Distance (N20		
		N21330 C402 0.....Expiration Distance (N207)		
2091130	S	VMUX Electronics Architecture	0	0
2091305	S	Engine Idle Shutdown Timer Enabled	0	0
2091315	O	Enable EIST Ambient Temp Override	0	0
2091372		Eff EIST NA Expiration Miles	0	0
2091640		Effective VSL Setting NA	0	0
2092016	O	Typical Operating Speed 62 MPH	0	0
2092031	S	Powertrain Optimized for Fuel Economy Best analysis for vehicles which operate at or near cruise speed 90 plus percent of time.	0	0
2140220	S	CARB Engine Idling Compliance DECLINED By Dealer/Customer	0	0
2140450	O	Remote PTO/Throttle, 12-Pin Eng Bay Remote Control Provision	54	0
2140670	O	EPA Emission Warranty	0	0

Price Level: January 1, 2022

Deal: 535 Chassis

Printed On: 7/6/2022 4:40:07 PM

Date: July 06, 2022

Quote Number: QUO-970231-G2L5K9



Sales Code	Std/ Opt	Description	\$ List	Weight
2513060	S	PACCAR 160 Amp Alternator, Brushed PACCAR 160 AMP alternator, brushed producing 160 Amps at road speed and 100 Amps at idle.	0	0
2521090	O	Immersion Type Block Heater 110-120V Standard location for 2.1M and 1.9M models is left-hand under cab, Model 520 is in bumper, and for Model 220 it is at the driver step. Plug includes a weather-proof cover that protects the receptacle. This pre-heater keeps the coolant in the engine block from freezing when the engine is not running.	82	2
2522160	S	PACCAR 12V Starter PX-7 Engine Only	0	0
2538030	S	2 PACCAR Premium 12V Starting Batteries 2000 CCA Threaded stud type terminal. Stranded copper battery cables are double aught (00) or larger to reduce resistance.	0	0
2539430	O	Batteries In RH Box U/C	0	0
2539700	O	Battery Jumper Terminal Mtd under hood RH frame rail. Available with PX-7 engines only.	110	4
2539840	O	MD - Battery Disconnect Switch Mounted on Battery Box	398	9
2621130	S	Belt Driven Variable Speed Fan Clutch PX9 Engine PX7/ PX9/L9N/B6.7N. The belt-driven fully variable speed fan drives communicate directly with the PX9 ECM through the included electronic controller, managing the fan speed to match the exact amount of cooling required. The optimized setup creates smoother engagements, reduces noise and frees up available horsepower. These fan drives are also maintenance-free. A belt, additional pulleys, idlers, tensioners, and a drive hub are included to drive the fan.	0	0
2711200	S	Compressor Not Required (Hydraulic Brakes)	0	0
2812210	S	VGT Exhaust Brake (Variable Geometry Turbo). Provides approximately 90-100 HP of retardation and is part of the turbocharger.	0	0
2921110	S	PACCAR Fuel/Water Separator Standard Service PACCAR Fuel/Water separator standard service intervals. High efficiency media protects critical engine components.	0	0
2921210	S	No Fluid Heat Option for Fuel Filter	0	0
2921310	S	No Electric Heat Option for Fuel Filter	0	0
3010400	O	Engine Protection Shutdown w/ Label Includes oil pressure, oil temperature, coolant temperature, and intake manifold temperature.	5	0
3114270	S	High Efficiency Cooling System Cooling module is a combination of steel and aluminum components, with aluminum connections to maximize performance and cooling capability. Silicone radiator & heater hoses enhance value, durability, & reliability. Constant tension band clamps reduce leaks. Chevron Delo Extended Life Coolant (NOAT) extends maintenance intervals reducing maintenance costs. Anti-freeze effective to -30 degrees F helps protect	0	0

Price Level: January 1, 2022

Deal: 535 Chassis

Printed On: 7/6/2022 4:40:07 PM

Date: July 06, 2022

Quote Number: QUO-970231-G2L5K9



Sales Code	Std/ Opt	Description	\$ List	Weight
		the engine. Low coolant level sensor warns of low coolant condition to prevent engine damage. Radiator Size by Model: 579/367 FEPTO 1325 sq in, 567/365/367: 1440 sq in, 365 FEPTO: 1184 sq in, 389/367 HH: 1669 sq in, 348: 1000 sq in, 520: 1242 sq in.		
3211140	S	(1) Air Cleaner Engine Mounted	0	0
3365290	S	Exhaust Single RH Horizontal DPF/SCR RH Under Frame.	0	0
Transmission & Equipment				
4058030	O	PACCAR TX-8 8AP660 Automatic 8-Speed, No Cooler	532	0
4210080	O	1710 HD Driveline, 1 Midship Bearing	308	75
4252610	S	Column Mounted Shifter RH Side	0	0
4256365	O	TP-650 Torque Converter PACCAR 8 Speed Transmission	0	0
4257110	O	LH Mounted Trans PTO Provisions	35	0
Air & Trailer Equipment				
4540270	S	Hydraulic Brake Package	0	0
Tires & Wheels				
5033660	O	FF: GY 16ply 245/70R19.5 Endurance RSA ETRTO	264	-4
5133660	O	RR: GY 16ply 245/70R19.5 Endurance RSA	528	-8
5190004	S	Code-rear Tire Qty 04	0	0
5220610	O	FF: Alcoa 765427 19.5X6.75 High Polish Aluminum, 8-hole (hydraulic brakes). LVL ONE technology.	346	-48
5320610	O	RR: Alcoa 765427 19.5X6.75 High Polish Aluminum, 8-hole (hydraulic brakes). LVL ONE technology.	692	-96
5390004	O	Code-rear Rim Qty 04	0	0
5407640	O	FF: Mirror Polish Wheels, Outer Surface Single/tandem steer. Mirror Polish outer surface of outer wheel. Without chrome wheel nuts.	65	0
5407650	O	RR: Mirror Polish Wheels, Outer Surface, Single Drive without chrome wheel nuts. Mirror polish outer surface of outer wheel.	251	0
Fuel Tanks				
5584070	O	D-Shaped Aluminum 60 Gallon Fuel Tank LH U/C Non-slip step LH under cab	89	-5
5602060	O	Location LH U/C 60 Gallon	0	0

Price Level: January 1, 2022

Deal: 535 Chassis

Printed On: 7/6/2022 4:40:07 PM

Date: July 06, 2022

Quote Number: QUO-970231-G2L5K9



Sales Code	Std/ Opt	Description	\$ List	Weight
5652890	S	DEF Tank Mounted LH BOC Models 220 and 520 mounted left hand back-of-cab.	0	0
5652980	S	DEF To Fuel Ratio Between 1:1 And 2:1	0	0
5655019	S	DEF Tank Small, HD 14 Gal 2.1M MD 5.5 Gal	0	0
Battery Box & Bumper				
6020040	O	MD Battery Box, Non-Slip Step RH Under Cab	122	0
6030630	O	Aluminum Battery Box Cover	123	4
6121790	S	Aero Bumper Molded One Piece Gray ***Warning*** Due to a new legal regulations, all New Medium Duty trucks require headlights to be located in the bumper when the chassis height is GREATER than the following chassis height: Measurement to bottom of frame at front of frame: for the 107 Aero Hood 32.6, for the 109 Aero Hood 31.4, for the 109 Vocational Hood 26.7. Work with applications if your chassis height is unacceptable.	0	0
Cab & Equipment				
6510150	S	Aerodynamic 107in BBC Aluminum Cab & SMC Hood With molded gray crown.	0	0
6540740	O	Peterbilt Keyless Entry The Peterbilt key fob functions to lock or unlock the vehicle. With a single click, the drivers door is locked or unlocked and with a double click all doors are locked or unlocked. The third button, depicted by a picture of a lamp, will start the exterior light self-test sequence, helpful when performing the daily pre-trip inspection.	211	2
6917350	S	Seats Inc. Non-Adjustable Driver Seat	0	0
6923160	S	(2) Person Passenger Seat	0	0
6937040	O	Cloth Driver	0	0
6939110	S	Toolbox Under Passenger Seat Non-Suspension Seat	0	0
6939410	S	Non-Air Ride Driver	0	0
6939420	O	High Back Driver	44	0
6939510	S	Non-Air Ride Passenger	0	0
6939540	S	Low Back Passenger	0	0
6939570	S	Vinyl Passenger	0	0



Sales Code	Std/ Opt	Description	\$ List	Weight
7000025	O	Steering Wheel With Multi-Function Includes Peterbilt logo on horn button , audio volume, seek, mute and mode button on LH pod with cruise control on/off/cancel, set/resume and accelerate/coast on the right pod.	246	4
7000045	O	High-Visibility Interior Grabhandles, Painted Bright yellow interior grabhandle for vocational vehicles.	65	0
7001520	S	Adjustable Steering Column - Tilt/Telescope	0	0
7036130	O	Probilt Interior Grey/Black - Curved Roof	176	0
7110680	O	Exterior Cab Entry Grabhandle Textured; NFPA compliant. Available on Day Cab specifications only.	169	0
7210510	O	3-Piece Glass Rear Cab Window, All Pieces Fixed	157	12
7210540	S	Day Cab Rear Window Day cab rear window flush to back of cab.	0	0
7230060	S	1-Piece Curved Windshield	0	0
7230360	S	Power Door Locks and Power Window Lifts Standard	0	0
7322010	S	Combo Fresh Air Heater/Air Conditioner With radiator mounted condenser, dedicated side window defrosters, Bi-Level Heater/Defroster Controls, 54,500 BTU/HR, and silicone heater hoses.	0	0
7410040	O	Outside Sunvisor - Stainless Steel Not available with 2.1M high roof sleeper.	250	4
7510060	O	Aero Rear View Mirror Housing, Bright Finish	173	3
7514010	O	Peterbilt Aero Rear View Mirror, Motorized Includes top mirror with motorized, adjustable dual axis heated glass. Bottom mirror is an integrated convex surface. Includes black textured arms with breakaway feature.	257	3
7514050	S	Look Down Mirror Over Passenger Door with Black Housing	0	0
7561190	O	LH/RH Round hood Mirrors Bright Housing Convex mirrors, left hand / right hand hood mirrors with Bright finish. Includes one-piece straight arms for rearward visibility.	234	8
7721050	O	Satellite Radio Requires USB port and bluetooth for phone and audio.	222	0
7722120	O	ConcertClass, AM/FM, Weatherband, 3.5 Aux	331	11
7725710	O	Standard Speaker Package For Cab (2) Speakers	50	4
7728030	O	Radio Mute When In Reverse For automatic or automated transmission	0	0
7728040	O	Bluetooth Phone and Audio Requires USB Port	38	0
7728050	O	USB Port	38	0

Price Level: January 1, 2022

Deal: 535 Chassis

Printed On: 7/6/2022 4:40:07 PM

Date: July 06, 2022

Quote Number: QUO-970231-G2L5K9



Sales Code	Std/ Opt	Description	\$ List	Weight
7851480	S	Peterbilt Electric Windshield Wipers With Intermittent Feature.	0	0
7852020	O	Cab Air Suspension	177	15
7855120	O	Bugscreen - Removable External Mounted	211	2
7900090	O	Triangle Reflector Kit, Ship Loose Florescent triangle emergency road flares are designed to meet and exceed all DOT standards.	18	13
7900310	O	Fire Extinguisher, Mounted Outboard Driver Seat Hazmat approval UL listed/rated ABC	56	9
7900520	O	Headlamps To Turn On When Wipers On	0	0
7901130	O	Backup Alarm (107 DB)	34	3
8021380	S	Air Restriction Indicator Mounted on air cleaner, intake piping, or firewall	0	0
8070030	O	Up to (12) Additional Electric Switches Up to (12) additional electric switches without wiring. Switch will short pin 5 to 4 when off and pin5 to 6 when on. Backlighting provided by Lin jumper.	312	2
8070860	S	Main Instrumentation Panel Digital Cluster 7" Display includes: Physical (Analog) - Speedometer, Tachometer, Oil Pressure, Coolant Temp and Display Gauges - Fuel Level, DEF Level, DPF Filter Status, Fuel Economy, Volts Telltale, OAT and Primary Air Pressure, Secondary Air Pressure for air brake trucks.	0	0
8111110	S	Headlights Composite Fender Mounted Integral park, turn, and side marker	0	0
8120980	S	(5) Marker Lights, Aero LED	0	0
8131560	O	(2) Peterbilt Fog Lights Recessed in bumper	262	6
8134160	S	Self-Canceling Turn Signal	0	0
8140080	S	LED Stop/Turn/Tail/Backup Bracket mounted left-hand / right-hand end of frame	0	0
Paint				
8500710	O	Standard Paint Color Selection	-200	0
8530770	S	(1) Color Axalta Two Stage - Cab/Hood Base Coat/Clear Coat N85020 A - L0006EY WHITE N85500 CAB ROOF L0006EY WHITE N85300 FENDER L0006EY WHITE N85200 FRAME L0001EA BLACK N85400 HOOD TOP L0006EY WHITE	0	0

Shipping Destination

Price Level: January 1, 2022

Deal: 535 Chassis

Printed On: 7/6/2022 4:40:07 PM

Date: July 06, 2022

Quote Number: QUO-970231-G2L5K9



Sales Code	Std/ Opt	Description	\$ List	Weight
Options Not Subject To Discount				
9400091	S	Peterbilt Class 7 Standard Coverage 1 year/Unlimited Miles/km	0	0
9400093	S	PACCAR PX-7 Standard Coverage 3 years/Unlimited Miles/Unlimited hrs	0	0
9407103	O	Prepaid Freight Increase For 2022 Delivery	-500	0
9408703	O	Base Warr: Emissions 5YR/100K MI-EPA Engine	0	0
Miscellaneous				
9409040	S	Aero Hood (MODEL 535)	0	0
9409096	O	State Registry: Virginia	0	0

Promotions

Order Comments



Total List Price (W/O Freight & Warranty & Surcharges)	\$104,407
Marketing and Service Support Fee	\$670
Prepaid Freight	\$2,800
Total Surcharge/Options Not Subject To Discount	\$-500
Total Weight	7,726

Prices and Specifications Subject to Change Without Notice.

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in CRM.

PRICING DISCLAIMER

While we make every effort to maintain the web site to preserve pricing accuracy, prices are subject to change without notice. Although the information in this price list is presented in good faith and believed to be correct at the time of printing, we make no representations or warranties as to the completeness or accuracy of this information. We reserve the right to change, delete or otherwise modify the pricing information which is represented herein without any prior notice. We carefully check pricing specifications, but occasionally errors can occur, therefore we reserve the right to change such prices without notice. We disclaim all liability for any errors or omissions in the materials. In no event will we be responsible for any damages of any nature whatsoever from the reliance upon information from these materials. Please check your order prebills to confirm your pricing information



Shipping Destinations

Intermediate Destination: NONE

Final Destinations	Quantity
--------------------	----------