



Peterbilt of Richmond (H830)
2800A Deepwater Terminal
Richmond, Virginia 23212

Virginia Sheriffs Association
901 East Byrd St Suite 1301
Richmond, Virginia 23219
United States of America

David Askew
Cell Phone:
Office Phone:
Email: daskew@thepetestore.com

Kaylyn Mitman
Office Phone: 919-459-6471
Email: kmitman@virginiasheriffs.org

Vehicle Summary

| Unit | | Chassis | |
|-------------------------|---------------------|----------------------------|-------|
| Model: | Model 536 | Fr Axle Load (lbs): | 10000 |
| Type: | Full Truck | Rr Axle Load (lbs): | 18000 |
| Description 1: | 536 Chassis Specs | G.C.W. (lbs): | 26000 |
| Description 2: | 536 Chassis Options | | |
| Application | | Road Conditions: | |
| Intended Serv.: | Snowplow | Class A (Highway) | 100 |
| Commodity: | Other Commodity | Class B (Hwy/Mtn) | 0 |
| | | Class C (Off-Hwy) | 0 |
| | | Class D (Off-Road) | 0 |
| Body | | Maximum Grade: | |
| Type: | End Dump | | 6 |
| Length (ft): | 24 | Wheelbase (in): | 175 |
| Height (ft): | 13.5 | Overhang (in): | 60 |
| Max Laden Weight (lbs): | 1000 | Fr Axle to BOC (in): | 69.5 |
| Trailer | | Cab to Axle (in): | 105.5 |
| No. of Trailer Axles: | 0 | Cab to EOF (in): | 165.5 |
| Type: | | Overall Comb. Length (in): | 275 |
| Length (ft): | 0 | Special Req. | |
| Height (ft): | 0 | | |
| Kingpin Inset (in): | 0 | | |
| Corner Radius (in): | 0 | | |
| Restrictions | | | |
| Length (ft): | 40 | | |
| Width (in): | 102 | | |
| Height (ft): | 13.5 | | |

Approved by: _____

Date: _____

Note: All sales are F.O.B. designated plant of manufacture.



| Sales Code | Std/ Opt | Description | \$ List | Weight |
|-----------------------------------|----------|---|---------|--------------|
| Base Model | | | | |
| 0005361 | S | Model 536 The Model 536 is the ultimate Class 6 medium duty. It is highly adaptable and can be configured up to 26,000 lbs. to meet the demands of a variety of medium-duty applications. Combining durability and power with options to match the needs of both the job and driver, the 536 is an exceptional performer and ideal for refrigerated van, pickup and delivery, wrecker and municipal utility applications. | 96,375 | 9,470 |
| 0091200 | S | Other Commodity | 0 | 0 |
| 0093150 | O | Snowplow Truck which is configured for mounting a snowplow to the front. May also have dump or other body. | 0 | 0 |
| 0095170 | O | End Dump | 0 | 0 |
| 0098170 | S | United States Registry Canadian Registry Package Requires Air Conditioning Excise Tax Canada, Speedometer to be KPH ipo MPH, Daytime Running Lights and Rubber Battery Pad in Bottom of Battery Box. | 0 | 0 |
| Configuration | | | | |
| 0200700 | S | Not Applicable Secondary Manufacturer | 0 | 0 |
| 0210260 | S | Class 6 Chassis Weight Rating 26,000 lb GVWR | 0 | 0 |
| Frame & Equipment | | | | |
| 0515030 | O | 10-5/8" Steel Rails to 285" 10.625 x 3.45 x .313 Dimension, 1,776,000 RBM; Yield Strength: 120,000 psi. Section Modulus: 14.8 cubic inches. Weight: 1.44 lbs/inch pair | 141 | 258 |
| 0601500 | O | Full Steel Inner Liner | 1,759 | 489 |
| 0611300 | O | Heavy Duty 5-Piece Crossmember BOC IPO Standard Class 5, 6, 7 | 17 | 20 |
| 0611330 | O | Zinc Coated Anti Corrosion Treated Frame Rails Requires Frame Rail Code. Zinc Phosphate coating will replace the standard frame rail primer and provide added corrosion prevention for your customer's operating in severe conditions or in climates where vehicle rust is common. | 362 | 2 |
| 0611790 | O | Aluminum Frame Rail Crossmembers Excludes suspension | 144 | 0 |
| 0644090 | S | EOF Square without Crossmember End-of-frame square without crossmember. For use with body builder installed crossmember. | 0 | 0 |
| 0651090 | S | Omit Rear Mudflaps and Hangers | 0 | 0 |
| Front Axle & Equipment | | | | |



| Sales Code | Std/ Opt | Description | \$ List | Weight |
|-------------------|-----------------|---|----------------|---------------|
| 1014130 | S | Hendrickson SteerTek NXT 10,000 lb 3.32" Drop | 0 | 0 |
| 1111155 | S | Mono-Leaf Springs, Shocks, 10,000 LBS. | 0 | 0 |
| 1243040 | S | Power Steering Sheppard HD94 Sheppard HD94 power steering gear is a light weight version of heavy duty line-haul power steering gear. For use with 10,000 to 13,200 lb. axle ratings. | 0 | 0 |
| 1250180 | O | Power Steering Reservoir Frame Mounted The power steering reservoir is a steering system that eases drivability by applying hydraulic pressure to the steering gear. | 0 | 0 |
| 1354840 | S | PHP10 Iron PreSet PLUS Hubs PHP10 iron PreSet PLUS hubs have a fully integrated spindle nut design, an optimized wheel spacer, magnetic fill plug on drive and trailer hubs for inspection of metal particles in lubricant, with a long life oil seal and bearings are pre-adjusted. Use with Front Axle. | 0 | 0 |
| 1380260 | O | Bendix Air Cam Front Drum Brakes 16.5x5 For use with 10,000 lbs to 14,600 lbs steer axles. Includes automatic slack adjusters & outboard mounted brake drums. | -53 | 0 |
| 1380550 | O | Hendrickson Wide Track IPO Standard Hendrickson Wide Track in place of standard front axle 71" KPI IPO 69" front axle for improved turning radius. | 0 | 15 |
| 1391410 | O | Gusseted Cam Brackets, Steer Axle | 0 | 0 |

Rear Axle & Equipment

| | | | | |
|---------|---|--|-------|----|
| 1513270 | O | Dana Spicer S21-172 Single Axle, 21000 lb | 2,474 | 94 |
| 1616300 | S | PHP10 Iron PreSet PLUS Hubs | 0 | 0 |
| 1671060 | O | Dana Spicer Trac-Lok Limited Slip Differential; S140/S14 Axles Only. Dana Spicer Trac-Loc Limited slip differential that improves traction for medium duty trucks. Trac-Lock is available on Spicer S140 single drive axle models with a gross axle weight rating from 17,000 lbs. up to 21,000 lbs. During a slip event, it automatically sends approximately three times more torque to the high-traction wheel-end. The Spicer Trac-Loc then returns to normal wheel-end differentiation as conditions change in order to deliver maximum vehicle handling. | 1,039 | 0 |
| 1680450 | O | Rear Brake Camshaft Reinforcement Rear brake camshaft reinforcement helps guard against wear and corrosion. | 11 | 9 |
| 1680490 | O | Gusseted Cam Brackets, Drive Axle(s) | 26 | 2 |
| 1680500 | S | SBM Valve Full trucks require a spring brake modulation (SBM) system for emergency braking application. This system requires an SBM valve and a relay valve with spring brakes on the rear axles. The SBM valve allows the foot valve to operate the rear axle spring brakes if a failure exists in the rear air system. | 0 | 0 |
| 1680795 | O | Diff Lock, Single Drive Axle with Speed Interlock | 1,042 | 30 |

Price Level: January 1, 2022

Deal: 536 Chassis Specs

Printed On: 7/6/2022 4:54:01 PM

Date: July 06, 2022

Quote Number: QUO-970234-D8P4P5



| Sales Code | Std/ Opt | Description | \$ List | Weight |
|------------|----------|---|---------|--------|
| 1680950 | S | Stability System Not Selected Or Not Available | 0 | 0 |
| 1682430 | S | Anti-Lock Braking System (ABS) 4S4M ABS-6. Includes air braking system. | 0 | 0 |
| 1683225 | O | SmarTire Tire Pressure Monitoring System Next generation TPMS. | 923 | 25 |
| 1684200 | S | Synthetic Axle Lubricant All Axles Peterbilt heavy duty models include Fuel Efficient Cognis EMGARD FE75W-90 which provides customers performance advantages over current synthetic lubricants with reduced gear wear and extended maintenance intervals, resulting in increased uptime. In addition, the lubricant provides improved fluid flow to protect gears in extreme cold conditions and withstand the stress from high temperatures, extending component life. | 0 | 0 |
| 1687010 | S | Bendix Air Cam Rear Drum Brakes 16.5x7 Bendix Air Cam Rear Drum Brakes to fit all heavy haul, construction, refuse and highway truck and tractor applications. Includes Automatic Slack Adjusters & Outboard Mounted Brake Drums. | 0 | 0 |
| 1705380 | O | Ratio 5.38 Rear Axle | 0 | 0 |
| 1811190 | S | Peterbilt Taper Leaf, 18,000 LBS | 0 | 0 |

Engine & Equipment

| | | | | |
|---------|---|--|-------|-----|
| 2074307 | O | PACCAR PX-9 300@2000 GOV@2200 860@1200 Productivity (2021 Emissions) | 9,601 | 475 |
| | | N21350 C121 75....Maximum Accelerator Pedal Ve | | |
| | | N21370 C128 75....Maximum Cruise Speed (P059) | | |
| | | N21460 C132 1400..Max PTO Speed (P046) | | |
| | | N21520 C133 5.....Timer Setting (P030) | | |
| | | N21610 C188 39....Low Ambient Temperature Thre | | |
| | | N21620 C189 60....Intermediate Ambient Tempera | | |
| | | N21630 C190 80....High Ambient Temperature Thr | | |
| | | N21550 C206 35....Engine Load Threshold (P516) | | |
| | | N21340 C209 120....Hard Maximum Speed Limit (P1 | | |
| | | N21510 C225 YES...Enable Idle Shutdown Park Br | | |
| | | N21450 C231 NO....Gear Down Protection (P026) | | |
| | | N21570 C233 NO....Idle Shutdown Manual Overrul | | |
| | | N21440 C234 NO....Engine Protection Shutdown (| | |
| | | N21480 C238 NO....Auto Engine Brake in Cruise | | |
| | | N21470 C239 NO....Cruise Control Auto Resume (| | |
| | | N21430 C333 0.....Reserve Speed Limit Offset (| | |
| | | N21410 C334 0.....Maximum Cycle Distance (N202 | | |
| | | N21590 C382 YES...Enable Hot Ambient Automatic | | |
| | | N21500 C395 0.....Expiration Distance (N209) | | |
| | | N21530 C396 YES...Enable Impending Shutdown Wa | | |
| | | N21540 C397 60....Timer For Impending Shutdown | | |
| | | N21320 C399 120....Standard Maximum Speed Limit | | |
| | | N21400 C400 252....Reserve Speed Function Reset | | |

Price Level: January 1, 2022

Deal: 536 Chassis Specs

Printed On: 7/6/2022 4:54:01 PM

Date: July 06, 2022

Quote Number: QUO-970234-D8P4P5



| Sales Code | Std/ Opt | Description | \$ List | Weight |
|------------|----------|---|---------|--------|
| | | N21420 C401 10....Maximum Active Distance (N20 N21330 C402 0.....Expiration Distance (N207) | | |
| 2091130 | S | VMUX Electronics Architecture | 0 | 0 |
| 2091305 | O | Engine Idle Shutdown Timer Enabled | 0 | 0 |
| 2091315 | O | Enable EIST Ambient Temp Override | 0 | 0 |
| 2091372 | | Eff EIST NA Expiration Miles | 0 | 0 |
| 2091640 | | Effective VSL Setting NA | 0 | 0 |
| 2092016 | O | Typical Operating Speed 62 MPH | 0 | 0 |
| 2092033 | O | Powertrain Optimized for Balance Best analysis for vehicles where service includes frequent start and stop cycles. | 0 | 0 |
| 2140220 | S | CARB Engine Idling Compliance DECLINED By Dealer/Customer | 0 | 0 |
| 2140670 | O | EPA Emission Warranty | 0 | 0 |
| 2513060 | S | PACCAR 160 Amp Alternator, Brushed PACCAR 160 AMP alternator, brushed producing 160 Amps at road speed and 100 Amps at idle. | 0 | 0 |
| 2521090 | O | Immersion Type Block Heater 110-120V Standard location for 2.1M and 1.9M models is left-hand under cab, Model 520 is in bumper, and for Model 220 it is at the driver step. Plug includes a weather-proof cover that protects the receptacle. This pre-heater keeps the coolant in the engine block from freezing when the engine is not running. | 82 | 2 |
| 2522110 | O | PACCAR 12V Starter, N/A PACCAR MX Engines PACCAR 12-volt electrical system. With centralized power distribution incorporating plug-in style relays. Circuit protection for serviceability, 12-volt light system w/circuit protection circuits number & color coded. | 0 | 0 |
| 2538040 | O | 3 PACCAR Premium 12V Dual Purpose Batt 2190 CCA Threaded stud type terminal. Stranded copper battery cables are double aught (00) or larger to reduce resistance. | 302 | 62 |
| 2539410 | O | Battery Jumper Terminal Mounted Under Hood LH Frame Rail. Not available with PX-7 engines. | 113 | 4 |
| 2539840 | O | MD - Battery Disconnect Switch Mounted on Battery Box | 398 | 9 |
| 2621030 | O | On/Off Fan Clutch On/Off Fan Clutch provides increased torque to provide engine cooling to prevent the engine from overheating. | 341 | 0 |
| 2723210 | S | 18.7 CFM Air Compressor N/A X15. Furnished on engine. Teflon lined stainless steel braided compressor discharge line. | 0 | 0 |
| 2812210 | S | VGT Exhaust Brake | 0 | 0 |

Price Level: January 1, 2022

Deal: 536 Chassis Specs

Printed On: 7/6/2022 4:54:01 PM

Date: July 06, 2022

Quote Number: QUO-970234-D8P4P5



| Sales Code | Std/ Opt | Description | \$ List | Weight |
|------------|----------|---|---------|--------|
| | | (Variable Geometry Turbo). Provides approximately 90-100 HP of retardation and is part of the turbocharger. | | |
| 2921110 | S | PACCAR Fuel/Water Separator Standard Service PACCAR Fuel/Water separator standard service intervals. High efficiency media protects critical engine components. | 0 | 0 |
| 2921210 | S | No Fluid Heat Option for Fuel Filter | 0 | 0 |
| 2921310 | S | No Electric Heat Option for Fuel Filter | 0 | 0 |
| 3010400 | O | Engine Protection Shutdown w/ Label Includes oil pressure, oil temperature, coolant temperature, and intake manifold temperature. | 5 | 0 |
| 3114270 | S | High Efficiency Cooling System Cooling module is a combination of steel and aluminum components, with aluminum connections to maximize performance and cooling capability. Silicone radiator & heater hoses enhance value, durability, & reliability. Constant tension band clamps reduce leaks. Chevron Delo Extended Life Coolant (NOAT) extends maintenance intervals reducing maintenance costs. Anti-freeze effective to -30 degrees F helps protect the engine. Low coolant level sensor warns of low coolant condition to prevent engine damage. Radiator Size by Model: 579/367 FEPTO 1325 sq in, 567/365/367: 1440 sq in, 365 FEPTO: 1184 sq in, 389/367 HH: 1669 sq in, 348: 1000 sq in, 520: 1242 sq in. | 0 | 0 |
| 3211140 | S | (1) Air Cleaner Engine Mounted | 0 | 0 |
| 3365270 | O | Exhaust Single RH Side of Cab DPF/SCR right-hand Under Cab. | 2,375 | 187 |
| 3383040 | O | DPF Regeneration Switch Remove Stop Position | 0 | 0 |
| 3387880 | O | 7" Dia Chrome Plated Steel Standpipe(s) IPO 5" | 159 | 1 |
| 3387890 | O | 36" Ht, 5" Dia Chrome, Clear Coat Standpipe(s) | 208 | 4 |

Transmission & Equipment

| | | | | |
|---------|---|---|-------|-----|
| 4052110 | O | Allison 3000 RDS-P Transmission, Gen 5 Rugged Duty Series. Includes Rear Transmission Support except on MX engines, Mobil Delvac Automatic Transmission Fluid, and Water-Oil Heat Exchange. Also includes features that monitor the transmission fluid, filter and clutch condition. Will display percent life remaining for the transmission fluid, filter and clutches on the shift selector. This information may be displayed using the Mode and Up and Down buttons. A wrench icon will also be included to indicate when the transmission fluid, filter or clutches need servicing. Suited for vehicles operating on/off highway and/or requiring PTO operation. Forward ratios: 1st-3.49, 2nd-1.86, 3rd-1.41, 4th-1.00, 5th-0.75, 6th-0.65. Reverse ratios: DR-(5.03). | 8,997 | 459 |
| 4210080 | O | 1710 HD Driveline, 1 Midship Bearing | 308 | 75 |
| 4240010 | O | Allison Transmission Oil Cooler | 481 | 13 |

Price Level: January 1, 2022

Deal: 536 Chassis Specs

Printed On: 7/6/2022 4:54:01 PM

Date: July 06, 2022

Quote Number: QUO-970234-D8P4P5



| Sales Code | Std/ Opt | Description | \$ List | Weight |
|------------------------------------|----------|--|---------|--------|
| | | Aero with Allison 4000 or high torque PX-9 | | |
| 4252890 | O | Allison FuelSense 2.0 Not Desired | 0 | 0 |
| 4252940 | O | Allison Neutral At Stop Neutral at Stop features and benefits: Reduces or eliminates the load on the engine when vehicle is stopped, can help lower fuel consumption and CO2 emissions, and is included in FuelSense 2.0 Plus and Max packages only. | 0 | 0 |
| 4256640 | O | Allison 6-Speed Configuration, Close Ratio Gears 3000 Series Transmissions. | 0 | 0 |
| 4256920 | O | Dash Mounted Push Button Shifter Available with Allison transmissions | 513 | 3 |
| 4257110 | O | LH Mounted Trans PTO Provisions | 35 | 0 |
| Air & Trailer Equipment | | | | |
| 4510190 | S | Bendix AD-HF Air Dryer, Heater Bendix AD-HF air filters protect the life of your engine system and components. Proven PuraGuard oil coalescing technology in the air dryer cartridge. This oil coalescing filter ensures the removal of oil and oil aerosols before they can contaminate the moisture removing desiccant. | 0 | 0 |
| 4540420 | S | Nylon Chassis Hose | 0 | 0 |
| 4543320 | S | Steel Painted Air Tanks All air tanks are steel with painted finish except when Code 4543330 Polish Aluminum Air Tanks is also selected (then exposed air tanks outside the frame rails will be polished aluminum). Peterbilt will determine the optimal size and location of required air tanks. Narratives requesting a specific air tank size or location will not be accepted for factory installation. See ECAT to determine number or location of air tanks installed. | 0 | 0 |
| Tires & Wheels | | | | |
| 5004210 | S | FF: CN 14ply 295/75R22.5 Conti HSL3 | 0 | 0 |
| 5104210 | S | RR: CN 14ply 295/75R22.5 Conti HSL3 | 0 | 0 |
| 5190004 | O | Code-rear Tire Qty 04 | 0 | 0 |
| 5211020 | S | FF: Accur Std Armor 51455PK 22.5X8.25 PHP10-5 hand holes. | 0 | 0 |
| 5311020 | S | RR: Accur Std Armor 51455PK 22.5X8.25 PHP10-5 hand holes. | 0 | 0 |
| 5390004 | O | Code-rear Rim Qty 04 | 0 | 0 |
| Fuel Tanks | | | | |
| 5584070 | O | D-Shaped Aluminum 60 Gallon Fuel Tank LH U/C | 89 | -5 |



| Sales Code | Std/ Opt | Description | \$ List | Weight |
|---------------------------------|----------|---|---------|--------|
| | | Non-slip step LH under cab | | |
| 5602060 | O | Location LH U/C 60 Gallon | 0 | 0 |
| 5652890 | S | DEF Tank Mounted LH BOC Models 220 and 520 mounted left hand back-of-cab. | 0 | 0 |
| 5652980 | S | DEF To Fuel Ratio Between 1:1 And 2:1 | 0 | 0 |
| 5655019 | S | DEF Tank Small, HD 14 Gal 2.1M MD 5.5 Gal | 0 | 0 |
| Battery Box & Bumper | | | | |
| 6010780 | O | Aluminum Space Saver Battery Box RH BOC Battery access from side | 196 | -84 |
| 6030540 | O | Polish Battery/Tool Box(s), Aftertreatment Cab Entry complete | 437 | 0 |
| 6040550 | O | Aftertreatment Aluminum Non-Slip Cab Entry Aftertreatment right-hand under cab step. DPF/SCR for diesel engines, catalyst for natural gas engines. On Models 579 specifying chassis fairings, the box is aerodynamic. | 0 | 0 |
| 6121770 | O | Steel Bumper Tapered Painted Two tow points, painted same color as frame. ***Warning*** Due to a new legal regulations, all New Medium Duty trucks require headlights to be located in the bumper when the chassis height is GREATER than the following chassis height: Measurement to bottom of frame at front of frame: for the 107 Aero Hood 32.6, for the 109 Aero Hood 31.4, for the 109 Vocational Hood 26.7. Work with applications if your chassis height is unacceptable. | 463 | 40 |
| Cab & Equipment | | | | |
| 6510160 | O | Aerodynamic 109in BBC Aluminum Cab & SMC Hood With molded gray crown. | 1,163 | 15 |
| 6540160 | O | Thermal Insulation Package in Cab The thermal insulation package is designed to make the cab thermally efficient in extreme temperatures. The model 520 adds insulation surrounding the doghouse to reduce engine heat transmitted to the cab. | 67 | 2 |
| 6917340 | O | Peterbilt Premium Driver Seat | 118 | 4 |
| 6927340 | O | Peterbilt Premium Passenger Seat | 53 | 14 |
| 6930230 | O | Seat Skirt - All Eligible Air Seats | 24 | 2 |
| 6930580 | O | Drivers Armrests - LH & RH | 56 | 4 |
| 6931120 | O | Seat Belt Color Orange IPO Standard Black | 10 | 0 |
| 6937040 | O | Cloth Driver | 0 | 0 |
| 6937050 | O | Cloth Passenger | 0 | 0 |



| Sales Code | Std/ Opt | Description | \$ List | Weight |
|-------------------|-----------------|---|----------------|---------------|
| 6939390 | O | Seat Belt Alarm System Driver and Passenger Seats Seat belt alarm system driver and passenger seats. Radio mute when seat belt warning active and compatible radio. Driver/Passenger feature to alert occupants if the seat belt is not buckled. Light will appear in the dash when vehicle has key power turned on as well as a seat belt "chime" will alert the occupants as the vehicle travels at an increased speed. | 114 | 0 |
| 6939400 | S | Air Ride Driver | 0 | 0 |
| 6939420 | O | High Back Driver | 44 | 0 |
| 6939500 | O | Air Ride Passenger | 119 | 0 |
| 6939520 | O | High Back Passenger | 8 | 0 |
| 7000025 | O | Steering Wheel With Multi-Function Includes Peterbilt logo on horn button , audio volume, seek, mute and mode button on LH pod with cruise control on/off/cancel, set/resume and accelerate/coast on the right pod. | 246 | 4 |
| 7000045 | O | High-Visibility Interior Grabhandles, Painted Bright yellow interior grabhandle for vocational vehicles. | 65 | 0 |
| 7001520 | S | Adjustable Steering Column - Tilt/Telescope | 0 | 0 |
| 7036130 | O | Probilt Interior Grey/Black - Curved Roof | 176 | 0 |
| 7110680 | O | Exterior Cab Entry Grabhandle Textured; NFPA compliant. Available on Day Cab specifications only. | 169 | 0 |
| 7210510 | O | 3-Piece Glass Rear Cab Window, All Pieces Fixed | 157 | 12 |
| 7210540 | S | Day Cab Rear Window Day cab rear window flush to back of cab. | 0 | 0 |
| 7230060 | S | 1-Piece Curved Windshield | 0 | 0 |
| 7230360 | S | Power Door Locks and Power Window Lifts Standard | 0 | 0 |
| 7322010 | S | Combo Fresh Air Heater/Air Conditioner With radiator mounted condenser, dedicated side window defrosters, Bi-Level Heater/Defroster Controls, 54,500 BTU/HR, and silicone heater hoses. | 0 | 0 |
| 7510060 | O | Aero Rear View Mirror Housing, Bright Finish | 173 | 3 |
| 7514010 | O | Peterbilt Aero Rear View Mirror, Motorized Includes top mirror with motorized, adjustable dual axis heated glass. Bottom mirror is an integrated convex surface. Includes black textured arms with breakaway feature. | 257 | 3 |
| 7514050 | S | Look Down Mirror Over Passenger Door with Black Housing | 0 | 0 |
| 7620040 | O | (2) Air Horns Round, 26" Length | 278 | 16 |

Price Level: January 1, 2022

Deal: 536 Chassis Specs

Printed On: 7/6/2022 4:54:01 PM

Date: July 06, 2022

Quote Number: QUO-970234-D8P4P5



| Sales Code | Std/ Opt | Description | \$ List | Weight |
|------------|----------|---|---------|--------|
| | | Roof mounted. Round horn shield. | | |
| 7721050 | O | Satellite Radio Requires USB port and bluetooth for phone and audio. | 222 | 0 |
| 7722120 | O | ConcertClass, AM/FM, Weatherband, 3.5 Aux | 331 | 11 |
| 7725710 | O | Standard Speaker Package For Cab (2) Speakers | 50 | 4 |
| 7728030 | O | Radio Mute When In Reverse For automatic or automated transmission | 0 | 0 |
| 7728040 | O | Bluetooth Phone and Audio Requires USB Port | 38 | 0 |
| 7728050 | O | USB Port | 38 | 0 |
| 7851480 | S | Peterbilt Electric Windshield Wipers With Intermittent Feature. | 0 | 0 |
| 7852020 | O | Cab Air Suspension | 177 | 15 |
| 7852050 | O | Auto Reset Circuit Protection Daycab and Sleeper | 19 | 0 |
| 7900090 | O | Triangle Reflector Kit, Ship Loose Florescent triangle emergency road flares are designed to meet and exceed all DOT standards. | 18 | 13 |
| 7900310 | O | Fire Extinguisher, Mounted Outboard Driver Seat Hazmat approval UL listed/rated ABC | 56 | 9 |
| 7900970 | O | Backup Alarm Wiring To EOF | 14 | 6 |
| 8011850 | O | Transmission Oil Temperature (Main) Located in Digital Cluster Display. | 24 | 0 |
| 8021380 | S | Air Restriction Indicator Mounted on air cleaner, intake piping, or firewall | 0 | 0 |
| 8070030 | O | Up to (12) Additional Electric Switches Up to (12) additional electric switches without wiring. Switch will short pin 5 to 4 when off and pin5 to 6 when on. Backlighting provided by Lin jumper. | 312 | 2 |
| 8070250 | O | Switch & Wiring For F/O Snow Plow Light Install. Switch and wiring for furnished by owner snow plow light installation. J168 on chassis harness. | 192 | 0 |
| 8070860 | S | Main Instrumentation Panel Digital Cluster 7" Display includes: Physical (Analog) - Speedometer, Tachometer, Oil Pressure, Coolant Temp and Display Gauges - Fuel Level, DEF Level, DPF Filter Status, Fuel Economy, Volts Telltale, OAT and Primary Air Pressure, Secondary Air Pressure for air brake trucks. | 0 | 0 |
| 8111110 | S | Headlights Composite Fender Mounted Integral park, turn, and side marker | 0 | 0 |
| 8120980 | S | (5) Marker Lights, Aero LED | 0 | 0 |
| 8132210 | O | (1) 6 in Spotlight, Round Halogen LH (1) 6" spotlight, round halogen left hand side. | 164 | 4 |

Price Level: January 1, 2022

Deal: 536 Chassis Specs

Printed On: 7/6/2022 4:54:01 PM

Date: July 06, 2022

Quote Number: QUO-970234-D8P4P5



| Sales Code | Std/ Opt | Description | \$ List | Weight |
|------------|----------|--|---------|--------|
| 8133470 | O | Switch & Wiring for F/O Beacon/Strobe Switch and wiring for furnished by owner beacon / strobe, 10' coiled wire back-of-cab / back-of-sleeper, at rear sill. | 74 | 2 |
| 8134160 | S | Self-Canceling Turn Signal | 0 | 0 |
| 8140080 | S | LED Stop/Turn/Tail/Backup Bracket mounted left-hand / right-hand end of frame | 0 | 0 |
| 8140850 | S | Moveable EOF Crossmember For Mounting Tail Lights Square end of frame with or without end of frame crossmember | 0 | 0 |

Paint

| | | | | |
|---------|---|--|------|---|
| 8500710 | O | Standard Paint Color Selection | -200 | 0 |
| 8530770 | S | (1) Color Axalta Two Stage - Cab/Hood Base Coat/Clear Coat N85020 A - L0006EY WHITE N85700 BUMPER L0001EA BLACK N85500 CAB ROOF L0006EY WHITE N85300 FENDER L0006EY WHITE N85200 FRAME L0001EA BLACK N85400 HOOD TOP L0006EY WHITE | 0 | 0 |

Shipping Destination

Options Not Subject To Discount

| | | | | |
|---------|---|---|------|---|
| 9400091 | S | Peterbilt Class 7 Standard Coverage 1 year/Unlimited Miles/km | 0 | 0 |
| 9407103 | O | Prepaid Freight Increase For 2022 Delivery | -500 | 0 |
| 9408703 | O | Base Warr: Emissions 5YR/100K MI-EPA Engine | 0 | 0 |

Miscellaneous

| | | | | |
|---------|---|---------------------------------|---|---|
| 9409041 | S | Aero Hood (MODEL 536) | 0 | 0 |
| 9409096 | O | State Registry: Virginia | 0 | 0 |

Promotions

Order Comments



| | |
|---|-----------|
| Total List Price (W/O Freight & Warranty & Surcharges) | \$134,189 |
| Marketing and Service Support Fee | \$670 |
| Prepaid Freight | \$2,800 |
| Total Surcharge/Options Not Subject To Discount | \$-500 |
| Total Weight | 11,804 |

Prices and Specifications Subject to Change Without Notice.

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in CRM.

PRICING DISCLAIMER

While we make every effort to maintain the web site to preserve pricing accuracy, prices are subject to change without notice. Although the information in this price list is presented in good faith and believed to be correct at the time of printing, we make no representations or warranties as to the completeness or accuracy of this information. We reserve the right to change, delete or otherwise modify the pricing information which is represented herein without any prior notice. We carefully check pricing specifications, but occasionally errors can occur, therefore we reserve the right to change such prices without notice. We disclaim all liability for any errors or omissions in the materials. In no event will we be responsible for any damages of any nature whatsoever from the reliance upon information from these materials. Please check your order prebills to confirm your pricing information



Shipping Destinations

Intermediate Destination: NONE

| Final Destinations | Quantity |
|--------------------|----------|
|--------------------|----------|