



Peterbilt of Richmond (H830)  
2800A Deepwater Terminal  
Richmond, Virginia 23212

Virginia Sheriffs Association  
901 East Byrd St Suite 1301  
Richmond, Virginia 23219  
United States of America

David Askew  
Cell Phone:  
Office Phone:  
Email: daskew@thepetestore.com

Kaylyn Mitman  
Office Phone: 919-459-6471  
Email: kmitman@virginiasheriffs.org

## Vehicle Summary

Unit		Chassis	
Model:	Model 537	Fr Axle Load (lbs):	12000
Type:	Full Truck	Rr Axle Load (lbs):	21000
Description 1:	537 Chassis	G.C.W. (lbs):	33000
Description 2:	537 Chassis Options		
Application		Road Conditions:	
Intended Serv.:	Snowplow	Class A (Highway)	100
Commodity:	Other Commodity	Class B (Hwy/Mtn)	0
		Class C (Off-Hwy)	0
		Class D (Off-Road)	0
Body		Maximum Grade:	
Type:	End Dump		6
Length (ft):	24	Wheelbase (in):	175
Height (ft):	13.5	Overhang (in):	60
Max Laden Weight (lbs):	1000	Fr Axle to BOC (in):	69.5
Trailer		Cab to Axle (in):	105.5
No. of Trailer Axles:	0	Cab to EOF (in):	165.5
Type:		Overall Comb. Length (in):	275
Length (ft):	0	Special Req.	
Height (ft):	0		
Kingpin Inset (in):	0		
Corner Radius (in):	0		
Restrictions			
Length (ft):	40		
Width (in):	102		
Height (ft):	13.5		

Approved by: \_\_\_\_\_

Date: \_\_\_\_\_

Note: All sales are F.O.B. designated plant of manufacture.



Sales Code	Std/ Opt	Description	\$ List	Weight
<b>Base Model</b>				
0005371	S	<b>Model 537</b> The Peterbilt Model 537 is highly versatile to take on the big jobs. It is available as a Class 7 truck or tractor with a GVW up to 33,000 lbs. With a full range of suspensions and an available all-wheel-drive configuration, the 537 is the perfect match for applications such as wrecker, tanker, beverage delivery, and municipal utilities just about any job you can throw at it.	98,059	<b>9,870</b>
0091200	S	<b>Other Commodity</b>	0	<b>0</b>
0093150	O	<b>Snowplow</b> Truck which is configured for mounting a snowplow to the front. May also have dump or other body.	0	<b>0</b>
0095170	O	<b>End Dump</b>	0	<b>0</b>
0098170	S	<b>United States Registry</b> Canadian Registry Package Requires Air Conditioning Excise Tax Canada, Speedometer to be KPH ipo MPH, Daytime Running Lights and Rubber Battery Pad in Bottom of Battery Box.	0	<b>0</b>
<b>Configuration</b>				
0200700	S	<b>Not Applicable</b> Secondary Manufacturer	0	<b>0</b>
<b>Frame &amp; Equipment</b>				
0514000	O	<b>10-3/4" Steel Rails To 354"</b> 10.75x3.5x.375 Dimension, 2,136,000 RBM; Yield Strength: 120,000 psi. Section Modulus: 17.8 cubic inches. Weight: 1.74 lbs/inch pair	609	<b>231</b>
0601500	O	<b>Full Steel Inner Liner</b>	1,759	<b>489</b>
0611300	O	<b>Heavy Duty 5-Piece Crossmember BOC IPO Standard</b> Class 5, 6, 7	17	<b>20</b>
0611330	O	<b>Zinc Coated Anti Corrosion Treated Frame Rails</b> Requires Frame Rail Code. Zinc Phosphate coating will replace the standard frame rail primer and provide added corrosion prevention for your customer's operating in severe conditions or in climates where vehicle rust is common.	362	<b>2</b>
0611790	O	<b>Aluminum Frame Rail Crossmembers</b> Excludes suspension	144	<b>0</b>
0644090	S	<b>EOF Square without Crossmember</b> End-of-frame square without crossmember. For use with body builder installed crossmember.	0	<b>0</b>
0651090	S	<b>Omit Rear Mudflaps and Hangers</b>	0	<b>0</b>
<b>Front Axle &amp; Equipment</b>				
1012130	O	<b>Meritor MFS+12 12,000 lb, 3.5 in. Drop</b> Axle is designed for applications with a gross axle weight rating (GAWR) of 12,000 pounds. Axles include special low-friction bushings,	64	<b>-8</b>

Price Level: January 1, 2022

Deal: 537 Chassis

Printed On: 7/6/2022 5:11:30 PM

Date: July 07, 2022

Quote Number: QUO-970236-Q2Y3P4



Sales Code	Std/ Opt	Description	\$ List	Weight
		double draw keys and integral thrust bearing and seal design for durability, low maintenance and ease of service		
1111190	O	<b>Taper Leaf Springs, Shocks 12,000 lb</b> Hendrickson taper leaf springs, shocks for 12,000 lbs.	204	169
1243040	S	<b>Power Steering Sheppard HD94</b> Sheppard HD94 power steering gear is a light weight version of heavy duty line-haul power steering gear. For use with 10,000 to 13,200 lb. axle ratings.	0	0
1250180	O	<b>Power Steering Reservoir Frame Mounted</b> The power steering reservoir is a steering system that eases drivability by applying hydraulic pressure to the steering gear.	0	0
1354850	O	<b>PHP10 Iron PreSet PLUS Hubs - Air Disc</b> Preset iron hub assemblies are designed for demanding conditions and require less maintenance while still offering dependability and superior performance. Precisely engineered to minimize roller stress under heavy loads and increase bearing life when used in demanding conditions such as wide-based single wheels and misalignment due to spindle wear.	1,046	27
1380290	O	<b>Bendix Air Disc Front Brakes</b> Bendix air disc front brakes use a floating caliper design to provide foundation braking on all axles and complies with reduced stopping distance regulations.	-84	30
1380470	O	<b>Meritor Wide Track IPO Standard, Front Axle</b> Meritor wide track front axle offers greater turning radius and ease of service. MFS+ 3.5" Drop / MFS 3.74" Drop. 71in KPI IPO 69in with MFS and MFS+ axles.	0	15
<b>Rear Axle &amp; Equipment</b>				
1511940	S	<b>Meritor MS21-14X 21,000 LB</b> MS-14X single rear drive axles have hypoid-generoid gearing options that offer long life and increased durability. Rigid differential cases offer precise gear alignment and durability. Optional driver-controlled differential lock (DCDL) maximizes traction and spinout protections in slippery conditions.	0	0
1616295	O	<b>PHP10 Aluminum Preset PLUS Hubs - Air Disc</b>	896	0
1680500	S	<b>SBM Valve</b> Full trucks require a spring brake modulation (SBM) system for emergency braking application. This system requires an SBM valve and a relay valve with spring brakes on the rear axles. The SBM valve allows the foot valve to operate the rear axle spring brakes if a failure exists in the rear air system.	0	0
1680795	O	<b>Diff Lock, Single Drive Axle with Speed Interlock</b>	1,042	30
1680950	S	<b>Stability System Not Selected Or Not Available</b>	0	0
1682430	S	<b>Anti-Lock Braking System (ABS) 4S4M</b> ABS-6. Includes air braking system.	0	0
1684200	S	<b>Synthetic Axle Lubricant All Axles</b>	0	0

Price Level: January 1, 2022

Deal: 537 Chassis

Printed On: 7/6/2022 5:11:30 PM

Date: July 07, 2022

Quote Number: QUO-970236-Q2Y3P4



Sales Code	Std/ Opt	Description	\$ List	Weight
		Peterbilt heavy duty models include Fuel Efficient Cognis EMGARD FE75W-90 which provides customers performance advantages over current synthetic lubricants with reduced gear wear and extended maintenance intervals, resulting in increased uptime. In addition, the lubricant provides improved fluid flow to protect gears in extreme cold conditions and withstand the stress from high temperatures, extending component life.		
1687080	O	<b>Air Disc Rear Brakes, Single Drive Axle</b>	2,059	<b>0</b>
1705570	O	<b>Ratio 5.57 Rear Axle</b>	0	<b>0</b>
1816140	S	<b>Reyco 79KB Taper Leaf 21,000 lb</b>	0	<b>0</b>
1911280	O	<b>Reyco Helper Springs 3,000 lb</b> For use with Reyco 79KB suspension	350	<b>60</b>
1920380	O	<b>Heavy-Duty Shock Absorbers - Reyco 102/79KB</b> Single Drive Suspension Only	349	<b>30</b>
<b>Engine &amp; Equipment</b>				
2074407	O	<b>PACCAR PX-9 330@2000 GOV@2200 1000@1200</b> Productivity (2021 Emissions)	10,648	<b>475</b>
		N21350 C121 75....Maximum Accelerator Pedal Ve N21370 C128 75....Maximum Cruise Speed (P059) N21460 C132 1400..Max PTO Speed (P046) N21520 C133 5.....Timer Setting (P030) N21610 C188 39....Low Ambient Temperature Thre N21620 C189 60....Intermediate Ambient Tempera N21630 C190 80....High Ambient Temperature Thr N21550 C206 35....Engine Load Threshold (P516) N21340 C209 120...Hard Maximum Speed Limit (P1 N21510 C225 YES...Enable Idle Shutdown Park Br N21450 C231 NO....Gear Down Protection (P026) N21570 C233 NO....Idle Shutdown Manual OVERRUL N21440 C234 NO....Engine Protection Shutdown (P N21480 C238 NO....Auto Engine Brake in Cruise N21470 C239 NO....Cruise Control Auto Resume (P N21430 C333 0.....Reserve Speed Limit Offset (P N21410 C334 0.....Maximum Cycle Distance (N202) N21590 C382 YES...Enable Hot Ambient Automatic N21500 C395 0.....Expiration Distance (N209) N21530 C396 YES...Enable Impending Shutdown Wa N21540 C397 60....Timer For Impending Shutdown N21320 C399 120...Standard Maximum Speed Limit N21400 C400 252...Reserve Speed Function Reset N21420 C401 10....Maximum Active Distance (N207) N21330 C402 0.....Expiration Distance (N207)		
2091130	S	<b>VMUX Electronics Architecture</b>	0	<b>0</b>

Price Level: January 1, 2022

Deal: 537 Chassis

Printed On: 7/6/2022 5:11:30 PM

Date: July 07, 2022

Quote Number: QUO-970236-Q2Y3P4



<b>Sales Code</b>	<b>Std/ Opt</b>	<b>Description</b>	<b>\$ List</b>	<b>Weight</b>
2091305	O	<b>Engine Idle Shutdown Timer Enabled</b>	0	0
2091315	O	<b>Enable EIST Ambient Temp Override</b>	0	0
2091372		<b>Eff EIST NA Expiration Miles</b>	0	0
2091640		<b>Effective VSL Setting NA</b>	0	0
2092016	O	<b>Typical Operating Speed 62 MPH</b>	0	0
2092033	O	<b>Powertrain Optimized for Balance</b> Best analysis for vehicles where service includes frequent start and stop cycles.	0	0
2140220	S	<b>CARB Engine Idling Compliance DECLINED By</b> Dealer/Customer	0	0
2140450	O	<b>Remote PTO/Throttle, 12-Pin</b> Eng Bay Remote Control Provision	54	0
2140670	O	<b>EPA Emission Warranty</b>	0	0
2513060	S	<b>PACCAR 160 Amp Alternator, Brushed</b> PACCAR 160 AMP alternator, brushed producing 160 Amps at road speed and 100 Amps at idle.	0	0
2522110	O	<b>PACCAR 12V Starter, N/A PACCAR MX Engines</b> PACCAR 12-volt electrical system. With centralized power distribution incorporating plug-in style relays. Circuit protection for serviceability, 12-volt light system w/circuit protection circuits number & color coded.	0	0
2538040	O	<b>3 PACCAR Premium 12V Dual Purpose Batt 2190 CCA</b> Threaded stud type terminal. Stranded copper battery cables are double aught (00) or larger to reduce resistance.	302	62
2539410	O	<b>Battery Jumper Terminal Mounted Under Hood</b> LH Frame Rail. Not available with PX-7 engines.	113	4
2539840	O	<b>MD - Battery Disconnect Switch</b> Mounted on Battery Box	398	9
2621030	O	<b>On/Off Fan Clutch</b> On/Off Fan Clutch provides increased torque to provide engine cooling to prevent the engine from overheating.	341	0
2723210	S	<b>18.7 CFM Air Compressor</b> N/A X15. Furnished on engine. Teflon lined stainless steel braided compressor discharge line.	0	0
2812210	S	<b>VGT Exhaust Brake</b> (Variable Geometry Turbo). Provides approximately 90-100 HP of retardation and is part of the turbocharger.	0	0
2921110	S	<b>PACCAR Fuel/Water Separator Standard Service</b> PACCAR Fuel/Water separator standard service intervals. High efficiency media protects critical engine components.	0	0
2921220	O	<b>Fuel Heat for Fuel Filter</b>	49	0
2921320	O	<b>12V Heat for Fuel Filter</b>	61	0

Price Level: January 1, 2022

Deal: 537 Chassis

Printed On: 7/6/2022 5:11:30 PM

Date: July 07, 2022

Quote Number: QUO-970236-Q2Y3P4



Sales Code	Std/ Opt	Description	\$ List	Weight
		Fuel filter heaters help ensure a seamless flow of diesel from the tank to the combustion chamber. Eliminating any possibility of moisture freezing within the fuel filter while simultaneously increasing the fuel temperature for atomization within the engine.		
3010400	O	<b>Engine Protection Shutdown w/ Label</b> Includes oil pressure, oil temperature, coolant temperature, and intake manifold temperature.	5	0
3114270	S	<b>High Efficiency Cooling System</b> Cooling module is a combination of steel and aluminum components, with aluminum connections to maximize performance and cooling capability. Silicone radiator & heater hoses enhance value, durability, & reliability. Constant tension band clamps reduce leaks. Chevron Delo Extended Life Coolant (NOAT) extends maintenance intervals reducing maintenance costs. Anti-freeze effective to -30 degrees F helps protect the engine. Low coolant level sensor warns of low coolant condition to prevent engine damage. Radiator Size by Model: 579/367 FEPTO 1325 sq in, 567/365/367: 1440 sq in, 365 FEPTO: 1184 sq in, 389/367 HH: 1669 sq in, 348: 1000 sq in, 520: 1242 sq in.	0	0
3211140	S	<b>(1) Air Cleaner Engine Mounted</b>	0	0
3365270	O	<b>Exhaust Single RH Side of Cab</b> DPF/SCR right-hand Under Cab.	2,375	187
3381770	O	<b>Curved Tip Standpipe(s)</b>	39	1
3387880	O	<b>7" Dia Chrome Plated Steel Standpipe(s) IPO 5"</b>	159	1
3387890	O	<b>36" Ht, 5" Dia Chrome, Clear Coat Standpipe(s)</b>	208	4
<b>Transmission &amp; Equipment</b>				
4052110	O	<b>Allison 3000 RDS-P Transmission, Gen 5</b> Rugged Duty Series. Includes Rear Transmission Support except on MX engines, Mobil Delvac Automatic Transmission Fluid, and Water-Oil Heat Exchange. Also includes features that monitor the transmission fluid, filter and clutch condition. Will display percent life remaining for the transmission fluid, filter and clutches on the shift selector. This information may be displayed using the Mode and Up and Down buttons. A wrench icon will also be included to indicate when the transmission fluid, filter or clutches need servicing. Suited for vehicles operating on/off highway and/or requiring PTO operation. Forward ratios: 1st-3.49, 2nd-1.86, 3rd-1.41, 4th-1.00, 5th-0.75, 6th-0.65. Reverse ratios: DR-(5.03).	8,997	459
4211000	O	<b>SPL170 HD-XL Driveline, 1 Midship Bearing</b>	735	95
4252890	O	<b>Allison FuelSense 2.0 Not Desired</b>	0	0
4252940	O	<b>Allison Neutral At Stop</b> Neutral at Stop features and benefits: Reduces or eliminates the load on the engine when vehicle is stopped, can help lower fuel consumption and CO2 emissions, and is included in FuelSense 2.0 Plus and Max	0	0

Price Level: January 1, 2022

Deal: 537 Chassis

Printed On: 7/6/2022 5:11:30 PM

Date: July 07, 2022

Quote Number: QUO-970236-Q2Y3P4



Sales Code	Std/ Opt	Description	\$ List	Weight
		packages only.		
4256640	O	<b>Allison 6-Speed Configuration, Close Ratio Gears</b> 3000 Series Transmissions.	0	0
4256920	O	<b>Dash Mounted Push Button Shifter</b> Available with Allison transmissions	513	3
4257110	O	<b>LH Mounted Trans PTO Provisions</b>	35	0
<b>Air &amp; Trailer Equipment</b>				
4510210	O	<b>Bendix AD-HF EP Air Dryer, Heater</b> Coalescing filter, extended purge. Bendix AD-HF air filters protects the life of your engine system and components. Proven PuraGuard oil coalescing technology in the the air dryer cartridge. This oil coalescing filter ensures the removal of oil and oil aerosols before they can contaminate the moisture removing desiccant.	210	-2
4520420	O	<b>Pull Cords All Air Tanks</b>	6	0
4540420	S	<b>Nylon Chassis Hose</b>	0	0
4543320	S	<b>Steel Painted Air Tanks</b> All air tanks are steel with painted finish except when Code 4543330 Polish Aluminum Air Tanks is also selected (then exposed air tanks outside the frame rails will be polished aluminum). Peterbilt will determine the optimal size and location of required air tanks. Narratives requesting a specific air tank size or location will not be accepted for factory installation. See ECAT to determine number or location of air tanks installed.	0	0
4543330	O	<b>Aluminum Polished Air Tanks</b> Exposed air tanks outside the frame rails will be polished aluminum. Air tanks mounted inside the frame rails or covered by other components will be either painted aluminum (4543340) or painted steel (4543320) air tanks depending on air tank option selected.	260	0
4611930	O	<b>Body Connections 5' BOC</b> Junction box contains light and power circuits for body connections located 5' from back-of-cab	82	4
<b>Tires &amp; Wheels</b>				
5056840	O	<b>FF: MN 16ply 11R22.5 X Line Energy Z</b> Efficiency Rating: Fair The MICHELIN X LINE ENERGY Z tire is a line haul steer tire built for high miles and better rolling resistance. Diameter= 41.3 inches; SLR= 19.3 inches	411	8
5156120	O	<b>RR: MN 16ply 11R22.5 X Multi D</b> Efficiency Rating: Poor Diameter= 41.4 inches; SLR= 19.4 inches	1,416	56
5190004	O	<b>Code-rear Tire Qty 04</b>	0	0

Price Level: January 1, 2022

Deal: 537 Chassis

Printed On: 7/6/2022 5:11:30 PM

Date: July 07, 2022

Quote Number: QUO-970236-Q2Y3P4





Sales Code	Std/ Opt	Description	\$ List	Weight
5220600	O	<b>FF: Peterbilt 88U677 22.5X8.25 High Polish</b> Aluminum, Ultra ONE technology.	334	-40
5320600	O	<b>RR: Peterbilt 88U677 22.5X8.25 High Polish</b> Aluminum. Ultra ONE technology.	668	-80
5390004	O	<b>Code-rear Rim Qty 04</b>	0	0
5407640	O	<b>FF: Mirror Polish Wheels, Outer Surface</b> Single/tandem steer. Mirror Polish outer surface of outer wheel. Without chrome wheel nuts.	65	0
5407650	O	<b>RR: Mirror Polish Wheels, Outer Surface, Single</b> Drive without chrome wheel nuts. Mirror polish outer surface of outer wheel.	251	0
<b>Fuel Tanks</b>				
5584070	O	<b>D-Shaped Aluminum 60 Gallon Fuel Tank LH U/C</b> Non-slip step LH under cab	89	-5
5602060	O	<b>Location LH U/C 60 Gallon</b>	0	0
5652890	S	<b>DEF Tank Mounted LH BOC</b> Models 220 and 520 mounted left hand back-of-cab.	0	0
5652980	S	<b>DEF To Fuel Ratio Between 1:1 And 2:1</b>	0	0
5655019	S	<b>DEF Tank Small, HD 14 Gal 2.1M MD 5.5 Gal</b>	0	0
<b>Battery Box &amp; Bumper</b>				
6010780	O	<b>Aluminum Space Saver Battery Box RH BOC</b> Battery access from side	196	-84
6040550	O	<b>Aftertreatment Aluminum Non-Slip Cab Entry</b> Aftertreatment right-hand under cab step. DPF/SCR for diesel engines, catalyst for natural gas engines. On Models 579 specifying chassis fairings, the box is aerodynamic.	0	0
6121770	O	<b>Steel Bumper Tapered Painted</b> Two tow points, painted same color as frame. ***Warning*** Due to a new legal regulations, all New Medium Duty trucks require headlights to be located in the bumper when the chassis height is GREATER than the following chassis height:  Measurement to bottom of frame at front of frame: for the 107 Aero Hood 32.6, for the 109 Aero Hood 31.4, for the 109 Vocational Hood 26.7. Work with applications if your chassis height is unacceptable.	463	40
<b>Cab &amp; Equipment</b>				
6510160	O	<b>Aerodynamic 109in BBC Aluminum Cab &amp; SMC Hood</b> With molded gray crown.	1,163	15
6540160	O	<b>Thermal Insulation Package in Cab</b> The thermal insulation package is designed to make the cab thermally efficient in extreme temperatures. The model 520 adds insulation surrounding the doghouse to reduce engine heat transmitted to the cab.	67	2

Price Level: January 1, 2022

Deal: 537 Chassis

Printed On: 7/6/2022 5:11:30 PM

Date: July 07, 2022

Quote Number: QUO-970236-Q2Y3P4





<b>Sales Code</b>	<b>Std/ Opt</b>	<b>Description</b>	<b>\$ List</b>	<b>Weight</b>
6917340	O	<b>Peterbilt Premium Driver Seat</b>	118	4
6927340	O	<b>Peterbilt Premium Passenger Seat</b>	53	14
6930230	O	<b>Seat Skirt - All Eligible Air Seats</b>	24	2
6930580	O	<b>Drivers Armrests - LH &amp; RH</b>	56	4
6931120	O	<b>Seat Belt Color Orange IPO Standard Black</b>	10	0
6937040	O	<b>Cloth Driver</b>	0	0
6937050	O	<b>Cloth Passenger</b>	0	0
6939390	O	<b>Seat Belt Alarm System Driver and Passenger Seats</b> Seat belt alarm system driver and passenger seats. Radio mute when seat belt warning active and compatible radio. Driver/Passenger feature to alert occupants if the seat belt is not buckled. Light will appear in the dash when vehicle has key power turned on as well as a seat belt "chime" will alert the occupants as the vehicle travels at an increased speed.	114	0
6939400	S	<b>Air Ride Driver</b>	0	0
6939420	O	<b>High Back Driver</b>	44	0
6939500	O	<b>Air Ride Passenger</b>	119	0
6939520	O	<b>High Back Passenger</b>	8	0
7000025	O	<b>Steering Wheel With Multi-Function</b> Includes Peterbilt logo on horn button , audio volume, seek, mute and mode button on LH pod with cruise control on/off/cancel, set/resume and accelerate/coast on the right pod.	246	4
7001520	S	<b>Adjustable Steering Column - Tilt/Telescope</b>	0	0
7036130	O	<b>Probilt Interior Grey/Black - Curved Roof</b>	176	0
7110680	O	<b>Exterior Cab Entry Grabhandle</b> Textured; NFPA compliant. Available on Day Cab specifications only.	169	0
7210510	O	<b>3-Piece Glass Rear Cab Window, All Pieces Fixed</b>	157	12
7210540	S	<b>Day Cab Rear Window</b> Day cab rear window flush to back of cab.	0	0
7230060	S	<b>1-Piece Curved Windshield</b>	0	0
7230360	S	<b>Power Door Locks and Power Window Lifts</b> Standard	0	0
7322010	S	<b>Combo Fresh Air Heater/Air Conditioner</b>	0	0

Price Level: January 1, 2022

Deal: 537 Chassis

Printed On: 7/6/2022 5:11:30 PM

Date: July 07, 2022

Quote Number: QUO-970236-Q2Y3P4



Sales Code	Std/ Opt	Description	\$ List	Weight
		With radiator mounted condenser, dedicated side window defrosters, Bi-Level Heater/Defroster Controls, 54,500 BTU/HR, and silicone heater hoses.		
7510060	O	<b>Aero Rear View Mirror Housing, Bright Finish</b>	173	3
7514010	O	<b>Peterbilt Aero Rear View Mirror, Motorized</b> Includes top mirror with motorized, adjustable dual axis heated glass. Bottom mirror is an integrated convex surface. Includes black textured arms with breakaway feature.	257	3
7514050	S	<b>Look Down Mirror Over Passenger Door</b> with Black Housing	0	0
7620040	O	<b>(2) Air Horns Round, 26" Length</b> Roof mounted. Round horn shield.	278	16
7721050	O	<b>Satellite Radio</b> Requires USB port and bluetooth for phone and audio.	222	0
7722120	O	<b>ConcertClass, AM/FM, Weatherband, 3.5 Aux</b>	331	11
7725710	O	<b>Standard Speaker Package For Cab</b> (2) Speakers	50	4
7728030	O	<b>Radio Mute When In Reverse</b> For automatic or automated transmission	0	0
7728040	O	<b>Bluetooth Phone and Audio Requires USB Port</b>	38	0
7728050	O	<b>USB Port</b>	38	0
7851480	S	<b>Peterbilt Electric Windshield Wipers</b> With Intermittent Feature.	0	0
7852020	O	<b>Cab Air Suspension</b>	177	15
7852050	O	<b>Auto Reset Circuit Protection</b> Daycab and Sleeper	19	0
7900090	O	<b>Triangle Reflector Kit, Ship Loose</b> Florescent triangle emergency road flares are designed to meet and exceed all DOT standards.	18	13
7900310	O	<b>Fire Extinguisher, Mounted Outboard Driver Seat</b> Hazmat approval UL listed/rated ABC	56	9
7900970	O	<b>Backup Alarm Wiring To EOF</b>	14	6
8011410	O	<b>Drive Axle #1 Front Oil Temperature Gauge</b> 52mm round, backlit. Physical gauges must be ordered in pairs and are limited to a total of 6. If this option is selected on a truck with VMUX electrical architecture, the gauge will be included in the digital display.	125	0
8011850	O	<b>Transmission Oil Temperature (Main)</b> Located in Digital Cluster Display.	24	0
8021380	S	<b>Air Restriction Indicator</b> Mounted on air cleaner, intake piping, or firewall	0	0
8022160	O	<b>Fuel Filter Restriction Gauge</b>	195	0

Price Level: January 1, 2022

Deal: 537 Chassis

Printed On: 7/6/2022 5:11:30 PM

Date: July 07, 2022

Quote Number: QUO-970236-Q2Y3P4



Sales Code	Std/Opt	Description	\$ List	Weight
		52mm Round, backlit. Physical gauges must be ordered in pairs and are limited to a total of 6. If this option is selected on a truck with VMUX electrical architecture, the gauge will be included in the digital display.		
8070030	O	<b>Up to (12) Additional Electric Switches</b> Up to (12) additional electric switches without wiring. Switch will short pin 5 to 4 when off and pin5 to 6 when on. Backlighting provided by Lin jumper.	312	2
8070250	O	<b>Switch &amp; Wiring For F/O Snow Plow Light Install.</b> Switch and wiring for furnished by owner snow plow light installation. J168 on chassis harness.	192	0
8070860	S	<b>Main Instrumentation Panel</b> Digital Cluster 7" Display includes: Physical (Analog) - Speedometer, Tachometer, Oil Pressure, Coolant Temp and Display Gauges - Fuel Level, DEF Level, DPF Filter Status, Fuel Economy, Volts Telltale, OAT and Primary Air Pressure, Secondary Air Pressure for air brake trucks.	0	0
8111110	S	<b>Headlights Composite Fender Mounted</b> Integral park, turn, and side marker	0	0
8120980	S	<b>(5) Marker Lights, Aero LED</b>	0	0
8133470	O	<b>Switch &amp; Wiring for F/O Beacon/Strobe</b> Switch and wiring for furnished by owner beacon / strobe, 10' coiled wire back-of-cab / back-of-sleeper, at rear sill.	74	2
8134160	S	<b>Self-Canceling Turn Signal</b>	0	0
8140080	S	<b>LED Stop/Turn/Tail/Backup</b> Bracket mounted left-hand / right-hand end of frame	0	0
8140850	S	<b>Moveable EOF Crossmember For Mounting Tail Lights</b> Square end of frame with or without end of frame crossmember	0	0
<b>Paint</b>				
8500710	O	<b>Standard Paint Color Selection</b>	-200	0
8530770	S	<b>(1) Color Axalta Two Stage - Cab/Hood</b> Base Coat/Clear Coat N85020 A - L0006EY WHITE N85700 BUMPER L0001EA BLACK N85500 CAB ROOF L0006EY WHITE N85300 FENDER L0006EY WHITE N85200 FRAME L0001EA BLACK N85400 HOOD TOP L0006EY WHITE	0	0
<b>Shipping Destination</b>				
<b>Options Not Subject To Discount</b>				
9400091	S	<b>Peterbilt Class 7 Standard Coverage</b> 1 year/Unlimited Miles/km	0	0
9407103	O	<b>Prepaid Freight Increase For 2022 Delivery</b>	-500	0
9408703	O	<b>Base Warr: Emissions 5YR/100K MI-EPA Engine</b>	0	0

Price Level: January 1, 2022

Deal: 537 Chassis

Printed On: 7/6/2022 5:11:30 PM

Date: July 07, 2022

Quote Number: QUO-970236-Q2Y3P4



<i>Sales Code</i>	<i>Std/ Opt</i>	<i>Description</i>	<i>\$ List</i>	<i>Weight</i>
<b>Miscellaneous</b>				
9409043	S	Aero Hood (MODEL 537)	0	0
9409096	O	State Registry: Virginia	0	0

### Promotions

### Order Comments



Total List Price (W/O Freight & Warranty & Surcharges )	\$141,276
Marketing and Service Support Fee	\$670
Prepaid Freight	\$2,800
Total Surcharge/Options Not Subject To Discount	\$-500
Total Weight	12,303

## Prices and Specifications Subject to Change Without Notice.

---

Unpublished options may require review/approval.  
Dimensional and performance data for unpublished options may vary from that displayed in CRM.

---

### **PRICING DISCLAIMER**

*While we make every effort to maintain the web site to preserve pricing accuracy, prices are subject to change without notice. Although the information in this price list is presented in good faith and believed to be correct at the time of printing, we make no representations or warranties as to the completeness or accuracy of this information. We reserve the right to change, delete or otherwise modify the pricing information which is represented herein without any prior notice. We carefully check pricing specifications, but occasionally errors can occur, therefore we reserve the right to change such prices without notice. We disclaim all liability for any errors or omissions in the materials. In no event will we be responsible for any damages of any nature whatsoever from the reliance upon information from these materials. Please check your order prebills to confirm your pricing information*



**Shipping Destinations**

**Intermediate Destination:** NONE

Final Destinations	Quantity
--------------------	----------