



Peterbilt of Richmond (H830)  
2800A Deepwater Terminal  
Richmond, Virginia 23212

Virginia Sheriffs Association  
901 East Byrd St Suite1301  
Richmond, Virginia 23219  
United States of America

David Askew  
Cell Phone:  
Office Phone:  
Email: daskew@thepetestore.com

Kaylyn Mitman  
Office Phone: 919-459-6471  
Email: kmitman@virginiasheriffs.org

## Vehicle Summary

Unit		Chassis	
Model:	Model 579	Fr Axle Load (lbs):	12000
Type:	Tractor	Rr Axle Load (lbs):	38000
Description 1:	579 Standard Specs	G.C.W. (lbs):	80000
Description 2:	Daycab		
Application		Road Conditions:	
Intended Serv.:	General Freight	Class A (Highway)	100
Commodity:	Other Commodity	Class B (Hwy/Mtn)	0
		Class C (Off-Hwy)	0
Body		Class D (Off-Road)	0
Type:		Maximum Grade:	6
Length (ft):	0	Wheelbase (in):	183
Height (ft):	0	Overhang (in):	54.7
Max Laden Weight (lbs):	0	Fr Axle to BOC (in):	68.2
Trailer		Cab to Axle (in):	114.8
No. of Trailer Axles:	2	Cab to EOF (in):	169.5
Type:	Van	Overall Comb. Length (in):	832.38
Length (ft):	53	Special Req.	
Height (ft):	13.5		
Kingpin Inset (in):	36		
Corner Radius (in):	1		
Restrictions			
Length (ft):	65		
Width (in):	102		
Height (ft):	13.5		

Approved by: \_\_\_\_\_

Date: \_\_\_\_\_

Note: All sales are F.O.B. designated plant of manufacture.



Sales Code	Std/ Opt	Description	\$ List	Weight
<b>Base Model</b>				
0005791	S	<b>Model 579</b> The Model 579 combines aerodynamic innovation and powertrain optimization to deliver confidence and efficiency for the most cost-conscious companies. A solid and durable aluminum cab consists of the highest quality fit and finish. An in-mold process embeds color directly onto the dash for a long-lasting finish that virtually eliminates fading, scratching and peeling. Electrical wiring carriages support wiring and reduce wear and tear, adding to the overall durability of the components. Peterbilt's flexible Aero Packages provide the right combination of fairings, skirts and closeouts to exceed application-specific aerodynamic requirements. Available in a day cab, or with detachable sleeper, that adds versatility and longevity of a second life for highest resale value.	201,683	14,680
0091200	S	<b>Other Commodity</b>	0	0
0093170	S	<b>General Freight</b> Truck or tractor used in over-the-road hauling of general freight. Pickup to delivery distance is typically over 100 miles and annual mileage is typically over 60,000 miles per year. Operation is typically on-highway.	0	0
0096010	S	<b>Van</b> An enclosed box trailer without temperature control. Designed to carry pallets or boxes of cargo or equipment.	0	0
0098170	S	<b>United States Registry</b> Canadian Registry Package Requires Air Conditioning Excise Tax Canada, Speedometer to be KPH ipo MPH, Daytime Running Lights and Rubber Battery Pad in Bottom of Battery Box.	0	0
<b>Configuration</b>				
0200614	S	<b>SmartWay Designated - Not Selected or Unavailable</b> For this vehicle configuration.	0	0
0200700	S	<b>Not Applicable</b> Secondary Manufacturer	0	0
<b>Frame &amp; Equipment</b>				
0515030	S	<b>10-5/8" Steel Rails to 285"</b> 10.625 x 3.45 x .313 Dimension, 1,776,000 RBM; Yield Strength: 120,000 psi. Section Modulus: 14.8 cubic inches. Weight: 1.44 lbs/inch pair	0	-12
0611790	S	<b>Aluminum Frame Rail Crossmembers</b> Excludes suspension	0	0
0644000	S	<b>EOF Tractor Tapered with Crossmember</b> Includes Kingpin Cutout	0	0
0651010	S	<b>Peterbilt Rear Mudflaps and Straight Hangers</b> Mudflaps aid in protecting the frame and undercarriage from road salt, grime and debris that can cause rust and corrosion. Mud flaps also shield other vehicles from gravel, rocks and road spray.	0	0
0854110	S	<b>JOST JSK37 Fifth Wheel Top Plate</b>	0	0

Price Level: January 1, 2022

Deal: 579 Standard Specs

Printed On: 7/6/2022 8:46:17 PM

Date: July 07, 2022

Quote Number: QUO-970635-N8X2S9



Sales Code	Std/ Opt	Description	\$ List	Weight
		JOST's fifth wheels are the simplest and safest design in the market, with only four moving parts. JOST's simple mechanism allows infinite adjustments versus competitors' notched adjustments.		
0870000		<b>Rear Or Fixd Setting Centerline Bogie</b>	0	0
0890090	S	<b>LH Fifth Wheel Release</b>	0	0
0890550	O	<b>7.6in - 8in Fifth Wheel Height</b>	0	16
0890665	S	<b>Jost Lightweight Inboard Slider</b>	0	0
0891210	S	<b>12" Air Slide</b> For Fifth Wheel	0	0
0898030	S	<b>Fifth Wheel Slide Controls</b> Provided with Speed Interlock to prevent accidental activation above 7 MPH. Configurable from 5 to 10 MPH. Required with sliding Fifth Wheels.	0	0
0940330	S	<b>No Access Package or Deckplate Desired</b> Use with tractors without access package or deckplate	0	0
<b>Front Axle &amp; Equipment</b>				
1012140	S	<b>Meritor MFS+12E 12,500 lb, 3.5 in. Drop</b> Axle is designed for applications with a gross axle weight rating (GAWR) of 13,000 pounds. Axles include special low-friction bushings, double draw keys and integral thrust bearing and seal design for durability, low maintenance and ease of service.	0	0
1111190	S	<b>Taper Leaf Springs, Shocks 12,000 lb</b> Hendrickson taper leaf springs, shocks for 12,000 lbs.	0	0
1243040	S	<b>Power Steering Sheppard HD94</b> Sheppard HD94 power steering gear is a light weight version of heavy duty line-haul power steering gear. For use with 10,000 to 13,200 lb. axle ratings.	0	0
1250180	S	<b>Power Steering Reservoir Frame Mounted</b> The power steering reservoir is a steering system that eases drivability by applying hydraulic pressure to the steering gear.	0	0
1353550	S	<b>PHP10 Aluminum PreSet PLUS Hubs Air Disc</b> PHP10 aluminum PreSet PLUS hubs air disc have a fully integrated spindle nut design, an optimized wheel spacer, magnetic fill plug, with a seal and bearings. Use with Front Axle.	0	0
1380290	S	<b>Bendix Air Disc Front Brakes</b> Bendix air disc front brakes use a floating caliper design to provide foundation braking on all axles and complies with reduced stopping distance regulations.	0	0
1380380	S	<b>Tenneco Shocks For Steer Axle</b> Integrated front suspension to suit heavy duty truck market, combining the air spring and the damper into one module.	0	0
1380470	O	<b>Meritor Wide Track IPO Standard, Front Axle</b> Meritor wide track front axle offers greater turning radius and ease of service. MFS+ 3.5" Drop / MFS 3.74" Drop. 71in KPI IPO 69in with MFS and MFS+ axles.	0	15

Price Level: January 1, 2022

Deal: 579 Standard Specs

Printed On: 7/6/2022 8:46:17 PM

Date: July 07, 2022

Quote Number: QUO-970635-N8X2S9



<b>Sales Code</b>	<b>Std/ Opt</b>	<b>Description</b>	<b>\$ List</b>	<b>Weight</b>
1390630		<b>80mm Front Spring Spacer Blocks</b>	0	0
<b>Rear Axle &amp; Equipment</b>				
1527050	S	<b>PACCAR DX-40 40K Tandem Axle</b>	0	0
1616295	S	<b>PHP10 Aluminum Preset PLUS Hubs - Air Disc</b>	0	0
1680390	S	<b>Bendix ESP Electronic Stability Program With ATC</b> Tractor service only. The Bendix ESP system is designed to continuously monitor a variety of vehicle parameters and sensors to determine if the vehicle is reaching a critical stability threshold. If such a situation develops, the system will quickly and automatically intervene to assist the driver by selectively applying tractor and trailer brakes, and de-throttling the engine.	0	0
1680985	S	<b>Bendix Fusion</b> Bendix Fusion is an integrated driver assistance technology, utilizing a windshield mounted camera, bumper mounted radar and brake system information for the following features: Collision Mitigation, Stationary Vehicle Braking, Multi-lane Autonomous Emergency Braking, Highway Departure Warning and Braking, Following Distance Alerts, Lane Departure Warning, Overspeed Alert and Adaptive Cruise Control with Auto-Resume at speed.	0	0
1681025	O	<b>Adjustable Following Distance</b> Adaptive CC	0	0
1681035	O	<b>Standard Following Distance</b> Adaptive CC	0	0
1682430	S	<b>Anti-Lock Braking System (ABS) 4S4M</b> ABS-6. Includes air braking system.	0	0
1683225	S	<b>SmarTire Tire Pressure Monitoring System</b> Next generation TPMS.	0	0
1684200	S	<b>Synthetic Axle Lubricant All Axles</b> Peterbilt heavy duty models include Fuel Efficient Cognis EMGARD FE75W-90 which provides customers performance advantages over current synthetic lubricants with reduced gear wear and extended maintenance intervals, resulting in increased uptime. In addition, the lubricant provides improved fluid flow to protect gears in extreme cold conditions and withstand the stress from high temperatures, extending component life.	0	0
1687040	S	<b>Air Disc Rear Brakes, Tandem Drive Axle</b> Includes Automatic Slack Adjusters.	0	0
1703080	O	<b>Ratio 3.08 Rear Axle</b>	0	0
1821700	S	<b>Peterbilt Air Leaf 38,000 lb, 52in Axle Spacing</b> Light Weight with Tracking Rods.	0	0
<b>Engine &amp; Equipment</b>				
2072828	S	<b>PACCAR MX-13 455@1600 GV@2200 1650@900</b> (2021 Emissions)	0	0



Sales Code	Std/ Opt	Description	\$ List	Weight
		N20700 AA003 75....CC MAX TARGET SPEED		
		N20800 AA004 10....CC MIN ENABLE SPEED		
		N22000 AA005 OFF...DYNAMIC CC ENABLE		
		N20830 AA006 MT....MULTI TORQUE IN CC		
		N21930 AA009 0....DRIVER REWARD VEH SPD BONUS		
		N21940 AA010 -5....DRIVER REWARD VEH SPD PNLTY		
		N21920 AA013 BOTH..OFFSET MODE		
		N21950 AA015 3.....MIN SPEED FOR DR SHIFT AID		
		N21960 AA016 1.....DSA LOWEST ACTV GEAR		
		N21970 AA017 10....DSA HIGHEST ACTV GEAR		
		N21640 AA019 YES...EIST PARK BRAKE RESET ENABLE		
		N21910 AA022 30....EIST LO CLNT TEMP OVRDRD		
		N20870 AA023 80....EIST HI AMBAIR TEMP OVRDRD		
		N20860 AA024 39....EIST LO AMBAIR TEMP OVRDRD		
		N20900 AA025 5.....EIST PTO MAX IDLE TIME		
		N20840 AA026 5.....EIST PARKED MAX IDLE TIME		
		N20850 AA027 5.....EIST STANDSTILL IDLE TIME		
		N20910 AA029 YES...EIST RESET FROM ENG LOAD		
		N21170 AA030 NO....EIST OVERRIDE FROM ENG LOAD		
		N21190 AA031 0.....EIST EXPIRATION DISTANCE		
		N21230 AA032 YES...EIST ACCEL PEDAL RESET		
		N21240 AA033 YES...EIST SERVICE BRK RESET		
		N21250 AA034 YES...EIST CLUTCH PEDAL RESET		
		N21260 AA035 YES...EIST PTO OVERRIDE		
		N20770 AA037 4.....DSL SPD OFFSET		
		N20760 AA038 2.....AUTO RTRDR VEH SPD OFFSET		
		N20750 AA039 0.1...TIME DELAY FOR RTRDR ACT		
		N20940 AA042 1900..FIC MAX ENG SPEED		
		N22080 AA043 CNCL..CAB/REM: CUSTOM PRESET 1 FUN		
		N22090 AA044 750...CAB/REM: CUSTOM PRESET 1		
		N22100 AA045 CNCL..CAB/REM: CUSTOM PRESET 2 FUN		
		N22110 AA046 850...CAB/REM: CUSTOM PRESET 2		
		N22120 AA047 CNCL..CAB/REM: CUSTOM PRESET 3 FUN		
		N22130 AA048 950...CAB/REM: CUSTOM PRESET 3		
		N22010 AA049 CNCL..CAB: CUSTOM PRESET 1 FUNC		
		N22020 AA050 0....CAB: CUSTOM PRESET 1		
		N22030 AA051 CNCL..CAB: CUSTOM PRESET 2 FUNC		
		N22040 AA052 0.....CAB: CUSTOM PRESET 2		
		N22050 AA053 CNCL..CAB: CUSTOM PRESET 3 FUNC		
		N22060 AA054 0....CAB: CUSTOM PRESET 3		
		N20990 AA055 ON A..CAB: CLUTCH INTLK		
		N21010 AA058 ON A..CAB: PARK BRK INTLK		
		N21030 AA057 ON A..CAB: NEUTRAL INTLK		
		N21150 AA059 ON A..SER BRK INTLK: NO PTO		
		N21130 AA060 OFF...CAB: PRESET +/- SWITCH TYPE		
		N21180 AA061 2000..CAB: MAX ENG SPD- ACCEL CTRL		
		N21120 AA062 2000..CAB: MAX ENG SPD- SW CTRL		
		N21020 AA063 6.....CAB:MAX VEH SPEED		
		N21200 AA064 650...CAB: MIN ENG SPD		
		N21220 AA065 800...CAB: DEDICATED PRESET (-)		
		N21270 AA066 900...CAB: DEDICATED PRESET (+)		

Price Level: January 1, 2022

Deal: 579 Standard Specs

Printed On: 7/6/2022 8:46:17 PM

Date: July 07, 2022

Quote Number: QUO-970635-N8X2S9



Sales Code	Std/ Opt	Description	\$ List	Weight
		N21900 AA067 TRQ...CAB: ACCEL PEDAL TYPE IN PTO		
		N21140 AA068 YES...CAB: ACCEL ACTV IN CAB PTO		
		N21990 AA069 YES...PTO REM PEDAL ENABLE		
		N21600 AA070 ON AD.REM: CLUTCH INTLK		
		N22140 AA071 OFF...REM: CUSTOM INTLK		
		N21700 AA072 ON AD.REM: NEUTRAL INTLK		
		N21710 AA073 ON AD.REM: SER BRK INTLK: NO PTO		
		N21980 AA074 2000..REM:MAX ENG SPD-ACCEL CTRL		
		N21110 AA075 2000..REM: MAX ENG SPD-SW/ TSC1 CT		
		N21320 AA076 650...REM: MIN ENG SPD		
		N21290 AA077 800...REM: DEDICATED PRESET (-)		
		N21490 AA078 900...REM: DEDICATED PRESET (+)		
		N21580 AA079 DEDIC.REM: PRESET +/- SWITCH TYPE		
		N20690 AA086 75....MAX ACCEL PEDAL VEH SPD		
		N21300 AA087 0.....VSL EXPIRATION DISTANCE		
		N21310 AA088 155...LRSL SPD LMT		
		N20740 AE001 NO....ENBL MX RETARDER IN NEUTRAL		
		N20710 AE002 650...IDLE TARGET		
		N20930 AE003 ON....FIC ENABLE/DISABLE		
		N22070 AA056 OFF...CAB: CUSTOM INTLK		
		N22170 AQ001 4.....PCC Max Negative Offset (AQ0		
		N22180 AQ002 4.....PCC Max Positive Offset (AQ0		
2091130	S	<b>VMUX Electronics Architecture</b>	0	0
2091305	S	<b>Engine Idle Shutdown Timer Enabled</b>	0	0
2091315	O	<b>Enable EIST Ambient Temp Overrule</b>	0	0
2091372		<b>Eff EIST NA Expiration Miles</b>	0	0
2091638		<b>Effective VSL Setting 65.0 MPH or Greater (USA)</b>	0	0
2092014	S	<b>Typical Operating Speed 65 MPH</b>	0	0
2092027	O	<b>MX Retarder State Cruise Control On</b> (Manual Mode Engine Parameter)	0	0
2092033	O	<b>Powertrain Optimized for Balance</b> Best analysis for vehicles where service includes frequent start and stop cycles.	0	0
2092079	O	<b>Decline Driver Performance Assistant</b>	0	0
2092082	S	<b>Engine Monitoring Protection - Derate</b> (PACCAR MX) A warning is provided in the A-Panel display when DPF regeneration is required. Continued operation without regeneration will initiate automate derating of the engine's power and can result in damage to the engine.	0	0
2092108	S	<b>Predictive Cruise Control Package</b>	0	0
2140220	S	<b>CARB Engine Idling Compliance DECLINED By</b>	0	0

Price Level: January 1, 2022

Deal: 579 Standard Specs

Printed On: 7/6/2022 8:46:17 PM

Date: July 07, 2022

Quote Number: QUO-970635-N8X2S9



<b>Sales Code</b>	<b>Std/ Opt</b>	<b>Description</b>	<b>\$ List</b>	<b>Weight</b>
		Dealer/Customer		
2140410	S	<b>Engine Brake Controls Located on RH Column</b>	0	0
2140670	O	<b>EPA Emission Warranty</b>	0	0
2513060	S	<b>PACCAR 160 Amp Alternator, Brushed</b> PACCAR 160 AMP alternator, brushed producing 160 Amps at road speed and 100 Amps at idle.	0	0
2521090	S	<b>Immersion Type Block Heater 110-120V</b> Standard location for 2.1M and 1.9M models is left-hand under cab, Model 520 is in bumper, and for Model 220 it is at the driver step. Plug includes a weather-proof cover that protects the receptacle. This pre-heater keeps the coolant in the engine block from freezing when the engine is not running.	0	0
2522080	S	<b>PACCAR Premium Starter - MX Engines Only</b> PACCAR Premium 12 volt. Better cranking power, lower current draw and improved warranty to 5-yr/500K miles.	0	0
2538040	S	<b>3 PACCAR Premium 12V Dual Purpose Batt 2190 CCA</b> Threaded stud type terminal. Stranded copper battery cables are double aught (00) or larger to reduce resistance.	0	0
2539720	S	<b>Low Voltage Disconnect System</b>	0	0
2641010	S	<b>Crank Mounted Variable Speed Fan Clutch MX-13 Eng</b> Crank Mounted Variable Speed Fan Clutch MX-13 Eng. The crank-mounted fully variable speed fan drives communicate directly with the MX-13 ECM, managing the fan speed to match the exact amount of cooling required. The optimized setup creates smoother engagements, reduces noise, frees up available horsepower, and removes the requirement of a belt line to drive the fan. These fan drives are also maintenance-free.	0	0
2738410	S	<b>WABCO 25.9 CFM Air Compressor, MX only</b> WABCO 25.9 CFM air compressor, MX only, provides greater air output aiding in cleaner operation, higher efficiency, and durability.	0	0
2811160	S	<b>Compression Brake, MX</b> The Mx brake features a Jacobs Brake with an integrated compression-release brake and engine overhead. the specially designed exhaust came lobe provides both exhaust cam motion and deicated Compression release timing. This results in precise timing of the valve opening, unleashing higher retarding performance with minimum loading on the engine.	0	0
2921180	S	<b>PACCAR Fuel/Water Separator On Engine</b> Extended life fuel filter, optimized for MX engines and Includes fuel heat, 12V electric heat and WIF sensor.	0	0
3114270	S	<b>High Efficiency Cooling System</b> Cooling module is a combination of steel and aluminum components, with aluminum connections to maximize performance and cooling capability. Silicone radiator & heater hoses enhance value, durability, & reliability. Constant tension band clamps reduce leaks. Chevron Delo Extended Life Coolant (NOAT) extends maintenance intervals reducing maintenance costs. Anti-freeze effective to -30 degrees F helps protect	0	0

Price Level: January 1, 2022

Deal: 579 Standard Specs

Printed On: 7/6/2022 8:46:17 PM

Date: July 07, 2022

Quote Number: QUO-970635-N8X2S9





Sales Code	Std/ Opt	Description	\$ List	Weight
		the engine. Low coolant level sensor warns of low coolant condition to prevent engine damage. Radiator Size by Model: 367 1325 sq in, 367 HH Fepto 1325 sq in, 365 Fepto 1183 sq in, 365 Full Frame Extension 1000 sq in, 520 1202 sq in, 579 1456.9 sq in, 535/536/537/548 949.3 sq in, 537/548 VOC 1000.3 sq in, 389/367 HH 1604 sq in, 365/567 1379 sq in.		
3211140	S	<b>(1) Air Cleaner Engine Mounted</b>	0	0
3365280	S	<b>Exhaust Single RH Horizontal</b> DPF/SCR RH Under Cab.	0	0
3383040	O	<b>DPF Regeneration Switch</b> Remove Stop Position	0	0
<b>Transmission &amp; Equipment</b>				
4030040	S	<b>PACCAR TX-12 PO-16F112C12 Automated</b> Linehaul, On Highway Intended Service with 1,650 lbs.-ft. torque. Includes 12-speed Linehaul Overdrive, transmission fluid pressure sensor notifies driver of low oil to prevent low oil failure and is backed by a low oil failure protection. Internal electrical system routing which minimizes exposure and corrosion of wires and connectors, vehicle oil-coalescing air filter to protect transmission from contamination. No oil cooler required. Forward ratios: 1st-14.4, 2nd-11.0, 3rd-8.44, 4th -6.46, 5th-4.95, 6th- 3.79, 7th- 2.91, 8th-2.23, 9th-1.71, 10th-1.30, 11th-1.0, 12th-.766. Reverse ratios: R1-16.92, R2-12.95. Overall ratio 18.85. PTO capability: 8-bolt bottom mount only. Reference Engineering Data Book for available PTOs.	0	0
4210870	O	<b>RPL20 Driveline Interaxle</b> Requires RPL20 Driveline interaxle (option 4210870) for tandem rear axles. RPL20 series drivelines are built for heavy-duty commercial vehicles and are permanently lubricated and sealed for life with triple lip seals to protect against contaminants. All Meritor drivelines will be primed before painted, improving paint adhesion for longer lasting quality in the field.	0	0
4211350	S	<b>RPL25 SD Driveline, Without Midship Bearing</b> All Meritor drivelines will be primed before painted, improving paint adhesion for longer lasting quality in the field.	0	0
4252610	S	<b>Column Mounted Shifter RH Side</b>	0	0
4257050	S	<b>Neutral Coast Mode</b> Automated transmission.	0	0
<b>Air &amp; Trailer Equipment</b>				
4510190	S	<b>Bendix AD-HF Air Dryer, Heater</b> Bendix AD-HF air filters protects the life of your engine system and components. Proven PuraGuard oil coalescing technology in the the air dryer cartridge. This oil coalescing filter ensures the removal of oil and oil aerosols before they can contaminate the moisture removing desiccant.	0	0
4540420	S	<b>Nylon Chassis Hose</b>	0	0

Price Level: January 1, 2022

Deal: 579 Standard Specs

Printed On: 7/6/2022 8:46:17 PM

Date: July 07, 2022

Quote Number: QUO-970635-N8X2S9





Sales Code	Std/ Opt	Description	\$ List	Weight
4543320	S	<b>Steel Painted Air Tanks</b> All air tanks are steel with painted finish except when Code 4543330 Polish Aluminum Air Tanks is also selected (then exposed air tanks outside the frame rails will be polished aluminum). Peterbilt will determine the optimal size and location of required air tanks. Narratives requesting a specific air tank size or location will not be accepted for factory installation. See ECAT to determine number or location of air tanks installed.	0	0
4543390	O	<b>High Mount Air Tanks BOC/BOS Where Possible</b> Subject to frame review	0	0
4610920	S	<b>Self-Returning Brake Hand Valve</b> Dash mounted controls	0	0
4614810	S	<b>AE Connections BOC/BOS, Hose Tenna</b>	0	0
<b>Tires &amp; Wheels</b>				
5066100	S	<b>FF: BR 14ply 295/75R22.5 R213 Ecopia</b>	0	0
5166100	S	<b>RR: BR 14ply 295/75R22.5 R213 Ecopia</b>	0	0
5190008	S	<b>Code-rear Tire Qty 08</b>	0	0
5211990	S	<b>FF: Accu-Lite Steel Armor 51408PK 22.5X8.25</b> PHP10-2 hand holes	0	0
5311990	S	<b>RR: Accu-Lite Steel Armor 51408PK 22.5X8.25</b> PHP10-2 hand holes	0	0
5390008	S	<b>Code-rear Rim Qty 08</b>	0	0
<b>Fuel Tanks</b>				
5552070	S	<b>26" Aluminum 60 Gallon Fuel Tank RH BOC</b> Paddle handle filler cap with threadless filler neck. Top draw fuel plumbing reduces chance of introducing air into the fuel system during low fuel level conditions due to the central placement of fuel pickup tube. Wire braid fuel lines increase durability & reduce potential for leaks.	0	0
5556070	S	<b>26" Aluminum 60 Gallon Fuel Tank LH BOC</b> Paddle handle filler cap with threadless filler neck. Top draw fuel plumbing reduces chance of introducing air into the fuel system during low fuel level conditions due to the central placement of fuel pickup tube. Wire braid fuel lines increase durability & reduce potential for leaks.	0	0
5603060	S	<b>Location RH BOC 60 Gallon</b>	0	0
5604060	S	<b>Location LH BOC 60 Gallon</b>	0	0
5652880	S	<b>DEF Tank Mounted RH BOC</b> You have selected a Diesel Exhaust Fluid (DEF) tank mounted on the right-hand (passenger) side of the vehicle. Note, some retail fuel distributors have chosen to standardize on DEF dispensing pumps	0	0

Price Level: January 1, 2022

Deal: 579 Standard Specs

Printed On: 7/6/2022 8:46:17 PM

Date: July 07, 2022

Quote Number: QUO-970635-N8X2S9



Sales Code	Std/ Opt	Description	\$ List	Weight
		oriented to the left-hand (driver) side of the vehicle. Please verify your selection for DEF tank mounting.		
5652990	O	<b>DEF To Fuel Ratio 2:1 Or Greater</b>	0	0
5655019	S	<b>DEF Tank Small, HD 14 Gal 2.1M MD 5.5 Gal</b>	0	0
<b>Battery Box &amp; Bumper</b>				
6010030	S	<b>Aluminum Battery Box LH Under Cab, Non-Slip Step</b> Includes diamond pattern block shaped cover in traditional/vocational models and a smooth finish tapered cover on aerodynamic models	0	0
6040550	S	<b>Aftertreatment Aluminum Non-Slip Cab Entry</b> Aftertreatment right-hand under cab step. DPF/SCR for diesel engines, catalyst for natural gas engines. On Models 579 specifying chassis fairings, the box is aerodynamic.	0	0
6112540	S	<b>Aero Bumper Molded 3-Piece Molded Black</b>	0	0
<b>Cab &amp; Equipment</b>				
6515790	S	<b>Aero 118" BBC Alum Cab &amp; Metton Hood w/ SBFA</b> Hood has stainless steel grille with chrome plated grille surround and Peterbilt bird. Includes anti-blow down hood device.	0	0
6700000	S	<b>No Sleeper Selected</b>	0	0
6911100	S	<b>Peterbilt ST Driver</b> Peterbilt ST air seat, high height backrest, adjustable seat track length, 1 chamber lumbar support, suspension with fixed damping, fore-aft isolator with lockout, Vinyl bellows over suspension. Adds 40mm of increased space for steering wheel to chest and improved driver ingress/egress into cab and sleeper (knee sweep) with improved passenger side ingress/egress for personal carog/luggage. Standard vinyl finish - color coordinate with interior color.	0	0
6921740	S	<b>Peterbilt ST Non-Adjustable Passenger Seat</b> Standard vinyl, no suspension cover, no seat back recline.	0	0
6939140	S	<b>Tube frame under Passenger Seat</b> Only available with Peterbilt ST non-adjustable passenger seat.	0	0
6939400	S	<b>Air Ride Driver</b>	0	0
6939420	S	<b>High Back Driver</b>	0	0
6939470	S	<b>Vinyl Driver</b>	0	0
6939510	S	<b>Non-Air Ride Passenger</b>	0	0
6939520	S	<b>High Back Passenger</b>	0	0
6939570	S	<b>Vinyl Passenger</b>	0	0
7000025	S	<b>Steering Wheel With Multi-Function</b>	0	0



Sales Code	Std/ Opt	Description	\$ List	Weight
		Includes Peterbilt logo on horn button , audio volume, seek, mute and mode button on LH pod with cruise control on/off/cancel, set/resume and accelerate/coast on the right pod.		
7001520	S	<b>Adjustable Steering Column - Tilt/Telescope</b>	0	0
7037130	S	<b>Prestige Interior - Sterling Gray</b>	0	0
7210540	S	<b>Day Cab Rear Window</b> Day cab rear window flush to back of cab.	0	0
7210550	S	<b>1-Piece Glass Rear Cab Window Fixed</b>	0	0
7230060	S	<b>1-Piece Curved Windshield</b>	0	0
7230360	S	<b>Power Door Locks and Power Window Lifts</b> Standard	0	0
7322010	S	<b>Combo Fresh Air Heater/Air Conditioner</b> With radiator mounted condenser, dedicated side window defrosters, Bi-Level Heater/Defroster Controls, 54,500 BTU/HR, and silicone heater hoses.	0	0
7510070	S	<b>Aero Rear View Mirror Housing, Molded Black</b>	0	0
7514000	S	<b>Peterbilt Aero Rear View Mirror, Non-Motorized</b> Includes top mirror with non-motorized, adjustable dual axis heated glass. Bottom mirror is an integrated convex surface. Includes black textured arms with breakaway feature.	0	0
7514050	S	<b>Look Down Mirror Over Passenger Door</b> with Black Housing	0	0
7610500	S	<b>Air Horn Mounted Under Cab</b>	0	0
7725720	S	<b>No Head Unit or Audio Speakers Selected</b>	0	0
7788055	S	<b>SmartLINQ Remote Diagnostics</b> SmartLINQ is Peterbilts proprietary remote diagnostics service which monitors the engine and aftertreatment for diagnostic codes providing real-time code analysis maximizing vehicle uptime and strengthening the fleets partnership with their dealer. SmartLINQ provides fault coverage for over 800 codes, a customizable email notification for 116 codes plus a web portal to manage your entire fleet included at no additional charge. SmartLINQ is compatible with any telematics system and doesnt require a specific fleet management system. For those whose customers utilize PeopleNet, the pre-wire with remote diagnostics will provide a more integrated solution utilizing the existing SmartLINQ modem. For those whose customers utilize other fleet services products, the existing pre-wire option for the other fleet service devices will continue to be available. Standard on Class 8 engines and available on Models 348, 337, 330 and 325 with a PX-9, PX-7 or Cummins Westport natural gas engine.	0	0
7788056	S	<b>24 Months SmartLINQ Subscription With OTA</b> Functionality - PACCAR MX Engines	0	0

Price Level: January 1, 2022

Deal: 579 Standard Specs

Printed On: 7/6/2022 8:46:17 PM

Date: July 07, 2022

Quote Number: QUO-970635-N8X2S9



Sales Code	Std/ Opt	Description	\$ List	Weight
7851480	S	<b>Peterbilt Electric Windshield Wipers</b> With Intermittent Feature.	0	0
7852060	S	<b>Solid Rear Day Cab Mounts</b>	0	0
8011830	S	<b>Engine Oil Temperature</b> Located in Digital Cluster Display.	0	0
8021800	S	<b>Air Filter Restriction Pressure Gauge</b> Located in Digital Cluster Display	0	0
8021810	S	<b>Brake Application Air Pressure (Tractor)</b> Located in Digital Cluster Display.	0	0
8070810	S	<b>Engine Manifold Pressure (Turbo Boost)</b> Located in Digital Cluster Display	0	0
8070820	S	<b>Engine Percent Torque</b> Located in Digital Cluster Display	0	0
8070830	O	<b>Main Instrumentation Panel</b> Digital Cluster 15" Display includes: Speedometer, Tachometer, Primary Air Pressure, Secondary Air Pressure, Fuel Level, DEF Level, DPF Filter Status, Fuel Economy, Oil Pressure, Coolant Temp, and Voltmeter.	0	0
8111110	S	<b>Headlights Composite Fender Mounted</b> Integral park, turn, and side marker	0	0
8120990	S	<b>(5) Marker Lights, Aero LED</b> On roof, visor, or fairing	0	0
8133960	S	<b>Daytime Running Lights</b> The brake interlock turns the daytime running lights off when the parking brakes are engaged. This is required on all Canadian vehicles.	0	0
8140000	S	<b>Incandescent Oval Stop/Turn/Tail/Backup</b> In tractor taper end of frame crossmember	0	0

### Paint

8500710	S	<b>Standard Paint Color Selection</b>	-200	0
8530770	S	<b>(1) Color Axalta Two Stage - Cab/Hood</b> Base Coat/Clear Coat N85020 A - L0006EY WHITE N85500 CAB ROOF L0006EY WHITE N85300 FENDER L0006EY WHITE N85200 FRAME L0001EA BLACK N85400 HOOD TOP L0006EY WHITE	0	0

### Shipping Destination

### Options Not Subject To Discount

9400090	S	<b>Peterbilt Class 8 Standard Coverage</b> 1 year/100,000 Miles (160,000 km)	0	0
9400092	S	<b>PACCAR MX Standard Coverage</b> 2 yrs/250,000 mi (400,000 km)/6,250 hrs	0	0
9407103	O	<b>Prepaid Freight Increase For 2022 Delivery</b>	500	0

Price Level: January 1, 2022

Deal: 579 Standard Specs

Printed On: 7/6/2022 8:46:17 PM

Date: July 07, 2022

Quote Number: QUO-970635-N8X2S9



<b>Sales Code</b>	<b>Std/ Opt</b>	<b>Description</b>	<b>\$ List</b>	<b>Weight</b>
9407147	O	Fuel Price Index Factor \$507 Net	507	0
9408703	O	Base Warr: Emissions 5YR/100K MI-EPA Engine	0	0
<b>Miscellaneous</b>				
9409001	S	Day Cab / Prestige Interior (DM)	0	0
9409096	O	State Registry: Virginia	0	0

**Promotions**

**Order Comments**



Total List Price (W/O Freight & Warranty & Surcharges )	\$201,483
Marketing and Service Support Fee	\$995
Prepaid Freight	\$2,825
Total Surcharge/Options Not Subject To Discount	\$1,007
Total Weight	14,699

## Prices and Specifications Subject to Change Without Notice.

---

Unpublished options may require review/approval.

Dimensional and performance data for unpublished options may vary from that displayed in CRM.

---

### **PRICING DISCLAIMER**

*While we make every effort to maintain the web site to preserve pricing accuracy, prices are subject to change without notice. Although the information in this price list is presented in good faith and believed to be correct at the time of printing, we make no representations or warranties as to the completeness or accuracy of this information. We reserve the right to change, delete or otherwise modify the pricing information which is represented herein without any prior notice. We carefully check pricing specifications, but occasionally errors can occur, therefore we reserve the right to change such prices without notice. We disclaim all liability for any errors or omissions in the materials. In no event will we be responsible for any damages of any nature whatsoever from the reliance upon information from these materials. Please check your order prebills to confirm your pricing information*



**Shipping Destinations**

**Intermediate Destination:** NONE

Final Destinations	Quantity
--------------------	----------